




MBA

Bearings - Press - Acetal - Flange Mounted



Retainer : Carbon Steel / Zinc Plated or Oxycote® Hardened to HRB 93.98.

Bearing : PTFE Filled Acetal Self Lubricating / -40 to 150 Deg C.

Self lubricating.

Use any shaft material with 0.4 um or finer finish.

<http://www.minibearings.com.au//categories/shafting/all/pics/>

Bearings - Press - Acetal - Flange Mounted

Part Number	Shaft Diameter (d) mm	Overall Length (L) mm	Height along Centre Line (H) mm	Overall Width (F)	Panel Clearance Diameter (d1)	Distance between holes (E)	Max. Radial Load N	Flange Thickness (T)	Type	Max. Speed RPM
	<i>inches</i>	<i>inches</i>	<i>inches</i>							
# PBF-04.76-ACE-SA	4.788 - 4.839	45.720	7.112	22.350	10.310	30.734	44	13.495	Self aligning (+/- 5 Deg)	4630
		<i>1.800</i>	<i>0.280</i>							
# PBF-06.00-ACE	6.020 - 6.070	45.200	6.900	22.500	10.300	31.000	100	1.200	Non Aligning	4120
		<i>1.780</i>	<i>0.272</i>							
PBF-06.35-ACE-SA	6.375 - 6.426	45.720	7.112	22.350	10.310	30.734	88	13.495	Self aligning (+/- 5 Deg)	4630
		<i>1.800</i>	<i>0.280</i>							

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Bearings - Press - Acetal - Flange Mounted

Part Number	Shaft Diameter (d) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Height along Centre Line (H) mm <i>inches</i>	Overall Width (F)	Panel Clearance Diameter (d1)	Distance between holes (E)	Max. Radial Load N	Flange Thickness (T)	Type	Max. Speed RPM
# PBF-07.94-ACE-SA	7.963 - 8.012	53.340 <i>2.100</i>	9.906 <i>0.390</i>	30.480	14.290	38.862	175	16.670	Self aligning (+/- 5 Deg)	5250
# PBF-08.00-ACE	8.030 - 8.080	53.200 <i>2.094</i>	10.000 <i>0.394</i>	30.200	15.000	38.900	200	1.500	Non Aligning	5200
PBF-09.53-ACE-SA	9.550 - 9.601	53.340 <i>2.100</i>	12.446 <i>0.490</i>	30.480	16.660	38.862	219	16.670	Self aligning (+/- 5 Deg)	4370
PBF-10.00-ACE	10.030 - 10.080	53.200 <i>2.094</i>	13.000 <i>0.512</i>	30.200	17.000	38.900	200	1.500	Non Aligning	4170
# PBF-12.00-ACE	12.030 - 12.080	59.400 <i>2.339</i>	17.000 <i>0.669</i>	36.600	21.700	45.200	400	1.500	Non Aligning	3470
# PBF-12.70-ACE-SA	12.725 - 12.802	59.690 <i>2.350</i>	17.018 <i>0.670</i>	36.580	21.430	45.212	438	21.433	Self aligning (+/- 5 Deg)	3280
# PBF-15.00-ACE	15.030 - 15.080	59.400 <i>2.339</i>	19.400 <i>0.764</i>	39.600	28.100	45.200	800	2.300	Non Aligning	2780
# PBF-15.88-ACE-SA	15.900 - 15.951	59.690 <i>2.350</i>	19.558 <i>0.770</i>	39.620	27.780	45.212	875	27.783	Self aligning (+/- 5 Deg)	2620
# PBF-18.00-ACE	18.030 - 18.080	59.400 <i>2.339</i>	22.400 <i>0.882</i>	39.600	32.900	45.200	1000	2.300	Non Aligning	2315

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Bearings - Press - Acetal - Flange Mounted

Part Number	Shaft Diameter (d) mm	Overall Length (L) mm	Height along Centre Line (H) mm	Overall Width (F)	Panel Clearance Diameter (d1)	Distance between holes (E)	Max. Radial Load N	Flange Thickness (T)	Type	Max. Speed RPM
	<i>inches</i>	<i>inches</i>	<i>inches</i>							
# PBF-19.05-ACE-SA	19.075 - 19.126	82.550	22.606	39.620	32.540	63.500	875	32.545	Self aligning (+/- 5 Deg)	2180
		<i>3.250</i>	<i>0.890</i>							

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
