




MBA

Belts - Timing - 3.000mm Pitch - HTD Double Sided



HTD Series Metric Timing Belts Double Sided.

Pitch (P) - 3.000mm.

Tooth Height (H) - 1.20mm.

Belt Height (W) - 3.20mm.

Breaking strength is not indicative of working strength.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
		<i>inches</i>	<i>inches</i>						
# BD-H3-132-060-NF	132	6.00	396.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>15.591</i>						
# BD-H3-132-090-NF	132	9.00	396.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>15.591</i>						
# BD-H3-133-060-NF	133	6.00	399.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>15.709</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
		<i>inches</i>	<i>inches</i>						
# BD-H3-133-090-NF	133	9.00	399.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>15.709</i>						
# BD-H3-135-060-NF	135	6.00	405.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>15.945</i>						
# BD-H3-135-090-NF	135	9.00	405.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>15.945</i>						
# BD-H3-137-060-NF	137	6.00	411.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>16.181</i>						
# BD-H3-137-090-NF	137	9.00	411.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>16.181</i>						
# BD-H3-140-060-NF	140	6.00	420.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>16.535</i>						
# BD-H3-140-090-NF	140	9.00	420.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>16.535</i>						
# BD-H3-142-060-NF	142	6.00	426.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>16.772</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
		<i>inches</i>	<i>inches</i>						
# BD-H3-142-090-NF	142	9.00	426.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>16.772</i>						
# BD-H3-144-060-NF	144	6.00	432.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>17.008</i>						
# BD-H3-144-090-NF	144	9.00	432.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>17.008</i>						
# BD-H3-145-060-NF	145	6.00	435.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>17.126</i>						
# BD-H3-145-090-NF	145	9.00	435.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>17.126</i>						
# BD-H3-149-060-NF	149	6.00	447.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>17.598</i>						
# BD-H3-149-090-NF	149	9.00	447.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>17.598</i>						
# BD-H3-155-060-NF	155	6.00	465.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>18.307</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-155-090-NF	155	9.00 <i>0.354 inches</i>	465.00 <i>18.307 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-156-060-NF	156	6.00 <i>0.236 inches</i>	468.00 <i>18.425 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-156-090-NF	156	9.00 <i>0.354 inches</i>	468.00 <i>18.425 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-157-060-NF	157	6.00 <i>0.236 inches</i>	471.00 <i>18.543 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-157-090-NF	157	9.00 <i>0.354 inches</i>	471.00 <i>18.543 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-158-060-NF	158	6.00 <i>0.236 inches</i>	474.00 <i>18.661 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-158-090-NF	158	9.00 <i>0.354 inches</i>	474.00 <i>18.661 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-160-060-NF	160	6.00 <i>0.236 inches</i>	480.00 <i>18.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-160-090-NF	160	9.00 <i>0.354 inches</i>	480.00 <i>18.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-162-060-NF	162	6.00 <i>0.236 inches</i>	486.00 <i>19.134 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-162-090-NF	162	9.00 <i>0.354 inches</i>	486.00 <i>19.134 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-163-060-NF	163	6.00 <i>0.236 inches</i>	489.00 <i>19.252 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-163-090-NF	163	9.00 <i>0.354 inches</i>	489.00 <i>19.252 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-164-060-NF	164	6.00 <i>0.236 inches</i>	492.00 <i>19.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-164-090-NF	164	9.00 <i>0.354 inches</i>	492.00 <i>19.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-167-060-NF	167	6.00 <i>0.236 inches</i>	501.00 <i>19.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-167-090-NF	167	9.00 <i>0.354 inches</i>	501.00 <i>19.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-168-060-NF	168	6.00 <i>0.236 inches</i>	504.00 <i>19.843 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-168-090-NF	168	9.00 <i>0.354 inches</i>	504.00 <i>19.843 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-170-060-NF	170	6.00 <i>0.236 inches</i>	510.00 <i>20.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-170-090-NF	170	9.00 <i>0.354 inches</i>	510.00 <i>20.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-171-060-NF	171	6.00 <i>0.236 inches</i>	513.00 <i>20.197 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-171-090-NF	171	9.00 <i>0.354 inches</i>	513.00 <i>20.197 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-175-060-NF	175	6.00 <i>0.236 inches</i>	525.00 <i>20.669 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-175-090-NF	175	9.00 <i>0.354 inches</i>	525.00 <i>20.669 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-176-060-NF	176	6.00 <i>0.236 inches</i>	528.00 <i>20.787 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-176-090-NF	176	9.00 <i>0.354 inches</i>	528.00 <i>20.787 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-177-060-NF	177	6.00 <i>0.236 inches</i>	531.00 <i>20.906 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-177-090-NF	177	9.00 <i>0.354 inches</i>	531.00 <i>20.906 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-179-060-NF	179	6.00 <i>0.236 inches</i>	537.00 <i>21.142 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-179-090-NF	179	9.00 <i>0.354 inches</i>	537.00 <i>21.142 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-184-060-NF	184	6.00 <i>0.236 inches</i>	552.00 <i>21.732 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-184-090-NF	184	9.00 <i>0.354 inches</i>	552.00 <i>21.732 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-186-060-NF	186	6.00 <i>0.236 inches</i>	558.00 <i>21.969 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-186-090-NF	186	9.00 <i>0.354 inches</i>	558.00 <i>21.969 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-188-060-NF	188	6.00 <i>0.236 inches</i>	564.00 <i>22.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-188-090-NF	188	9.00 <i>0.354 inches</i>	564.00 <i>22.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-190-060-NF	190	6.00 <i>0.236 inches</i>	570.00 <i>22.441 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-190-090-NF	190	9.00 <i>0.354 inches</i>	570.00 <i>22.441 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-192-060-NF	192	6.00 <i>0.236 inches</i>	576.00 <i>22.677 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-192-090-NF	192	9.00 <i>0.354 inches</i>	576.00 <i>22.677 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-195-060-NF	195	6.00 <i>0.236 inches</i>	585.00 <i>23.031 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-195-090-NF	195	9.00 <i>0.354 inches</i>	585.00 <i>23.031 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-197-060-NF	197	6.00 <i>0.236 inches</i>	591.00 <i>23.268 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-197-090-NF	197	9.00 <i>0.354 inches</i>	591.00 <i>23.268 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-199-060-NF	199	6.00 <i>0.236 inches</i>	597.00 <i>23.504 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-199-090-NF	199	9.00 <i>0.354 inches</i>	597.00 <i>23.504 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-200-060-NF	200	6.00 <i>0.236 inches</i>	600.00 <i>23.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
		<i>inches</i>	<i>inches</i>						
# BD-H3-200-090-NF	200	9.00	600.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>23.622</i>						
# BD-H3-202-060-NF	202	6.00	606.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>23.858</i>						
# BD-H3-202-090-NF	202	9.00	606.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>23.858</i>						
# BD-H3-203-060-NF	203	6.00	609.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>23.976</i>						
# BD-H3-203-090-NF	203	9.00	609.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>23.976</i>						
# BD-H3-204-060-NF	204	6.00	612.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>24.094</i>						
# BD-H3-204-090-NF	204	9.00	612.00	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
		<i>0.354</i>	<i>24.094</i>						
# BD-H3-209-060-NF	209	6.00	627.00	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
		<i>0.236</i>	<i>24.685</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-209-090-NF	209	9.00 <i>0.354 inches</i>	627.00 <i>24.685 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-211-060-NF	211	6.00 <i>0.236 inches</i>	633.00 <i>24.921 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-211-090-NF	211	9.00 <i>0.354 inches</i>	633.00 <i>24.921 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-213-060-NF	213	6.00 <i>0.236 inches</i>	639.00 <i>25.157 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-213-090-NF	213	9.00 <i>0.354 inches</i>	639.00 <i>25.157 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-215-060-NF	215	6.00 <i>0.236 inches</i>	645.00 <i>25.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-215-090-NF	215	9.00 <i>0.354 inches</i>	645.00 <i>25.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-216-060-NF	216	6.00 <i>0.236 inches</i>	648.00 <i>25.512 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-216-090-NF	216	9.00 <i>0.354 inches</i>	648.00 <i>25.512 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-219-060-NF	219	6.00 <i>0.236 inches</i>	657.00 <i>25.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-219-090-NF	219	9.00 <i>0.354 inches</i>	657.00 <i>25.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-221-060-NF	221	6.00 <i>0.236 inches</i>	663.00 <i>26.102 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-221-090-NF	221	9.00 <i>0.354 inches</i>	663.00 <i>26.102 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-223-060-NF	223	6.00 <i>0.236 inches</i>	669.00 <i>26.339 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-223-090-NF	223	9.00 <i>0.354 inches</i>	669.00 <i>26.339 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-228-060-NF	228	6.00 <i>0.236 inches</i>	684.00 <i>26.929 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-228-090-NF	228	9.00 <i>0.354 inches</i>	684.00 <i>26.929 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-229-060-NF	229	6.00 <i>0.236 inches</i>	687.00 <i>27.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-229-090-NF	229	9.00 <i>0.354 inches</i>	687.00 <i>27.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-232-060-NF	232	6.00 <i>0.236 inches</i>	696.00 <i>27.402 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-232-090-NF	232	9.00 <i>0.354 inches</i>	696.00 <i>27.402 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-236-060-NF	236	6.00 <i>0.236 inches</i>	708.00 <i>27.874 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-236-090-NF	236	9.00 <i>0.354 inches</i>	708.00 <i>27.874 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-237-060-NF	237	6.00 <i>0.236 inches</i>	711.00 <i>27.992 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-237-090-NF	237	9.00 <i>0.354 inches</i>	711.00 <i>27.992 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-245-060-NF	245	6.00 <i>0.236 inches</i>	735.00 <i>28.937 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-245-090-NF	245	9.00 <i>0.354 inches</i>	735.00 <i>28.937 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-246-060-NF	246	6.00 <i>0.236 inches</i>	738.00 <i>29.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-246-090-NF	246	9.00 <i>0.354 inches</i>	738.00 <i>29.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-250-060-NF	250	6.00 <i>0.236 inches</i>	750.00 <i>29.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-250-090-NF	250	9.00 <i>0.354 inches</i>	750.00 <i>29.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-251-060-NF	251	6.00 <i>0.236 inches</i>	753.00 <i>29.646 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-251-090-NF	251	9.00 <i>0.354</i> <i>inches</i>	753.00 <i>29.646</i> <i>inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-265-060-NF	265	6.00 <i>0.236</i>	795.00 <i>31.299</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-265-090-NF	265	9.00 <i>0.354</i>	795.00 <i>31.299</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-274-060-NF	274	6.00 <i>0.236</i>	822.00 <i>32.362</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-274-090-NF	274	9.00 <i>0.354</i>	822.00 <i>32.362</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-279-060-NF	279	6.00 <i>0.236</i>	837.00 <i>32.953</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-279-090-NF	279	9.00 <i>0.354</i>	837.00 <i>32.953</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-281-060-NF	281	6.00 <i>0.236</i>	843.00 <i>33.189</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-281-090-NF	281	9.00 <i>0.354 inches</i>	843.00 <i>33.189 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-291-060-NF	291	6.00 <i>0.236 inches</i>	873.00 <i>34.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-291-090-NF	291	9.00 <i>0.354 inches</i>	873.00 <i>34.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-294-060-NF	294	6.00 <i>0.236 inches</i>	882.00 <i>34.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-294-090-NF	294	9.00 <i>0.354 inches</i>	882.00 <i>34.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-297-060-NF	297	6.00 <i>0.236 inches</i>	891.00 <i>35.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-297-090-NF	297	9.00 <i>0.354 inches</i>	891.00 <i>35.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-300-060-NF	300	6.00 <i>0.236 inches</i>	900.00 <i>35.433 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-300-090-NF	300	9.00 <i>0.354 inches</i>	900.00 <i>35.433 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-305-060-NF	305	6.00 <i>0.236 inches</i>	915.00 <i>36.024 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-305-090-NF	305	9.00 <i>0.354 inches</i>	915.00 <i>36.024 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-315-060-NF	315	6.00 <i>0.236 inches</i>	945.00 <i>37.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-315-090-NF	315	9.00 <i>0.354 inches</i>	945.00 <i>37.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-327-060-NF	327	6.00 <i>0.236 inches</i>	981.00 <i>38.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-327-090-NF	327	9.00 <i>0.354 inches</i>	981.00 <i>38.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-334-060-NF	334	6.00 <i>0.236 inches</i>	1002.00 <i>39.449 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-334-090-NF	334	9.00 <i>0.354</i>	1002.00 <i>39.449</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-342-060-NF	342	6.00 <i>0.236</i>	1026.00 <i>40.394</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-342-090-NF	342	9.00 <i>0.354</i>	1026.00 <i>40.394</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-345-060-NF	345	6.00 <i>0.236</i>	1035.00 <i>40.748</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-345-090-NF	345	9.00 <i>0.354</i>	1035.00 <i>40.748</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-347-060-NF	347	6.00 <i>0.236</i>	1041.00 <i>40.984</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-347-090-NF	347	9.00 <i>0.354</i>	1041.00 <i>40.984</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-352-060-NF	352	6.00 <i>0.236</i>	1056.00 <i>41.575</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-352-090-NF	352	9.00 <i>0.354 inches</i>	1056.00 <i>41.575 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-354-060-NF	354	6.00 <i>0.236 inches</i>	1062.00 <i>41.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-354-090-NF	354	9.00 <i>0.354 inches</i>	1062.00 <i>41.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-356-060-NF	356	6.00 <i>0.236 inches</i>	1068.00 <i>42.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-356-090-NF	356	9.00 <i>0.354 inches</i>	1068.00 <i>42.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-375-060-NF	375	6.00 <i>0.236 inches</i>	1125.00 <i>44.291 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-375-090-NF	375	9.00 <i>0.354 inches</i>	1125.00 <i>44.291 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-385-060-NF	385	6.00 <i>0.236 inches</i>	1155.00 <i>45.472 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-385-090-NF	385	9.00 <i>0.354 inches</i>	1155.00 <i>45.472 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-397-060-NF	397	6.00 <i>0.236 inches</i>	1191.00 <i>46.890 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-397-090-NF	397	9.00 <i>0.354 inches</i>	1191.00 <i>46.890 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-421-060-NF	421	6.00 <i>0.236 inches</i>	1263.00 <i>49.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-421-090-NF	421	9.00 <i>0.354 inches</i>	1263.00 <i>49.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-500-060-NF	500	6.00 <i>0.236 inches</i>	1500.00 <i>59.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-500-090-NF	500	9.00 <i>0.354 inches</i>	1500.00 <i>59.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-504-060-NF	504	6.00 <i>0.236 inches</i>	1512.00 <i>59.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-504-090-NF	504	9.00 <i>0.354 inches</i>	1512.00 <i>59.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-523-060-NF	523	6.00 <i>0.236 inches</i>	1569.00 <i>61.772 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-523-090-NF	523	9.00 <i>0.354 inches</i>	1569.00 <i>61.772 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-529-060-NF	529	6.00 <i>0.236 inches</i>	1587.00 <i>62.480 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-529-090-NF	529	9.00 <i>0.354 inches</i>	1587.00 <i>62.480 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-600-060-NF	600	6.00 <i>0.236 inches</i>	1800.00 <i>70.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-600-090-NF	600	9.00 <i>0.354 inches</i>	1800.00 <i>70.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-652-060-NF	652	6.00 <i>0.236 inches</i>	1956.00 <i>77.008 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD Double Sided

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# BD-H3-652-090-NF	652	9.00 <i>0.354 inches</i>	1956.00 <i>77.008 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# BD-H3-668-060-NF	668	6.00 <i>0.236 inches</i>	2004.00 <i>78.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# BD-H3-668-090-NF	668	9.00 <i>0.354 inches</i>	2004.00 <i>78.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

