




MBA

Belts - Timing - 3.000mm Pitch - HTD



HTD Series Metric Timing Belts.

Pitch (P) - 3.000mm.

Tooth Height (H) - 1.22mm.

Belt Height (W) - 2.41mm.

Breaking strength is not indicative of working strength.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
B-H3-029-060-NF	29	6.00 <i>0.236 inches</i>	87.00 <i>3.425 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-029-090-NF	29	9.00 <i>0.354 inches</i>	87.00 <i>3.425 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-034-060-NF	34	6.00 <i>0.236 inches</i>	102.00 <i>4.016 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-034-090-NF	34	9.00 <i>0.354 inches</i>	102.00 <i>4.016 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-035-060-NF	35	6.00 <i>0.236 inches</i>	105.00 <i>4.134 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-035-090-NF	35	9.00 <i>0.354 inches</i>	105.00 <i>4.134 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-037-060-NF	37	6.00 <i>0.236 inches</i>	111.00 <i>4.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-037-090-NF	37	9.00 <i>0.354 inches</i>	111.00 <i>4.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-040-060-NF	40	6.00 <i>0.236 inches</i>	120.00 <i>4.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-040-090-NF	40	9.00 <i>0.354 inches</i>	120.00 <i>4.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-041-060-NF	41	6.00 <i>0.236 inches</i>	123.00 <i>4.843 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
B-H3-041-090-NF	41	9.00 <i>0.354 inches</i>	123.00 <i>4.843 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-042-060-NF	42	6.00 <i>0.236 inches</i>	126.00 <i>4.961 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-042-090-NF	42	9.00 <i>0.354 inches</i>	126.00 <i>4.961 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-043-060-NF	43	6.00 <i>0.236 inches</i>	129.00 <i>5.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-043-090-NF	43	9.00 <i>0.354 inches</i>	129.00 <i>5.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-047-060-NF	47	6.00 <i>0.236 inches</i>	141.00 <i>5.551 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-047-090-NF	47	9.00 <i>0.354 inches</i>	141.00 <i>5.551 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-048-060-NF	48	6.00 <i>0.236 inches</i>	144.00 <i>5.669 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-048-090-NF	48	9.00 <i>0.354 inches</i>	144.00 <i>5.669 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-049-060-NF	49	6.00 <i>0.236 inches</i>	147.00 <i>5.787 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-049-090-NF	49	9.00 <i>0.354 inches</i>	147.00 <i>5.787 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-050-060-NF	50	6.00 <i>0.236 inches</i>	150.00 <i>5.906 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-050-090-NF	50	9.00 <i>0.354 inches</i>	150.00 <i>5.906 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-052-060-NF	52	6.00 <i>0.236 inches</i>	156.00 <i>6.142 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-052-090-NF	52	9.00 <i>0.354 inches</i>	156.00 <i>6.142 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-053-060-NF	53	6.00 <i>0.236 inches</i>	159.00 <i>6.260 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-053-090-NF	53	9.00 <i>0.354 inches</i>	159.00 <i>6.260 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-055-060-NF	55	6.00 <i>0.236 inches</i>	165.00 <i>6.496 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-055-090-NF	55	9.00 <i>0.354 inches</i>	165.00 <i>6.496 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-056-060-NF	56	6.00 <i>0.236 inches</i>	168.00 <i>6.614 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-056-090-NF	56	9.00 <i>0.354 inches</i>	168.00 <i>6.614 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-058-060-NF	58	6.00 <i>0.236 inches</i>	174.00 <i>6.850 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-058-090-NF	58	9.00 <i>0.354 inches</i>	174.00 <i>6.850 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-059-060-NF	59	6.00 <i>0.236 inches</i>	177.00 <i>6.969 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-059-090-NF	59	9.00 <i>0.354 inches</i>	177.00 <i>6.969 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-060-060-NF	60	6.00 <i>0.236 inches</i>	180.00 <i>7.087 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-060-090-NF	60	9.00 <i>0.354 inches</i>	180.00 <i>7.087 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-061-060-NF	61	6.00 <i>0.236 inches</i>	183.00 <i>7.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-061-090-NF	61	9.00 <i>0.354 inches</i>	183.00 <i>7.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-062-060-NF	62	6.00 <i>0.236 inches</i>	186.00 <i>7.323 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-062-090-NF	62	9.00 <i>0.354 inches</i>	186.00 <i>7.323 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-063-060-NF	63	6.00 <i>0.236 inches</i>	189.00 <i>7.441 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-063-090-NF	63	9.00 <i>0.354 inches</i>	189.00 <i>7.441 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-064-060-NF	64	6.00 <i>0.236 inches</i>	192.00 <i>7.559 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-064-090-NF	64	9.00 <i>0.354 inches</i>	192.00 <i>7.559 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-065-060-NF	65	6.00 <i>0.236 inches</i>	195.00 <i>7.677 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-065-090-NF	65	9.00 <i>0.354 inches</i>	195.00 <i>7.677 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-067-060-NF	67	6.00 <i>0.236 inches</i>	201.00 <i>7.913 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-067-090-NF	67	9.00 <i>0.354 inches</i>	201.00 <i>7.913 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-068-060-NF	68	6.00 <i>0.236 inches</i>	204.00 <i>8.031 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-068-090-NF	68	9.00 <i>0.354 inches</i>	204.00 <i>8.031 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-069-060-NF	69	6.00 <i>0.236 inches</i>	207.00 <i>8.150 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-069-090-NF	69	9.00 <i>0.354 inches</i>	207.00 <i>8.150 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-070-060-NF	70	6.00 <i>0.236 inches</i>	210.00 <i>8.268 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-070-090-NF	70	9.00 <i>0.354 inches</i>	210.00 <i>8.268 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-071-060-NF	71	6.00 <i>0.236 inches</i>	213.00 <i>8.386 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-071-090-NF	71	9.00 <i>0.354 inches</i>	213.00 <i>8.386 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-072-060-NF	72	6.00 <i>0.236 inches</i>	216.00 <i>8.504 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-072-090-NF	72	9.00 <i>0.354 inches</i>	216.00 <i>8.504 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-073-060-NF	73	6.00 <i>0.236 inches</i>	219.00 <i>8.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-073-090-NF	73	9.00 <i>0.354 inches</i>	219.00 <i>8.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-074-060-NF	74	6.00 <i>0.236 inches</i>	222.00 <i>8.740 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-074-090-NF	74	9.00 <i>0.354 inches</i>	222.00 <i>8.740 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-075-060-NF	75	6.00 <i>0.236 inches</i>	225.00 <i>8.858 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-075-090-NF	75	9.00 <i>0.354 inches</i>	225.00 <i>8.858 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-076-060-NF	76	6.00 <i>0.236 inches</i>	228.00 <i>8.976 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-076-090-NF	76	9.00 <i>0.354 inches</i>	228.00 <i>8.976 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-078-060-NF	78	6.00 <i>0.236 inches</i>	234.00 <i>9.213 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-078-090-NF	78	9.00 <i>0.354 inches</i>	234.00 <i>9.213 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-079-060-NF	79	6.00 <i>0.236 inches</i>	237.00 <i>9.331 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-079-090-NF	79	9.00 <i>0.354 inches</i>	237.00 <i>9.331 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-080-060-NF	80	6.00 <i>0.236 inches</i>	240.00 <i>9.449 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-080-090-NF	80	9.00 <i>0.354 inches</i>	240.00 <i>9.449 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-081-060-NF	81	6.00 <i>0.236 inches</i>	243.00 <i>9.567 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-081-090-NF	81	9.00 <i>0.354 inches</i>	243.00 <i>9.567 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-082-060-NF	82	6.00 <i>0.236 inches</i>	246.00 <i>9.685 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-082-090-NF	82	9.00 <i>0.354 inches</i>	246.00 <i>9.685 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-083-060-NF	83	6.00 <i>0.236 inches</i>	249.00 <i>9.803 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-083-090-NF	83	9.00 <i>0.354 inches</i>	249.00 <i>9.803 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-084-060-NF	84	6.00 <i>0.236 inches</i>	252.00 <i>9.921 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-084-090-NF	84	9.00 <i>0.354 inches</i>	252.00 <i>9.921 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-085-060-NF	85	6.00 <i>0.236 inches</i>	255.00 <i>10.039 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-085-090-NF	85	9.00 <i>0.354 inches</i>	255.00 <i>10.039 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-086-060-NF	86	6.00 <i>0.236 inches</i>	258.00 <i>10.157 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-086-090-NF	86	9.00 <i>0.354 inches</i>	258.00 <i>10.157 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-087-060-NF	87	6.00 <i>0.236 inches</i>	261.00 <i>10.276 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-087-090-NF	87	9.00 <i>0.354 inches</i>	261.00 <i>10.276 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-088-060-NF	88	6.00 <i>0.236 inches</i>	264.00 <i>10.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-088-090-NF	88	9.00 <i>0.354 inches</i>	264.00 <i>10.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-089-060-NF	89	6.00 <i>0.236 inches</i>	267.00 <i>10.512 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-089-090-NF	89	9.00 <i>0.354 inches</i>	267.00 <i>10.512 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-090-060-NF	90	6.00 <i>0.236 inches</i>	270.00 <i>10.630 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-090-090-NF	90	9.00 <i>0.354 inches</i>	270.00 <i>10.630 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-092-060-NF	92	6.00 <i>0.236 inches</i>	276.00 <i>10.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-092-090-NF	92	9.00 <i>0.354 inches</i>	276.00 <i>10.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-094-060-NF	94	6.00 <i>0.236 inches</i>	282.00 <i>11.102 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-094-090-NF	94	9.00 <i>0.354 inches</i>	282.00 <i>11.102 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-095-060-NF	95	6.00 <i>0.236 inches</i>	285.00 <i>11.220 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-095-090-NF	95	9.00 <i>0.354 inches</i>	285.00 <i>11.220 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-096-060-NF	96	6.00 <i>0.236 inches</i>	288.00 <i>11.339 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-096-090-NF	96	9.00 <i>0.354 inches</i>	288.00 <i>11.339 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-097-060-NF	97	6.00 <i>0.236 inches</i>	291.00 <i>11.457 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-097-090-NF	97	9.00 <i>0.354 inches</i>	291.00 <i>11.457 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-098-060-NF	98	6.00 <i>0.236 inches</i>	294.00 <i>11.575 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-098-090-NF	98	9.00 <i>0.354 inches</i>	294.00 <i>11.575 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-099-060-NF	99	6.00 <i>0.236 inches</i>	297.00 <i>11.693 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
B-H3-099-090-NF	99	9.00 <i>0.354 inches</i>	297.00 <i>11.693 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-100-060-NF	100	6.00 <i>0.236 inches</i>	300.00 <i>11.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-100-090-NF	100	9.00 <i>0.354 inches</i>	300.00 <i>11.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-102-060-NF	102	6.00 <i>0.236 inches</i>	306.00 <i>12.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-102-090-NF	102	9.00 <i>0.354 inches</i>	306.00 <i>12.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-104-060-NF	104	6.00 <i>0.236 inches</i>	312.00 <i>12.283 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-104-090-NF	104	9.00 <i>0.354 inches</i>	312.00 <i>12.283 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-105-060-NF	105	6.00 <i>0.236 inches</i>	315.00 <i>12.402 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-105-090-NF	105	9.00 <i>0.354 inches</i>	315.00 <i>12.402 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-106-060-NF	106	6.00 <i>0.236 inches</i>	318.00 <i>12.520 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-106-090-NF	106	9.00 <i>0.354 inches</i>	318.00 <i>12.520 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-108-060-NF	108	6.00 <i>0.236 inches</i>	324.00 <i>12.756 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-108-090-NF	108	9.00 <i>0.354 inches</i>	324.00 <i>12.756 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-110-060-NF	110	6.00 <i>0.236 inches</i>	330.00 <i>12.992 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-110-090-NF	110	9.00 <i>0.354 inches</i>	330.00 <i>12.992 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-111-060-NF	111	6.00 <i>0.236 inches</i>	333.00 <i>13.110 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-111-090-NF	111	9.00 <i>0.354 inches</i>	333.00 <i>13.110 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-112-060-NF	112	6.00 <i>0.236 inches</i>	336.00 <i>13.228 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-112-090-NF	112	9.00 <i>0.354 inches</i>	336.00 <i>13.228 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-113-060-NF	113	6.00 <i>0.236 inches</i>	339.00 <i>13.346 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-113-090-NF	113	9.00 <i>0.354 inches</i>	339.00 <i>13.346 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-115-060-NF	115	6.00 <i>0.236 inches</i>	345.00 <i>13.583 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-115-090-NF	115	9.00 <i>0.354 inches</i>	345.00 <i>13.583 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-119-060-NF	119	6.00 <i>0.236 inches</i>	357.00 <i>14.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-119-090-NF	119	9.00 <i>0.354 inches</i>	357.00 <i>14.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-120-060-NF	120	6.00 <i>0.236 inches</i>	360.00 <i>14.173 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-120-090-NF	120	9.00 <i>0.354 inches</i>	360.00 <i>14.173 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-121-060-NF	121	6.00 <i>0.236 inches</i>	363.00 <i>14.291 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-121-090-NF	121	9.00 <i>0.354 inches</i>	363.00 <i>14.291 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-122-060-NF	122	6.00 <i>0.236 inches</i>	366.00 <i>14.409 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-122-090-NF	122	9.00 <i>0.354 inches</i>	366.00 <i>14.409 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-123-060-NF	123	6.00 <i>0.236 inches</i>	369.00 <i>14.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-123-090-NF	123	9.00 <i>0.354 inches</i>	369.00 <i>14.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-124-060-NF	124	6.00 <i>0.236 inches</i>	372.00 <i>14.646 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-124-090-NF	124	9.00 <i>0.354 inches</i>	372.00 <i>14.646 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-127-060-NF	127	6.00 <i>0.236 inches</i>	381.00 <i>15.000 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-127-090-NF	127	9.00 <i>0.354 inches</i>	381.00 <i>15.000 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-128-060-NF	128	6.00 <i>0.236 inches</i>	384.00 <i>15.118 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-128-090-NF	128	9.00 <i>0.354 inches</i>	384.00 <i>15.118 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-130-060-NF	130	6.00 <i>0.236 inches</i>	390.00 <i>15.354 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-130-090-NF	130	9.00 <i>0.354 inches</i>	390.00 <i>15.354 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-132-060-NF	132	6.00 <i>0.236 inches</i>	396.00 <i>15.591 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-132-090-NF	132	9.00 <i>0.354 inches</i>	396.00 <i>15.591 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-133-060-NF	133	6.00 <i>0.236 inches</i>	399.00 <i>15.709 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-133-090-NF	133	9.00 <i>0.354 inches</i>	399.00 <i>15.709 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-135-060-NF	135	6.00 <i>0.236 inches</i>	405.00 <i>15.945 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-135-090-NF	135	9.00 <i>0.354 inches</i>	405.00 <i>15.945 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-137-060-NF	137	6.00 <i>0.236 inches</i>	411.00 <i>16.181 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-137-090-NF	137	9.00 <i>0.354 inches</i>	411.00 <i>16.181 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-139-060-NF	139	6.00 <i>0.236 inches</i>	417.00 <i>16.417 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-139-090-NF	139	9.00 <i>0.354 inches</i>	417.00 <i>16.417 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-140-060-NF	140	6.00 <i>0.236 inches</i>	420.00 <i>16.535 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-140-090-NF	140	9.00 <i>0.354 inches</i>	420.00 <i>16.535 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-142-060-NF	142	6.00 <i>0.236 inches</i>	426.00 <i>16.772 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-142-090-NF	142	9.00 <i>0.354 inches</i>	426.00 <i>16.772 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-144-060-NF	144	6.00 <i>0.236 inches</i>	432.00 <i>17.008 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-144-090-NF	144	9.00 <i>0.354 inches</i>	432.00 <i>17.008 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-145-060-NF	145	6.00 <i>0.236 inches</i>	435.00 <i>17.126 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-145-090-NF	145	9.00 <i>0.354 inches</i>	435.00 <i>17.126 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-146-060-NF	146	6.00 <i>0.236 inches</i>	438.00 <i>17.244 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-146-090-NF	146	9.00 <i>0.354 inches</i>	438.00 <i>17.244 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-148-060-NF	148	6.00 <i>0.236 inches</i>	444.00 <i>17.480 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-148-090-NF	148	9.00 <i>0.354 inches</i>	444.00 <i>17.480 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-149-060-NF	149	6.00 <i>0.236 inches</i>	447.00 <i>17.598 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-149-090-NF	149	9.00 <i>0.354 inches</i>	447.00 <i>17.598 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-153-060-NF	153	6.00 <i>0.236 inches</i>	459.00 <i>18.071 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-153-090-NF	153	9.00 <i>0.354 inches</i>	459.00 <i>18.071 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-154-060-NF	154	6.00 <i>0.236 inches</i>	462.00 <i>18.189 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-154-090-NF	154	9.00 <i>0.354 inches</i>	462.00 <i>18.189 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-155-060-NF	155	6.00 <i>0.236 inches</i>	465.00 <i>18.307 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-155-090-NF	155	9.00 <i>0.354 inches</i>	465.00 <i>18.307 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-156-060-NF	156	6.00 <i>0.236 inches</i>	468.00 <i>18.425 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-156-090-NF	156	9.00 <i>0.354 inches</i>	468.00 <i>18.425 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-157-060-NF	157	6.00 <i>0.236 inches</i>	471.00 <i>18.543 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-157-090-NF	157	9.00 <i>0.354 inches</i>	471.00 <i>18.543 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-158-060-NF	158	6.00 <i>0.236 inches</i>	474.00 <i>18.661 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-158-090-NF	158	9.00 <i>0.354 inches</i>	474.00 <i>18.661 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-159-060-NF	159	6.00 <i>0.236 inches</i>	477.00 <i>18.780 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-159-090-NF	159	9.00 <i>0.354 inches</i>	477.00 <i>18.780 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-160-060-NF	160	6.00 <i>0.236 inches</i>	480.00 <i>18.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-160-090-NF	160	9.00 <i>0.354 inches</i>	480.00 <i>18.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-162-060-NF	162	6.00 <i>0.236 inches</i>	486.00 <i>19.134 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-162-090-NF	162	9.00 <i>0.354 inches</i>	486.00 <i>19.134 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-163-060-NF	163	6.00 <i>0.236 inches</i>	489.00 <i>19.252 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-163-090-NF	163	9.00 <i>0.354 inches</i>	489.00 <i>19.252 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-164-060-NF	164	6.00 <i>0.236 inches</i>	492.00 <i>19.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-164-090-NF	164	9.00 <i>0.354 inches</i>	492.00 <i>19.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-167-060-NF	167	6.00 <i>0.236 inches</i>	501.00 <i>19.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-167-090-NF	167	9.00 <i>0.354 inches</i>	501.00 <i>19.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-168-060-NF	168	6.00 <i>0.236 inches</i>	504.00 <i>19.843 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-168-090-NF	168	9.00 <i>0.354 inches</i>	504.00 <i>19.843 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-170-060-NF	170	6.00 <i>0.236 inches</i>	510.00 <i>20.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-170-090-NF	170	9.00 <i>0.354 inches</i>	510.00 <i>20.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-171-060-NF	171	6.00 <i>0.236 inches</i>	513.00 <i>20.197 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-171-090-NF	171	9.00 <i>0.354 inches</i>	513.00 <i>20.197 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-173-060-NF	173	6.00 <i>0.236 inches</i>	519.00 <i>20.433 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-173-090-NF	173	9.00 <i>0.354 inches</i>	519.00 <i>20.433 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-174-060-NF	174	6.00 <i>0.236 inches</i>	522.00 <i>20.551 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-174-090-NF	174	9.00 <i>0.354 inches</i>	522.00 <i>20.551 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-175-060-NF	175	6.00 <i>0.236 inches</i>	525.00 <i>20.669 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-175-090-NF	175	9.00 <i>0.354 inches</i>	525.00 <i>20.669 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-176-060-NF	176	6.00 <i>0.236 inches</i>	528.00 <i>20.787 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-176-090-NF	176	9.00 <i>0.354 inches</i>	528.00 <i>20.787 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-177-060-NF	177	6.00 <i>0.236 inches</i>	531.00 <i>20.906 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-177-090-NF	177	9.00 <i>0.354 inches</i>	531.00 <i>20.906 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-179-060-NF	179	6.00 <i>0.236 inches</i>	537.00 <i>21.142 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-179-090-NF	179	9.00 <i>0.354 inches</i>	537.00 <i>21.142 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-184-060-NF	184	6.00 <i>0.236 inches</i>	552.00 <i>21.732 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-184-090-NF	184	9.00 <i>0.354 inches</i>	552.00 <i>21.732 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-186-060-NF	186	6.00 <i>0.236 inches</i>	558.00 <i>21.969 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-186-090-NF	186	9.00 <i>0.354 inches</i>	558.00 <i>21.969 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-188-060-NF	188	6.00 <i>0.236 inches</i>	564.00 <i>22.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
B-H3-188-090-NF	188	9.00 <i>0.354 inches</i>	564.00 <i>22.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-190-060-NF	190	6.00 <i>0.236 inches</i>	570.00 <i>22.441 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-190-090-NF	190	9.00 <i>0.354 inches</i>	570.00 <i>22.441 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-191-060-NF	191	6.00 <i>0.236 inches</i>	573.00 <i>22.559 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-191-090-NF	191	9.00 <i>0.354 inches</i>	573.00 <i>22.559 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-192-060-NF	192	6.00 <i>0.236 inches</i>	576.00 <i>22.677 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-192-090-NF	192	9.00 <i>0.354 inches</i>	576.00 <i>22.677 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-194-060-NF	194	6.00 <i>0.236 inches</i>	582.00 <i>22.913 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-194-090-NF	194	9.00 <i>0.354 inches</i>	582.00 <i>22.913 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-195-060-NF	195	6.00 <i>0.236 inches</i>	585.00 <i>23.031 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-195-090-NF	195	9.00 <i>0.354 inches</i>	585.00 <i>23.031 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-197-060-NF	197	6.00 <i>0.236 inches</i>	591.00 <i>23.268 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-197-090-NF	197	9.00 <i>0.354 inches</i>	591.00 <i>23.268 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-198-060-NF	198	6.00 <i>0.236 inches</i>	594.00 <i>23.386 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-198-090-NF	198	9.00 <i>0.354 inches</i>	594.00 <i>23.386 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-199-060-NF	199	6.00 <i>0.236 inches</i>	597.00 <i>23.504 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-199-090-NF	199	9.00 <i>0.354 inches</i>	597.00 <i>23.504 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-200-060-NF	200	6.00 <i>0.236 inches</i>	600.00 <i>23.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-200-090-NF	200	9.00 <i>0.354 inches</i>	600.00 <i>23.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-202-060-NF	202	6.00 <i>0.236 inches</i>	606.00 <i>23.858 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-202-090-NF	202	9.00 <i>0.354 inches</i>	606.00 <i>23.858 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-203-060-NF	203	6.00 <i>0.236 inches</i>	609.00 <i>23.976 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-203-090-NF	203	9.00 <i>0.354 inches</i>	609.00 <i>23.976 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-204-060-NF	204	6.00 <i>0.236 inches</i>	612.00 <i>24.094 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-204-090-NF	204	9.00 <i>0.354 inches</i>	612.00 <i>24.094 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-209-060-NF	209	6.00 <i>0.236 inches</i>	627.00 <i>24.685 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-209-090-NF	209	9.00 <i>0.354 inches</i>	627.00 <i>24.685 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-211-060-NF	211	6.00 <i>0.236 inches</i>	633.00 <i>24.921 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-211-090-NF	211	9.00 <i>0.354 inches</i>	633.00 <i>24.921 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-213-060-NF	213	6.00 <i>0.236 inches</i>	639.00 <i>25.157 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-213-090-NF	213	9.00 <i>0.354 inches</i>	639.00 <i>25.157 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-215-060-NF	215	6.00 <i>0.236 inches</i>	645.00 <i>25.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-215-090-NF	215	9.00 <i>0.354 inches</i>	645.00 <i>25.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-216-060-NF	216	6.00 <i>0.236 inches</i>	648.00 <i>25.512 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-216-090-NF	216	9.00 <i>0.354 inches</i>	648.00 <i>25.512 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-218-060-NF	218	6.00 <i>0.236 inches</i>	654.00 <i>25.748 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-218-090-NF	218	9.00 <i>0.354 inches</i>	654.00 <i>25.748 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-219-060-NF	219	6.00 <i>0.236 inches</i>	657.00 <i>25.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-219-090-NF	219	9.00 <i>0.354 inches</i>	657.00 <i>25.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-221-060-NF	221	6.00 <i>0.236 inches</i>	663.00 <i>26.102 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-221-090-NF	221	9.00 <i>0.354 inches</i>	663.00 <i>26.102 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-223-060-NF	223	6.00 <i>0.236 inches</i>	669.00 <i>26.339 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
B-H3-223-090-NF	223	9.00 <i>0.354 inches</i>	669.00 <i>26.339 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-224-060-NF	224	6.00 <i>0.236 inches</i>	672.00 <i>26.457 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-224-090-NF	224	9.00 <i>0.354 inches</i>	672.00 <i>26.457 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-227-060-NF	227	6.00 <i>0.236 inches</i>	681.00 <i>26.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-227-090-NF	227	9.00 <i>0.354 inches</i>	681.00 <i>26.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-228-060-NF	228	6.00 <i>0.236 inches</i>	684.00 <i>26.929 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-228-090-NF	228	9.00 <i>0.354 inches</i>	684.00 <i>26.929 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-229-060-NF	229	6.00 <i>0.236 inches</i>	687.00 <i>27.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-229-090-NF	229	9.00 <i>0.354 inches</i>	687.00 <i>27.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-232-060-NF	232	6.00 <i>0.236 inches</i>	696.00 <i>27.402 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-232-090-NF	232	9.00 <i>0.354 inches</i>	696.00 <i>27.402 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-236-060-NF	236	6.00 <i>0.236 inches</i>	708.00 <i>27.874 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-236-090-NF	236	9.00 <i>0.354 inches</i>	708.00 <i>27.874 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-237-060-NF	237	6.00 <i>0.236 inches</i>	711.00 <i>27.992 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-237-090-NF	237	9.00 <i>0.354 inches</i>	711.00 <i>27.992 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-240-060-NF	240	6.00 <i>0.236 inches</i>	720.00 <i>28.346 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-240-090-NF	240	9.00 <i>0.354 inches</i>	720.00 <i>28.346 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-245-060-NF	245	6.00 <i>0.236 inches</i>	735.00 <i>28.937 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-245-090-NF	245	9.00 <i>0.354 inches</i>	735.00 <i>28.937 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-246-060-NF	246	6.00 <i>0.236 inches</i>	738.00 <i>29.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-246-090-NF	246	9.00 <i>0.354 inches</i>	738.00 <i>29.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-250-060-NF	250	6.00 <i>0.236 inches</i>	750.00 <i>29.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-250-090-NF	250	9.00 <i>0.354 inches</i>	750.00 <i>29.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-251-060-NF	251	6.00 <i>0.236 inches</i>	753.00 <i>29.646 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-251-090-NF	251	9.00 <i>0.354 inches</i>	753.00 <i>29.646 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-265-060-NF	265	6.00 <i>0.236 inches</i>	795.00 <i>31.299 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-265-090-NF	265	9.00 <i>0.354 inches</i>	795.00 <i>31.299 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-268-060-NF	268	6.00 <i>0.236 inches</i>	804.00 <i>31.654 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-268-090-NF	268	9.00 <i>0.354 inches</i>	804.00 <i>31.654 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-274-060-NF	274	6.00 <i>0.236 inches</i>	822.00 <i>32.362 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-274-090-NF	274	9.00 <i>0.354 inches</i>	822.00 <i>32.362 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-279-060-NF	279	6.00 <i>0.236 inches</i>	837.00 <i>32.953 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-279-090-NF	279	9.00 <i>0.354 inches</i>	837.00 <i>32.953 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-281-060-NF	281	6.00 <i>0.236 inches</i>	843.00 <i>33.189 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-281-090-NF	281	9.00 <i>0.354 inches</i>	843.00 <i>33.189 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-291-060-NF	291	6.00 <i>0.236 inches</i>	873.00 <i>34.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-291-090-NF	291	9.00 <i>0.354 inches</i>	873.00 <i>34.370 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-294-060-NF	294	6.00 <i>0.236 inches</i>	882.00 <i>34.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-294-090-NF	294	9.00 <i>0.354 inches</i>	882.00 <i>34.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-297-060-NF	297	6.00 <i>0.236 inches</i>	891.00 <i>35.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-297-090-NF	297	9.00 <i>0.354 inches</i>	891.00 <i>35.079 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-300-060-NF	300	6.00 <i>0.236 inches</i>	900.00 <i>35.433 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-300-090-NF	300	9.00 <i>0.354 inches</i>	900.00 <i>35.433 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-305-060-NF	305	6.00 <i>0.236 inches</i>	915.00 <i>36.024 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-305-090-NF	305	9.00 <i>0.354 inches</i>	915.00 <i>36.024 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-315-060-NF	315	6.00 <i>0.236 inches</i>	945.00 <i>37.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-315-090-NF	315	9.00 <i>0.354 inches</i>	945.00 <i>37.205 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-327-060-NF	327	6.00 <i>0.236 inches</i>	981.00 <i>38.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-327-090-NF	327	9.00 <i>0.354 inches</i>	981.00 <i>38.622 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-334-060-NF	334	6.00 <i>0.236 inches</i>	1002.00 <i>39.449 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-334-090-NF	334	9.00 <i>0.354 inches</i>	1002.00 <i>39.449 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-342-060-NF	342	6.00 <i>0.236 inches</i>	1026.00 <i>40.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-342-090-NF	342	9.00 <i>0.354 inches</i>	1026.00 <i>40.394 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-345-060-NF	345	6.00 <i>0.236 inches</i>	1035.00 <i>40.748 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
B-H3-345-090-NF	345	9.00 <i>0.354 inches</i>	1035.00 <i>40.748 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-347-060-NF	347	6.00 <i>0.236 inches</i>	1041.00 <i>40.984 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-347-090-NF	347	9.00 <i>0.354 inches</i>	1041.00 <i>40.984 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-352-060-NF	352	6.00 <i>0.236 inches</i>	1056.00 <i>41.575 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-352-090-NF	352	9.00 <i>0.354 inches</i>	1056.00 <i>41.575 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-354-060-NF	354	6.00 <i>0.236 inches</i>	1062.00 <i>41.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-354-090-NF	354	9.00 <i>0.354 inches</i>	1062.00 <i>41.811 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-356-060-NF	356	6.00 <i>0.236 inches</i>	1068.00 <i>42.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-356-090-NF	356	9.00 <i>0.354 inches</i>	1068.00 <i>42.047 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-357-060-NF	357	6.00 <i>0.236 inches</i>	1071.00 <i>42.165 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-357-090-NF	357	9.00 <i>0.354 inches</i>	1071.00 <i>42.165 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-360-060-NF	360	6.00 <i>0.236 inches</i>	1080.00 <i>42.520 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-360-090-NF	360	9.00 <i>0.354 inches</i>	1080.00 <i>42.520 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-375-060-NF	375	6.00 <i>0.236 inches</i>	1125.00 <i>44.291 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-375-090-NF	375	9.00 <i>0.354 inches</i>	1125.00 <i>44.291 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-385-060-NF	385	6.00 <i>0.236 inches</i>	1155.00 <i>45.472 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-385-090-NF	385	9.00 <i>0.354 inches</i>	1155.00 <i>45.472 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-397-060-NF	397	6.00 <i>0.236 inches</i>	1191.00 <i>46.890 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-397-090-NF	397	9.00 <i>0.354 inches</i>	1191.00 <i>46.890 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-415-060-NF	415	6.00 <i>0.236 inches</i>	1245.00 <i>49.016 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-415-090-NF	415	9.00 <i>0.354 inches</i>	1245.00 <i>49.016 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-421-060-NF	421	6.00 <i>0.236 inches</i>	1263.00 <i>49.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-421-090-NF	421	9.00 <i>0.354 inches</i>	1263.00 <i>49.724 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-500-060-NF	500	6.00 <i>0.236 inches</i>	1500.00 <i>59.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-500-090-NF	500	9.00 <i>0.354 inches</i>	1500.00 <i>59.055 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-504-060-NF	504	6.00 <i>0.236 inches</i>	1512.00 <i>59.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-504-090-NF	504	9.00 <i>0.354 inches</i>	1512.00 <i>59.528 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-510-060-NF	510	6.00 <i>0.236 inches</i>	1530.00 <i>60.236 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-510-090-NF	510	9.00 <i>0.354 inches</i>	1530.00 <i>60.236 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-523-060-NF	523	6.00 <i>0.236 inches</i>	1569.00 <i>61.772 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-523-090-NF	523	9.00 <i>0.354 inches</i>	1569.00 <i>61.772 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-529-060-NF	529	6.00 <i>0.236 inches</i>	1587.00 <i>62.480 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-529-090-NF	529	9.00 <i>0.354 inches</i>	1587.00 <i>62.480 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-600-060-NF	600	6.00 <i>0.236 inches</i>	1800.00 <i>70.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-600-090-NF	600	9.00 <i>0.354 inches</i>	1800.00 <i>70.866 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-621-060-NF	621	6.00 <i>0.236 inches</i>	1863.00 <i>73.346 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-621-090-NF	621	9.00 <i>0.354 inches</i>	1863.00 <i>73.346 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-642-060-NF	642	6.00 <i>0.236 inches</i>	1926.00 <i>75.827 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-642-090-NF	642	9.00 <i>0.354 inches</i>	1926.00 <i>75.827 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
B-H3-652-060-NF	652	6.00 <i>0.236 inches</i>	1956.00 <i>77.008 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 3.000mm Pitch - HTD

Part Number	Teeth (No.)	Nom. Width mm	Length mm	Material	Reinforcement	Appearance	Breaking Strength N	Min Temperature Deg C	Max Temperature Deg C
# B-H3-652-090-NF	652	9.00 <i>0.354 inches</i>	1956.00 <i>77.008 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85
# B-H3-668-060-NF	668	6.00 <i>0.236 inches</i>	2004.00 <i>78.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	948	-34	85
# B-H3-668-090-NF	668	9.00 <i>0.354 inches</i>	2004.00 <i>78.898 inches</i>	Nylon Covered Neoprene	Fibreglass	Black	1422	-34	85

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
