




MBA

Belts - Timing - 9.525mm Pitch - L



Standard Series Timing Belts 9.525mm or 0.375 inch pitch.

Pitch (P) - 9.525mm (0.200 inch).

Tooth Length (T) - 3.25mm.

Tooth Height (H) - 1.90mm.

Belt Height (W) - 3.56mm - Corner Radii (r) - 0.50mm.

Breaking strength is not indicative of working strength.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-026-127-NF | 26 | 12.70 | 247.65 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>9.750</i> | | | | | | | |
| # B-L9-026-191-NF | 26 | 19.05 | 247.65 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>9.750</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-033-127-NF | 33 | 12.70 <i>0.500</i> | 314.33 <i>12.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-033-191-NF | 33 | 19.05 <i>0.750</i> | 314.33 <i>12.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-033-254-NF | 33 | 25.40 <i>1.000</i> | 314.32 <i>12.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-033-381-NF | 33 | 38.10 <i>1.500</i> | 314.32 <i>12.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-033-508-NF | 33 | 50.80 <i>2.000</i> | 314.32 <i>12.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-036-127-NF | 36 | 12.70 <i>0.500</i> | 342.90 <i>13.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-036-191-NF | 36 | 19.05 <i>0.750</i> | 342.90 <i>13.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-038-127-NF | 38 | 12.70 <i>0.500</i> | 361.95 <i>14.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| # B-L9-038-191-NF | 38 | 19.05 <i>0.750</i> | 361.95 <i>14.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-040-063-NF | 40 | 6.35 <i>0.250</i> | 381 <i>15.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| # B-L9-040-095-NF | 40 | 9.53 <i>0.375</i> | 381 <i>15.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| # B-L9-040-127-NF | 40 | 12.70 <i>0.500</i> | 381.00 <i>15.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-040-191-NF | 40 | 19.05 <i>0.750</i> | 381.00 <i>15.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-040-254-NF | 40 | 25.40 <i>1.000</i> | 381 <i>15.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-040-381-NF | 40 | 38.10 <i>1.500</i> | 381 <i>15.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-041-127-NF | 41 | 12.70 <i>0.500</i> | 390.53 <i>15.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-041-191-NF | 41 | 19.05 <i>0.750</i> | 390.53 <i>15.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-042-127-NF | 42 | 12.70 <i>0.500</i> | 400.05 <i>15.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-042-191-NF | 42 | 19.05 <i>0.750</i> | 400.05 <i>15.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-044-127-NF | 44 | 12.70 <i>0.500</i> | 419.10 <i>16.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-044-191-NF | 44 | 19.05 <i>0.750</i> | 419.10 <i>16.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-045-127-NF | 45 | 12.70 <i>0.500</i> | 428.63 <i>16.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-045-191-NF | 45 | 19.05 <i>0.750</i> | 428.63 <i>16.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-046-127-NF | 46 | 12.70 <i>0.500</i> | 438.15 <i>17.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-046-191-NF | 46 | 19.05 | 438.15 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>17.250</i> | | | | | | | |
| # B-L9-047-127-NF | 47 | 12.70 | 447.68 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>17.625</i> | | | | | | | |
| # B-L9-047-191-NF | 47 | 19.05 | 447.68 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>17.625</i> | | | | | | | |
| # B-L9-050-063-NF | 50 | 6.35 | 476.25 | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| | | <i>0.250</i> | <i>18.750</i> | | | | | | | |
| # B-L9-050-095-NF | 50 | 9.53 | 476.25 | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| | | <i>0.375</i> | <i>18.750</i> | | | | | | | |
| B-L9-050-127-NF | 50 | 12.70 | 476.25 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>18.750</i> | | | | | | | |
| # B-L9-050-191-NF | 50 | 19.05 | 476.25 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>18.750</i> | | | | | | | |
| # B-L9-050-254-NF | 50 | 25.40 | 476.25 | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| | | <i>1.000</i> | <i>18.750</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-050-508-NF | 50 | 50.80 <i>2.000</i> | 476.25 <i>18.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-052-127-NF | 52 | 12.70 <i>0.500</i> | 495.30 <i>19.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-052-191-NF | 52 | 19.05 <i>0.750</i> | 495.30 <i>19.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-053-127-NF | 53 | 12.70 <i>0.500</i> | 504.83 <i>19.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-053-191-NF | 53 | 19.05 <i>0.750</i> | 504.83 <i>19.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-054-127-NF | 54 | 12.70 <i>0.500</i> | 514.35 <i>20.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-054-191-NF | 54 | 19.05 <i>0.750</i> | 514.35 <i>20.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-055-127-NF | 55 | 12.70 <i>0.500</i> | 523.88 <i>20.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-055-191-NF | 55 | 19.05 <i>0.750</i> | 523.88 <i>20.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-056-063-NF | 56 | 6.35 <i>0.250</i> | 533.4 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| # B-L9-056-095-NF | 56 | 9.53 <i>0.375</i> | 533.4 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| # B-L9-056-127-NF | 56 | 12.70 <i>0.500</i> | 533.40 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-056-191-NF | 56 | 19.05 <i>0.750</i> | 533.40 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-056-254-NF | 56 | 25.40 <i>1.000</i> | 533.4 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-056-381-NF | 56 | 38.10 <i>1.500</i> | 533.4 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-056-508-NF | 56 | 50.80 <i>2.000</i> | 533.4 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-056-762-NF | 56 | 76.20 <i>3.000</i> | 533.4 <i>21.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 13332 | -34 | 85 | 40 |
| # B-L9-058-127-NF | 58 | 12.70 <i>0.500</i> | 552.45 <i>21.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-058-191-NF | 58 | 19.05 <i>0.750</i> | 552.45 <i>21.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-060-063-NF | 60 | 6.35 <i>0.250</i> | 571.5 <i>22.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| # B-L9-060-095-NF | 60 | 9.53 <i>0.375</i> | 571.5 <i>22.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| # B-L9-060-127-NF | 60 | 12.70 <i>0.500</i> | 571.50 <i>22.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-060-191-NF | 60 | 19.05 <i>0.750</i> | 571.50 <i>22.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-060-254-NF | 60 | 25.40 <i>1.000</i> | 571.5 <i>22.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|--------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-060-381-NF | 60 | 38.10 <i>1.500</i> | 571.5 <i>22.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-060-1016-NF | 60 | 101.6 <i>4.000</i> | 571.5 <i>22.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 17776 | -34 | 85 | 40 |
| # B-L9-061-127-NF | 61 | 12.70 <i>0.500</i> | 581.03 <i>22.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-061-191-NF | 61 | 19.05 <i>0.750</i> | 581.03 <i>22.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-062-127-NF | 62 | 12.70 <i>0.500</i> | 590.55 <i>23.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-062-191-NF | 62 | 19.05 <i>0.750</i> | 590.55 <i>23.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-063-127-NF | 63 | 12.70 <i>0.500</i> | 600.08 <i>23.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-063-191-NF | 63 | 19.05 <i>0.750</i> | 600.08 <i>23.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-064-095-NF | 64 | 9.53 <i>0.375</i> | 609.6 <i>24.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| # B-L9-064-127-NF | 64 | 12.70 <i>0.500</i> | 609.60 <i>24.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-064-191-NF | 64 | 19.05 <i>0.750</i> | 609.60 <i>24.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-064-254-NF | 64 | 25.40 <i>1.000</i> | 609.6 <i>24.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-064-381-NF | 64 | 38.10 <i>1.500</i> | 609.6 <i>24.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-064-508-NF | 64 | 50.80 <i>2.000</i> | 609.6 <i>24.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-064-762-NF | 64 | 76.20 <i>3.000</i> | 609.6 <i>24.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 13332 | -34 | 85 | 40 |
| # B-L9-065-127-NF | 65 | 12.70 <i>0.500</i> | 619.13 <i>24.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-065-191-NF | 65 | 19.05 <i>0.750</i> | 619.13 <i>24.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-066-127-NF | 66 | 12.70 <i>0.500</i> | 628.65 <i>24.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-066-191-NF | 66 | 19.05 <i>0.750</i> | 628.65 <i>24.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-067-127-NF | 67 | 12.70 <i>0.500</i> | 638.18 <i>25.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-067-191-NF | 67 | 19.05 <i>0.750</i> | 638.18 <i>25.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-068-063-NF | 68 | 6.35 <i>0.250</i> | 647.7 <i>25.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| # B-L9-068-095-NF | 68 | 9.53 <i>0.375</i> | 647.7 <i>25.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| # B-L9-068-127-NF | 68 | 12.70 <i>0.500</i> | 647.70 <i>25.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| B-L9-068-191-NF | 68 | 19.05 | 647.70 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>25.500</i> | | | | | | | |
| # B-L9-068-254-NF | 68 | 25.40 | 647.7 | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| | | <i>1.000</i> | <i>25.500</i> | | | | | | | |
| B-L9-070-127-NF | 70 | 12.70 | 666.75 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>26.250</i> | | | | | | | |
| # B-L9-070-191-NF | 70 | 19.05 | 666.75 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>26.250</i> | | | | | | | |
| # B-L9-071-127-NF | 71 | 12.70 | 676.28 | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>26.625</i> | | | | | | | |
| # B-L9-071-191-NF | 71 | 19.05 | 676.28 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>26.625</i> | | | | | | | |
| # B-L9-072-127-NF | 72 | 12.70 | 685.80 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>27.000</i> | | | | | | | |
| # B-L9-072-191-NF | 72 | 19.05 | 685.80 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>27.000</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-072-254-NF | 72 | 25.40 <i>1.000</i> | 685.8 <i>27.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-072-381-NF | 72 | 38.10 <i>1.500</i> | 685.8 <i>27.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-072-508-NF | 72 | 50.80 <i>2.000</i> | 685.8 <i>27.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-074-127-NF | 74 | 12.70 <i>0.500</i> | 704.85 <i>27.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-074-191-NF | 74 | 19.05 <i>0.750</i> | 704.85 <i>27.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-075-127-NF | 75 | 12.70 <i>0.500</i> | 714.38 <i>28.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-075-191-NF | 75 | 19.05 <i>0.750</i> | 714.38 <i>28.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| B-L9-076-127-NF | 76 | 12.70 <i>0.500</i> | 723.90 <i>28.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| B-L9-076-191-NF | 76 | 19.05 | 723.90 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>28.500</i> | | | | | | | |
| # B-L9-076-254-NF | 76 | 25.40 | 723.9 | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| | | <i>1.000</i> | <i>28.500</i> | | | | | | | |
| # B-L9-076-317-NF | 76 | 31.75 | 723.9 | Nylon Covered Neoprene | Fibreglass | Black | 5546 | -34 | 85 | 40 |
| | | <i>1.250</i> | <i>28.500</i> | | | | | | | |
| # B-L9-076-381-NF | 76 | 38.10 | 723.9 | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| | | <i>1.500</i> | <i>28.500</i> | | | | | | | |
| # B-L9-080-063-NF | 80 | 6.35 | 762 | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| | | <i>0.250</i> | <i>30.000</i> | | | | | | | |
| B-L9-080-127-NF | 80 | 12.70 | 762.00 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>30.000</i> | | | | | | | |
| # B-L9-080-191-NF | 80 | 19.05 | 762.00 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>30.000</i> | | | | | | | |
| # B-L9-080-254-NF | 80 | 25.40 | 762 | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| | | <i>1.000</i> | <i>30.000</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-080-381-NF | 80 | 38.10 <i>1.500</i> | 762 <i>30.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-080-762-NF | 80 | 76.20 <i>3.000</i> | 762 <i>30.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 13332 | -34 | 85 | 40 |
| # B-L9-081-127-NF | 81 | 12.70 <i>0.500</i> | 771.53 <i>30.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-081-191-NF | 81 | 19.05 <i>0.750</i> | 771.53 <i>30.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-082-127-NF | 82 | 12.70 <i>0.500</i> | 781.05 <i>30.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-082-191-NF | 82 | 19.05 <i>0.750</i> | 781.05 <i>30.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-084-127-NF | 84 | 12.70 <i>0.500</i> | 800.10 <i>31.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-084-191-NF | 84 | 19.05 <i>0.750</i> | 800.10 <i>31.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-085-127-NF | 85 | 12.70 <i>0.500</i> | 809.63 <i>31.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-085-191-NF | 85 | 19.05 <i>0.750</i> | 809.63 <i>31.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-086-095-NF | 86 | 9.53 <i>0.375</i> | 819.15 <i>32.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| # B-L9-086-127-NF | 86 | 12.70 <i>0.500</i> | 819.15 <i>32.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-086-191-NF | 86 | 19.05 <i>0.750</i> | 819.15 <i>32.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-086-254-NF | 86 | 25.40 <i>1.000</i> | 819.15 <i>32.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-086-381-NF | 86 | 38.10 <i>1.500</i> | 819.15 <i>32.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-086-508-NF | 86 | 50.80 <i>2.000</i> | 819.15 <i>32.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-087-127-NF | 87 | 12.70 <i>0.500</i> | 828.68 <i>32.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-087-191-NF | 87 | 19.05 <i>0.750</i> | 828.68 <i>32.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-088-127-NF | 88 | 12.70 <i>0.500</i> | 838.20 <i>33.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-088-191-NF | 88 | 19.05 <i>0.750</i> | 838.20 <i>33.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-089-127-NF | 89 | 12.70 <i>0.500</i> | 847.73 <i>33.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-089-191-NF | 89 | 19.05 <i>0.750</i> | 847.73 <i>33.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-090-127-NF | 90 | 12.70 <i>0.500</i> | 857.25 <i>33.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-090-191-NF | 90 | 19.05 <i>0.750</i> | 857.25 <i>33.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-091-127-NF | 91 | 12.70 <i>0.500</i> | 866.78 <i>34.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-091-191-NF | 91 | 19.05 <i>0.750</i> | 866.78 <i>34.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-092-063-NF | 92 | 6.35 <i>0.250</i> | 876.3 <i>34.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| # B-L9-092-127-NF | 92 | 12.70 <i>0.500</i> | 876.30 <i>34.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-092-191-NF | 92 | 19.05 <i>0.750</i> | 876.30 <i>34.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-092-254-NF | 92 | 25.40 <i>1.000</i> | 876.3 <i>34.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-092-381-NF | 92 | 38.10 <i>1.500</i> | 876.3 <i>34.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-093-127-NF | 93 | 12.70 <i>0.500</i> | 885.83 <i>34.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-093-191-NF | 93 | 19.05 <i>0.750</i> | 885.83 <i>34.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-094-127-NF | 94 | 12.70 <i>0.500</i> | 895.35 <i>35.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-094-191-NF | 94 | 19.05 <i>0.750</i> | 895.35 <i>35.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-095-127-NF | 95 | 12.70 <i>0.500</i> | 904.88 <i>35.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-095-191-NF | 95 | 19.05 <i>0.750</i> | 904.88 <i>35.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-096-127-NF | 96 | 12.70 <i>0.500</i> | 914.40 <i>36.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-096-191-NF | 96 | 19.05 <i>0.750</i> | 914.40 <i>36.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-097-127-NF | 97 | 12.70 <i>0.500</i> | 923.93 <i>36.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-098-063-NF | 98 | 6.35 <i>0.250</i> | 933.45 <i>36.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| # B-L9-098-095-NF | 98 | 9.53 <i>0.375</i> | 933.45 <i>36.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| # B-L9-098-127-NF | 98 | 12.70 <i>0.500</i> | 933.45 <i>36.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-098-191-NF | 98 | 19.05 <i>0.750</i> | 933.45 <i>36.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-098-254-NF | 98 | 25.40 <i>1.000</i> | 933.45 <i>36.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-098-381-NF | 98 | 38.10 <i>1.500</i> | 933.45 <i>36.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-099-127-NF | 99 | 12.70 <i>0.500</i> | 942.98 <i>37.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-099-191-NF | 99 | 19.05 <i>0.750</i> | 942.98 <i>37.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|-------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-100-127-NF | 100 | 12.70 <i>0.500</i> | 952.50 <i>37.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-100-191-NF | 100 | 19.05 <i>0.750</i> | 952.50 <i>37.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-101-127-NF | 101 | 12.70 <i>0.500</i> | 962.03 <i>37.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-101-191-NF | 101 | 19.05 <i>0.750</i> | 962.03 <i>37.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-102-191-NF | 102 | 19.05 <i>0.750</i> | 971.55 <i>38.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-103-127-NF | 103 | 12.70 <i>0.500</i> | 981.08 <i>38.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-103-191-NF | 103 | 19.05 <i>0.750</i> | 981.08 <i>38.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-104-127-NF | 104 | 12.70 <i>0.500</i> | 990.60 <i>39.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-104-191-NF | 104 | 19.05 <i>0.750</i> | 990.60 <i>39.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-104-254-NF | 104 | 25.40 <i>1.000</i> | 990.6 <i>39.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-104-381-NF | 104 | 38.10 <i>1.500</i> | 990.6 <i>39.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-104-508-NF | 104 | 50.80 <i>2.000</i> | 990.6 <i>39.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-105-127-NF | 105 | 12.70 <i>0.500</i> | 1000.13 <i>39.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-105-191-NF | 105 | 19.05 <i>0.750</i> | 1000.13 <i>39.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-106-127-NF | 106 | 12.70 <i>0.500</i> | 1009.65 <i>39.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-106-191-NF | 106 | 19.05 <i>0.750</i> | 1009.65 <i>39.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-108-127-NF | 108 | 12.70 | 1028.70 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>40.500</i> | | | | | | | |
| # B-L9-108-191-NF | 108 | 19.05 | 1028.70 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>40.500</i> | | | | | | | |
| # B-L9-109-127-NF | 109 | 12.70 | 1038.23 | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>40.875</i> | | | | | | | |
| # B-L9-109-191-NF | 109 | 19.05 | 1038.23 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>40.875</i> | | | | | | | |
| # B-L9-110-127-NF | 110 | 12.70 | 1047.75 | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>41.250</i> | | | | | | | |
| # B-L9-110-191-NF | 110 | 19.05 | 1047.75 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>41.250</i> | | | | | | | |
| # B-L9-111-127-NF | 111 | 12.70 | 1057.28 | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>41.625</i> | | | | | | | |
| # B-L9-111-191-NF | 111 | 19.05 | 1057.28 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>41.625</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|--------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| # B-L9-112-1016-NF | 112 | 101.6 <i>4.000</i> | 1066.8 <i>42.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1767 | -34 | 85 | 40 |
| # B-L9-112-127-NF | 112 | 12.70 <i>0.500</i> | 1066.80 <i>42.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-112-191-NF | 112 | 19.05 <i>0.750</i> | 1066.80 <i>42.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-112-254-NF | 112 | 25.40 <i>1.000</i> | 1066.8 <i>42.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-112-381-NF | 112 | 38.10 <i>1.500</i> | 1066.8 <i>42.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-112-508-NF | 112 | 50.80 <i>2.000</i> | 1066.8 <i>42.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-113-127-NF | 113 | 12.70 <i>0.500</i> | 1076.33 <i>42.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-113-191-NF | 113 | 19.05 <i>0.750</i> | 1076.33 <i>42.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-114-127-NF | 114 | 12.70 <i>0.500</i> | 1085.85 <i>42.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-114-191-NF | 114 | 19.05 <i>0.750</i> | 1085.85 <i>42.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-115-127-NF | 115 | 12.70 <i>0.500</i> | 1095.38 <i>43.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-115-191-NF | 115 | 19.05 <i>0.750</i> | 1095.38 <i>43.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-116-127-NF | 116 | 12.70 <i>0.500</i> | 1104.90 <i>43.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-116-191-NF | 116 | 19.05 <i>0.750</i> | 1104.90 <i>43.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-117-127-NF | 117 | 12.70 <i>0.500</i> | 1114.43 <i>43.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-117-191-NF | 117 | 19.05 <i>0.750</i> | 1114.43 <i>43.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-118-127-NF | 118 | 12.70 <i>0.500</i> | 1123.95 <i>44.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-118-191-NF | 118 | 19.05 <i>0.750</i> | 1123.95 <i>44.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-119-127-NF | 119 | 12.70 <i>0.500</i> | 1133.48 <i>44.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-119-191-NF | 119 | 19.05 <i>0.750</i> | 1133.48 <i>44.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-120-051-NF | 120 | 5.10 <i>0.201</i> | 1143 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 892 | -34 | 85 | 40 |
| # B-L9-120-063-NF | 120 | 6.35 <i>0.250</i> | 1143 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1102 | -34 | 85 | 40 |
| # B-L9-120-095-NF | 120 | 9.53 <i>0.375</i> | 1143 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 1662 | -34 | 85 | 40 |
| B-L9-120-127-NF | 120 | 12.70 <i>0.500</i> | 1143.00 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| B-L9-120-191-NF | 120 | 19.05 <i>0.750</i> | 1143.00 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-120-254-NF | 120 | 25.40 <i>1.000</i> | 1143 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-120-381-NF | 120 | 38.10 <i>1.500</i> | 1143 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-120-508-NF | 120 | 50.80 <i>2.000</i> | 1143 <i>45.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-121-127-NF | 121 | 12.70 <i>0.500</i> | 1152.53 <i>45.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-121-191-NF | 121 | 19.05 <i>0.750</i> | 1152.53 <i>45.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-122-127-NF | 122 | 12.70 <i>0.500</i> | 1162.05 <i>45.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-122-191-NF | 122 | 19.05 <i>0.750</i> | 1162.05 <i>45.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-123-127-NF | 123 | 12.70 <i>0.500</i> | 1171.58 <i>46.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-123-191-NF | 123 | 19.05 <i>0.750</i> | 1171.58 <i>46.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-124-127-NF | 124 | 12.70 <i>0.500</i> | 1181.10 <i>46.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-124-191-NF | 124 | 19.05 <i>0.750</i> | 1181.10 <i>46.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-125-127-NF | 125 | 12.70 <i>0.500</i> | 1190.63 <i>46.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-125-191-NF | 125 | 19.05 <i>0.750</i> | 1190.63 <i>46.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-126-127-NF | 126 | 12.70 <i>0.500</i> | 1200.15 <i>47.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-126-191-NF | 126 | 19.05 <i>0.750</i> | 1200.15 <i>47.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|--------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-127-127-NF | 127 | 12.70 | 1209.68 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>47.625</i> | | | | | | | |
| # B-L9-127-191-NF | 127 | 19.05 | 1209.68 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>47.625</i> | | | | | | | |
| # B-L9-128-1016-NF | 128 | 101.6 | 1219.2 | Nylon Covered Neoprene | Fibreglass | Black | 1767 | -34 | 85 | 40 |
| | | <i>4.000</i> | <i>48.000</i> | | | | | | | |
| # B-L9-128-127-NF | 128 | 12.70 | 1219.20 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>48.000</i> | | | | | | | |
| # B-L9-128-191-NF | 128 | 19.05 | 1219.20 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>48.000</i> | | | | | | | |
| # B-L9-128-254-NF | 128 | 25.40 | 1219.2 | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| | | <i>1.000</i> | <i>48.000</i> | | | | | | | |
| # B-L9-128-317-NF | 128 | 31.75 | 1219.2 | Nylon Covered Neoprene | Fibreglass | Black | 5546 | -34 | 85 | 40 |
| | | <i>1.250</i> | <i>48.000</i> | | | | | | | |
| # B-L9-128-381-NF | 128 | 38.10 | 1219.2 | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| | | <i>1.500</i> | <i>48.000</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-129-127-NF | 129 | 12.70 <i>0.500</i> | 1228.73 <i>48.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-129-191-NF | 129 | 19.05 <i>0.750</i> | 1228.73 <i>48.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-133-127-NF | 133 | 12.70 <i>0.500</i> | 1266.83 <i>49.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-133-191-NF | 133 | 19.05 <i>0.750</i> | 1266.83 <i>49.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-134-127-NF | 134 | 12.70 <i>0.500</i> | 1276.35 <i>50.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-134-191-NF | 134 | 19.05 <i>0.750</i> | 1276.35 <i>50.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-135-127-NF | 135 | 12.70 <i>0.500</i> | 1285.88 <i>50.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-135-191-NF | 135 | 19.05 <i>0.750</i> | 1285.88 <i>50.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-136-127-NF | 136 | 12.70 <i>0.500</i> | 1295.40 <i>51.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-136-191-NF | 136 | 19.05 <i>0.750</i> | 1295.40 <i>51.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-136-254-NF | 136 | 25.40 <i>1.000</i> | 1295.4 <i>51.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-136-381-NF | 136 | 38.10 <i>1.500</i> | 1295.4 <i>51.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-136-508-NF | 136 | 50.80 <i>2.000</i> | 1295.4 <i>51.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |
| # B-L9-137-127-NF | 137 | 12.70 <i>0.500</i> | 1304.93 <i>51.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-137-191-NF | 137 | 19.05 <i>0.750</i> | 1304.93 <i>51.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-139-127-NF | 139 | 12.70 <i>0.500</i> | 1323.98 <i>52.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-139-191-NF | 139 | 19.05 <i>0.750</i> | 1323.98 <i>52.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-140-127-NF | 140 | 12.70 <i>0.500</i> | 1333.50 <i>52.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-140-191-NF | 140 | 19.05 <i>0.750</i> | 1333.50 <i>52.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-142-127-NF | 142 | 12.70 <i>0.500</i> | 1352.55 <i>53.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-142-191-NF | 142 | 19.05 <i>0.750</i> | 1352.55 <i>53.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-144-127-NF | 144 | 12.70 <i>0.500</i> | 1371.60 <i>54.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-144-191-NF | 144 | 19.05 <i>0.750</i> | 1371.60 <i>54.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-144-254-NF | 144 | 25.40 <i>1.000</i> | 1371.6 <i>54.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-144-381-NF | 144 | 38.10 | 1371.6 | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| | | <i>1.500</i> | <i>54.000</i> | | | | | | | |
| # B-L9-146-191-NF | 146 | 19.05 | 1390.65 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>54.750</i> | | | | | | | |
| # B-L9-148-127-NF | 148 | 12.70 | 1409.70 | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>55.500</i> | | | | | | | |
| # B-L9-148-191-NF | 148 | 19.05 | 1409.70 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>55.500</i> | | | | | | | |
| # B-L9-151-127-NF | 151 | 12.70 | 1438.28 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>56.625</i> | | | | | | | |
| # B-L9-151-191-NF | 151 | 19.05 | 1438.28 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>56.625</i> | | | | | | | |
| # B-L9-152-127-NF | 152 | 12.70 | 1447.80 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>57.000</i> | | | | | | | |
| B-L9-152-191-NF | 152 | 19.05 | 1447.80 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>57.000</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-155-127-NF | 155 | 12.70 <i>0.500</i> | 1476.38 <i>58.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-155-191-NF | 155 | 19.05 <i>0.750</i> | 1476.38 <i>58.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-160-127-NF | 160 | 12.70 <i>0.500</i> | 1524.00 <i>60.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-160-191-NF | 160 | 19.05 <i>0.750</i> | 1524.00 <i>60.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-160-254-NF | 160 | 25.40 <i>1.000</i> | 1524 <i>60.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 4444 | -34 | 85 | 40 |
| # B-L9-160-317-NF | 160 | 31.70 <i>1.248</i> | 1524 <i>60.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 5546 | -34 | 85 | 40 |
| # B-L9-160-381-NF | 160 | 38.10 <i>1.500</i> | 1524 <i>60.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 6666 | -34 | 85 | 40 |
| # B-L9-160-508-NF | 160 | 50.80 <i>2.000</i> | 1524 <i>60.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 8888 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-161-127-NF | 161 | 12.70 <i>0.500</i> | 1533.53 <i>60.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-161-191-NF | 161 | 19.05 <i>0.750</i> | 1533.53 <i>60.375</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-165-127-NF | 165 | 12.70 <i>0.500</i> | 1571.63 <i>61.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-165-191-NF | 165 | 19.05 <i>0.750</i> | 1571.63 <i>61.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-168-127-NF | 168 | 12.70 <i>0.500</i> | 1600.20 <i>63.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-168-191-NF | 168 | 19.05 <i>0.750</i> | 1600.20 <i>63.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-171-127-NF | 171 | 12.70 <i>0.500</i> | 1628.78 <i>64.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-171-191-NF | 171 | 19.05 <i>0.750</i> | 1628.78 <i>64.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-174-127-NF | 174 | 12.70 <i>0.500</i> | 1657.35 <i>65.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-174-191-NF | 174 | 19.05 <i>0.750</i> | 1657.35 <i>65.250</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-176-127-NF | 176 | 12.70 <i>0.500</i> | 1676.40 <i>66.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-176-191-NF | 176 | 19.05 <i>0.750</i> | 1676.40 <i>66.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-186-127-NF | 186 | 12.70 <i>0.500</i> | 1771.65 <i>69.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-186-191-NF | 186 | 19.05 <i>0.750</i> | 1771.65 <i>69.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-192-127-NF | 192 | 12.70 <i>0.500</i> | 1828.80 <i>72.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2187 | -34 | 85 | 40 |
| # B-L9-192-190-NF | 192 | 19.00 <i>0.748</i> | 1828.80 <i>72.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3325 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-194-127-NF | 194 | 12.70 <i>0.500</i> | 1847.85 <i>72.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-194-191-NF | 194 | 19.05 <i>0.750</i> | 1847.85 <i>72.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-195-127-NF | 195 | 12.70 <i>0.500</i> | 1857.38 <i>73.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-195-191-NF | 195 | 19.05 <i>0.750</i> | 1857.38 <i>73.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-205-127-NF | 205 | 12.70 <i>0.500</i> | 1952.63 <i>76.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-205-191-NF | 205 | 19.05 <i>0.750</i> | 1952.63 <i>76.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-208-127-NF | 208 | 12.70 <i>0.500</i> | 1981.20 <i>78.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-208-191-NF | 208 | 19.05 <i>0.750</i> | 1981.20 <i>78.000</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-210-127-NF | 210 | 12.70 <i>0.500</i> | 2000.25 <i>78.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-210-191-NF | 210 | 19.05 <i>0.750</i> | 2000.25 <i>78.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-215-127-NF | 215 | 12.70 <i>0.500</i> | 2047.88 <i>80.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-215-191-NF | 215 | 19.05 <i>0.750</i> | 2047.88 <i>80.625</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-218-127-NF | 218 | 12.70 <i>0.500</i> | 2076.45 <i>81.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-218-191-NF | 218 | 19.05 <i>0.750</i> | 2076.45 <i>81.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-219-127-NF | 219 | 12.70 <i>0.500</i> | 2085.98 <i>82.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| # B-L9-219-191-NF | 219 | 19.05 <i>0.750</i> | 2085.98 <i>82.125</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|---------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-228-127-NF | 228 | 12.70 | 2171.70 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>85.500</i> | | | | | | | |
| # B-L9-228-191-NF | 228 | 19.05 | 2171.70 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>85.500</i> | | | | | | | |
| # B-L9-230-127-NF | 230 | 12.70 | 2190.75 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>86.250</i> | | | | | | | |
| # B-L9-230-191-NF | 230 | 19.05 | 2190.75 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>86.250</i> | | | | | | | |
| # B-L9-235-127-NF | 235 | 12.70 | 2238.38 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>88.125</i> | | | | | | | |
| # B-L9-235-191-NF | 235 | 19.05 | 2238.38 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>88.125</i> | | | | | | | |
| # B-L9-240-127-NF | 240 | 12.70 | 2286.00 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>90.000</i> | | | | | | | |
| # B-L9-240-191-NF | 240 | 19.05 | 2286.00 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>90.000</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|--------------------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-244-127-NF | 244 | 12.70 <i>0.500</i> | 2324.10 <i>91.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-244-191-NF | 244 | 19.05 <i>0.750</i> | 2324.10 <i>91.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-245-127-NF | 245 | 12.70 <i>0.500</i> | 2333.63 <i>91.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-245-191-NF | 245 | 19.05 <i>0.750</i> | 2333.63 <i>91.875</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-250-127-NF | 250 | 12.70 <i>0.500</i> | 2381.25 <i>93.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| # B-L9-250-191-NF | 250 | 19.05 <i>0.750</i> | 2381.25 <i>93.750</i> | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| # B-L9-252-127-NF | 252 | 12.70 <i>0.500</i> | 2400.30 <i>94.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 2187 | -34 | 85 | 40 |
| # B-L9-252-190-NF | 252 | 19.00 <i>0.748</i> | 2400.30 <i>94.500</i> | Nylon Covered Neoprene | Fibreglass | Black | 3325 | -34 | 85 | 40 |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Belts - Timing - 9.525mm Pitch - L

| Part Number | Teeth (No.) | Nom. Width (+/-0.2) mm | Length mm | Material | Reinforcement | Appearance | Breaking Strength N | Min Temperature Deg C | Max Temperature Deg C | Tooth Angle (A) Deg. |
|-------------------|-------------|---------------------------|----------------|---------------------------|---------------|------------|------------------------|-----------------------------|-----------------------------|-------------------------|
| | | <i>inches</i> | <i>inches</i> | | | | | | | |
| # B-L9-480-127-NF | 480 | 12.70 | 4572.00 | Nylon Covered Neoprene | Fibreglass | Black | 2223 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>180.000</i> | | | | | | | |
| # B-L9-480-191-NF | 480 | 19.05 | 4572.00 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>180.000</i> | | | | | | | |
| # B-L9-590-127-NF | 590 | 12.70 | 5619.75 | Nylon Covered Neoprene | Fibreglass | Black | 2222 | -34 | 85 | 40 |
| | | <i>0.500</i> | <i>221.250</i> | | | | | | | |
| # B-L9-590-191-NF | 590 | 19.05 | 5619.75 | Nylon Covered Neoprene | Fibreglass | Black | 3334 | -34 | 85 | 40 |
| | | <i>0.750</i> | <i>221.250</i> | | | | | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

