




MBA

Brakes - Cap Style - Power Off



Brake loads in absence of power.

This catalogue to be read in conjunction with information at http://www.minibearings.com.au/ogue/tech/brakes/brakes_capstyle.pdf

Brakes - Cap Style - Power Off

Part Number	Rotor Bore mm	Overall Width (K+H) mm	Outside Diameter (A) mm	Mounting Plate (E) mm	Max. Wattage W	Voltage (V-DC)	Keyway Width mm	Weight g	Min. Static Torque N.m
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>		
# BR-CS-04.76x36.20	4.763 <i>0.188</i>	36.20 <i>1.425</i>	32.10 <i>1.264</i>	28.96 SQ.	7.00	24	1.59 x 0.93	113	0.56
# BR-CS-06.00x36.20	6.000 <i>0.236</i>	36.20 <i>1.425</i>	32.10 <i>1.264</i>	28.96 SQ.	7.00	24	2.00 x 1.00	113	0.57
# BR-CS-06.00x37.30	6.000 <i>0.236</i>	37.30 <i>1.469</i>	49.60 <i>1.953</i>	46.40 SQ.	9.00	24	2.00 x 1.00	340	1.70
# BR-CS-06.35x36.20	6.350 <i>0.250</i>	36.20 <i>1.425</i>	32.13 <i>1.265</i>	28.96 SQ.	7.00	24	1.59 x 0.93	113	0.56

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Brakes - Cap Style - Power Off

Part Number	Rotor Bore mm <i>inches</i>	Overall Width (K+H) mm <i>inches</i>	Outside Diameter (A) mm <i>inches</i>	Mounting Plate (E) mm <i>inches</i>	Max. Wattage W	Voltage (V-DC)	Keyway Width mm <i>inches</i>	Weight g	Min. Static Torque N.m
# BR-CS-06.35x37.08	6.350 <i>0.250</i>	37.10 <i>1.461</i>	49.60 <i>1.953</i>	46.41 SQ.	9.00	24	1.59 x 0.93	340	1.69
# BR-CS-06.35x37.29	6.350 <i>0.250</i>	37.30 <i>1.469</i>	57.53 <i>2.265</i>	54.36 SQ.	11.00	24	1.59 x 0.93	454	3.39
# BR-CS-07.94x37.08	7.938 <i>0.313</i>	37.10 <i>1.461</i>	49.60 <i>1.953</i>	46.41 SQ.	9.00	24	2.38 x 1.31	340	1.69
# BR-CS-07.94x37.29	7.938 <i>0.313</i>	37.30 <i>1.469</i>	57.53 <i>2.265</i>	54.36 SQ.	11.00	24	2.38 x 1.31	454	3.39
# BR-CS-08.00x37.30	8.000 <i>0.315</i>	37.30 <i>1.469</i>	49.60 <i>1.953</i>	46.40 SQ.	9.00	24	3.00 x 1.40	340	1.70
# BR-CS-09.53x37.08	9.525 <i>0.375</i>	37.10 <i>1.461</i>	49.60 <i>1.953</i>	46.41 SQ.	9.00	24	2.38 x 1.31	340	1.69
# BR-CS-09.53x37.29	9.525 <i>0.375</i>	37.30 <i>1.469</i>	57.53 <i>2.265</i>	54.36 SQ.	11.00	24	2.38 x 1.31	454	3.39
# BR-CS-09.53x48.01	9.525 <i>0.375</i>	48.10 <i>1.894</i>	67.10 <i>2.642</i>	66.80 SQ.	14.00	24	2.38 x 1.31	737	5.66
# BR-CS-10.00x37.30	10.000 <i>0.394</i>	37.30 <i>1.469</i>	49.60 <i>1.953</i>	54.40 SQ.	11.00	24	3.00 x 1.40	454	3.39
# BR-CS-11.11x48.01	11.113 <i>0.438</i>	48.10 <i>1.894</i>	67.10 <i>2.642</i>	66.80 SQ.	14.00	24	2.38 x 1.63	737	5.66

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Brakes - Cap Style - Power Off

Part Number	Rotor Bore mm	Overall Width (K+H) mm	Outside Diameter (A) mm	Mounting Plate (E) mm	Max. Wattage W	Voltage (V-DC)	Keyway Width mm	Weight g	Min. Static Torque N.m
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>		
# BR-CS-12.70x48.01	12.700	48.10	67.10	66.80 SQ.	14.00	24	3.18 x 1.63	737	5.66
	<i>0.500</i>	<i>1.894</i>	<i>2.642</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
