




MBA

Brakes - Flange Mounted - Power On - SDP



Anti backlash when energised - zero drag when de-energised.

24 V DC.

Brakes - Flange Mounted - Power On - SDP

Part Number	Rotor Bore mm <i>inches</i>	Overall Width mm <i>inches</i>	Outside Diameter mm <i>inches</i>	Mounting Plate (SQ) mm <i>inches</i>	Max. Wattage	Keyway Width	Bore Config.	Mech. Response msec	Min. Static Torque N.m
# BR-FL-06.00x29.00	6.000 <i>0.236</i>	29.000 <i>1.142</i>	31.800 <i>1.252</i>	29.8 SQ.	5.0	2.000	With Keyway	18	0.565
# BR-FL-06.35x28.96	6.350 <i>0.250</i>	28.956 <i>1.140</i>	31.750 <i>1.250</i>	29.8 SQ.	5.0	1.588	With Keyway	18	0.565
# BR-FL-06.35x32.26	6.350 <i>0.250</i>	32.258 <i>1.270</i>	45.212 <i>1.780</i>	46.3 SQ.	6.0	1.588	With Keyway	27	1.695
# BR-FL-07.95x44.20	7.950 <i>0.313</i>	44.196 <i>1.740</i>	57.404 <i>2.260</i>	59.2 SQ.	8.5	2.383	With Keyway	32	4.520

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Brakes - Flange Mounted - Power On - SDP

Part Number	Rotor Bore mm <i>inches</i>	Overall Width mm <i>inches</i>	Outside Diameter mm <i>inches</i>	Mounting Plate (SQ) mm <i>inches</i>	Max. Wattage	Keyway Width	Bore Config.	Mech. Response msec	Min. Static Torque N.m
# BR-FL-08.00x29.00	8.000 <i>0.315</i>	29.000 <i>1.142</i>	31.800 <i>1.252</i>	29.8 SQ.	5.0	3.000	With Keyway	18	0.565
# BR-FL-08.00x32.20	8.000 <i>0.315</i>	32.200 <i>1.268</i>	45.300 <i>1.783</i>	46.3 SQ.	6.0	3.000	With Keyway	27	1.695
# BR-FL-08.00x44.20	8.000 <i>0.315</i>	44.200 <i>1.740</i>	57.400 <i>2.260</i>	59.2 SQ.	8.5	3.000	With Keyway	32	4.519
# BR-FL-09.53x46.74	9.525 <i>0.375</i>	46.736 <i>1.840</i>	66.802 <i>2.630</i>	66.8 SQ.	9.5	2.383	With Keyway	35	9.040
# BR-FL-10.00x44.20	10.000 <i>0.394</i>	44.200 <i>1.740</i>	57.400 <i>2.260</i>	59.2 SQ.	8.5	3.000	With Keyway	32	4.519
# BR-FL-10.00x46.80	10.000 <i>0.394</i>	46.800 <i>1.843</i>	66.700 <i>2.626</i>	66.8 SQ.	9.5	3.000	With Keyway	35	9.039
# BR-FL-12.00x46.80	12.000 <i>0.472</i>	46.800 <i>1.843</i>	66.700 <i>2.626</i>	66.8 SQ.	9.5	4.000	With Keyway	35	9.039
# BR-FL-12.70x46.74	12.700 <i>0.500</i>	46.736 <i>1.840</i>	66.802 <i>2.630</i>	66.8 SQ.	9.5	3.180	With Keyway	35	9.040
# BR-FL-15.87x49.52	15.875 <i>0.625</i>	49.022 <i>1.930</i>	83.058 <i>3.270</i>	82.6 SQ.	15.0	4.775	With Keyway	45	14.124
# BR-FL-16.00x49.10	16.000 <i>0.630</i>	49.100 <i>1.933</i>	83.000 <i>3.268</i>	82.6 SQ.	12.0	5.000	With Keyway	45	14.123

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Brakes - Flange Mounted - Power On - SDP

Part Number	Rotor Bore mm	Overall Width mm	Outside Diameter mm	Mounting Plate (SQ) mm	Max. Wattage	Keyway Width	Bore Config.	Mech. Response msec	Min. Static Torque N.m
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>					
# BR-FL-19.05x49.02	19.050	49.022	83.058	82.6 SQ.	15.0	4.775	With Keyway	45	14.124
	<i>0.750</i>	<i>1.930</i>	<i>3.270</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

