




MBA

Brakes - Magnetic - Bu-Ord Size 18 - Reverse Acting



Breakaway Torque (Energised) at 24-28 V DC : 3.6g.cm (0.05 oz.in).

Breakaway Torque (De-Energised) at 24-28 V DC : 3.6g.cm (0.05 oz.in).

Backlash (Enaged) : 5 Min Max.

Power Consumption at 24 V DC : 3.7 watts.

Brakes - Magnetic - Bu-Ord Size 18 - Reverse Acting

Part Number	Inertia oz.in sq	Shaft Diameter mm	Brake Type	Brake Torque g.cm	Configuration	Outside Diameter mm	Backlash min
		<i>inches</i>				<i>inches</i>	
# BMR44-0635-08-3600	7.68	6.35 <i>0.250</i>	Friction	3600.00	Single End	44.45 <i>1.750</i>	5 Min Max
# BMR44-0635-08-7200	7.68	6.35 <i>0.250</i>	Crown Tooth	7200.00	Single End	44.45 <i>1.750</i>	5 Min Max
# BMR44-0635-14-1440	13.72	6.35 <i>0.250</i>	Friction	1440.00	Single End	44.45 <i>1.750</i>	5 Min Max
# BMR44-0635-14-2880	13.72	6.35 <i>0.250</i>	Crown Tooth	2880.00	Single End	44.45 <i>1.750</i>	5 Min Max

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

