




MBA

Clutch Assemblies - Slip - Precision



Adjustable Torque range 360-3600 g.cm (5-50 oz.in).

303 Stainless Steel.

Brake : Oil Impregnated Bronze.

Use with hubless gears with 9.525 bore and 3.175 face width.

Clutch Assemblies - Slip - Precision

Part Number	Inner Diameter	Mounting Diameter (Input)	Overall Length	Hub Type	Clutch Type	Friction Plate Diameter	Hub Diameter
# PSCA-3.05-CL	3.048	9.515	12.304	Clamp Hub	Adjustable	23.020	6.731
# PSCA-3.05	3.048	9.515	25.796	Pin Hub	Adjustable	23.020	7.925
# PSCA-3.17-CL	3.170	9.515	12.306	Clamp Hub	Adjustable	23.020	6.731
# PSCA-3.17	3.170	9.515	25.796	Pin Hub	Adjustable	23.020	7.925
# PSCA-4.76-CL	4.757	9.515	12.309	Clamp Hub	Adjustable	23.020	6.731
# PSCA-4.76	4.757	9.515	25.796	Pin Hub	Adjustable	23.020	9.525

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Clutch Assemblies - Slip - Precision

Part Number	Inner Diameter	Mounting Diameter (Input)	Overall Length	Hub Type	Clutch Type	Friction Plate Diameter	Hub Diameter
PSCA-6.34-CL	6.345	9.515	12.311	Clamp Hub	Adjustable	23.020	6.731
# PSCA-6.34	6.345	9.515	25.796	Pin Hub	Adjustable	23.020	12.700

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

