

Clutches - Slip - Magnetic Particle - No Power

Part Number	Optimum Torque Range g.cm	Inner Diameter (d) mm <i>inches</i>	Overall Length mm <i>inches</i>	Static Torque g.cm	Hub Diameter (D1) mm <i>inches</i>	Max. Speed RPM	Body Diameter mm <i>inches</i>	Shell (Material)	End Caps (Material)
# CMP-08.00x020.0x35-1224	612 to 1224	8.000 <i>0.315</i>	34.5 <i>1.358</i>	1224	17.0 <i>0.669</i>	250	20.0 <i>0.787</i>	Steel	Plastic
# CMP-08.00x032.0x37-1530	1010 to 1530	8.000 <i>0.315</i>	37.0 <i>1.457</i>	1531	20.0 <i>0.787</i>	400	32.0 <i>1.260</i>	Steel	Plastic
# CMP-08.00x032.0x44-2030	1530 to 2030	8.000 <i>0.315</i>	44.0 <i>1.732</i>	2031	20.0 <i>0.787</i>	300	32.0 <i>1.260</i>	Steel	Plastic
# CMP-08.00x032.0x44-3071	2030 to 3071	8.000 <i>0.315</i>	44.0 <i>1.732</i>	3071	20.0 <i>0.787</i>	300	32.0 <i>1.260</i>	Steel	Plastic

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
