




MBA

Couplings - Clutch - Shaft Mounted



0.565 to 14 N.m. For in-line loads.

24 Volt DC.

Zero Backlash Armature.

For in-line loads.

Dynamic torque is 80% of static torque.

0.565 N.m Models have no keyway in rotor.

Couplings - Clutch - Shaft Mounted

Part Number	Bore Armature (R) D10 mm	Bore Rotor (G) H8 mm	Overall Width (K) mm	Min. Static Torque N.m	Voltage V	Max. Wattage	Keyway Dimension / Bore Config	Outside Diameter (A)	Mech. Response msec
	<i>inches</i>	<i>inches</i>	<i>inches</i>						
# CCSM-32-06.00	6.000	6.000	32.6	0.565	24	5.000	2.000 / Keyway in Armature Only	31.8	18
	<i>0.236</i>	<i>0.236</i>	<i>1.283</i>						
# CCSM-45-06.00	6.000	6.000	39.4	1.695	24	6.000	2.000 / With Keyway	45.3	27
	<i>0.236</i>	<i>0.236</i>	<i>1.551</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Clutch - Shaft Mounted

Part Number	Bore Armature (R) D10 mm	Bore Rotor (G) H8 mm	Overall Width (K) mm	Min. Static Torque N.m	Voltage V	Max. Wattage	Keyway Dimension / Bore Config	Outside Diameter (A)	Mech. Response msec
	<i>inches</i>	<i>inches</i>	<i>inches</i>						
# CCSM-32-06.35	6.350 <i>0.250</i>	6.350 <i>0.250</i>	32.5 <i>1.280</i>	0.565	24	5.000	1.588 / Keyway in Armature Only	31.8	18
# CCSM-45-06.35	6.350 <i>0.250</i>	6.350 <i>0.250</i>	39.4 <i>1.551</i>	1.695	24	6.000	1.588 / With Keyway	45.2	27
# CCSM-39-06.35	6.350 <i>0.250</i>	6.350 <i>0.250</i>	42.7 <i>1.681</i>	1.130	24	5.000	1.588 / With Keyway	38.9	22
# CCSM-32-08.00	8.000 <i>0.315</i>	8.000 <i>0.315</i>	32.6 <i>1.283</i>	0.565	24	5.000	3.000 / Keyway in Armature Only	31.8	18
# CCSM-45-08.00	8.000 <i>0.315</i>	8.000 <i>0.315</i>	39.4 <i>1.551</i>	1.695	24	6.000	3.000 / With Keyway	45.3	27
# CCSM-57-09.53	9.525 <i>0.375</i>	9.525 <i>0.375</i>	52.3 <i>2.059</i>	4.520	24	8.500	2.383 / With Keyway	57.4	32
# CCSM-67-09.53	9.525 <i>0.375</i>	9.525 <i>0.375</i>	53.3 <i>2.098</i>	9.040	24	9.500	2.383 / With Keyway	66.7	35
# CCSM-67-10.00	10.000 <i>0.394</i>	10.000 <i>0.394</i>	53.4 <i>2.102</i>	9.039	24	9.500	3.000 / With Keyway	66.7	35

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Clutch - Shaft Mounted

Part Number	Bore Armature (R) D10 mm	Bore Rotor (G) H8 mm	Overall Width (K) mm	Min. Static Torque N.m	Voltage V	Max. Wattage	Keyway Dimension / Bore Config	Outside Diameter (A)	Mech. Response msec
	<i>inches</i>	<i>inches</i>	<i>inches</i>						
# CCSM-67-12.70	12.700	12.700	53.3	9.040	24	9.500	3.180 / With Keyway	66.7	35
	<i>0.500</i>	<i>0.500</i>	<i>2.098</i>						
# CCSM-83-15.87	15.870	5.875	55.1	14.124	24	15.000	4.775 / With Keyway	83.0	45
	<i>0.625</i>	<i>0.231</i>	<i>2.169</i>						
# CCSM-83-19.05	19.050	19.050	55.1	14.124	24	15.000	4.775 / With Keyway	83.0	45
	<i>0.750</i>	<i>0.750</i>	<i>2.169</i>						

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

