




MBA

Couplings - Crowned Tooth Gear Type. 19.55 to 88 Nm. 8500 to 14000 rpm.



Steel hubs with Moulded Nylon Sleeve.

+/- 1.02 mm Axial Displacement.

0.41mm Parallel offset per hub.

1 Degree Angular Displacement.

Free axial movement.

High torque / low inertia.

Couplings - Crowned Tooth Gear Type. 19.55 to 88 Nm. 8500 to 14000 rpm.

Part Number	Sleeve OD mm	Bore mm	Length (L) mm	Description	Max Speed RPM	Max Torque n.m	Hub. Config	Hub Diameter (C) mm	Hub Length (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>					<i>inches</i>	<i>inches</i>
# CPCT40-0635	39.9	6.350	45.72	Complete Coupling	14000	19.55	Pin Type	25.40	36.83
	<i>1.571</i>	<i>0.250</i>	<i>1.800</i>					<i>1.000</i>	<i>1.450</i>
# CPCT40-HALF-0635	39.9	6.350	-	Hub Only	14000	19.55	Pin Type	25.40	
	<i>1.571</i>	<i>0.250</i>						<i>1.000</i>	
# CPCT40-0953	39.9	9.525	45.72	Complete Coupling	14000	19.55	Pin Type	25.40	36.83
	<i>1.571</i>	<i>0.375</i>	<i>1.800</i>					<i>1.000</i>	<i>1.450</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Crowned Tooth Gear Type. 19.55 to 88 Nm. 8500 to 14000 rpm.

Part Number	Sleeve OD mm	Bore mm	Length (L) mm	Description	Max Speed RPM	Max Torque n.m	Hub. Config	Hub Diameter (C) mm	Hub Length (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>					<i>inches</i>	<i>inches</i>
# CPCT40-HALF-0953	39.9 <i>1.571</i>	9.525 <i>0.375</i>	-	Hub Only	14000	19.55	Pin Type	25.40 <i>1.000</i>	
# CPCT40-1111	39.9 <i>1.571</i>	11.112 <i>0.437</i>	45.72 <i>1.800</i>	Complete Coupling	14000	19.55	Pin Type	25.40 <i>1.000</i>	36.83 <i>1.450</i>
# CPCT40-HALF-1111	39.9 <i>1.571</i>	11.112 <i>0.437</i>	-	Hub Only	14000	19.55	Pin Type	25.40 <i>1.000</i>	
# CPCT40-1270	39.9 <i>1.571</i>	12.700 <i>0.500</i>	45.72 <i>1.800</i>	Complete Coupling	14000	19.55	Pin Type	25.40 <i>1.000</i>	36.83 <i>1.450</i>
# CPCT40-HALF-1270	39.9 <i>1.571</i>	12.700 <i>0.500</i>	-	Hub Only	14000	19.55	Pin Type	25.40 <i>1.000</i>	
# CPCT40-1588	39.9 <i>1.571</i>	15.875 <i>0.625</i>	45.72 <i>1.800</i>	Complete Coupling	14000	19.55	Pin Type	25.40 <i>1.000</i>	36.83 <i>1.450</i>
# CPCT40-HALF-1588	39.9 <i>1.571</i>	15.875 <i>0.625</i>	-	Hub Only	14000	19.55	Pin Type	25.40 <i>1.000</i>	
# CPCT40-SLV	39.9 <i>1.571</i>	N/A	36.83 <i>1.450</i>	Sleeve Only	14000	19.55	Pin Type		36.83 <i>1.450</i>
# CPCT48-1111	48.3 <i>1.902</i>	11.112 <i>0.437</i>	49.78 <i>1.960</i>	Complete Coupling	11800	31.30	Pin Type	31.75 <i>1.250</i>	36.83 <i>1.450</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Crowned Tooth Gear Type. 19.55 to 88 Nm. 8500 to 14000 rpm.

Part Number	Sleeve OD mm	Bore mm	Length (L) mm	Description	Max Speed RPM	Max Torque n.m	Hub. Config	Hub Diameter (C) mm	Hub Length (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>					<i>inches</i>	<i>inches</i>
# CPCT48-HALF-1111	48.3 <i>1.902</i>	11.112 <i>0.437</i>	-	Hub Only	11800	31.30	Pin Type	31.75 <i>1.250</i>	
# CPCT48-1270	48.3 <i>1.902</i>	12.700 <i>0.500</i>	49.78 <i>1.960</i>	Complete Coupling	11800	31.30	Pin Type	31.75 <i>1.250</i>	36.83 <i>1.450</i>
# CPCT48-HALF-1270	48.3 <i>1.902</i>	12.700 <i>0.500</i>	-	Hub Only	11800	31.30	Pin Type	31.75 <i>1.250</i>	
# CPCT48-1588	48.3 <i>1.902</i>	15.875 <i>0.625</i>	49.78 <i>1.960</i>	Complete Coupling	11800	31.30	Pin Type	31.75 <i>1.250</i>	36.83 <i>1.450</i>
# CPCT48-HALF-1588	48.3 <i>1.902</i>	15.875 <i>0.625</i>	-	Hub Only	11800	31.30	Pin Type	31.75 <i>1.250</i>	
# CPCT48-SLV	48.3 <i>1.902</i>	N/A	49.78 <i>1.960</i>	Sleeve Only	11800	31.30	Pin Type		36.83 <i>1.450</i>
# CPCT48-19050	48.3 <i>1.902</i>	19.050 <i>0.750</i>	49.78 <i>1.960</i>	Complete Coupling	11800	31.30	Pin Type	31.75 <i>1.250</i>	36.83 <i>1.450</i>
# CPCT48-HALF-19050	48.3 <i>1.902</i>	19.050 <i>0.750</i>	-	Hub Only	11800	31.30	Pin Type	31.75 <i>1.250</i>	
# CPCT52-1111	52.1 <i>2.051</i>	11.112 <i>0.437</i>	52.58 <i>2.070</i>	Complete Coupling	10600	39.21	Pin Type	35.56 <i>1.400</i>	40.64 <i>1.600</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Crowned Tooth Gear Type. 19.55 to 88 Nm. 8500 to 14000 rpm.

Part Number	Sleeve OD mm	Bore mm	Length (L) mm	Description	Max Speed RPM	Max Torque n.m	Hub. Config	Hub Diameter (C) mm	Hub Length (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>					<i>inches</i>	<i>inches</i>
# CPCT52-HALF-1111	52.1 <i>2.051</i>	11.112 <i>0.437</i>	-	Hub Only	10600	39.21	Pin Type	35.56 <i>1.400</i>	
# CPCT52-1270	52.1 <i>2.051</i>	12.700 <i>0.500</i>	52.58 <i>2.070</i>	Complete Coupling	10600	39.21	Pin Type	35.56 <i>1.400</i>	40.64 <i>1.600</i>
# CPCT52-HALF-1270	52.1 <i>2.051</i>	12.700 <i>0.500</i>	-	Hub Only	10600	39.21	Pin Type	35.56 <i>1.400</i>	
# CPCT52-SLV	52.1 <i>2.051</i>	N/A	52.58 <i>2.070</i>	Sleeve Only	10600	39.21	Pin Type		40.64 <i>1.600</i>
# CPCT66-1111	66.1 <i>2.602</i>	11.112 <i>0.437</i>	83.82 <i>3.300</i>	Complete Coupling	8500	88.25	Pin Type	43.94 <i>1.730</i>	45.72 <i>1.800</i>
# CPCT66-HALF-1111	66.1 <i>2.602</i>	11.112 <i>0.437</i>	-	Hub Only	8500	88.25	Pin Type	43.94 <i>1.730</i>	
# CPCT66-1270	66.1 <i>2.602</i>	12.700 <i>0.500</i>	83.82 <i>3.300</i>	Complete Coupling	8500	88.25	Pin Type	43.94 <i>1.730</i>	45.72 <i>1.800</i>
# CPCT66-HALF-1270	66.1 <i>2.602</i>	12.700 <i>0.500</i>	-	Hub Only	8500	88.25	Pin Type	43.94 <i>1.730</i>	
# CPCT66-SLV	66.1 <i>2.602</i>	N/A	83.82 <i>3.300</i>	Sleeve Only	8500	88.25	Pin Type		45.72 <i>1.800</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

