




MBA

Couplings - Flexible-Shaft Type



Nonmagnetic flexible shaft couplings. Max torque 0.39 Nm.

Maximum Torque 0.39 N.m (3.5 lb.in).

Minimum operating radius 89 mm (3.5 in.).

Torsional deflection 1.8 Deg per lb.in per inch (25mm) of shaft in Winding Direction.

Torsional deflection 2.6 Deg per lb.in per inch (25mm) of shaft in Unwinding Direction.

Cadmium Plated Brass Ends - Phosphor Bronze Cable - 300 Series Stainless Screws.

Couplings - Flexible-Shaft Type

Part Number	Bore Size mm	Length mm	Maximum Operating Angle Deg	Winding Deflection at 1lb.in Deg	Unwinding Deflection at 1lb.in Deg	Coupling OD mm	Wire Diameter mm
	<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
# CFS-0635x102	6.35 - 6.40	101.60 <i>4.000</i>	37.800	4.1	6.0	12.7 <i>0.500</i>	3.302 <i>0.130</i>
# CFS-0635x127	6.35 - 6.40	127.00 <i>5.000</i>	54.200	5.1	8.6	12.7 <i>0.500</i>	3.302 <i>0.130</i>
# CFS-0635x152	6.35 - 6.40	152.40 <i>6.000</i>	70.600	7.8	11.2	12.7 <i>0.500</i>	3.302 <i>0.130</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Flexible-Shaft Type

Part Number	Bore Size mm	Length mm	Maximum Operating Angle Deg	Winding Deflection at 1lb.in Deg	Unwinding Deflection at 1lb.in Deg	Coupling OD mm	Wire Diameter mm
	<i>inches</i>	<i>inches</i>				<i>inches</i>	<i>inches</i>
# CFS-0635x178	6.35 - 6.40	177.80 <i>7.000</i>	86.900	9.6	13.8	12.7 <i>0.500</i>	3.302 <i>0.130</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
