




MBA

Couplings - Jaw Type - With Polyurethane Spider



(1) Red disc (supplied) High Torque. (W) White Disc Medium Torque. (B) Blue Disc Low Torque. (M) & (L) Torque Size as requested only.

Miniature aluminium curved jaw flexible couplings. 2 to 160 Nm.

Discs (either red as standard with blue or white optional) are available to purchase separately.

Flexible couplings transmit torque and rotational angle while absorbing misalignment.

When the misalignment exceeds allowable values, vibration may result or the life of the coupling may become shortened.

Zero backlash in low torque application, made capable by having the hubs pressed in a spacer.

Can be used as a flexible coupling in a high torque application.

Couplings - Jaw Type - With Polyurethane Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Rated Torque Nm	Max. Torque Nm	Wrench Torque Nm	Fixing Type
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
# MJT-14C-RD	14.0 <i>0.551</i>	3.00 <i>0.118</i>	22.00 <i>0.866</i>	Complete	2.00	4.00	0.50	Clamp
CUS14x03.00-COM	14.0 <i>0.551</i>	3.00 <i>0.118</i>	22.00 <i>0.866</i>	Complete	2.00	4.00	0.70	Set Screw
# CUS20x05.00-COM	20.0 <i>0.787</i>	5.00 <i>0.197</i>	30.00 <i>1.181</i>	Complete	5.00	10.00	0.70	Set Screw

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Jaw Type - With Polyurethane Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Rated Torque Nm	Max. Torque Nm	Wrench Torque Nm	Fixing Type
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
# MJT-20C-RD	20.0 <i>0.787</i>	5.00 <i>0.197</i>	30.00 <i>1.181</i>	Complete	5.00	10.00	1.00	Clamp
# CUS30x07.00-COM	30.0 <i>1.181</i>	7.00 <i>0.276</i>	35.00 <i>1.378</i>	Complete	12.50	25.00	1.70	Set Screw
# MJT-30C-RD	30.0 <i>1.181</i>	7.00 <i>0.276</i>	35.00 <i>1.378</i>	Complete	12.50	25.00	2.50	Clamp
# MJT-40-RD	40.0 <i>1.575</i>	10.00 <i>0.394</i>	66.00 <i>2.598</i>	Complete	17.00	34.00	4.00	Set Screw
# CUS40x10.00-COM	40.0 <i>1.575</i>	10.00 <i>0.394</i>	66.00 <i>2.598</i>	Complete	17.00	34.00	4.00	Clamp
# MJT-55C-RD	55.0 <i>2.165</i>	15.00 <i>0.591</i>	78.00 <i>3.071</i>	Complete	60.00	120.00	8.00	Clamp
# CUS55x15.00-COM	55.0 <i>2.165</i>	15.00 <i>0.591</i>	78.00 <i>3.071</i>	Complete	60.00	120.00	7.00	Set Screw
# CUS65x15.00-COM	65.0 <i>2.559</i>	15.00 <i>0.591</i>	90.00 <i>3.543</i>	Complete	160.00	320.00	15.00	Set Screw
# MJT-65C-RD	65.0 <i>2.559</i>	15.00 <i>0.591</i>	90.00 <i>3.543</i>	Complete	160.00	320.00	16.00	Clamp

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

