




MBA

Couplings - Jaw Type - With Rubber Spider



Max 3600 RPM. 0.39 to 16.27 Nm.

Angular Offset = 1 Deg. Max.

Parallel Offset = 0.381mm Max.

Max Recommended Speed 3600 RPM.

Couplings - Jaw Type - With Rubber Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Windup at Maximum Torque Deg	Max. Torque N.m	KW at 1800 RPM KW	KW at 3600 RPM KW
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
CRS16x03.18-COM	15.9 <i>0.626</i>	3.175 <i>0.125</i>	20.638 <i>0.813</i>	Complete	5.000	0.395	0.075	0.15
CRS16x03.18-HUB	15.9 <i>0.626</i>	3.175 <i>0.125</i>	20.638 <i>0.813</i>	Single Hub	5.000	0.395		
# CRS16x04.78-COM	15.9 <i>0.626</i>	4.775 <i>0.188</i>	20.638 <i>0.813</i>	Complete	5.000	0.395	0.075	0.15
# CRS16x04.78-HUB	15.9 <i>0.626</i>	4.775 <i>0.188</i>	20.638 <i>0.813</i>	Single Hub	5.000	0.395		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Jaw Type - With Rubber Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Windup at Maximum Torque Deg	Max. Torque N.m	KW at 1800 RPM KW	KW at 3600 RPM KW
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
# CRS16x06.35-COM	15.9 <i>0.626</i>	6.350 <i>0.250</i>	20.638 <i>0.813</i>	Complete	5.000	0.395	0.075	0.15
CRS16x06.35-HUB	15.9 <i>0.626</i>	6.350 <i>0.250</i>	20.638 <i>0.813</i>	Single Hub	5.000	0.395		
CRS16x07.95-COM	15.9 <i>0.626</i>	7.950 <i>0.313</i>	20.638 <i>0.813</i>	Complete	5.000	0.395	0.075	0.15
CRS16x07.95-HUB	15.9 <i>0.626</i>	7.950 <i>0.313</i>	20.638 <i>0.813</i>	Single Hub	5.000	0.395		
CRS16x09.53-COM	15.9 <i>0.626</i>	9.525 <i>0.375</i>	20.638 <i>0.813</i>	Complete	5.000	0.395	0.075	0.15
# CRS16x09.53-HUB	15.9 <i>0.626</i>	9.525 <i>0.375</i>	20.638 <i>0.813</i>	Single Hub	5.000	0.395		
CRS16-RSP	15.9 <i>0.626</i>	N/A	20.638 <i>0.813</i>	Rubber Spider Only	5.000	0.395		
# CRS27x06.35-COM	27.4 <i>1.079</i>	6.350 <i>0.250</i>	43.656 <i>1.719</i>	Complete	4.500	2.972	0.56	1.1
# CRS27x06.35-HUB	27.4 <i>1.079</i>	6.350 <i>0.250</i>	43.656 <i>1.719</i>	Single Hub	4.500	2.972		
# CRS27x07.95-COM	27.4 <i>1.079</i>	7.950 <i>0.313</i>	43.656 <i>1.719</i>	Complete	4.500	2.972	0.56	1.1

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Jaw Type - With Rubber Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Windup at Maximum Torque Deg	Max. Torque N.m	KW at 1800 RPM KW	KW at 3600 RPM KW
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
# CRS27x07.95-HUB	27.4 <i>1.079</i>	7.950 <i>0.313</i>	43.656 <i>1.719</i>	Single Hub	4.500	2.972		
# CRS27x09.53-COM	27.4 <i>1.079</i>	9.525 <i>0.375</i>	43.656 <i>1.719</i>	Complete	4.500	2.972	0.56	1.1
# CRS27x09.53-HUB	27.4 <i>1.079</i>	9.525 <i>0.375</i>	43.656 <i>1.719</i>	Single Hub	4.500	2.972		
# CRS27x11.13-COM	27.4 <i>1.079</i>	11.125 <i>0.438</i>	43.656 <i>1.719</i>	Complete	4.500	2.972	0.56	1.1
# CRS27x11.13-HUB	27.4 <i>1.079</i>	11.125 <i>0.438</i>	43.656 <i>1.719</i>	Single Hub	4.500	2.972		
# CRS27x12.70-COM	27.4 <i>1.079</i>	12.700 <i>0.500</i>	43.656 <i>1.719</i>	Complete	4.500	2.972	0.56	1.1
# CRS27x12.70-HUB	27.4 <i>1.079</i>	12.700 <i>0.500</i>	43.656 <i>1.719</i>	Single Hub	4.500	2.972		
# CRS27-RSP	27.4 <i>1.079</i>	N/A	43.656 <i>1.719</i>	Rubber Spider Only	4.500	2.972		
# CRS35x09.53-COM	34.5 <i>1.358</i>	9.525 <i>0.375</i>	50.800 <i>2.000</i>	Complete	3.500	4.881	32.2	64.4
# CRS35x09.53-HUB	34.5 <i>1.358</i>	9.525 <i>0.375</i>	50.800 <i>2.000</i>	Single Hub	3.500	4.881		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Jaw Type - With Rubber Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Windup at Maximum Torque Deg	Max. Torque N.m	KW at 1800 RPM KW	KW at 3600 RPM KW
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
# CRS35x11.13-HUB	34.5 <i>1.358</i>	11.125 <i>0.438</i>	50.800 <i>2.000</i>	Single Hub	3.500	4.881		
CRS35x11.13-COM	34.5 <i>1.358</i>	11.125 <i>0.438</i>	50.800 <i>2.000</i>	Complete	3.500	4.881	32.2	64.4
CRS35x12.70-COM	34.5 <i>1.358</i>	12.700 <i>0.500</i>	50.800 <i>2.000</i>	Complete	3.500	4.881	32.2	64.4
# CRS35x12.70-HUB	34.5 <i>1.358</i>	12.700 <i>0.500</i>	50.800 <i>2.000</i>	Single Hub	3.500	4.881		
# CRS35-RSP	34.5 <i>1.358</i>	N/A	50.800 <i>2.000</i>	Rubber Spider Only	3.500	4.881		
CRS44x06.35-COM	44.5 <i>1.752</i>	6.350 <i>0.250</i>	53.975 <i>2.125</i>	Complete	4.700	10.169	67.1	134.2
# CRS44x06.35-HUB	44.5 <i>1.752</i>	6.350 <i>0.250</i>	53.975 <i>2.125</i>	Single Hub	4.700	10.169		
CRS44x07.95-COM	44.5 <i>1.752</i>	7.950 <i>0.313</i>	53.975 <i>2.125</i>	Complete	4.700	10.169	67.1	134.2
# CRS44x07.95-HUB	44.5 <i>1.752</i>	7.950 <i>0.313</i>	53.975 <i>2.125</i>	Single Hub	4.700	10.169		
CRS44x09.53-COM	44.5 <i>1.752</i>	9.525 <i>0.375</i>	53.975 <i>2.125</i>	Complete	4.700	10.169	67.1	134.2

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Jaw Type - With Rubber Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Windup at Maximum Torque Deg	Max. Torque N.m	KW at 1800 RPM KW	KW at 3600 RPM KW
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
# CRS44x09.53-HUB	44.5 <i>1.752</i>	9.525 <i>0.375</i>	53.975 <i>2.125</i>	Single Hub	4.700	10.169		
# CRS44x11.13-HUB	44.5 <i>1.752</i>	11.125 <i>0.438</i>	53.975 <i>2.125</i>	Single Hub	4.700	10.169		
# CRS44x11.13-COM	44.5 <i>1.752</i>	11.125 <i>0.438</i>	53.975 <i>2.125</i>	Complete	4.700	10.169	67.1	134.2
# CRS44x12.70-COM	44.5 <i>1.752</i>	12.700 <i>0.500</i>	53.975 <i>2.125</i>	Complete	4.700	10.169	67.1	134.2
# CRS44x12.70-HUB	44.5 <i>1.752</i>	12.700 <i>0.500</i>	53.975 <i>2.125</i>	Single Hub	4.700	10.169		
# CRS44-RSP	44.5 <i>1.752</i>	N/A	53.975 <i>2.125</i>	Rubber Spider Only	4.700	10.169		
CRS54x06.35-COM	53.6 <i>2.110</i>	6.350 <i>0.250</i>	53.975 <i>2.125</i>	Complete	3.200	16.271	107.4	214.8
# CRS54x06.35-HUB	53.6 <i>2.110</i>	6.350 <i>0.250</i>	53.975 <i>2.125</i>	Single Hub	3.200	16.271		
CRS54x07.95-COM	53.6 <i>2.110</i>	7.950 <i>0.313</i>	53.975 <i>2.125</i>	Complete	3.200	16.271	107.4	214.8
# CRS54x07.95-HUB	53.6 <i>2.110</i>	7.950 <i>0.313</i>	53.975 <i>2.125</i>	Single Hub	3.200	16.271		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Jaw Type - With Rubber Spider

Part Number	OD (D) mm	Bore (B) mm	Overall Length (L) mm	Description	Windup at Maximum Torque Deg	Max. Torque N.m	KW at 1800 RPM KW	KW at 3600 RPM KW
	<i>inches</i>	<i>inches</i>	<i>inches</i>					
CRS54x09.53-COM	53.6 <i>2.110</i>	9.525 <i>0.375</i>	53.975 <i>2.125</i>	Complete	3.200	16.271	107.4	214.8
# CRS54x09.53-HUB	53.6 <i>2.110</i>	9.525 <i>0.375</i>	53.975 <i>2.125</i>	Single Hub	3.200	16.271		
CRS54x11.13-COM	53.6 <i>2.110</i>	11.125 <i>0.438</i>	53.975 <i>2.125</i>	Complete	3.200	16.271	107.4	214.8
# CRS54x11.13-HUB	53.6 <i>2.110</i>	11.125 <i>0.438</i>	53.975 <i>2.125</i>	Single Hub	3.200	16.271		
# CRS54x12.70-HUB	53.6 <i>2.110</i>	12.700 <i>0.500</i>	53.975 <i>2.125</i>	Single Hub	3.200	16.271		
CRS54x12.70-COM	53.6 <i>2.110</i>	12.700 <i>0.500</i>	53.975 <i>2.125</i>	Complete	3.200	16.271	107.4	214.8
# CRS54-RSP	53.6 <i>2.110</i>	N/A	53.975 <i>2.125</i>	Rubber Spider Only	3.200	16.271		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
