




MBA

Couplings - Slit Type



Aluminium - Stainless Steel - Flexible - Zero Backlash. 0.1 to 35 Nm. 2400 to 48000 rpm.

High Torsional Stiffness.

Zero Backlash.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL0814-0200-0200-3G	8.0 <i>0.315</i>	2.000 / 2.000 <i>inches</i>	14.0 <i>0.551</i>	0.2	48000	Pin Hub - Set Screw	Stainless Steel	2.0	0.87
# CPSL0814-0200-0200-AG	8.0 <i>0.315</i>	2.000 / 2.000 <i>inches</i>	14.0 <i>0.551</i>	0.1	48000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.44
# CPSL0814-0200-0300-3G	8.0 <i>0.315</i>	2.000 / 3.000 <i>inches</i>	14.0 <i>0.551</i>	0.2	48000	Pin Hub - Set Screw	Stainless Steel	2.0	0.87

Indicates item not stocked at time of printing - Please enquire for lead time
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
CPSL0814-0200-0300-AG	8.0 <i>0.315</i>	2.000 / 3.000	14.0 <i>0.551</i>	0.1	48000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.44
# CPSL0814-0300-0300-3G	8.0 <i>0.315</i>	3.000 / 3.000	14.0 <i>0.551</i>	0.2	48000	Pin Hub - Set Screw	Stainless Steel	2.0	0.87
# CPSL0814-0300-0300-AG	8.0 <i>0.315</i>	3.000 / 3.000	14.0 <i>0.551</i>	0.1	48000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.44
# CPSL0814-0318-0318-3G	8.0 <i>0.315</i>	3.175 / 3.175	14.0 <i>0.551</i>	0.2	48000	Pin Hub	Stainless Steel	2.0	0.87
# CPSL0814-0318-0318-AG	8.0 <i>0.315</i>	3.175 / 3.175	14.0 <i>0.551</i>	0.1	48000	Pin Hub	Aluminum Alloy	2.0	0.44
# CPSL1219-0300-0300-AG	12.0 <i>0.472</i>	3.000 / 3.000	18.5 <i>0.728</i>	0.2	32000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.61
# CPSL1219-0300-0300-3G	12.0 <i>0.472</i>	3.000 / 3.000	18.5 <i>0.728</i>	0.3	32000	Pin Hub - Set Screw	Stainless Steel	2.0	1.12
# CPSL1218-0318-0318-3S	12.0 <i>0.472</i>	3.175 / 3.175	18.5 <i>0.728</i>	0.3	12000	Split Hub	Stainless Steel	2.0	1.12
# CPSL1218-0318-0318-AS	12.0 <i>0.472</i>	3.175 / 3.175	18.5 <i>0.728</i>	0.2	12000	Split Hub	Aluminum Alloy	2.0	0.61

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL1219-0400-0400-AG	12.0 <i>0.472</i>	4.000 / 4.000	18.5 <i>0.728</i>	0.2	32000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.61
# CPSL1219-0400-0400-AS	12.0 <i>0.472</i>	4.000 / 4.000	18.5 <i>0.728</i>	0.2	12000	Split Hub	Anodized Aluminum	2.0	0.61
# CPSL1219-0400-0400-3G	12.0 <i>0.472</i>	4.000 / 4.000	18.5 <i>0.728</i>	0.3	32000	Pin Hub - Set Screw	Stainless Steel	2.0	1.12
# CPSL1219-0400-0400-3S	12.0 <i>0.472</i>	4.000 / 4.000	18.5 <i>0.728</i>	0.3	12000	Split Hub	Stainless Steel	2.0	1.12
# CPSL1219-0400-0500-AS	12.0 <i>0.472</i>	4.000 / 5.000	18.5 <i>0.728</i>	0.2	12000	Split Hub	Anodized Aluminum	2.0	0.61
# CPSL1219-0400-0500-3S	12.0 <i>0.472</i>	4.000 / 5.000	18.5 <i>0.728</i>	0.3	12000	Split Hub	Stainless Steel	2.0	1.12
# CPSL1218-0476-0476-3S	12.0 <i>0.472</i>	4.763 / 4.763	18.5 <i>0.728</i>	0.3	12000	Split Hub	Stainless Steel	2.0	1.12
CPSL1218-0476-0476-AG	12.0 <i>0.472</i>	4.763 / 4.763	18.5 <i>0.728</i>	0.2	32000	Pin Hub	Aluminum Alloy	2.0	0.61
# CPSL1218-0476-0476-3G	12.0 <i>0.472</i>	4.763 / 4.763	18.5 <i>0.728</i>	0.3	32000	Pin Hub	Stainless Steel	2.0	1.12

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL1218-0476-0476-AS	12.0 <i>0.472</i>	4.763 / 4.763	18.5 <i>0.728</i>	0.2	12000	Split Hub	Aluminum Alloy	2.0	0.61
# CPSL1219-0500-0500-AG	12.0 <i>0.472</i>	5.000 / 5.000	18.5 <i>0.728</i>	0.2	32000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.61
# CPSL1219-0500-0500-AS	12.0 <i>0.472</i>	5.000 / 5.000	18.5 <i>0.728</i>	0.2	12000	Split Hub	Anodized Aluminum	2.0	0.61
CPSL1219-0500-0500-3G	12.0 <i>0.472</i>	5.000 / 5.000	18.5 <i>0.728</i>	0.3	32000	Pin Hub - Set Screw	Stainless Steel	2.0	1.12
# CPSL1219-0500-0500-3S	12.0 <i>0.472</i>	5.000 / 5.000	18.5 <i>0.728</i>	0.3	12000	Split Hub	Stainless Steel	2.0	1.12
# CPSL1617-0318-0318-AS	16.0 <i>0.630</i>	3.175 / 3.175	17.4 <i>0.685</i>	0.5	9500	Split Hub	Aluminum Alloy	0.5	3.49
# CPSL1623-0318-0318-AS	16.0 <i>0.630</i>	3.175 / 3.175	23.0 <i>0.906</i>	0.3	9500	Split Hub	Aluminum Alloy	2.0	0.82
# CPSL1623-0318-0318-3S	16.0 <i>0.630</i>	3.175 / 3.175	23.0 <i>0.906</i>	0.5	9500	Split Hub	Stainless Steel	2.0	1.48
# CPSL1623-0400-0400-3G	16.0 <i>0.630</i>	4.000 / 4.000	23.0 <i>0.906</i>	0.5	24000	Pin Hub - Set Screw	Stainless Steel	2.0	1.48

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL1623-0400-0400-AG	16.0 <i>0.630</i>	4.000 / 4.000	23.0 <i>0.906</i>	0.3	24000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.82
# CPSL1623-0400-0600-AG	16.0 <i>0.630</i>	4.000 / 6.000	23.0 <i>0.906</i>	0.3	24000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.82
# CPSL1623-0400-0600-3G	16.0 <i>0.630</i>	4.000 / 6.000	23.0 <i>0.906</i>	0.5	24000	Pin Hub - Set Screw	Stainless Steel	2.0	1.48
# CPSL1617-0476-0476-AS	16.0 <i>0.630</i>	4.763 / 4.763	17.4 <i>0.685</i>	0.5	9500	Split Hub	Aluminum Alloy	0.5	3.49
# CPSL1623-0476-0476-3S	16.0 <i>0.630</i>	4.763 / 4.763	23.0 <i>0.906</i>	0.5	9500	Split Hub	Stainless Steel	2.0	1.48
# CPSL1623-0476-0476-AS	16.0 <i>0.630</i>	4.763 / 4.763	23.0 <i>0.906</i>	0.3	9500	Split Hub	Aluminum Alloy	2.0	0.82
# CPSL1623-0500-0500-3S	16.0 <i>0.630</i>	5.000 / 5.000	23.0 <i>0.906</i>	0.5	9500	Split Hub	Stainless Steel	2.0	1.48
# CPSL1623-0500-0500-AS	16.0 <i>0.630</i>	5.000 / 5.000	23.0 <i>0.906</i>	0.3	9500	Split Hub	Anodized Aluminum	2.0	0.82
# CPSL1623-0500-0600-3S	16.0 <i>0.630</i>	5.000 / 6.000	23.0 <i>0.906</i>	0.5	9500	Split Hub	Stainless Steel	2.0	1.48

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL1623-0500-0600-AS	16.0 <i>0.630</i>	5.000 / 6.000 <i>inches</i>	23.0 <i>0.906</i>	0.3	9500	Split Hub	Anodized Aluminum	2.0	0.82
# CPSL1617-0600-0600-DG	16.0 <i>0.630</i>	6.000 / 6.000	17.4 <i>0.685</i>	0.5	24000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	3.49
# CPSL1623-0600-0600-AG	16.0 <i>0.630</i>	6.000 / 6.000	23.0 <i>0.906</i>	0.3	24000	Pin Hub - Set Screw	Anodized Aluminum	2.0	0.82
# CPSL1623-0600-0600-3S	16.0 <i>0.630</i>	6.000 / 6.000	23.0 <i>0.906</i>	0.5	9500	Split Hub	Stainless Steel	2.0	1.48
# CPSL1623-0600-0600-AS	16.0 <i>0.630</i>	6.000 / 6.000	23.0 <i>0.906</i>	0.3	9500	Split Hub	Anodized Aluminum	2.0	0.82
CPSL1623-0600-0600-3G	16.0 <i>0.630</i>	6.000 / 6.000	23.0 <i>0.906</i>	0.5	24000	Pin Hub - Set Screw	Stainless Steel	2.0	1.48
# CPSL1617-0600-0600-DS	16.0 <i>0.630</i>	6.000 / 6.000	17.4 <i>0.685</i>	0.5	9500	Split Hub	Extra Super Duralumin	0.5	3.49
# CPSL1623-0635-0635-3G	16.0 <i>0.630</i>	6.350 / 6.350	23.0 <i>0.906</i>	0.5	24000	Pin Hub	Stainless Steel	2.0	1.48
CPSL1623-0635-0635-AG	16.0 <i>0.630</i>	6.350 / 6.350	23.0 <i>0.906</i>	0.3	24000	Pin Hub	Aluminum Alloy	2.0	0.82

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL1617-0635-0635-AG	16.0 <i>0.630</i>	6.350 / 6.350	17.4 <i>0.685</i>	0.5	24000	Pin Hub - Set Screw	Aluminum Alloy	0.5	3.49
# CPSL1920-0476-0476-AS	19.0 <i>0.748</i>	4.763 / 4.763	20.0 <i>0.787</i>	1.0	8000	Split Hub	Aluminum Alloy	0.5	4.71
# CPSL1920-0600-0600-DG	19.0 <i>0.748</i>	6.000 / 6.000	20.0 <i>0.787</i>	1.0	20000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	4.71
# CPSL1920-0600-0600-DS	19.0 <i>0.748</i>	6.000 / 6.000	20.0 <i>0.787</i>	1.0	8000	Split Hub	Extra Super Duralumin	0.5	4.71
# CPSL1920-0600-0800-DG	19.0 <i>0.748</i>	6.000 / 8.000	20.0 <i>0.787</i>	1.0	20000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	4.71
# CPSL1920-0600-0800-DS	19.0 <i>0.748</i>	6.000 / 8.000	20.0 <i>0.787</i>	1.0	8000	Split Hub	Extra Super Duralumin	0.5	4.71
# CPSL1920-0635-0635-AG	19.0 <i>0.748</i>	6.350 / 6.350	20.0 <i>0.787</i>	1.0	20000	Pin Hub - Set Screw	Aluminum Alloy	0.5	4.71
CPSL1920-0635-0635-AS	19.0 <i>0.748</i>	6.350 / 6.350	20.0 <i>0.787</i>	1.0	8000	Split Hub	Aluminum Alloy	0.5	4.71
# CPSL1920-0800-0800-DG	19.0 <i>0.748</i>	8.000 / 8.000	20.0 <i>0.787</i>	1.0	20000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	4.71

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL1920-0800-0800-DS	19.0 <i>0.748</i>	8.000 / 8.000	20.0 <i>0.787</i>	1.0	8000	Split Hub	Extra Super Duralumin	0.5	4.71
CPSL1920-0953-0953-AG	19.0 <i>0.748</i>	9.525 / 9.525	20.0 <i>0.787</i>	1.0	20000	Pin Hub - Set Screw	Aluminum Alloy	0.5	4.71
# CPSL2026-0476-0476-AS	20.0 <i>0.787</i>	4.763 / 4.763	26.0 <i>1.024</i>	0.5	7600	Split Hub	Aluminum Alloy	2.0	2.10
# CPSL2026-0476-0476-3S	20.0 <i>0.787</i>	4.763 / 4.763	26.0 <i>1.024</i>	1.0	7600	Split Hub	Stainless Steel	2.0	4.36
# CPSL2026-0600-0600-3G	20.0 <i>0.787</i>	6.000 / 6.000	26.0 <i>1.024</i>	1.0	19000	Pin Hub - Set Screw	Stainless Steel	2.0	4.36
# CPSL2026-0600-0600-3S	20.0 <i>0.787</i>	6.000 / 6.000	26.0 <i>1.024</i>	1.0	7600	Split Hub	Stainless Steel	2.0	4.36
# CPSL2026-0600-0600-AG	20.0 <i>0.787</i>	6.000 / 6.000	26.0 <i>1.024</i>	0.5	19000	Pin Hub - Set Screw	Anodized Aluminum	2.0	2.09
CPSL2026-0600-0600-AS	20.0 <i>0.787</i>	6.000 / 6.000	26.0 <i>1.024</i>	0.5	7600	Split Hub	Anodized Aluminum	2.0	2.09
# CPSL2026-0600-0800-3S	20.0 <i>0.787</i>	6.000 / 8.000	26.0 <i>1.024</i>	1.0	7600	Split Hub	Stainless Steel	2.0	4.36

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL2026-0600-0800-AG	20.0 <i>0.787</i>	6.000 / 8.000	26.0 <i>1.024</i>	0.5	19000	Pin Hub - Set Screw	Anodized Aluminum	2.0	2.09
# CPSL2026-0600-0800-3G	20.0 <i>0.787</i>	6.000 / 8.000	26.0 <i>1.024</i>	1.0	19000	Pin Hub - Set Screw	Stainless Steel	2.0	4.36
# CPSL2026-0600-0800-AS	20.0 <i>0.787</i>	6.000 / 8.000	26.0 <i>1.024</i>	0.5	7600	Split Hub	Anodized Aluminum	2.0	2.09
# CPSL2026-0635-0635-3G	20.0 <i>0.787</i>	6.350 / 6.350	26.0 <i>1.024</i>	1.0	19000	Pin Hub	Stainless Steel	2.0	4.36
# CPSL2026-0635-0635-3S	20.0 <i>0.787</i>	6.350 / 6.350	26.0 <i>1.024</i>	1.0	7600	Split Hub	Stainless Steel	2.0	4.36
CPSL2026-0635-0635-AG	20.0 <i>0.787</i>	6.350 / 6.350	26.0 <i>1.024</i>	0.5	19000	Pin Hub	Aluminum Alloy	2.0	2.10
CPSL2026-0635-0635-AS	20.0 <i>0.787</i>	6.350 / 6.350	26.0 <i>1.024</i>	0.5	7600	Split Hub	Aluminum Alloy	2.0	2.10
# CPSL2026-0800-0800-3G	20.0 <i>0.787</i>	8.000 / 8.000	26.0 <i>1.024</i>	1.0	19000	Pin Hub - Set Screw	Stainless Steel	2.0	4.36
# CPSL2026-0800-0800-AS	20.0 <i>0.787</i>	8.000 / 8.000	26.0 <i>1.024</i>	0.5	7600	Split Hub	Anodized Aluminum	2.0	2.09

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL2026-0800-0800-3S	20.0 <i>0.787</i>	8.000 / 8.000	26.0 <i>1.024</i>	1.0	7600	Split Hub	Stainless Steel	2.0	4.36
# CPSL2026-0800-0800-AG	20.0 <i>0.787</i>	8.000 / 8.000	26.0 <i>1.024</i>	0.5	19000	Pin Hub - Set Screw	Anodized Aluminum	2.0	2.09
# CPSL2026-0953-0953-3G	20.0 <i>0.787</i>	9.525 / 9.525	26.0 <i>1.024</i>	1.0	19000	Pin Hub	Stainless Steel	2.0	4.36
# CPSL2026-0953-0953-AG	20.0 <i>0.787</i>	9.525 / 9.525	26.0 <i>1.024</i>	0.5	19000	Pin Hub	Aluminum Alloy	2.0	2.10
# CPSL2425-0635-0635-AG	24.0 <i>0.945</i>	6.350 / 6.350	25.0 <i>0.984</i>	1.5	16000	Pin Hub - Set Screw	Aluminum Alloy	0.5	13.79
# CPSL2425-0635-0635-AS	24.0 <i>0.945</i>	6.350 / 6.350	25.0 <i>0.984</i>	1.5	6300	Split Hub	Aluminum Alloy	0.5	13.79
# CPSL2425-0800-0800-DG	24.0 <i>0.945</i>	8.000 / 8.000	25.0 <i>0.984</i>	1.5	16000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	13.79
# CPSL2425-0800-0800-DS	24.0 <i>0.945</i>	8.000 / 8.000	25.0 <i>0.984</i>	1.5	6300	Split Hub	Extra Super Duralumin	0.5	13.79
# CPSL2425-0800-1000-DG	24.0 <i>0.945</i>	8.000 / 10.000	25.0 <i>0.984</i>	1.5	16000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	13.79

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL2425-0800-1000-DS	24.0 <i>0.945</i>	8.000 / 10.000	25.0 <i>0.984</i>	1.5	6300	Split Hub	Extra Super Duralumin	0.5	13.79
# CPSL2425-0953-0953-AG	24.0 <i>0.945</i>	9.525 / 9.525	25.0 <i>0.984</i>	1.5	16000	Pin Hub - Set Screw	Aluminum Alloy	0.5	13.79
# CPSL2425-0953-0953-AS	24.0 <i>0.945</i>	9.525 / 9.525	25.0 <i>0.984</i>	1.5	6300	Split Hub	Aluminum Alloy	0.5	13.79
# CPSL2425-1000-1000-DS	24.0 <i>0.945</i>	10.000 / 10.000	25.0 <i>0.984</i>	1.5	6300	Split Hub	Extra Super Duralumin	0.5	13.79
# CPSL2425-1000-1000-DG	24.0 <i>0.945</i>	10.000 / 10.000	25.0 <i>0.984</i>	1.5	16000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	13.79
# CPSL2531-0600-0600-AS	25.0 <i>0.984</i>	6.000 / 6.000	31.0 <i>1.220</i>	1.0	6100	Split Hub	Anodized Aluminum	2.0	2.97
# CPSL2531-0600-0600-3S	25.0 <i>0.984</i>	6.000 / 6.000	31.0 <i>1.220</i>	2.0	6100	Split Hub	Stainless Steel	2.0	5.76
# CPSL2531-0600-0800-3S	25.0 <i>0.984</i>	6.000 / 8.000	31.0 <i>1.220</i>	2.0	6100	Split Hub	Stainless Steel	2.0	5.76
# CPSL2531-0600-0800-AS	25.0 <i>0.984</i>	6.000 / 8.000	31.0 <i>1.220</i>	1.0	6100	Split Hub	Anodized Aluminum	2.0	2.97

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL2531-0635-0635-3G	25.0 <i>0.984</i>	6.350 / 6.350	31.0 <i>1.220</i>	2.0	15000	Pin Hub	Stainless Steel	2.0	5.76
# CPSL2531-0635-0635-3S	25.0 <i>0.984</i>	6.350 / 6.350	31.0 <i>1.220</i>	2.0	6100	Split Hub	Stainless Steel	2.0	5.76
# CPSL2531-0635-0635-AG	25.0 <i>0.984</i>	6.350 / 6.350	31.0 <i>1.220</i>	1.0	15000	Pin Hub	Aluminum Alloy	2.0	2.97
CPSL2531-0635-0635-AS	25.0 <i>0.984</i>	6.350 / 6.350	31.0 <i>1.220</i>	1.0	6100	Split Hub	Aluminum Alloy	2.0	2.97
# CPSL2531-0800-0800-3G	25.0 <i>0.984</i>	8.000 / 8.000	31.0 <i>1.220</i>	2.0	15000	Pin Hub - Set Screw	Stainless Steel	2.0	5.76
# CPSL2531-0800-0800-3S	25.0 <i>0.984</i>	8.000 / 8.000	31.0 <i>1.220</i>	2.0	6100	Split Hub	Stainless Steel	2.0	5.76
# CPSL2531-0800-0800-AG	25.0 <i>0.984</i>	8.000 / 8.000	31.0 <i>1.220</i>	1.0	15000	Pin Hub - Set Screw	Anodized Aluminum	2.0	2.97
# CPSL2531-0800-0800-AS	25.0 <i>0.984</i>	8.000 / 8.000	31.0 <i>1.220</i>	1.0	6100	Split Hub	Anodized Aluminum	2.0	2.97
# CPSL2531-0800-1000-AG	25.0 <i>0.984</i>	8.000 / 10.000	31.0 <i>1.220</i>	1.0	15000	Pin Hub - Set Screw	Anodized Aluminum	2.0	2.97

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL2531-0800-1000-AS	25.0 <i>0.984</i>	8.000 / 10.000	31.0 <i>1.220</i>	1.0	6100	Split Hub	Anodized Aluminum	2.0	2.97
# CPSL2531-0800-1000-3G	25.0 <i>0.984</i>	8.000 / 10.000	31.0 <i>1.220</i>	2.0	15000	Pin Hub - Set Screw	Stainless Steel	2.0	5.76
# CPSL2531-0800-1000-3S	25.0 <i>0.984</i>	8.000 / 10.000	31.0 <i>1.220</i>	2.0	6100	Split Hub	Stainless Steel	2.0	5.76
# CPSL2531-0953-0953-3G	25.0 <i>0.984</i>	9.525 / 9.525	31.0 <i>1.220</i>	2.0	15000	Pin Hub	Stainless Steel	2.0	5.76
# CPSL2531-0953-0953-3S	25.0 <i>0.984</i>	9.525 / 9.525	31.0 <i>1.220</i>	2.0	6100	Split Hub	Stainless Steel	2.0	5.76
# CPSL2531-0953-0953-AG	25.0 <i>0.984</i>	9.525 / 9.525	31.0 <i>1.220</i>	1.0	15000	Pin Hub	Aluminum Alloy	2.0	2.97
# CPSL2531-0953-0953-AS	25.0 <i>0.984</i>	9.525 / 9.525	31.0 <i>1.220</i>	1.0	6100	Split Hub	Aluminum Alloy	2.0	2.97
# CPSL2531-1000-1000-3S	25.0 <i>0.984</i>	10.000 / 10.000	31.0 <i>1.220</i>	2.0	6100	Split Hub	Stainless Steel	2.0	5.76
# CPSL2531-1000-1000-AG	25.0 <i>0.984</i>	10.000 / 10.000	31.0 <i>1.220</i>	1.0	15000	Pin Hub - Set Screw	Anodized Aluminum	2.0	2.97

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL2531-1000-1000-3G	25.0 <i>0.984</i>	10.000 / 10.000	31.0 <i>1.220</i>	2.0	15000	Pin Hub - Set Screw	Stainless Steel	2.0	5.76
# CPSL2531-1000-1000-AS	25.0 <i>0.984</i>	10.000 / 10.000	31.0 <i>1.220</i>	1.0	6100	Split Hub	Anodized Aluminum	2.0	2.97
# CPSL2930-0953-0953-AG	29.0 <i>1.142</i>	9.525 / 9.525	30.0 <i>1.181</i>	2.0	13000	Pin Hub - Set Screw	Aluminum Alloy	0.5	24.44
# CPSL2930-0953-0953-AS	29.0 <i>1.142</i>	9.525 / 9.525	30.0 <i>1.181</i>	2.0	5200	Split Hub	Aluminum Alloy	0.5	24.44
# CPSL2930-1000-1000-DG	29.0 <i>1.142</i>	10.000 / 10.000	30.0 <i>1.181</i>	2.0	13000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	24.43
CPSL2930-1000-1000-DS	29.0 <i>1.142</i>	10.000 / 10.000	30.0 <i>1.181</i>	2.0	5200	Split Hub	Extra Super Duralumin	0.5	24.43
# CPSL2930-1000-1200-DG	29.0 <i>1.142</i>	10.000 / 12.000	30.0 <i>1.181</i>	2.0	13000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	24.43
# CPSL2930-1000-1200-DS	29.0 <i>1.142</i>	10.000 / 12.000	30.0 <i>1.181</i>	2.0	5200	Split Hub	Extra Super Duralumin	0.5	24.43

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL2930-1200-1200-DS	29.0 <i>1.142</i>	12.000 / 12.000	30.0 <i>1.181</i>	2.0	5200	Split Hub	Extra Super Duralumin	0.5	24.43
CPSL2930-1200-1200-DG	29.0 <i>1.142</i>	12.000 / 12.000	30.0 <i>1.181</i>	2.0	13000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	24.43
# CPSL2930-1270-1270-AG	29.0 <i>1.142</i>	12.700 / 12.700	30.0 <i>1.181</i>	2.0	13000	Pin Hub - Set Screw	Aluminum Alloy	0.5	24.44
# CPSL32/41-0500-0600-AG	32.0 <i>1.260</i>	5.000 / 6.000	41.0 <i>1.614</i>	2.0	12000	Pin Hub / Set Screw	Aluminum Alloy	2.0	4.89
# CPSL3241-0800-0800-3G	32.0 <i>1.260</i>	8.000 / 8.000	41.0 <i>1.614</i>	3.5	12000	Pin Hub - Set Screw	Stainless Steel	2.0	14.83
# CPSL3241-0800-0800-3S	32.0 <i>1.260</i>	8.000 / 8.000	41.0 <i>1.614</i>	3.5	4800	Split Hub	Stainless Steel	2.0	14.83
# CPSL3241-0800-0800-AG	32.0 <i>1.260</i>	8.000 / 8.000	41.0 <i>1.614</i>	2.0	12000	Pin Hub - Set Screw	Anodized Aluminum	2.0	4.89
# CPSL3241-0800-0800-AS	32.0 <i>1.260</i>	8.000 / 8.000	41.0 <i>1.614</i>	2.0	4800	Split Hub	Anodized Aluminum	2.0	4.89

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL3241-0800-1000-3G	32.0 <i>1.260</i>	8.000 / 10.000	41.0 <i>1.614</i>	3.5	12000	Pin Hub - Set Screw	Stainless Steel	2.0	14.83
# CPSL3241-0800-1000-3S	32.0 <i>1.260</i>	8.000 / 10.000	41.0 <i>1.614</i>	3.5	4800	Split Hub	Stainless Steel	2.0	14.83
# CPSL3241-0800-1000-AG	32.0 <i>1.260</i>	8.000 / 10.000	41.0 <i>1.614</i>	2.0	12000	Pin Hub - Set Screw	Anodized Aluminum	2.0	4.89
# CPSL3241-0800-1000-AS	32.0 <i>1.260</i>	8.000 / 10.000	41.0 <i>1.614</i>	2.0	4800	Split Hub	Anodized Aluminum	2.0	4.89
# CPSL3241-0953-0953-3S	32.0 <i>1.260</i>	9.525 / 9.525	41.0 <i>1.614</i>	3.5	4800	Split Hub	Stainless Steel	2.0	14.84
# CPSL3241-0953-0953-AS	32.0 <i>1.260</i>	9.525 / 9.525	41.0 <i>1.614</i>	2.0	4800	Split Hub	Aluminum Alloy	2.0	4.89
# CPSL3241-0953-0953-AG	32.0 <i>1.260</i>	9.525 / 9.525	41.0 <i>1.614</i>	2.0	12000	Pin Hub	Aluminum Alloy	2.0	4.89
# CPSL3241-0953-0953-3G	32.0 <i>1.260</i>	9.525 / 9.525	41.0 <i>1.614</i>	3.5	4800	Pin Hub	Stainless Steel	2.0	14.84
# CPSL3241-0953-0953-3GK	32.0 <i>1.260</i>	9.525 / 9.525	41.0 <i>1.614</i>	3.5	4800	Pin Hub / Kwy.	Stainless Steel	2.0	4.89

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL3241-0953-0953-AGK	32.0 <i>1.260</i>	9.525 / 9.525 <i>inches</i>	41.0 <i>1.614</i>	3.5	4800	Pin Hub / Kwy.	Aluminum Alloy	2.0	14.84
# CPSL3241-1000-1000-3G	32.0 <i>1.260</i>	10.000 / 10.000	41.0 <i>1.614</i>	3.5	12000	Pin Hub - Set Screw	Stainless Steel	2.0	14.83
# CPSL3241-1000-1000-3S	32.0 <i>1.260</i>	10.000 / 10.000	41.0 <i>1.614</i>	3.5	4800	Split Hub	Stainless Steel	2.0	14.83
# CPSL3241-1000-1000-AG	32.0 <i>1.260</i>	10.000 / 10.000	41.0 <i>1.614</i>	2.0	12000	Pin Hub - Set Screw	Anodized Aluminum	2.0	4.89
# CPSL3241-1000-1000-AS	32.0 <i>1.260</i>	10.000 / 10.000	41.0 <i>1.614</i>	2.0	4800	Split Hub	Anodized Aluminum	2.0	4.89
# CPSL3241-1200-1200-3G	32.0 <i>1.260</i>	12.000 / 12.000	41.0 <i>1.614</i>	3.5	12000	Pin Hub - Set Screw	Stainless Steel	2.0	14.83
# CPSL3241-1200-1200-AS	32.0 <i>1.260</i>	12.000 / 12.000	41.0 <i>1.614</i>	2.0	4800	Split Hub	Anodized Aluminum	2.0	4.89
# CPSL3241-1200-1200-AG	32.0 <i>1.260</i>	12.000 / 12.000	41.0 <i>1.614</i>	2.0	12000	Pin Hub - Set Screw	Anodized Aluminum	2.0	4.89
# CPSL3241-1200-1200-3GK	32.0 <i>1.260</i>	12.000 / 12.000	41.0 <i>1.614</i>	3.5	4800	Pin Hub -4X1.8 KWY	Stainless Steel	2.0	14.83

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL3241-1200-1200-3S	32.0 <i>1.260</i>	12.000 / 12.000	41.0 <i>1.614</i>	3.5	4800	Split Hub	Stainless Steel	2.0	14.83
# CPSL3241-1200-1400-3S	32.0 <i>1.260</i>	12.000 / 14.000	41.0 <i>1.614</i>	3.5	4800	Split Hub	Stainless Steel	2.0	14.83
# CPSL3241-1200-1400-AS	32.0 <i>1.260</i>	12.000 / 14.000	41.0 <i>1.614</i>	2.0	4800	Split Hub	Anodized Aluminum	2.0	4.89
# CPSL3241-1270-1270-3S	32.0 <i>1.260</i>	12.700 / 12.700	41.0 <i>1.614</i>	3.5	4800	Split Hub	Stainless Steel	2.0	14.84
# CPSL3241-1270-1270-AG	32.0 <i>1.260</i>	12.700 / 12.700	41.0 <i>1.614</i>	2.0	12000	Pin Hub	Aluminum Alloy	2.0	4.89
# CPSL3241-1270-1270-3G	32.0 <i>1.260</i>	12.700 / 12.700	41.0 <i>1.614</i>	3.5	4800	Pin Hub	Stainless Steel	2.0	14.84
# CPSL3241-1270-1270-AS	32.0 <i>1.260</i>	12.700 / 12.700	41.0 <i>1.614</i>	2.0	4800	Split Hub	Aluminum Alloy	2.0	4.89
# CPSL3241-1400-1400-3G	32.0 <i>1.260</i>	14.000 / 14.000	41.0 <i>1.614</i>	3.5	12000	Pin Hub - Set Screw	Stainless Steel	2.0	14.83
# CPSL3241-1400-1400-3GK	32.0 <i>1.260</i>	14.000 / 14.000	41.0 <i>1.614</i>	3.5	4800	Pin Hub -5X2.3 KWY	Stainless Steel	2.0	14.83

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL3241-1400-1400-AG	32.0 <i>1.260</i>	14.000 / 14.000	41.0 <i>1.614</i>	2.0	12000	Pin Hub - Set Screw	Anodized Aluminum	2.0	4.89
# CPSL3241-1400-1400-AGK	32.0 <i>1.260</i>	14.000 / 14.000	41.0 <i>1.614</i>	2.0	4800	Pin Hub -5X2.3 KWY	Anodized Aluminum	2.0	4.89
# CPSL3435-0953-0953-AS	34.0 <i>1.339</i>	9.525 / 9.525	35.0 <i>1.378</i>	3.0	4400	Split Hub	Aluminum Alloy	0.5	38.40
# CPSL3435-1200-1200-DG	34.0 <i>1.339</i>	12.000 / 12.000	35.0 <i>1.378</i>	3.0	11000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	38.39
# CPSL3435-1200-1200-DS	34.0 <i>1.339</i>	12.000 / 12.000	35.0 <i>1.378</i>	3.0	4400	Split Hub	Extra Super Duralumin	0.5	38.39
# CPSL3435-1200-1600-DG	34.0 <i>1.339</i>	12.000 / 16.000	35.0 <i>1.378</i>	3.0	11000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	38.39
# CPSL3435-1200-1600-DS	34.0 <i>1.339</i>	12.000 / 16.000	35.0 <i>1.378</i>	3.0	4400	Split Hub	Extra Super Duralumin	0.5	38.39
# CPSL3435-1270-1270-AG	34.0 <i>1.339</i>	12.700 / 12.700	35.0 <i>1.378</i>	3.0	11000	Pin Hub - Set Screw	Aluminum Alloy	0.5	38.40
# CPSL3435-1270-1270-AS	34.0 <i>1.339</i>	12.700 / 12.700	35.0 <i>1.378</i>	3.0	4400	Split Hub	Aluminum Alloy	0.5	38.40

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
CPSL3435-1588-1588-AG	34.0 <i>1.339</i>	15.875 / 15.875 <i>inches</i>	35.0 <i>1.378</i>	3.0	11000	Pin Hub - Set Screw	Aluminum Alloy	0.5	38.40
# CPSL3435-1600-1600-DG	34.0 <i>1.339</i>	16.000 / 16.000	35.0 <i>1.378</i>	3.0	11000	Pin Hub - Set Screw	Extra Super Duralumin	0.5	38.39
# CPSL3435-1600-1600-DS	34.0 <i>1.339</i>	16.000 / 16.000	35.0 <i>1.378</i>	3.0	4400	Split Hub	Extra Super Duralumin	0.5	38.39
# CPSL4056-0800-0800-AS	40.0 <i>1.575</i>	8.000 / 8.000	56.0 <i>2.205</i>	5.0	3800	Split Hub	Anodized Aluminum	2.0	6.11
# CPSL4056-0800-0800-3S	40.0 <i>1.575</i>	8.000 / 8.000	56.0 <i>2.205</i>	8.0	3800	Split Hub	Stainless Steel	2.0	17.45
# CPSL4056-0953-0953-3S	40.0 <i>1.575</i>	9.525 / 9.525	56.0 <i>2.205</i>	8.0	3800	Split Hub	Stainless Steel	2.0	17.46
# CPSL4056-0953-0953-AS	40.0 <i>1.575</i>	9.525 / 9.525	56.0 <i>2.205</i>	5.0	3800	Split Hub	Aluminum Alloy	2.0	6.11
# CPSL4056-1000-1000-3G	40.0 <i>1.575</i>	10.000 / 10.000	56.0 <i>2.205</i>	8.0	9600	Pin Hub - Set Screw	Stainless Steel	2.0	17.45
# CPSL4056-1000-1000-AG	40.0 <i>1.575</i>	10.000 / 10.000	56.0 <i>2.205</i>	5.0	9600	Pin Hub - Set Screw	Anodized Aluminum	2.0	6.11

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL4056-1200-1200-3G	40.0 <i>1.575</i>	12.000 / 12.000	56.0 <i>2.205</i>	8.0	9600	Pin Hub - Set Screw	Stainless Steel	2.0	17.45
# CPSL4056-1200-1200-AS	40.0 <i>1.575</i>	12.000 / 12.000	56.0 <i>2.205</i>	5.0	3800	Split Hub	Anodized Aluminum	2.0	6.11
# CPSL4056-1200-1200-3S	40.0 <i>1.575</i>	12.000 / 12.000	56.0 <i>2.205</i>	8.0	3800	Split Hub	Stainless Steel	2.0	17.45
# CPSL4056-1200-1200-AG	40.0 <i>1.575</i>	12.000 / 12.000	56.0 <i>2.205</i>	5.0	9600	Pin Hub - Set Screw	Anodized Aluminum	2.0	6.11
# CPSL4056-1200-1400-AS	40.0 <i>1.575</i>	12.000 / 14.000	56.0 <i>2.205</i>	5.0	3800	Split Hub	Anodized Aluminum	2.0	6.11
# CPSL4056-1200-1400-3S	40.0 <i>1.575</i>	12.000 / 14.000	56.0 <i>2.205</i>	8.0	3800	Split Hub	Stainless Steel	2.0	17.45
# CPSL4056-1270-1270-AS	40.0 <i>1.575</i>	12.700 / 12.700	56.0 <i>2.205</i>	5.0	3800	Split Hub	Aluminum Alloy	2.0	6.11
# CPSL4056-1270-1270-AGK	40.0 <i>1.575</i>	12.700 / 12.700	56.0 <i>2.205</i>	8.0	3800	Pin Hub / Kwy.	Aluminum Alloy	2.0	17.46
# CPSL4056-1270-1270-AG	40.0 <i>1.575</i>	12.700 / 12.700	56.0 <i>2.205</i>	5.0	9600	Pin Hub	Aluminum Alloy	2.0	6.11

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL4056-1270-1270-3G	40.0 <i>1.575</i>	12.700 / 12.700	56.0 <i>2.205</i>	8.0	3800	Pin Hub	Stainless Steel	2.0	17.46
# CPSL4056-1270-1270-3GK	40.0 <i>1.575</i>	12.700 / 12.700	56.0 <i>2.205</i>	8.0	3800	Pin Hub / Kwy.	Stainless Steel	2.0	6.11
# CPSL4056-1270-1270-3S	40.0 <i>1.575</i>	12.700 / 12.700	56.0 <i>2.205</i>	8.0	3800	Split Hub	Stainless Steel	2.0	17.46
# CPSL4056-1400-1400-3G	40.0 <i>1.575</i>	14.000 / 14.000	56.0 <i>2.205</i>	8.0	9600	Pin Hub - Set Screw	Stainless Steel	2.0	17.45
# CPSL4056-1400-1400-3GK	40.0 <i>1.575</i>	14.000 / 14.000	56.0 <i>2.205</i>	3.5	4800	Pin Hub -5X2.3 KWY	Stainless Steel	2.0	14.83
# CPSL4056-1400-1400-3S	40.0 <i>1.575</i>	14.000 / 14.000	56.0 <i>2.205</i>	8.0	3800	Split Hub	Stainless Steel	2.0	17.45
# CPSL4056-1400-1400-AG	40.0 <i>1.575</i>	14.000 / 14.000	56.0 <i>2.205</i>	5.0	9600	Pin Hub - Set Screw	Anodized Aluminum	2.0	6.11
# CPSL4056-1400-1400-AGK	40.0 <i>1.575</i>	14.000 / 14.000	56.0 <i>2.205</i>	5.0	3800	Pin Hub -5X2.3 KWY	Anodized Aluminum	2.0	6.11
# CPSL4056-1400-1400-AS	40.0 <i>1.575</i>	14.000 / 14.000	56.0 <i>2.205</i>	5.0	3800	Split Hub	Anodized Aluminum	2.0	6.11

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL4056-1588-1588-3G	40.0 <i>1.575</i>	15.875 / 15.875	56.0 <i>2.205</i>	8.0	3800	Pin Hub	Stainless Steel	2.0	17.46
# CPSL4056-1588-1588-AG	40.0 <i>1.575</i>	15.875 / 15.875	56.0 <i>2.205</i>	5.0	9600	Pin Hub	Aluminum Alloy	2.0	6.11
# CPSL4056-1600-1600-AGK	40.0 <i>1.575</i>	16.000 / 16.000	56.0 <i>2.205</i>	5.0	3800	Pin Hub -5X2.3 KWY	Anodized Aluminum	2.0	6.11
# CPSL4056-1600-1600-3GK	40.0 <i>1.575</i>	16.000 / 16.000	56.0 <i>2.205</i>	8.0	3800	Pin Hub -5X2.3 KWY	Stainless Steel	2.0	17.45
# CPSL4056-1800-1800-3GK	40.0 <i>1.575</i>	18.000 / 18.000	56.0 <i>2.205</i>	8.0	3800	Pin Hub -6X2.8 KWY	Stainless Steel	2.0	17.45
# CPSL4056-1800-1800-AGK	40.0 <i>1.575</i>	18.000 / 18.000	56.0 <i>2.205</i>	5.0	3800	Pin Hub -6X2.8 KWY	Anodized Aluminum	2.0	6.11
# CPSL5071-1200-1200-3S	50.0 <i>1.969</i>	12.000 / 12.000	71.0 <i>2.795</i>	15.0	7700	Split Type	Stainless Steel	2.00	1400.00
# CPSL5071-1200-1200-AS	50.0 <i>1.969</i>	12.000 / 12.000	71.0 <i>2.795</i>	10.0	7700	Split Type	Anodized Aluminium	2.00	590.00
# CPSL5071-1270-1270-3G	50.0 <i>1.969</i>	12.700 / 12.700	71.0 <i>2.795</i>	15.0	3100	Pin Hub	Stainless Steel	2.0	24.44

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL5071-1270-1270-3S	50.0 <i>1.969</i>	12.700 / 12.700	71.0 <i>2.795</i>	15.0	3100	Split Hub	Stainless Steel	2.0	24.44
# CPSL5071-1270-1270-AG	50.0 <i>1.969</i>	12.700 / 12.700	71.0 <i>2.795</i>	10.0	7700	Pin Hub	Aluminum Alloy	2.0	10.30
# CPSL5071-1270-1270-AS	50.0 <i>1.969</i>	12.700 / 12.700	71.0 <i>2.795</i>	10.0	3100	Split Hub	Aluminum Alloy	2.0	10.30
# CPSL5071-1400-1400-3S	50.0 <i>1.969</i>	14.000 / 14.000	71.0 <i>2.795</i>	15.0	3100	Split Type	Stainless Steel	2.00	1400.00
# CPSL5071-1400-1400-AS	50.0 <i>1.969</i>	14.000 / 14.000	71.0 <i>2.795</i>	10.0	3100	Split Type	Anodized Aluminium	2.00	590.00
# CPSL5071-1588-1588-AG	50.0 <i>1.969</i>	15.875 / 15.875	71.0 <i>2.795</i>	10.0	7700	Pin Hub	Aluminum Alloy	2.0	10.30
# CPSL5071-1588-1588-AS	50.0 <i>1.969</i>	15.875 / 15.875	71.0 <i>2.795</i>	10.0	3100	Split Hub	Aluminum Alloy	2.0	10.30
# CPSL5071-1588-1588-AGK	50.0 <i>1.969</i>	15.875 / 15.875	71.0 <i>2.795</i>	15.0	3100	Pin Hub / Kwy.	Aluminum Alloy	2.0	24.44
# CPSL5071-1588-1588-3GK	50.0 <i>1.969</i>	15.875 / 15.875	71.0 <i>2.795</i>	15.0	3100	Pin Hub / Kwy.	Stainless Steel	2.0	10.29
# CPSL5071-1588-1588-3G	50.0 <i>1.969</i>	15.875 / 15.875	71.0 <i>2.795</i>	15.0	3100	Pin Hub	Stainless Steel	2.0	24.44

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL5071-1588-1588-3S	50.0 <i>1.969</i>	15.875 / 15.875	71.0 <i>2.795</i>	15.0	3100	Split Hub	Stainless Steel	2.0	24.44
# CPSL5071-1600-1600-3GK	50.0 <i>1.969</i>	16.000 / 16.000	71.0 <i>2.795</i>	15.0	3100	Pin Hub -5X2.3 KWY	Stainless Steel	2.0	24.43
# CPSL5071-1600-1600-3S	50.0 <i>1.969</i>	16.000 / 16.000	71.0 <i>2.795</i>	15.0	3100	Split Type	Stainless Steel	2.00	1400.00
# CPSL5071-1600-1600-AGK	50.0 <i>1.969</i>	16.000 / 16.000	71.0 <i>2.795</i>	10.0	3100	Pin Hub -5X2.3 KWY	Anodized Aluminum	2.0	10.30
# CPSL5071-1600-1600-AS	50.0 <i>1.969</i>	16.000 / 16.000	71.0 <i>2.795</i>	10.0	3100	Split Type	Anodized Aluminium	2.00	590.00
# CPSL5071-1800-1800-3GK	50.0 <i>1.969</i>	18.000 / 18.000	71.0 <i>2.795</i>	15.0	3100	Pin Hub -6X2.8 KWY	Stainless Steel	2.0	24.43
# CPSL5071-1800-1800-AGK	50.0 <i>1.969</i>	18.000 / 18.000	71.0 <i>2.795</i>	10.0	3100	Pin Hub -6X2.8 KWY	Anodized Aluminum	2.0	10.30
# CPSL5071-2000-2000-3GK	50.0 <i>1.969</i>	20.000 / 20.000	71.0 <i>2.795</i>	15.0	3100	Pin Hub -6X2.8 KWY	Stainless Steel	2.0	24.43
# CPSL5071-2000-2000-AGK	50.0 <i>1.969</i>	20.000 / 20.000	71.0 <i>2.795</i>	10.0	3100	Pin Hub -6X2.8 KWY	Anodized Aluminum	2.0	10.30

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL6390-1400-1400-3S	63.0 <i>2.480</i>	14.000 / 14.000	90.0 <i>3.543</i>	35.0	2400	Split Type	Stainless Steel	2.00	1800.00
# CPSL6390-1400-1400-AS	63.0 <i>2.480</i>	14.000 / 14.000	90.0 <i>3.543</i>	20.0	2400	Split Type	Anodized Aluminium	2.00	850.00
# CPSL6390-1588-1588-AG	63.0 <i>2.480</i>	15.875 / 15.875	90.0 <i>3.543</i>	20.0	6100	Pin Hub	Aluminum Alloy	2.0	14.84
# CPSL6390-1588-1588-3G	63.0 <i>2.480</i>	15.875 / 15.875	90.0 <i>3.543</i>	35.0	2400	Pin Hub	Stainless Steel	2.0	31.42
# CPSL6390-1600-1600-AS	63.0 <i>2.480</i>	16.000 / 16.000	90.0 <i>3.543</i>	20.0	2400	Split Type	Anodized Aluminium	2.00	850.00
# CPSL6390-1600-1600-3S	63.0 <i>2.480</i>	16.000 / 16.000	90.0 <i>3.543</i>	35.0	2400	Split Type	Stainless Steel	2.00	1800.00
# CPSL6390-1905-1905-AS	63.0 <i>2.480</i>	19.050 / 19.050	90.0 <i>3.543</i>	20.0	2400	Split Hub	Aluminum Alloy	2.0	14.84
# CPSL6390-1905-1905-3G	63.0 <i>2.480</i>	19.050 / 19.050	90.0 <i>3.543</i>	35.0	2400	Pin Hub	Stainless Steel	2.0	31.42
# CPSL6390-1905-1905-3GK	63.0 <i>2.480</i>	19.050 / 19.050	90.0 <i>3.543</i>	35.0	2400	Pin Hub / Kw.	Stainless Steel	2.0	14.84
# CPSL6390-1905-1905-3S	63.0 <i>2.480</i>	19.050 / 19.050	90.0 <i>3.543</i>	35.0	2400	Split Hub	Stainless Steel	2.0	31.42

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL6390-1905-1905-AG	63.0 <i>2.480</i>	19.050 / 19.050	90.0 <i>3.543</i>	20.0	6100	Pin Hub	Aluminum Alloy	2.0	14.84
# CPSL6390-1905-1905-AGK	63.0 <i>2.480</i>	19.050 / 19.050	90.0 <i>3.543</i>	35.0	2400	Pin Hub / Kwy.	Aluminum Alloy	2.0	31.43
# CPSL6390-2000-2000-3GK	63.0 <i>2.480</i>	20.000 / 20.000	90.0 <i>3.543</i>	35.0	2400	Pin Hub -6X2.8 KWY	Stainless Steel	2.0	31.41
# CPSL6390-2000-2000-AGK	63.0 <i>2.480</i>	20.000 / 20.000	90.0 <i>3.543</i>	20.0	2400	Pin Hub -6X2.8 KWY	Anodized Aluminum	2.0	14.83
# CPSL6390-2500-2500-3GK	63.0 <i>2.480</i>	25.000 / 25.000	90.0 <i>3.543</i>	35.0	2400	Pin Hub -8X3.3 KWY	Stainless Steel	2.0	31.41
# CPSL6390-2500-2500-AGK	63.0 <i>2.480</i>	25.000 / 25.000	90.0 <i>3.543</i>	20.0	2400	Pin Hub -8X3.3 KWY	Anodized Aluminum	2.0	14.83
# CPSL6390-2540-2540-3S	63.0 <i>2.480</i>	25.400 / 25.400	90.0 <i>3.543</i>	35.0	2400	Split Hub	Stainless Steel	2.0	31.42
# CPSL6390-2540-2540-AS	63.0 <i>2.480</i>	25.400 / 25.400	90.0 <i>3.543</i>	20.0	2400	Split Hub	Aluminum Alloy	2.0	14.84
# CPSL6390-3000-3000-AGK	63.0 <i>2.480</i>	30.000 / 30.000	90.0 <i>3.543</i>	20.0	2400	Pin Hub -8X3.3 KWY	Anodized Aluminum	2.0	14.83

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Slit Type

Part Number	Outside Diameter (D) mm <i>inches</i>	Bores mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Max Torque N.m	Rated Speed RPM	Hub Type	Material	Angular Offset Deg.	Torsional Stiffness N.m / Deg
# CPSL6390-3000-3000-3GK	63.0 <i>2.480</i>	30.000 / 30.000	90.0 <i>3.543</i>	35.0	2400	Pin Hub -8X3.3 KWY	Stainless Steel	2.0	31.41

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
