




MBA

Couplings - Uniflex



High speed to 30000 rpm. 2.3 to 9.27 Nm.

Spring : 1095 Steel Hubs : Cold Rolled Steel.

Operating Temperature : 121 Deg C (250 Deg F).

Maximum Speed : 30000 RPM.

For CUF15 series the spring diameter is the same as the hub diameter.

Couplings - Uniflex

Part Number	Hub Diameter (C) mm <i>inches</i>	Bore Size (B) mm <i>inches</i>	Overall Length mm <i>inches</i>	Max Torque N.m	Wind up at Max Torque Deg	Hub Length (D) / Set Screw mm <i>inches</i>	Material	Max. Angular Offset Deg	Max. Parallel Offset mm <i>inches</i>
# CUF15-0318	15.49 <i>0.610</i>	3.175 <i>0.125</i>	25.40 <i>1.000</i>	2.03	1.80	7.937 / 6-32	Carbon Steel	3	0.20 <i>0.008</i>
# CUF15-0476	15.49 <i>0.610</i>	4.763 <i>0.188</i>	25.40 <i>1.000</i>	2.03	1.80	7.937 / 6-32	Carbon Steel	3	0.20 <i>0.008</i>
# CUF15-0635	15.49 <i>0.610</i>	6.350 <i>0.250</i>	25.40 <i>1.000</i>	2.03	1.80	7.937 / 6-32	Carbon Steel	3	0.20 <i>0.008</i>
# CUF19-0318L	18.54 <i>0.730</i>	3.175 <i>0.125</i>	25.40 <i>1.000</i>	3.84	1.07	7.937 / 6-32	Carbon Steel	3	0.18 <i>0.007</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Uniflex

Part Number	Hub Diameter (C) mm <i>inches</i>	Bore Size (B) mm <i>inches</i>	Overall Length mm <i>inches</i>	Max Torque N.m	Wind up at Max Torque Deg	Hub Length (D) / Set Screw mm <i>inches</i>	Material	Max. Angular Offset Deg	Max. Parallel Offset mm <i>inches</i>
# CUF19-0318	18.54 <i>0.730</i>	3.175 <i>0.125</i>	38.51 <i>1.516</i>	3.84	1.80	7.937 / 6-32	Carbon Steel	4.5	0.28 <i>0.011</i>
# CUF19-0476L	18.54 <i>0.730</i>	4.763 <i>0.188</i>	25.40 <i>1.000</i>	3.84	1.07	9.525 / 6-32	Carbon Steel	3	0.18 <i>0.007</i>
# CUF19-0476	18.54 <i>0.730</i>	4.763 <i>0.188</i>	38.51 <i>1.516</i>	3.84	1.80	9.525 / 6-32	Carbon Steel	4.5	0.28 <i>0.011</i>
# CUF19-0635L	18.54 <i>0.730</i>	6.350 <i>0.250</i>	25.40 <i>1.000</i>	3.84	1.07	9.525 / 6-32	Carbon Steel	3	0.18 <i>0.007</i>
# CUF19-0635	18.54 <i>0.730</i>	6.350 <i>0.250</i>	38.51 <i>1.516</i>	3.84	1.80	9.525 / 6-32	Carbon Steel	4.5	0.28 <i>0.011</i>
# CUF19-0794L	18.54 <i>0.730</i>	7.938 <i>0.313</i>	25.40 <i>1.000</i>	3.84	1.07	9.525 / 6-32	Carbon Steel	3	0.18 <i>0.007</i>
# CUF19-0794	18.54 <i>0.730</i>	7.938 <i>0.313</i>	38.51 <i>1.516</i>	3.84	1.80	9.525 / 6-32	Carbon Steel	4.5	0.28 <i>0.011</i>
# CUF22-0635L	21.84 <i>0.860</i>	6.350 <i>0.250</i>	42.46 <i>1.672</i>	4.41	1.09	15.875 / 10-24	Carbon Steel	3	0.23 <i>0.009</i>
# CUF22-0635	21.84 <i>0.860</i>	6.350 <i>0.250</i>	52.40 <i>2.063</i>	4.41	1.78	15.875 / 10-24	Carbon Steel	4.5	0.36 <i>0.014</i>
# CUF22-0953L	21.84 <i>0.860</i>	9.525 <i>0.375</i>	42.46 <i>1.672</i>	4.41	1.09	15.875 / 10-24	Carbon Steel	3	0.23 <i>0.009</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Couplings - Uniflex

Part Number	Hub Diameter (C) mm <i>inches</i>	Bore Size (B) mm <i>inches</i>	Overall Length mm <i>inches</i>	Max Torque N.m	Wind up at Max Torque Deg	Hub Length (D) / Set Screw mm <i>inches</i>	Material	Max. Angular Offset Deg	Max. Parallel Offset mm <i>inches</i>
# CUF22-0953	21.84 <i>0.860</i>	9.525 <i>0.375</i>	52.40 <i>2.063</i>	4.41	1.78	15.875 / 10-24	Carbon Steel	4.5	0.36 <i>0.014</i>
# CUF26-0953L	26.42 <i>1.040</i>	9.525 <i>0.375</i>	46.83 <i>1.844</i>	9.27	1.05	19.05 / 1/4-20	Carbon Steel	3	0.36 <i>0.014</i>
# CUF26-0953	26.42 <i>1.040</i>	9.525 <i>0.375</i>	63.91 <i>2.516</i>	9.27	1.82	19.05 / 1/4-20	Carbon Steel	4.5	0.53 <i>0.021</i>
# CUF26-1270L	26.42 <i>1.040</i>	12.700 <i>0.500</i>	46.83 <i>1.844</i>	9.27	1.05	19.05 / 1/4-20	Carbon Steel	3	0.36 <i>0.014</i>
# CUF26-1270	26.42 <i>1.040</i>	12.700 <i>0.500</i>	63.91 <i>2.516</i>	9.27	1.82	19.05 / 1/4-20	Carbon Steel	4.5	0.53 <i>0.021</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
