



MBA

Epoxies

ZAP, Molytec, Pacer. 5 and 30 minute. Metal filled and standard.

Some items in this category are marked as only available for collection.

Epoxies

Part Number	Brand	Description	Size	Info	Info	Info	Notes	Info	Info	Info
PER-82093RS	Magic Bond	Epoxy Putty Stick	113 g (4 oz)	Works on wet & dry surfaces, sets up and cures even under water.	Use it to plug and fill cracks, gouges, leaks and holes.	It bonds to steel, copper, aluminum, wood, concrete, etc		Excellent for rebuilding and fabricating parts.	It can be drilled, tapped, filed, sanded and painted like metal.	Hardens fully within one hour
# PT55HINGE	Pacer Technology (ZAP)	Hinge Glue (Bonds Hinges)	28.4 g (1 oz)	-	-	-	-			
# PT40RESIN	Pacer Technology (ZAP)	Finishing Resin, Epoxy	240 g (12 oz)	-	-	-	-			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Epoxies

Part Number	Brand	Description	Size	Info	Info	Info	Notes	Info	Info	Info
PT39EPOXY30	Pacer Technology (ZAP)	Z-Poxy 30 Minute	227 g (8 oz)	-	-	-	-			
PT38EPOXY5	Pacer Technology (ZAP)	Z-Poxy 5 Minute	227 g (8 oz)	-	-	-	-			
# PT37EPOXY5	Pacer Technology (ZAP)	Z-Poxy 5 Minute	113 g (4 oz)	-	-	-	-			
PT36EXPOXY5	Pacer Technology (ZAP)	Z-Poxy 5 Minute	28.4 g (1 oz)	-	-	-	-			
Epoxy-Waterproof-28.3g	The Original Super Glue Corporation	Waterproof Epoxy Adhesive	28.3 g (1 oz)	Works underwater	Advanced industrial strength	3-4 Hour Setting Time	1000 PSI Strength			Flexible
Epoxy-Super-30	The Original Super Glue Corporation	Epoxy - Clear - Super Strength	28.3 g (1 oz) Syringe	Super Strength	Bonds Glass, Plastic, Metal	-	-			
Epoxy-Metal-28.3g	The Original Super Glue Corporation	Fast Setting Metal Epoxy	28.3 g (1 oz) Syringe	Industrial strength fast setting metal epoxy.	Bonds most metals including copper, steel, stainless, aluminium, brass & iron.	2-3 minutes positioning time, can be handled in 30 minutes.	Can be drilled, tapped or filed after full cure.			
EPOXY-GEL-28.3g	The Original Super Glue Corporation	Gap Filling Quick Set	28.3 g (1 oz)	Best product for gap filling	1500 psi Strength	Sets in 5 minutes	Cures cream colour			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Epoxies

Part Number	Brand	Description	Size	Info	Info	Info	Notes	Info	Info	Info
Epoxy-Copper-Bond-28.3g	The Original Super Glue Corporation	Copper-Bond	28.3 g (1 oz)	Assembles copper water pipe without solder	For hot and cold water systems		Sets in 20 minutes			
Epoxy-Cold-Weld-56g	Pro-Seal	Cold Weld Compound - Steel and Aluminium Epoxy Filler	56.8 g (2 oz)	Ideal for sleeve fitting. Temp to 150 Deg C with excellent thermal conductivity.	Can be filed, drilled, tapped, machined. Resistant to fuel, oil, antifreeze, water, battery acid.	-	-			
# Epoxy-5Min-Syr	The Original Super Glue Corporation	Epoxy - 4-6 minute Clear	28.3 g (1 oz) Syringe	5 minute set time	Bonds metal, glass, plastic	-	-			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

