




MBA

Gearboxes - Offset - 236 x 190 x 90



FF40 Series.

Case: AA15 Red Anodised Aluminum (6082-T6).

Gear: High Carbon Steel 817M40(EN24).

Backlash: 1°. Hours Life: 12000 hr. Max Input Speed: 1500 Rpm.

Lubrication: Greased for life - Shell Nerita Grease HV. Testing in your applications is necessary.

You will need to assess duty, cycles and confirm gearbox suitability with your own calculations. Torque figures are to be used for guidance only.

Gearboxes - Offset - 236 x 190 x 90

Part Number	Ratio	Max. Input Speed	Max. Output Speed	Efficiency at 1000 Rpm %	Nm Output at 1000 RPM Nm
# FF40-2	2 : 1	1500	750	93	90.00
# FF40-3	3 : 1	1500	500	93	90.00
# FF40-4	4 : 1	1500	395	93	82.00
# FF40-5	5 : 1	1500	300	93	76.00

Indicates item not stocked at time of printing - Please enquire for lead time
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Page 1 of 2

Gearboxes - Offset - 236 x 190 x 90

Part Number	Ratio	Max. Input Speed	Max. Output Speed	Efficiency at 1000 Rpm %	Nm Output at 1000 RPM Nm
# FF40-6	6 : 1	1500	250	93	66.00
# FF40-7	7 : 1	1500	214.29	93	64.00

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

