




MBA

Gearmotors - DC PM - Size 47



Permanent Magnet.

Max. Allowable Radial Load: 100N (10mm from mounting surface).

Max. Allowable Axial Load: 30N.

Axial Play: 0.05 - 0.6mm. Allowable Temperature Range: -20 °C to +60 °C.

Integral CD PM Motor - Brush type commutation - 12 segment commutator - RFI protection standard.

Gear train with steel and high quality plastic gears - Terminal dimensions 4.8 x 0.8 - Weight: 1200g.

Gearmotors - DC PM - Size 47

Part Number	Voltage DC	Rated Torque mNm	Rated Speed rpm	Rated Current mA	No Load Speed rpm	Terminal Resistance Ohms	Gear Ratio	Gear Stages
# 1.61.070.304	12V	650	103	1450	150	2.70	25.2 : 1	2
# 1.61.070.306	12V	1300	28	1050	39	4.20	108.3 : 1	2
# 1.61.070.305	12V	1300	53	1400	71	2.70	54.1 : 1	2
# 1.61.070.326	24V	1300	28	500	39	18.30	108.3 : 1	2
# 1.61.070.325	24V	1300	53	700	71	11.60	54.1 : 1	2

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
