




# MBA

## Gears - Spur - 32 Pitch - 14.5 Degree

Examples shown for basic dimensions. Individual gears may vary in characteristics.



PCD = No. of Teeth x 0.794mm (1/32 in.). 14.5 Degree Pressure Angle. 5052 aluminium, brass, carbon steel and nylon. Plastic and metallic.

Fairloc Hub Type require controlled shaft tolerances between 0.0025 and 0.0203 mm Clearance.

### Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X06-0159B0159-BR-N	6	4.78	1.588	6.375	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		0.188	0.063	0.251	0.063	0.063				
GS32X06-0476B0159-BR-N	6	4.78	1.588	6.375	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		0.188	0.063	0.251	0.187	0.187				
# GS32X07-0476B0238-BR-N	7	5.56	2.383	7.163	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		0.219	0.094	0.282	0.187	0.187				

# Indicates item not stocked at time of printing - Please enquire for lead time  
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd  
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X08-0159B0318-BR-N	8	6.35 <i>0.250</i>	3.175 <i>0.125</i>	7.950 <i>0.313</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X08-0476B0318-BR-N	8	6.35 <i>0.250</i>	3.175 <i>0.125</i>	7.950 <i>0.313</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X09-0159B0318-BR-N	9	7.14 <i>0.281</i>	3.175 <i>0.125</i>	8.737 <i>0.344</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X09-0476B0318-BR-N	9	7.14 <i>0.281</i>	3.175 <i>0.125</i>	8.737 <i>0.344</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X10-0476B0318-BR-N	10	7.94 <i>0.313</i>	3.175 <i>0.125</i>	9.550 <i>0.376</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X10-0159B0318-BR-N	10	7.94 <i>0.313</i>	3.175 <i>0.125</i>	9.550 <i>0.376</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X11-0159B0318-BR-N	11	8.74 <i>0.344</i>	3.175 <i>0.125</i>	10.338 <i>0.407</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
GS32X11-0476B0318-BR-N	11	8.74 <i>0.344</i>	3.175 <i>0.125</i>	10.338 <i>0.407</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X12-0476B0318-NY-HP	12	9.53	3.175	11.125	4.76	9.52	6.35	4.76 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>0.375</i>	<i>0.125</i>	<i>0.438</i>	<i>0.187</i>	<i>0.375</i>	<i>0.250</i>			
GS32X12-0476B0318-BR-N	12	9.53	3.175	11.125	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.375</i>	<i>0.125</i>	<i>0.438</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X12-0159B0318-BR-N	12	9.53	3.175	11.125	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.375</i>	<i>0.125</i>	<i>0.438</i>	<i>0.063</i>	<i>0.063</i>				
GS32X12-0476B0318-NY-N	12	9.53	3.175	11.125	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>0.375</i>	<i>0.125</i>	<i>0.438</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X12-0476B0476-C-HP	12	9.53	4.762	11.125	4.76	11.11	7.94	6.35 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>0.375</i>	<i>0.187</i>	<i>0.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.313</i>			
# GS32X13-0476B0318-BR-N	13	10.31	3.175	11.912	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.406</i>	<i>0.125</i>	<i>0.469</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X14-0476B0318-NY-HP	14	11.11	3.175	12.725	4.76	11.11	7.94	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>0.437</i>	<i>0.125</i>	<i>0.501</i>	<i>0.187</i>	<i>0.437</i>	<i>0.313</i>			
# GS32X14-0159B0318-BR-N	14	11.11	3.175	12.725	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.437</i>	<i>0.125</i>	<i>0.501</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
GS32X14-0476B0318-BR-N	14	11.11	3.175	12.725	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.437</i>	<i>0.125</i>	<i>0.501</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X14-0476B0318-NY-N	14	11.11	3.175	12.725	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>0.437</i>	<i>0.125</i>	<i>0.501</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X15-0159B0318-BR-N	15	11.91	3.175	13.513	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.469</i>	<i>0.125</i>	<i>0.532</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X15-0476B0318-BR-N	15	11.91	3.175	13.513	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.469</i>	<i>0.125</i>	<i>0.532</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X15-0476B0476-C-HP	15	11.91	4.762	13.513	4.76	12.70	9.53	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>0.469</i>	<i>0.187</i>	<i>0.532</i>	<i>0.187</i>	<i>0.500</i>	<i>0.375</i>			
# GS32X16-0476B0476-BR-N	16	12.70	4.762	14.300	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X16-0476B0476-NY-N	16	12.70	4.762	14.300	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X16-0159B0476-BR-N	16	12.70	4.762	14.300	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X16-0476B0476-NY-HP	16	12.70	4.762	14.300	4.76	11.11	9.53	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.375</i>			
# GS32X16-0476B0476-C-HP	16	12.70	4.762	14.300	4.76	12.70	10.32	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.406</i>			
GS32X16-0476B0476-C-N	16	12.70	4.762	14.300	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X18-0476B0476-C-HP	18	14.29	4.762	15.875	4.76	12.70	11.91	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>0.563</i>	<i>0.187</i>	<i>0.625</i>	<i>0.187</i>	<i>0.500</i>	<i>0.469</i>			
# GS32X18-0476B0476-NY-N	18	14.29	4.762	15.900	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>0.563</i>	<i>0.187</i>	<i>0.626</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X18-0476B0476-C-N	18	14.29	4.762	15.900	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>0.563</i>	<i>0.187</i>	<i>0.626</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X18-0476B0476-NY-HP	18	14.29	4.762	15.900	4.76	11.11	9.53	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>0.563</i>	<i>0.187</i>	<i>0.626</i>	<i>0.187</i>	<i>0.437</i>	<i>0.375</i>			
# GS32X18-0476B0476-BR-N	18	14.29	4.762	15.900	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.563</i>	<i>0.187</i>	<i>0.626</i>	<i>0.187</i>	<i>0.187</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X18-0159B0476-BR-N	18	14.29 <i>0.563</i>	4.762 <i>0.187</i>	15.900 <i>0.626</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X20-0476B0476-NY-N	20	15.88 <i>0.625</i>	4.762 <i>0.187</i>	17.475 <i>0.688</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
# GS32X20-0476B0476-NY-HP	20	15.88 <i>0.625</i>	4.762 <i>0.187</i>	17.475 <i>0.688</i>	4.76 <i>0.187</i>	11.11 <i>0.437</i>	12.70 <i>0.500</i>	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
# GS32X20-0476B0476-BR-N	20	15.88 <i>0.625</i>	4.762 <i>0.187</i>	17.475 <i>0.688</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X20-0159B0476-BR-N	20	15.88 <i>0.625</i>	4.762 <i>0.187</i>	17.475 <i>0.688</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X20-0476B0476-C-N	20	15.88 <i>0.625</i>	4.762 <i>0.187</i>	17.475 <i>0.688</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
# GS32X20-0476B0635-C-HP	20	15.88 <i>0.625</i>	6.350 <i>0.250</i>	17.475 <i>0.688</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	13.50 <i>0.531</i>	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
# GS32X22-0476B0635-C-HP	22	17.46 <i>0.687</i>	6.350 <i>0.250</i>	19.050 <i>0.750</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	15.08 <i>0.594</i>	7.94 / No Set Screw	14.5	Carbon Steel / Commercial

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X22-0476B0476-BR-N	22	17.48 <i>0.688</i>	4.762 <i>0.187</i>	19.075 <i>0.751</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X22-0476B0476-C-N	22	17.48 <i>0.688</i>	4.762 <i>0.187</i>	19.075 <i>0.751</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
# GS32X22-0476B0635-NY-HP	22	17.48 <i>0.688</i>	6.350 <i>0.250</i>	19.075 <i>0.751</i>	4.76 <i>0.187</i>	11.11 <i>0.437</i>	14.29 <i>0.563</i>	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
# GS32X24-0476B0476-NY-HP	24	19.05 <i>0.750</i>	4.762 <i>0.187</i>	20.650 <i>0.813</i>	4.76 <i>0.187</i>	11.11 <i>0.437</i>	15.88 <i>0.625</i>	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
GS32X24-0476B0476-NY-N	24	19.05 <i>0.750</i>	4.762 <i>0.187</i>	20.650 <i>0.813</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
# GS32X24-0476B0476-BR-N	24	19.05 <i>0.750</i>	4.762 <i>0.187</i>	20.650 <i>0.813</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X24-0159B0476-BR-N	24	19.05 <i>0.750</i>	4.762 <i>0.187</i>	20.650 <i>0.813</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X24-0476B0635-C-N	24	19.05 <i>0.750</i>	6.350 <i>0.250</i>	20.650 <i>0.813</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Carbon Steel / Commercial

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X24-0476B0794-C-N	24	19.05 <i>0.750</i>	7.938 <i>0.313</i>	20.650 <i>0.813</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
# GS32X24-0476B0794-C-HP	24	19.05 <i>0.750</i>	7.938 <i>0.313</i>	20.650 <i>0.813</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	16.67 <i>0.656</i>	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
# GS32X24-0159B0953-A52-N	24	19.05 <i>0.750</i>	9.525 <i>0.375</i>	20.650 <i>0.813</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
# GS32X24-0080B0953-A52-N	24	19.05 <i>0.750</i>	9.525 <i>0.375</i>	20.650 <i>0.813</i>	0.80 <i>0.031</i>	0.80 <i>0.031</i>	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
# GS32X25-0159B0953-A52-N	25	19.85 <i>0.781</i>	9.525 <i>0.375</i>	21.437 <i>0.844</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
# GS32X26-0476B0476-BR-N	26	20.64 <i>0.813</i>	4.762 <i>0.187</i>	22.250 <i>0.876</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X26-0476B0635-C-N	26	20.64 <i>0.813</i>	6.350 <i>0.250</i>	22.250 <i>0.876</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Carbon Steel / Commercial

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X26-0476B0794-C-HP	26	20.64	7.938	22.225	4.76	12.70	18.26	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>0.813</i>	<i>0.313</i>	<i>0.875</i>	<i>0.187</i>	<i>0.500</i>	<i>0.719</i>			
# GS32X26-0159B0953-A52-N	26	20.64	9.525	22.250	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>0.813</i>	<i>0.375</i>	<i>0.876</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X28-0476B0476-NY-N	28	22.23	4.762	23.825	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X28-0476B0476-BR-N	28	22.23	4.762	23.825	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X28-0159B0476-BR-N	28	22.23	4.762	23.825	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X28-0476B0635-NY-HP	28	22.23	6.350	23.825	4.76	11.11	15.88	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X28-0476B0794-C-HP	28	22.23	7.938	23.825	4.76	12.70	19.05	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>0.875</i>	<i>0.313</i>	<i>0.938</i>	<i>0.187</i>	<i>0.500</i>	<i>0.750</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X28-0159B0953-A52-N	28	22.23	9.525	23.825	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>0.875</i>	<i>0.375</i>	<i>0.938</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X28-0476B0953-C-N	28	22.23	9.525	23.825	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>0.875</i>	<i>0.375</i>	<i>0.938</i>	<i>0.187</i>	<i>0.187</i>				
GS32X30-0476B0476-BR-N	30	23.81	4.762	25.425	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>0.937</i>	<i>0.187</i>	<i>1.001</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X30-0476B0794-C-HP	30	23.81	7.938	25.400	4.76	12.70	19.05	7.94 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>0.937</i>	<i>0.313</i>	<i>1.000</i>	<i>0.187</i>	<i>0.500</i>	<i>0.750</i>			
GS32X30-0476B0794-C-N	30	23.81	7.938	25.400	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>0.937</i>	<i>0.313</i>	<i>1.000</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X30-0476B0953-C-N	30	23.81	9.525	25.400	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>0.937</i>	<i>0.375</i>	<i>1.000</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X30-0159B0953-A52-N	30	23.81	9.525	25.425	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>0.937</i>	<i>0.375</i>	<i>1.001</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X31-0080B0953-A52-N	31	24.61	9.525	26.213	0.80	0.80	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>0.969</i>	<i>0.375</i>	<i>1.032</i>	<i>0.031</i>	<i>0.031</i>				
# GS32X32-0159B0476-BR-N	32	25.40	4.762	27.000	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.000</i>	<i>0.187</i>	<i>1.063</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X32-0476B0635-NY-N	32	25.40	6.350	27.000	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.187</i>				
GS32X32-0476B0635-BR-N	32	25.40	6.350	27.000	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X32-0476B0794-C-HP-B	32	25.40	7.938	27.000	4.76	Unspecified	19.05	Unspecified / No Set Screw	14.5	Carbon Steel / Commercial
		<i>1.000</i>	<i>0.313</i>	<i>1.063</i>	<i>0.187</i>		<i>0.750</i>			
# GS32X32-0476B0794-C-HP	32	25.40	7.938	27.000	4.76	14.29	19.05	9.53 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>1.000</i>	<i>0.313</i>	<i>1.063</i>	<i>0.187</i>	<i>0.563</i>	<i>0.750</i>			
# GS32X32-0476B0953-C-N	32	25.40	9.525	27.000	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.000</i>	<i>0.375</i>	<i>1.063</i>	<i>0.187</i>	<i>0.187</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X32-0159B0953-A52-N	32	25.40	9.525	27.000	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.000</i>	<i>0.375</i>	<i>1.063</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X-32-0476B0794-C-HP	32	25.40	7.938	26.97	4.76		19.05	7.94	14.5	Carbon Steel / Commercial
		<i>1.000</i>	<i>0.313</i>	<i>1.062</i>	<i>0.187</i>		<i>0.750</i>	<i>0.313</i>		
# GS32X36-0476B0635-NY-HP	36	28.58	6.350	30.175	4.76	11.11	15.88	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X36-0476B0635-BR-N	36	28.58	6.350	30.175	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X36-0476B0635-NY-N	36	28.58	6.350	30.175	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X36-0476B0794-C-N	36	28.58	7.938	30.175	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.125</i>	<i>0.313</i>	<i>1.188</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X36-0080B0953-A52-N	36	28.58	9.525	30.175	0.80	0.80	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.031</i>	<i>0.031</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X36-0159B0953-A52-N	36	28.58	9.525	30.175	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X36-0476B0953-C-N	36	28.58	9.525	30.175	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X38-0635B0635-NY-HP	38	30.18	6.350	31.775	6.35	12.70	14.29	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>1.188</i>	<i>0.250</i>	<i>1.251</i>	<i>0.250</i>	<i>0.500</i>	<i>0.563</i>			
# GS32X38-0476B0635-NY-N	38	30.18	6.350	31.775	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.188</i>	<i>0.250</i>	<i>1.251</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X38-0159B0953-A52-N	38	30.18	9.525	31.775	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.188</i>	<i>0.375</i>	<i>1.251</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X39-0159B0953-A52-N	39	30.96	9.525	32.563	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.219</i>	<i>0.375</i>	<i>1.282</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X40-0159B0635-BR-N	40	31.75	6.350	33.350	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X40-0476B0635-BR-HP	40	31.75	6.350	33.350	4.76	11.11	12.70	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32X40-0476B0635-NY-HP	40	31.75	6.350	33.350	4.76	11.11	15.88	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X40-0476B0635-NY-N	40	31.75	6.350	33.350	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X40-0476B0635-BR-N	40	31.75	6.350	33.350	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X40-0476B0794-C-N	40	31.75	7.938	33.350	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.250</i>	<i>0.313</i>	<i>1.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X40-0476B0953-C-HP	40	31.75	9.525	33.350	4.76	14.29	22.23	9.53 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>1.250</i>	<i>0.375</i>	<i>1.313</i>	<i>0.187</i>	<i>0.563</i>	<i>0.875</i>			
# GS32X40-0159B0953-A52-N	40	31.75	9.525	33.350	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.250</i>	<i>0.375</i>	<i>1.313</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X44-0476B0794-C-N	44	34.92	7.938	36.52	4.76				14.5	Carbon Steel / Commercial
		<i>1.375</i>	<i>0.313</i>	<i>1.438</i>	<i>0.187</i>					
# GS32X44-0476B0635-NY-N	44	34.93	6.350	36.525	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X44-0476B0635-NY-HP	44	34.93	6.350	36.525	4.76	11.11	15.88	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X44-0476B0635-BR-HP	44	34.93	6.350	36.525	4.76	11.11	12.70	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32X44-0476B0635-BR-N	44	34.93	6.350	36.525	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X44-0476B0953-C-N	44	34.93	9.525	36.525	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.375</i>	<i>0.375</i>	<i>1.438</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X44-0159B0953-A52-N	44	34.93	9.525	36.525	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.375</i>	<i>0.375</i>	<i>1.438</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X48-0159B0635-BR-N	48	38.10	6.350	39.700	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X48-0476B0635-BR-N	48	38.10	6.350	39.700	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X48-0476B0635-NY-HP	48	38.10	6.350	39.700	4.76	11.11	15.88	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
GS32X48-0476B0635-NY-N	48	38.10	6.350	39.700	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X48-0476B0635-BR-HP	48	38.10	6.350	39.700	4.76	11.11	12.70	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32X48-0476B0794-C-N	48	38.10	7.938	39.700	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.500</i>	<i>0.313</i>	<i>1.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X48-0476B0953-C-HP	48	38.10	9.525	39.700	4.76	14.29	22.23	9.53 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.187</i>	<i>0.563</i>	<i>0.875</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X48-0080B0953-A52-N	48	38.10	9.525	39.700	0.80	0.80	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.031</i>	<i>0.031</i>				
# GS32X48-0159B0953-A52-N	48	38.10	9.525	39.700	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X50-0159B0794-BR-N	50	39.69	7.938	41.300	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.563</i>	<i>0.313</i>	<i>1.626</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X50-0159B0953-A52-N	50	39.69	9.525	41.300	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.563</i>	<i>0.375</i>	<i>1.626</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X52-0476B0635-BR-HP	52	41.28	6.350	42.875	4.76	11.11	12.70	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32X52-0476B0635-NY-HP	52	41.28	6.350	42.875	4.76	11.11	15.88	6.35 / Pin Hub - No Set Screw	14.5	Nylon / Commercial - Moulded
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X52-0476B0635-NY-N	52	41.28	6.350	42.875	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.187</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X52-0476B0953-C-N	52	41.28	9.525	42.875	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.625</i>	<i>0.375</i>	<i>1.688</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X54-0159B0953-A52-N	54	42.86	9.525	44.475	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.687</i>	<i>0.375</i>	<i>1.751</i>	<i>0.063</i>	<i>0.063</i>				
GS32X56-0476B0635-NY-N	56	44.45	6.350	46.050	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X56-0476B0794-C-N	56	44.45	7.938	46.050	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.750</i>	<i>0.313</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X56-0476B0794-BR-N	56	44.45	7.938	46.050	4.76	4.76	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.750</i>	<i>0.313</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X56-0476B0794-BR-HP	56	44.45	7.938	46.050	4.76	11.11	15.88	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>1.750</i>	<i>0.313</i>	<i>1.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X56-0476B0953-C-N	56	44.45	9.525	46.050	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X56-0476B0953-C-HP	56	44.45	9.525	46.050	4.76	14.29	25.40	9.53 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.187</i>	<i>0.563</i>	<i>1.000</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X60-0476B0794-BR-HP	60	47.63	7.938	49.225	4.76	11.11	15.88	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>1.875</i>	<i>0.313</i>	<i>1.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X60-0159B0794-BR-N	60	47.63	7.938	49.225	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>1.875</i>	<i>0.313</i>	<i>1.938</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X60-0159B0953-A52-N	60	47.63	9.525	49.225	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>1.875</i>	<i>0.375</i>	<i>1.938</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X60-0476B0953-C-N	60	47.63	9.525	49.225	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>1.875</i>	<i>0.375</i>	<i>1.938</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X62-0476B0635-NY-N	62	49.23	6.350	50.825	4.76	4.76	Hubless	0.00 / None	14.5	Nylon / Commercial - Moulded
		<i>1.938</i>	<i>0.250</i>	<i>2.001</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X62-0635B0953-NY-HP	62	49.23	9.525	50.825	6.35	15.88	15.88	9.53 / Pin No Set Screw - Hub has 2.59mm Diameter Cross Hole	14.5	Nylon / Commercial - Moulded
		<i>1.938</i>	<i>0.375</i>	<i>2.001</i>	<i>0.250</i>	<i>0.625</i>	<i>0.625</i>			
# GS32X64-0476B0794-BR-HP-B	64	50.80	7.938	52.400	4.76	11.11	15.88	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>2.000</i>	<i>0.313</i>	<i>2.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X64-0476B0794-BR-HP	64	50.80 <i>2.000</i>	7.938 <i>0.313</i>	52.400 <i>2.063</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	15.88 <i>0.625</i>	7.94 / No Set Screw	14.5	Brass / Commercial
# GS32X64-0159B0794-BR-N	64	50.80 <i>2.000</i>	7.938 <i>0.313</i>	52.400 <i>2.063</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X64-0476B0953-C-HP	64	50.80 <i>2.000</i>	9.525 <i>0.375</i>	52.400 <i>2.063</i>	4.76 <i>0.187</i>	14.29 <i>0.563</i>	25.40 <i>1.000</i>	9.53 / No Set Screw	14.5	Carbon Steel / Commercial
# GS32X64-0159B0953-A52-N	64	50.80 <i>2.000</i>	9.525 <i>0.375</i>	52.400 <i>2.063</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
# GS32X64-0476B0953-C-N	64	50.80 <i>2.000</i>	9.525 <i>0.375</i>	52.400 <i>2.063</i>	4.76 <i>0.187</i>	4.76 <i>0.187</i>	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
# GS32X70-0159B0794-BR-N	70	55.58 <i>2.188</i>	7.938 <i>0.313</i>	57.175 <i>2.251</i>	1.59 <i>0.063</i>	1.59 <i>0.063</i>	Hubless	0.00 / None	14.5	Brass / Commercial
# GS32X72-0476B0794-BR-HP	72	57.15 <i>2.250</i>	7.938 <i>0.313</i>	58.750 <i>2.313</i>	4.76 <i>0.187</i>	11.11 <i>0.437</i>	15.88 <i>0.625</i>	6.35 / No Set Screw	14.5	Brass / Commercial

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X72-0080B0953-A52-N	72	57.15	9.525	58.750	0.80	0.80	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.031</i>	<i>0.031</i>				
# GS32X72-0476B0953-C-N	72	57.15	9.525	58.750	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X72-0159B0953-A52-N	72	57.15	9.525	58.750	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X75-0159B0794-BR-N	75	59.54	7.938	61.138	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>2.344</i>	<i>0.313</i>	<i>2.407</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X80-0476B0794-BR-HP	80	63.50	7.938	65.100	4.76	12.70	15.88	7.94 / No Set Screw	14.5	Brass / Commercial
		<i>2.500</i>	<i>0.313</i>	<i>2.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.625</i>			
# GS32X80-0476B0794-BR-HP-B	80	63.50	7.938	65.100	4.762	11.11	17.46	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>2.500</i>	<i>0.313</i>	<i>2.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.687</i>			
# GS32X80-0159B0794-BR-N	80	63.50	7.938	65.100	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>2.500</i>	<i>0.313</i>	<i>2.563</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X80-0476B0953-C-N	80	63.50	9.525	65.100	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X80-0159B0953-A52-N	80	63.50	9.525	65.100	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X80-0476B0953-C-HP	80	63.50	9.525	65.100	4.76	14.29	28.58	9.53 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.187</i>	<i>0.563</i>	<i>1.125</i>			
# GS32X84-0159B0953-A52-N	84	66.68	9.525	68.275	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>2.625</i>	<i>0.375</i>	<i>2.688</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X88-0476B0953-C-N	88	69.85	9.525	71.450	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>2.750</i>	<i>0.375</i>	<i>2.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X90-0159B0794-BR-N	90	71.44	7.938	73.050	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>2.813</i>	<i>0.313</i>	<i>2.876</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X96-0159B0794-BR-N	96	76.20	7.938	77.800	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>3.000</i>	<i>0.313</i>	<i>3.063</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X96-0476B0794-BR-HP-B	96	76.20	7.938	77.800	4.76	12.70	17.46	7.94 / No Set Screw	14.5	Brass / Commercial
		<i>3.000</i>	<i>0.313</i>	<i>3.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.687</i>			
# GS32X96-0476B0794-BR-HP	96	76.20	7.938	77.800	4.76	11.11	15.88	6.35 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>3.000</i>	<i>0.313</i>	<i>3.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.625</i>			
# GS32X96-0159B0953-A52-N	96	76.20	9.525	77.800	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X96-0476B0953-C-HP	96	76.20	9.525	77.800	4.76	17.46	31.75	12.70 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.187</i>	<i>0.687</i>	<i>1.250</i>			
# GS32X96-0476B0953-C-N	96	76.20	9.525	77.800	4.76	4.76	Hubless	0.00 / None	14.5	Carbon Steel / Commercial
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.187</i>	<i>0.187</i>				
# GS32X96-0080B0953-A52-N	96	76.20	9.525	77.800	0.80	0.80	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.031</i>	<i>0.031</i>				
# GS32X100-0159B0794-BR-N	100	79.38	7.938	80.975	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>3.125</i>	<i>0.313</i>	<i>3.188</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X100-0159B0953-A52-N	100	79.38	9.525	80.975	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>3.125</i>	<i>0.375</i>	<i>3.188</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X108-0476B0794-BR-HP	108	85.73	7.938	87.325	4.76	11.11	19.05	6.35 / No Set Screw	14.5	Brass / Commercial
		<i>3.375</i>	<i>0.313</i>	<i>3.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.750</i>			
# GS32X112-0159B0794-BR-N	112	88.90	7.938	90.500	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>3.500</i>	<i>0.313</i>	<i>3.563</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X112-0476B0794-BR-HP	112	88.90	7.938	90.500	4.76	Unspecified	19.05	Unspecified / No Set Screw	14.5	Brass / Commercial
		<i>3.500</i>	<i>0.313</i>	<i>3.563</i>	<i>0.187</i>		<i>0.750</i>			
# GS32X120-0476B0794-BR-HP	120	95.25	7.938	96.850	4.76	11.11	19.05	6.35 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>3.750</i>	<i>0.313</i>	<i>3.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.750</i>			
# GS32X120-0159B0794-BR-N	120	95.25	7.938	96.850	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>3.750</i>	<i>0.313</i>	<i>3.813</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X128-0476B0794-BR-HP-B	128	101.60	7.938	103.200	4.76	12.70	19.05	7.94 / No Set Screw	14.5	Brass / Commercial
		<i>4.000</i>	<i>0.313</i>	<i>4.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.750</i>			

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X128-0476B0794-BR-HP	128	101.60	7.938	103.200	4.76	11.11	19.05	6.35 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>4.000</i>	<i>0.313</i>	<i>4.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.750</i>			
# GS32X128-0159B0953-BR-N	128	101.60	9.525	103.200	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>4.000</i>	<i>0.375</i>	<i>4.063</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X128-0080B0953-A52-N	128	101.60	9.525	103.200	0.80	0.80	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>4.000</i>	<i>0.375</i>	<i>4.063</i>	<i>0.031</i>	<i>0.031</i>				
# GS32X128-0476B0953-C-HP	128	101.60	9.525	103.200	4.76	17.46	34.93	12.70 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>4.000</i>	<i>0.375</i>	<i>4.063</i>	<i>0.187</i>	<i>0.687</i>	<i>1.375</i>			
# GS32X132-0476B0794-BR-HP	132	104.78	7.938	106.375	4.76	11.11	19.05	6.35 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>4.125</i>	<i>0.313</i>	<i>4.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.750</i>			
# GS32X144-0476B0794-BR-HP	144	114.30	7.938	115.900	4.76	11.11	19.05	6.35 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>4.500</i>	<i>0.313</i>	<i>4.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.750</i>			
# GS32X144-0159B0953-BR-N	144	114.30	9.525	115.900	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>4.500</i>	<i>0.375</i>	<i>4.563</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X156-0476B0794-BR-HP	156	123.83	7.938	125.425	4.76	11.11	22.23	6.35 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>4.875</i>	<i>0.313</i>	<i>4.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.875</i>			
# GS32X160-0476B0794-BR-HP	160	127.00	7.938	128.600	4.76	12.70	19.05	7.94 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>5.000</i>	<i>0.313</i>	<i>5.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.750</i>			
# GS32X160-0476B0953-C-HP	160	127.00	9.525	128.600	4.76	17.46	34.93	12.70 / No Set Screw	14.5	Carbon Steel / Commercial
		<i>5.000</i>	<i>0.375</i>	<i>5.063</i>	<i>0.187</i>	<i>0.687</i>	<i>1.375</i>			
# GS32X176-0159B0953-A52-N	176	139.70	9.525	141.300	1.59	1.59	Hubless	0.00 / None	14.5	5052 Aluminum Alloy / Stamped
		<i>5.500</i>	<i>0.375</i>	<i>5.563</i>	<i>0.063</i>	<i>0.063</i>				
# GS32X180-0476B0794-BR-HP	180	142.88	7.938	144.475	4.76	12.70	22.23	7.94 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>5.625</i>	<i>0.313</i>	<i>5.688</i>	<i>0.187</i>	<i>0.500</i>	<i>0.875</i>			
# GS32X192-0476B0794-BR-HP	192	152.40	7.938	154.000	4.76	12.70	22.23	7.94 / No Set Screw	14.5	Brass / Spoked / Commercial
		<i>6.000</i>	<i>0.313</i>	<i>6.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.875</i>			
# GS32X192-0159B0953-BR-N	192	152.40	9.525	154.000	1.59	1.59	Hubless	0.00 / None	14.5	Brass / Commercial
		<i>6.000</i>	<i>0.375</i>	<i>6.063</i>	<i>0.063</i>	<i>0.063</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Gears - Spur - 32 Pitch - 14.5 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32X192-0476B0953-C-HP	192	152.40 <i>6.000</i>	9.525 <i>0.375</i>	154.000 <i>6.063</i>	4.76 <i>0.187</i>	20.64 <i>0.813</i>	38.10 <i>1.500</i>	15.88 / No Set Screw	14.5	Carbon Steel / Commercial
# GS32X200-0476B0953-C-HP	200	158.75 <i>6.250</i>	9.525 <i>0.375</i>	160.350 <i>6.313</i>	4.76 <i>0.187</i>	20.64 <i>0.813</i>	38.10 <i>1.500</i>	15.88 / No Set Screw	14.5	Carbon Steel / Commercial
# GS32X204-0476B0794-BR-HP	204	161.93 <i>6.375</i>	7.938 <i>0.313</i>	163.525 <i>6.438</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	22.23 <i>0.875</i>	7.94 / No Set Screw	14.5	Brass / Commercial
# GS32X220-0476B0794-BR-HP	220	174.63 <i>6.875</i>	7.938 <i>0.313</i>	176.225 <i>6.938</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	22.23 <i>0.875</i>	7.94 / No Set Screw	14.5	Brass / Commercial

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

