




MBA

Gears - Spur - 32 Pitch - 20 Degree

Examples shown for basic dimensions. Individual gears may vary in characteristics.



PCD = No. of Teeth x 0.794mm (1/32 in.). 20 Degree Pressure Angle. 2024 aluminium, 303 stainless steel, acetal, bakelite, brass, carbon steel and nylon.

Plastic and metallic.

Fairloc Hub Type require controlled shaft tolerances between 0.0025 and 0.0203 mm Clearance.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-08-0476B0238-AC-HP	8	6.35	2.383	7.950	4.76	9.52	4.12	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.250</i>	<i>0.094</i>	<i>0.313</i>	<i>0.187</i>	<i>0.375</i>	<i>0.162</i>			
GS32-09-0635B0318-BR-N	9	7.14	3.175	8.737	6.35	6.35	Hubless	0.00 / None	20	Brass / Commercial
		<i>0.281</i>	<i>0.125</i>	<i>0.344</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-10-0476B0318-AC-HP	10	7.94	3.175	9.538	4.76	9.52	5.72	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.313</i>	<i>0.125</i>	<i>0.376</i>	<i>0.187</i>	<i>0.375</i>	<i>0.225</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-10-0635B0318-BR-N	10	7.94 <i>0.313</i>	3.175 <i>0.125</i>	9.525 <i>0.375</i>	6.35 <i>0.250</i>	6.35 <i>0.250</i>	Hubless	0.00 / None	20	Brass / Commercial
# GS32-11-0635B0318-BR-N	11	8.74 <i>0.344</i>	3.175 <i>0.125</i>	10.338 <i>0.407</i>	6.35 <i>0.250</i>	6.35 <i>0.250</i>	Hubless	0.00 / None	20	Brass / Commercial
GS32-12-0635B0318-BR-N	12	9.53 <i>0.375</i>	3.175 <i>0.125</i>	11.125 <i>0.438</i>	6.35 <i>0.250</i>	6.35 <i>0.250</i>	Hubless	0.00 / None	20	Brass / Commercial
# GS32-12-0476B0397-AC-HP	12	9.53 <i>0.375</i>	3.970 <i>0.156</i>	11.125 <i>0.438</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	7.15 <i>0.281</i>	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
# GS32-12-0476B0397-ACB-HS	12	9.53 <i>0.375</i>	3.970 <i>0.156</i>	11.125 <i>0.438</i>	4.76 <i>0.187</i>	12.70 <i>0.500</i>	7.15 <i>0.281</i>	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
# GS32-12-0476B0476-3-HS	12	9.53 <i>0.375</i>	4.762 <i>0.187</i>	11.125 <i>0.438</i>	4.76 <i>0.187</i>	10.31 <i>0.406</i>	9.53 <i>0.375</i>	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
# GS32-12-0476B0476-A2-HS	12	9.53 <i>0.375</i>	4.762 <i>0.187</i>	11.125 <i>0.438</i>	4.76 <i>0.187</i>	10.31 <i>0.406</i>	9.53 <i>0.375</i>	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
GS32-12-0476B0476-AC-HP	12	9.53	4.762	11.125	4.76	9.52	7.24	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.375</i>	<i>0.187</i>	<i>0.438</i>	<i>0.187</i>	<i>0.375</i>	<i>0.285</i>			
# GS32-14-0635B0317-3-FL	14	11.11	3.170	12.712	6.35	14.35	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.125</i>	<i>0.500</i>	<i>0.250</i>	<i>0.565</i>	<i>0.551</i>			
# GS32-14-0476B0397-AC-HP	14	11.11	3.970	12.725	4.76	12.70	7.94	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.437</i>	<i>0.156</i>	<i>0.501</i>	<i>0.187</i>	<i>0.500</i>	<i>0.313</i>			
# GS32-14-0476B0397-ACB-HS	14	11.11	3.970	12.725	4.76	12.70	7.94	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.437</i>	<i>0.156</i>	<i>0.501</i>	<i>0.187</i>	<i>0.500</i>	<i>0.313</i>			
# GS32-14-0476B0476-AC-HP	14	11.11	4.762	12.712	4.76	9.52	7.93	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.437</i>	<i>0.187</i>	<i>0.500</i>	<i>0.187</i>	<i>0.375</i>	<i>0.312</i>			
# GS32-14-0635B0478-BR-N	14	11.11	4.775	12.725	6.35	6.35	Hubless	0.00 / None	20	Brass / Commercial
		<i>0.437</i>	<i>0.188</i>	<i>0.501</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-14-0318B0635-A2-HS	14	11.11	6.350	12.712	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.437</i>	<i>0.250</i>	<i>0.500</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-14-0476B0635-3-HS	14	11.11	6.350	12.712	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.250</i>	<i>0.500</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-14-0476B0635-A2-HS	14	11.11	6.350	12.712	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.437</i>	<i>0.250</i>	<i>0.500</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-14-0318B0635-A2-CH	14	11.11	6.350	12.712	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.437</i>	<i>0.250</i>	<i>0.500</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-14-0318B0635-3-HS	14	11.11	6.350	12.712	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.250</i>	<i>0.500</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-14-0318B0635-3-CH	14	11.11	6.350	12.712	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.250</i>	<i>0.500</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-15-0635B0317-3-FL	15	11.91	3.170	13.508	6.35	14.35	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.469</i>	<i>0.125</i>	<i>0.532</i>	<i>0.250</i>	<i>0.565</i>	<i>0.551</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-15-0476B0397-ACB-HS	15	11.91	3.970	13.513	4.76	12.70	7.94	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.469</i>	<i>0.156</i>	<i>0.532</i>	<i>0.187</i>	<i>0.500</i>	<i>0.313</i>			
# GS32-15-0476B0397-AC-HP	15	11.91	3.970	13.513	4.76	12.70	7.94	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.469</i>	<i>0.156</i>	<i>0.532</i>	<i>0.187</i>	<i>0.500</i>	<i>0.313</i>			
# GS32-15-0476B0476-AC-HP	15	11.91	4.762	13.508	4.76	9.52	7.93	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.469</i>	<i>0.187</i>	<i>0.532</i>	<i>0.187</i>	<i>0.375</i>	<i>0.312</i>			
# GS32-15-0635B0478-BR-N	15	11.91	4.775	13.513	6.35	6.35	Hubless	0.00 / None	20	Brass / Commercial
		<i>0.469</i>	<i>0.188</i>	<i>0.532</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-16-0635B0317-3-FL	16	12.70	3.170	14.300	6.35	14.35	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.563</i>	<i>0.250</i>	<i>0.565</i>	<i>0.551</i>			
# GS32-16-0476B0397-AC-HP	16	12.70	3.970	14.300	4.76	12.70	8.73	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.500</i>	<i>0.156</i>	<i>0.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.344</i>			
# GS32-16-0476B0397-ACB-HS	16	12.70	3.970	14.300	4.76	12.70	8.73	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.500</i>	<i>0.156</i>	<i>0.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.344</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-16-0476B0476-A2-HS	16	12.70	4.762	14.300	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-16-0476B0476-3-HS	16	12.70	4.762	14.300	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-16-0635B0478-BR-N	16	12.70	4.775	14.300	6.35	6.35	Hubless	0.00 / None	20	Brass / Commercial
		<i>0.500</i>	<i>0.188</i>	<i>0.563</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-16-0476B0635-3-HS	16	12.70	6.350	14.300	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.250</i>	<i>0.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-16-0476B0635-A2-HS	16	12.70	6.350	14.300	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.250</i>	<i>0.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-16-0476B0635-AC-HP	16	12.70	6.350	14.300	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.500</i>	<i>0.250</i>	<i>0.563</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-16-0794B0794-BAK-N	16	12.70	7.938	14.300	7.94	7.94	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>0.500</i>	<i>0.313</i>	<i>0.563</i>	<i>0.313</i>	<i>0.313</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-18-0635B0317-3-FL	18	14.29	3.170	15.888	6.35	14.35	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.626</i>	<i>0.250</i>	<i>0.565</i>	<i>0.551</i>			
# GS32-18-0476B0397-AC-HP	18	14.29	3.970	15.900	4.76	12.70	8.73	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.563</i>	<i>0.156</i>	<i>0.626</i>	<i>0.187</i>	<i>0.500</i>	<i>0.344</i>			
# GS32-18-0476B0397-ACB-HS	18	14.29	3.970	15.900	4.76	12.70	8.73	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.563</i>	<i>0.156</i>	<i>0.626</i>	<i>0.187</i>	<i>0.500</i>	<i>0.344</i>			
# GS32-18-0476B0476-A2-HS	18	14.29	4.762	15.888	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.187</i>	<i>0.626</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-18-0476B0476-3-HS	18	14.29	4.762	15.888	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.187</i>	<i>0.626</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-18-0476B0635-3-HS	18	14.29	6.350	15.888	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.626</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-18-0318B0635-3-CH	18	14.29	6.350	15.888	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.626</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-18-0318B0635-A2-HS	18	14.29	6.350	15.888	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.626</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-18-0476B0635-A2-HS	18	14.29	6.350	15.888	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.626</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-18-0318B0635-3-HS	18	14.29	6.350	15.888	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.626</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
GS32-18-0476B0635-AC-HP	18	14.29	6.350	15.888	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.563</i>	<i>0.250</i>	<i>0.626</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-18-0318B0635-A2-CH	18	14.29	6.350	15.888	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.626</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-20-0475B0476-ACS-HS	20	15.88	4.757	17.475	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-20-0500B0476-3-FL	20	15.88	4.757	17.475	5.00	13.00	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.688</i>	<i>0.197</i>	<i>0.512</i>	<i>0.551</i>			
# GS32-20-0475B0476-ACS-FL	20	15.88	4.757	17.475	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.688</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-20-0476B0476-ACB-HS	20	15.88	4.762	17.475	4.76	12.70	11.91	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.625</i>	<i>0.187</i>	<i>0.688</i>	<i>0.187</i>	<i>0.500</i>	<i>0.469</i>			
# GS32-20-0476B0476-AC-HP	20	15.88	4.762	17.475	4.76	12.70	11.91	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.625</i>	<i>0.187</i>	<i>0.688</i>	<i>0.187</i>	<i>0.500</i>	<i>0.469</i>			
# GS32-20-0476B0476-A2-HS	20	15.88	4.762	17.475	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.688</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-20-0476B0476-3-HS	20	15.88	4.762	17.475	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.688</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-20-0475B0635-ACS-FL	20	15.88	6.345	17.475	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-20-0475B0635-ACS-HS	20	15.88	6.345	17.475	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-20-0476B0635-3-HS	20	15.88	6.350	17.475	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-20-0476B0635-AC-HP	20	15.88	6.350	17.475	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-20-0318B0635-3-HS	20	15.88	6.350	17.475	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-20-0476B0635-A2-HS	20	15.88	6.350	17.475	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-20-0318B0635-A2-HS	20	15.88	6.350	17.475	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-20-0318B0635-3-CH	20	15.88	6.350	17.475	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-20-0476B0635-C-N	20	15.88	6.350	17.475	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-20-0318B0635-A2-CH	20	15.88	6.350	17.475	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.688</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-20-0475B0953-AC-N	20	15.88	9.525	17.475	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.625</i>	<i>0.375</i>	<i>0.688</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-21-0475B0476-ACS-HS	21	16.67	4.757	18.270	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.656</i>	<i>0.187</i>	<i>0.719</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-21-0475B0476-ACS-FL	21	16.67	4.757	18.270	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.656</i>	<i>0.187</i>	<i>0.719</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-21-0475B0635-ACS-FL	21	16.67	6.345	18.270	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.656</i>	<i>0.250</i>	<i>0.719</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-21-0475B0635-ACS-HS	21	16.67	6.345	18.270	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.656</i>	<i>0.250</i>	<i>0.719</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-21-0475B0953-AC-N	21	16.67	9.525	18.270	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.656</i>	<i>0.375</i>	<i>0.719</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-22-0475B0476-ACS-HS	22	17.46	4.757	19.062	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.687</i>	<i>0.187</i>	<i>0.750</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-22-0475B0476-ACS-FL	22	17.46	4.757	19.062	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.687</i>	<i>0.187</i>	<i>0.750</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-22-0476B0476-A2-HS	22	17.46	4.762	19.062	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.687</i>	<i>0.187</i>	<i>0.750</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-22-0476B0476-3-HS	22	17.46	4.762	19.062	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.687</i>	<i>0.187</i>	<i>0.750</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-22-0475B0635-ACS-HS	22	17.46	6.345	19.062	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.687</i>	<i>0.250</i>	<i>0.750</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-22-0475B0635-ACS-FL	22	17.46	6.345	19.062	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.687</i>	<i>0.250</i>	<i>0.750</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-22-0476B0635-A2-HS	22	17.46	6.350	19.062	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.687</i>	<i>0.250</i>	<i>0.750</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-22-0476B0635-3-HS	22	17.46	6.350	19.062	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.687</i>	<i>0.250</i>	<i>0.750</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-22-0476B0635-AC-HP	22	17.46	6.350	19.062	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.687</i>	<i>0.250</i>	<i>0.750</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-22-0475B0953-AC-N	22	17.46	9.525	19.062	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.687</i>	<i>0.375</i>	<i>0.750</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-22-0476B0476-AC-HP	22	17.48	4.762	19.075	4.76	12.70	12.70	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.688</i>	<i>0.187</i>	<i>0.751</i>	<i>0.187</i>	<i>0.500</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-22-0476B0476-ACB-HS	22	17.48	4.762	19.075	4.76	12.70	12.70	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.688</i>	<i>0.187</i>	<i>0.751</i>	<i>0.187</i>	<i>0.500</i>	<i>0.500</i>			
# GS32-23-0475B0476-ACS-FL	23	18.26	4.757	19.858	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.719</i>	<i>0.187</i>	<i>0.782</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-23-0475B0476-ACS-HS	23	18.26	4.757	19.858	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.719</i>	<i>0.187</i>	<i>0.782</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-23-0475B0635-ACS-HS	23	18.26	6.345	19.858	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.719</i>	<i>0.250</i>	<i>0.782</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-23-0475B0635-ACS-FL	23	18.26	6.345	19.858	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.719</i>	<i>0.250</i>	<i>0.782</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-23-0475B0953-AC-N	23	18.26	9.525	19.858	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.719</i>	<i>0.375</i>	<i>0.782</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-24-0475B0476-ACS-HS	24	19.05	4.757	20.650	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-24-0500B0476-3-FL	24	19.05	4.757	20.650	5.00	13.00	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.813</i>	<i>0.197</i>	<i>0.512</i>	<i>0.551</i>			
# GS32-24-0475B0476-ACS-FL	24	19.05	4.757	20.650	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.813</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-24-0476B0476-3-HS	24	19.05	4.762	20.650	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-24-0476B0476-A2-HS	24	19.05	4.762	20.650	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-24-0476B0476-ACB-HS	24	19.05	4.762	20.650	4.76	12.70	12.70	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.750</i>	<i>0.187</i>	<i>0.813</i>	<i>0.187</i>	<i>0.500</i>	<i>0.500</i>			
# GS32-24-0476B0476-AC-HP	24	19.05	4.762	20.650	4.76	12.70	12.70	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.750</i>	<i>0.187</i>	<i>0.813</i>	<i>0.187</i>	<i>0.500</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-24-0635B0635-HS-HS	24	19.05	6.345	20.650	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-24-0475B0635-ACS-HS	24	19.05	6.345	20.650	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-24-0475B0635-ACS-FL	24	19.05	6.345	20.650	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-24-0953B0635-HS-HS	24	19.05	6.345	20.650	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-24-0318B0635-A2-HS	24	19.05	6.350	20.650	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-24-0794B0635-BAK-N	24	19.05	6.350	20.650	7.94	7.94	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.313</i>	<i>0.313</i>				
# GS32-24-0476B0635-A2-HS	24	19.05	6.350	20.650	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-24-0318B0635-3-HS	24	19.05	6.350	20.650	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-24-0476B0635-C-N	24	19.05	6.350	20.650	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-24-0318B0635-3-CH	24	19.05	6.350	20.650	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
GS32-24-0476B0635-AC-HP	24	19.05	6.350	20.650	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-24-0476B0635-3-HS	24	19.05	6.350	20.650	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-24-0318B0635-A2-CH	24	19.05	6.350	20.650	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-24-0953B0952-HS-HS	24	19.05	9.520	20.650	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.750</i>	<i>0.375</i>	<i>0.813</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-24-0635B0952-HS-HS	24	19.05	9.520	20.650	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.750</i>	<i>0.375</i>	<i>0.813</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-24-0475B0953-AC-N	24	19.05	9.525	20.650	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.750</i>	<i>0.375</i>	<i>0.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-24-0635B1270-HS-HS	24	19.05	12.695	20.650	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.750</i>	<i>0.500</i>	<i>0.813</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-24-0953B1270-HS-HS	24	19.05	12.695	20.650	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.750</i>	<i>0.500</i>	<i>0.813</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-25-0475B0476-ACS-FL	25	19.85	4.757	21.445	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.781</i>	<i>0.187</i>	<i>0.844</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-25-0475B0476-ACS-HS	25	19.85	4.757	21.445	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.781</i>	<i>0.187</i>	<i>0.844</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-25-0500B0476-3-FL	25	19.85	4.757	21.445	5.00	13.00	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.781</i>	<i>0.187</i>	<i>0.844</i>	<i>0.197</i>	<i>0.512</i>	<i>0.551</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-25-0475B0635-ACS-HS	25	19.85	6.345	21.445	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.781</i>	<i>0.250</i>	<i>0.844</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-25-0475B0635-ACS-FL	25	19.85	6.345	21.445	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.781</i>	<i>0.250</i>	<i>0.844</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-25-0475B0953-AC-N	25	19.85	9.525	21.445	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.781</i>	<i>0.375</i>	<i>0.844</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-26-0475B0476-ACS-HS	26	20.64	4.757	22.238	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.813</i>	<i>0.187</i>	<i>0.876</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-26-0475B0476-ACS-FL	26	20.64	4.757	22.238	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.813</i>	<i>0.187</i>	<i>0.876</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-26-0476B0476-ACB-HS	26	20.64	4.762	22.250	4.76	12.70	14.29	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.813</i>	<i>0.187</i>	<i>0.876</i>	<i>0.187</i>	<i>0.500</i>	<i>0.563</i>			
# GS32-26-0476B0476-AC-HP	26	20.64	4.762	22.250	4.76	12.70	14.29	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.813</i>	<i>0.187</i>	<i>0.876</i>	<i>0.187</i>	<i>0.500</i>	<i>0.563</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-26-0476B0476-A2-HS	26	20.64	4.762	22.238	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.813</i>	<i>0.187</i>	<i>0.876</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-26-0476B0476-3-HS	26	20.64	4.762	22.238	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.813</i>	<i>0.187</i>	<i>0.876</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-26-0475B0635-ACS-FL	26	20.64	6.345	22.238	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-26-0475B0635-ACS-HS	26	20.64	6.345	22.238	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-26-0476B0635-A2-HS	26	20.64	6.350	22.238	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-26-0476B0635-3-HS	26	20.64	6.350	22.238	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-26-0318B0635-3-CH	26	20.64	6.350	22.238	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-26-0318B0635-A2-HS	26	20.64	6.350	22.238	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-26-0318B0635-3-HS	26	20.64	6.350	22.238	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-26-0318B0635-A2-CH	26	20.64	6.350	22.238	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-26-0476B0635-AC-HP	26	20.64	6.350	22.238	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.813</i>	<i>0.250</i>	<i>0.876</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-26-0475B0953-AC-N	26	20.64	9.525	22.238	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.813</i>	<i>0.375</i>	<i>0.876</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-28-0500B0476-3-FL	28	22.23	4.757	23.825	5.00	13.00	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.197</i>	<i>0.512</i>	<i>0.551</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-28-0475B0476-ACS-HS	28	22.23	4.757	23.825	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-28-0475B0476-ACS-FL	28	22.23	4.757	23.825	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-28-0476B0476-ACB-HS	28	22.23	4.762	23.825	4.76	12.70	12.70	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.500</i>	<i>0.500</i>			
# GS32-28-0476B0476-3-HS	28	22.23	4.762	23.825	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-28-0476B0476-AC-HP	28	22.23	4.762	23.825	4.76	12.70	12.70	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.500</i>	<i>0.500</i>			
# GS32-28-0476B0476-A2-HS	28	22.23	4.762	23.825	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.187</i>	<i>0.938</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-28-0953B0635-HS-HS	28	22.23	6.345	23.825	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-28-0475B0635-ACS-HS	28	22.23	6.345	23.825	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-28-0635B0635-HS-HS	28	22.23	6.345	23.825	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-28-0475B0635-ACS-FL	28	22.23	6.345	23.825	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-28-0318B0635-A2-CH	28	22.23	6.350	23.825	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-28-0476B0635-3-HS	28	22.23	6.350	23.825	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-28-0318B0635-3-HS	28	22.23	6.350	23.825	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-28-0476B0635-A2-HS	28	22.23	6.350	23.825	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-28-0476B0635-AC-HP	28	22.23	6.350	23.825	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-28-0318B0635-3-CH	28	22.23	6.350	23.825	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-28-0318B0635-A2-HS	28	22.23	6.350	23.825	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.938</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-28-0953B0952-NS-N	28	22.23	9.520	23.825	9.53	9.53	Hubless (Core Diameter = 16.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>0.875</i>	<i>0.375</i>	<i>0.938</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-28-0635B0952-HS-HS	28	22.23	9.520	23.825	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.875</i>	<i>0.375</i>	<i>0.938</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-28-0953B0952-HS-HS	28	22.23	9.520	23.825	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.875</i>	<i>0.375</i>	<i>0.938</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-28-0635B0952-NS-N	28	22.23	9.520	23.825	6.35	6.35	Hubless (Core Diameter = 16.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>0.875</i>	<i>0.375</i>	<i>0.938</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-28-0475B0953-AC-N	28	22.23	9.525	23.825	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.875</i>	<i>0.375</i>	<i>0.938</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-28-0635B1270-HS-HS	28	22.23	12.695	23.825	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.875</i>	<i>0.500</i>	<i>0.938</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-28-0953B1270-HS-HS	28	22.23	12.695	23.825	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.875</i>	<i>0.500</i>	<i>0.938</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-30-0475B0476-ACS-FL	30	23.81	4.757	25.412	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.937</i>	<i>0.187</i>	<i>1.000</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-30-0475B0476-ACS-HS	30	23.81	4.757	25.412	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.937</i>	<i>0.187</i>	<i>1.000</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-30-0500B0476-3-FL	30	23.81	4.757	25.412	5.00	13.00	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.187</i>	<i>1.000</i>	<i>0.197</i>	<i>0.512</i>	<i>0.551</i>			
# GS32-30-0476B0476-AC-HP	30	23.81	4.762	25.425	4.76	12.70	14.29	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>0.937</i>	<i>0.187</i>	<i>1.001</i>	<i>0.187</i>	<i>0.500</i>	<i>0.563</i>			
# GS32-30-0476B0476-ACB-HS	30	23.81	4.762	25.425	4.76	12.70	14.29	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>0.937</i>	<i>0.187</i>	<i>1.001</i>	<i>0.187</i>	<i>0.500</i>	<i>0.563</i>			
# GS32-30-0476B0476-3-HS	30	23.81	4.762	25.412	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.187</i>	<i>1.000</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-30-0476B0476-A2-HS	30	23.81	4.762	25.412	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.187</i>	<i>1.000</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-30-0475B0635-ACS-HS	30	23.81	6.345	25.412	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-30-0635B0635-HS-HS	30	23.81	6.345	25.412	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-30-0475B0635-ACS-FL	30	23.81	6.345	25.412	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-30-0953B0635-HS-HS	30	23.81	6.345	25.412	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-30-0318B0635-3-CH	30	23.81	6.350	25.412	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-30-0318B0635-3-HS	30	23.81	6.350	25.412	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-30-0476B0635-AC-HP	30	23.81	6.350	25.412	4.76	9.52	9.53	4.76 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.187</i>	<i>0.375</i>	<i>0.375</i>			
# GS32-30-0318B0635-A2-HS	30	23.81	6.350	25.412	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-30-0318B0635-A2-CH	30	23.81	6.350	25.412	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-30-0476B0635-A2-HS	30	23.81	6.350	25.412	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-30-0476B0635-3-HS	30	23.81	6.350	25.412	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>1.000</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-30-0953B0952-HS-HS	30	23.81	9.520	25.412	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.937</i>	<i>0.375</i>	<i>1.000</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-30-0635B0952-HS-HS	30	23.81	9.520	25.412	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.937</i>	<i>0.375</i>	<i>1.000</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-30-0953B0952-NS-N	30	23.81	9.520	25.400	9.53	9.53	Hubless (Core Diameter = 16.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>0.937</i>	<i>0.375</i>	<i>1.000</i>	<i>0.375</i>	<i>0.375</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-30-0635B0952-NS-N	30	23.81	9.520	25.400	6.35	6.35	Hubless (Core Diameter = 16.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>0.937</i>	<i>0.375</i>	<i>1.000</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-30-0475B0953-AC-N	30	23.81	9.525	25.412	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.937</i>	<i>0.375</i>	<i>1.000</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-30-0953B1270-HS-HS	30	23.81	12.695	25.412	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.937</i>	<i>0.500</i>	<i>1.000</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-30-0635B1270-HS-HS	30	23.81	12.695	25.412	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>0.937</i>	<i>0.500</i>	<i>1.000</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-32-0475B0476-ACS-HS	32	25.40	4.757	27.000	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-32-0500B0476-3-FL	32	25.40	4.757	27.000	5.00	13.00	14.00	8.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.063</i>	<i>0.197</i>	<i>0.512</i>	<i>0.551</i>			
# GS32-32-0475B0476-ACS-FL	32	25.40	4.757	27.000	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.063</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-32-0476B0476-3-HS	32	25.40	4.762	27.000	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-32-0476B0476-A2-HS	32	25.40	4.762	27.000	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-32-0475B0635-ACS-HS	32	25.40	6.345	27.000	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-32-0475B0635-ACS-FL	32	25.40	6.345	27.000	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-32-0953B0635-HS-HS	32	25.40	6.345	27.000	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-32-0635B0635-HS-HS	32	25.40	6.345	27.000	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-32-0476B0635-3-HS	32	25.40	6.350	27.000	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-32-0476B0635-ACB-HS	32	25.40	6.350	27.000	4.76	12.70	15.88	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.625</i>			
# GS32-32-0476B0635-AC-HP	32	25.40	6.350	27.000	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
# GS32-32-0318B0635-A2-HS	32	25.40	6.350	27.000	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-32-0318B0635-3-CH	32	25.40	6.350	27.000	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-32-0476B0635-AC-HP-B	32	25.40	6.350	27.000	4.76	12.70	15.88	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.625</i>			
# GS32-32-0794B0635-BAK-N	32	25.40	6.350	27.000	7.94	7.94	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.313</i>	<i>0.313</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-32-0476B0635-A2-HS	32	25.40	6.350	27.000	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-32-0318B0635-A2-CH	32	25.40	6.350	27.000	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-32-0318B0635-3-HS	32	25.40	6.350	27.000	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.063</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-32-0953B0952-NS-N	32	25.40	9.520	27.000	9.53	9.53	Hubless (Core Diameter = 16.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.000</i>	<i>0.375</i>	<i>1.063</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-32-0953B0952-HS-HS	32	25.40	9.520	27.000	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.000</i>	<i>0.375</i>	<i>1.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-32-0635B0952-NS-N	32	25.40	9.520	27.000	6.35	6.35	Hubless (Core Diameter = 16.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.000</i>	<i>0.375</i>	<i>1.063</i>	<i>0.250</i>	<i>0.250</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-32-0635B0952-HS-HS	32	25.40	9.520	27.000	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.000</i>	<i>0.375</i>	<i>1.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-32-0475B0953-AC-N	32	25.40	9.525	27.000	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.000</i>	<i>0.375</i>	<i>1.063</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-32-0953B1270-HS-HS	32	25.40	12.695	27.000	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.000</i>	<i>0.500</i>	<i>1.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-32-0635B1270-HS-HS	32	25.40	12.695	27.000	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.000</i>	<i>0.500</i>	<i>1.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-34-0318B0635-3-CH	34	26.99	6.350	28.588	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.063</i>	<i>0.250</i>	<i>1.126</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-34-0476B0635-3-HS	34	26.99	6.350	28.588	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.063</i>	<i>0.250</i>	<i>1.126</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-34-0476B0635-AC-HP	34	26.99	6.350	28.600	4.76	12.70	15.48	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.063</i>	<i>0.250</i>	<i>1.126</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-34-0476B0635-A2-HS	34	26.99	6.350	28.588	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.063</i>	<i>0.250</i>	<i>1.126</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-34-0476B0635-ACB-HS	34	26.99	6.350	28.600	4.76	12.70	15.48	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.063</i>	<i>0.250</i>	<i>1.126</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-34-0318B0635-A2-CH	34	26.99	6.350	28.588	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.063</i>	<i>0.250</i>	<i>1.126</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-36-0475B0476-ACS-HS	36	28.58	4.757	30.175	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.125</i>	<i>0.187</i>	<i>1.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-36-0475B0476-ACS-FL	36	28.58	4.757	30.175	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.125</i>	<i>0.187</i>	<i>1.188</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-36-0476B0476-3-HS	36	28.58	4.762	30.175	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.187</i>	<i>1.188</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-36-0476B0476-A2-HS	36	28.58	4.762	30.175	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.125</i>	<i>0.187</i>	<i>1.188</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-36-0953B0635-HS-HS	36	28.58	6.345	30.175	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-36-0475B0635-ACS-FL	36	28.58	6.345	30.175	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-36-0475B0635-ACS-HS	36	28.58	6.345	30.175	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-36-0635B0635-HS-HS	36	28.58	6.345	30.175	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-36-0500B0635-3-FL	36	28.58	6.345	30.175	5.00	15.01	16.99	10.01 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.197</i>	<i>0.591</i>	<i>0.669</i>			
# GS32-36-0476B0635-3-HS	36	28.58	6.350	30.175	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-36-0318B0635-3-HS	36	28.58	6.350	30.175	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-36-0476B0635-AC-HP-B	36	28.58	6.350	30.175	4.76	12.70	15.48	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-36-0318B0635-A2-HS	36	28.58	6.350	30.175	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-36-0318B0635-3-CH	36	28.58	6.350	30.175	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-36-0318B0635-A2-CH	36	28.58	6.350	30.175	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-36-0476B0635-A2-HS	36	28.58	6.350	30.175	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-36-0476B0635-AC-HP	36	28.58	6.350	30.175	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
GS32-36-0476B0635-ACB-HS	36	28.58	6.350	30.175	4.76	12.70	15.48	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.125</i>	<i>0.250</i>	<i>1.188</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-36-0476B0794-C-N	36	28.58	7.938	30.175	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>1.125</i>	<i>0.313</i>	<i>1.188</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-36-0635B0952-HS-HS	36	28.58	9.520	30.175	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-36-0635B0952-NS-N	36	28.58	9.520	30.175	6.35	6.35	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-36-0953B0952-HS-HS	36	28.58	9.520	30.175	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-36-0953B0952-NS-N	36	28.58	9.520	30.175	9.53	9.53	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.375</i>	<i>0.375</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-36-0476B0953-C-N	36	28.58	9.525	30.175	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-36-0475B0953-AC-N	36	28.58	9.525	30.175	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.125</i>	<i>0.375</i>	<i>1.188</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-36-0953B1270-HS-HS	36	28.58	12.695	30.175	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.125</i>	<i>0.500</i>	<i>1.188</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-36-0635B1270-HS-HS	36	28.58	12.695	30.175	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.125</i>	<i>0.500</i>	<i>1.188</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-38-0476B0635-AC-HP	38	30.18	6.350	31.775	4.76	12.70	15.48	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.188</i>	<i>0.250</i>	<i>1.251</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-38-0476B0635-ACB-HS	38	30.18	6.350	31.775	4.76	12.70	15.48	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.188</i>	<i>0.250</i>	<i>1.251</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-40-0475B0476-ACS-FL	40	31.75	4.757	33.350	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.313</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-40-0475B0476-ACS-HS	40	31.75	4.757	33.350	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-40-0476B0476-A2-HS	40	31.75	4.762	33.350	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.313</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-40-0476B0476-3-HS	40	31.75	4.762	33.350	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.313</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-40-0475B0635-ACS-HS	40	31.75	6.345	33.350	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-40-0953B0635-HS-HS	40	31.75	6.345	33.350	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-40-0635B0635-HS-HS	40	31.75	6.345	33.350	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-40-0475B0635-ACS-FL	40	31.75	6.345	33.350	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-40-0500B0635-3-FL	40	31.75	6.345	33.350	5.00	15.01	16.99	10.01 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.197</i>	<i>0.591</i>	<i>0.669</i>			
# GS32-40-0318B0635-3-CH	40	31.75	6.350	33.350	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-40-0476B0635-AC-HP	40	31.75	6.350	33.350	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
# GS32-40-0318B0635-A2-CH	40	31.75	6.350	33.350	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-40-0476B0635-ACB-HS	40	31.75	6.350	33.350	4.76	12.70	15.48	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-40-0476B0635-3-HS	40	31.75	6.350	33.350	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-40-0318B0635-A2-HS	40	31.75	6.350	33.350	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-40-0318B0635-3-HS	40	31.75	6.350	33.350	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-40-0476B0635-A2-HS	40	31.75	6.350	33.350	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-40-0476B0635-AC-HP-B	40	31.75	6.350	33.350	4.76	12.70	15.48	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-40-0476B0635-BAK-N	40	31.75	6.350	33.350	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>1.250</i>	<i>0.250</i>	<i>1.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-40-0476B0794-C-N	40	31.75	7.938	33.350	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>1.250</i>	<i>0.313</i>	<i>1.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-40-0953B0952-HS-HS	40	31.75	9.520	33.350	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.250</i>	<i>0.375</i>	<i>1.313</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-40-0953B0952-NS-N	40	31.75	9.520	33.350	9.53	9.53	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.250</i>	<i>0.375</i>	<i>1.313</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-40-0635B0952-NS-N	40	31.75	9.520	33.350	6.35	6.35	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.250</i>	<i>0.375</i>	<i>1.313</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-40-0635B0952-HS-HS	40	31.75	9.520	33.350	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.250</i>	<i>0.375</i>	<i>1.313</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-40-0475B0953-AC-N	40	31.75	9.525	33.350	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.250</i>	<i>0.375</i>	<i>1.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-40-0953B1270-HS-HS	40	31.75	12.695	33.350	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.250</i>	<i>0.500</i>	<i>1.313</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-40-0635B1270-HS-HS	40	31.75	12.695	33.350	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.250</i>	<i>0.500</i>	<i>1.313</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-42-0475B0476-ACS-HS	42	33.34	4.757	34.938	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.313</i>	<i>0.187</i>	<i>1.376</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-42-0475B0476-ACS-FL	42	33.34	4.757	34.938	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.313</i>	<i>0.187</i>	<i>1.376</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-42-0475B0635-ACS-FL	42	33.34	6.345	34.938	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-42-0475B0635-ACS-HS	42	33.34	6.345	34.938	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-42-0318B0635-3-HS	42	33.34	6.350	34.938	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-42-0318B0635-3-CH	42	33.34	6.350	34.938	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-42-0476B0635-AC-HP	42	33.34	6.350	34.950	4.76	12.70	15.48	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-42-0318B0635-A2-HS	42	33.34	6.350	34.938	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-42-0476B0635-ACB-HS	42	33.34	6.350	34.950	4.76	12.70	15.48	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-42-0318B0635-A2-CH	42	33.34	6.350	34.938	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.376</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-42-0475B0953-AC-N	42	33.34	9.525	34.938	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.313</i>	<i>0.375</i>	<i>1.376</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-44-0475B0476-ACS-HS	44	34.93	4.757	36.525	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.187</i>	<i>1.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-44-0475B0476-ACS-FL	44	34.93	4.757	36.525	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.187</i>	<i>1.438</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-44-0475B0635-ACS-FL	44	34.93	6.345	36.525	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-44-0475B0635-ACS-HS	44	34.93	6.345	36.525	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-44-0476B0635-AC-HP	44	34.93	6.350	36.525	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
# GS32-44-0476B0635-ACB-HS	44	34.93	6.350	36.525	4.76	12.70	15.48	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-44-0476B0635-AC-HP-B	44	34.93	6.350	36.525	4.76	12.70	15.48	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.375</i>	<i>0.250</i>	<i>1.438</i>	<i>0.187</i>	<i>0.500</i>	<i>0.609</i>			
# GS32-44-0475B0953-AC-N	44	34.93	9.525	36.525	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.375</i>	<i>0.375</i>	<i>1.438</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-45-0500B0635-3-FL	45	35.72	6.345	37.320	5.00	15.01	16.99	10.01 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.406</i>	<i>0.250</i>	<i>1.469</i>	<i>0.197</i>	<i>0.591</i>	<i>0.669</i>			
# GS32-45-0318B0635-A2-CH	45	35.72	6.350	37.320	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.406</i>	<i>0.250</i>	<i>1.469</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-45-0318B0635-3-CH	45	35.72	6.350	37.320	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.406</i>	<i>0.250</i>	<i>1.469</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-46-0475B0476-ACS-FL	46	36.51	4.757	38.112	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.437</i>	<i>0.187</i>	<i>1.500</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-46-0475B0476-ACS-HS	46	36.51	4.757	38.112	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.437</i>	<i>0.187</i>	<i>1.500</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-46-0475B0635-ACS-FL	46	36.51	6.345	38.112	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.437</i>	<i>0.250</i>	<i>1.500</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-46-0475B0635-ACS-HS	46	36.51	6.345	38.112	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.437</i>	<i>0.250</i>	<i>1.500</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-46-0475B0953-AC-N	46	36.51	9.525	38.112	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.437</i>	<i>0.375</i>	<i>1.500</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-48-0475B0476-ACS-HS	48	38.10	4.757	39.700	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-48-0475B0476-ACS-FL	48	38.10	4.757	39.700	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.563</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-48-0476B0476-A2-HS	48	38.10	4.762	39.700	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-48-0476B0476-3-HS	48	38.10	4.762	39.700	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-48-0953B0635-HS-HS	48	38.10	6.345	39.700	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-48-0635B0635-HS-HS	48	38.10	6.345	39.700	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-48-0500B0635-3-FL	48	38.10	6.345	39.700	5.00	15.01	16.99	10.01 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.197</i>	<i>0.591</i>	<i>0.669</i>			
# GS32-48-0475B0635-ACS-FL	48	38.10	6.345	39.700	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-48-0475B0635-ACS-HS	48	38.10	6.345	39.700	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-48-0318B0635-A2-CH	48	38.10	6.350	39.700	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-48-0318B0635-3-HS	48	38.10	6.350	39.700	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-48-0318B0635-3-CH	48	38.10	6.350	39.700	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-48-0476B0635-3-HS	48	38.10	6.350	39.700	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-48-0476B0635-AC-HP-B	48	38.10	6.350	39.700	4.76	12.70	15.88	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.625</i>			
# GS32-48-0476B0635-ACB-HS	48	38.10	6.350	39.700	4.76	12.70	15.88	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.625</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-48-0476B0635-A2-HS	48	38.10	6.350	39.700	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
GS32-48-0476B0635-AC-HP	48	38.10	6.350	39.700	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
# GS32-48-0318B0635-A2-HS	48	38.10	6.350	39.700	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.563</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-48-0635B0952-NS-N	48	38.10	9.520	39.700	6.35	6.35	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-48-0953B0952-HS-HS	48	38.10	9.520	39.700	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-48-0953B0952-NS-N	48	38.10	9.520	39.700	9.53	9.53	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.375</i>	<i>0.375</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-48-0635B0952-HS-HS	48	38.10	9.520	39.700	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-48-0475B0953-AC-N	48	38.10	9.525	39.700	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.500</i>	<i>0.375</i>	<i>1.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-48-0953B1270-NS-N	48	38.10	12.695	39.700	9.53	9.53	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.500</i>	<i>0.500</i>	<i>1.563</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-48-0635B1270-NS-N	48	38.10	12.695	39.700	6.35	6.35	Hubless (Core Diameter = 19.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.500</i>	<i>0.500</i>	<i>1.563</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-48-0635B1270-HS-HS	48	38.10	12.695	39.700	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.500</i>	<i>0.500</i>	<i>1.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-48-0953B1270-HS-HS	48	38.10	12.695	39.700	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.500</i>	<i>0.500</i>	<i>1.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-50-0475B0476-ACS-FL	50	39.69	4.757	41.288	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.563</i>	<i>0.187</i>	<i>1.626</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-50-0475B0476-ACS-HS	50	39.69	4.757	41.288	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.563</i>	<i>0.187</i>	<i>1.626</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-50-0475B0635-ACS-FL	50	39.69	6.345	41.288	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.626</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-50-0500B0635-3-FL	50	39.69	6.345	41.288	5.00	15.01	16.99	10.01 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.626</i>	<i>0.197</i>	<i>0.591</i>	<i>0.669</i>			
# GS32-50-0475B0635-ACS-HS	50	39.69	6.345	41.288	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.626</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-50-0318B0635-A2-CH	50	39.69	6.350	41.288	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.626</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-50-0318B0635-3-CH	50	39.69	6.350	41.288	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.626</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-50-0318B0635-A2-HS	50	39.69	6.350	41.288	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.626</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-50-0318B0635-3-HS	50	39.69	6.350	41.288	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.626</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-50-0475B0953-AC-N	50	39.69	9.525	41.288	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.563</i>	<i>0.375</i>	<i>1.626</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-52-0475B0476-ACS-FL	52	41.28	4.757	42.875	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.625</i>	<i>0.187</i>	<i>1.688</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-52-0475B0476-ACS-HS	52	41.28	4.757	42.875	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.625</i>	<i>0.187</i>	<i>1.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-52-0475B0635-ACS-FL	52	41.28	6.345	42.875	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-52-0475B0635-ACS-HS	52	41.28	6.345	42.875	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-52-0476B0635-3-HS	52	41.28	6.350	42.875	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-52-0476B0635-AC-HP	52	41.28	6.350	42.875	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
# GS32-52-0476B0635-A2-HS	52	41.28	6.350	42.875	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.625</i>	<i>0.250</i>	<i>1.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-52-0476B0794-ACB-HS	52	41.28	7.938	42.875	4.76	12.70	17.07	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.625</i>	<i>0.313</i>	<i>1.688</i>	<i>0.187</i>	<i>0.500</i>	<i>0.672</i>			
# GS32-52-0476B0794-AC-HP	52	41.28	7.938	42.875	4.76	12.70	17.07	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.625</i>	<i>0.313</i>	<i>1.688</i>	<i>0.187</i>	<i>0.500</i>	<i>0.672</i>			
# GS32-52-0475B0953-AC-N	52	41.28	9.525	42.875	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.625</i>	<i>0.375</i>	<i>1.688</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-52-0476B0953-C-N	52	41.28	9.525	42.875	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>1.625</i>	<i>0.375</i>	<i>1.688</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-54-0500B0635-3-FL	54	42.86	6.345	44.462	5.00	15.01	16.99	10.01 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.687</i>	<i>0.250</i>	<i>1.750</i>	<i>0.197</i>	<i>0.591</i>	<i>0.669</i>			
# GS32-54-0318B0635-A2-HS	54	42.86	6.350	44.462	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.687</i>	<i>0.250</i>	<i>1.750</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-54-0318B0635-3-HS	54	42.86	6.350	44.462	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.687</i>	<i>0.250</i>	<i>1.750</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-56-0475B0476-ACS-HS	56	44.45	4.757	46.050	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-56-0475B0476-ACS-FL	56	44.45	4.757	46.050	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.813</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-56-0476B0476-3-HS	56	44.45	4.762	46.050	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-56-0476B0476-A2-HS	56	44.45	4.762	46.050	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-56-0635B0635-HS-HS	56	44.45	6.345	46.050	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-56-0953B0635-HS-HS	56	44.45	6.345	46.050	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-56-0475B0635-ACS-FL	56	44.45	6.345	46.050	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-56-0500B0635-3-FL	56	44.45	6.345	46.050	5.00	15.01	16.99	10.01 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.197</i>	<i>0.591</i>	<i>0.669</i>			
# GS32-56-0475B0635-ACS-HS	56	44.45	6.345	46.050	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-56-0476B0635-AC-HP	56	44.45	6.350	46.050	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-56-0476B0635-A2-HS	56	44.45	6.350	46.050	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-56-0318B0635-3-CH	56	44.45	6.350	46.050	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-56-0318B0635-A2-CH	56	44.45	6.350	46.050	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-56-0476B0635-BAK-N	56	44.45	6.350	46.050	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-56-0318B0635-3-HS	56	44.45	6.350	46.050	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-56-0476B0635-3-HS	56	44.45	6.350	46.050	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-56-0318B0635-A2-HS	56	44.45	6.350	46.050	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-56-0476B0794-AC-HP	56	44.45	7.938	46.050	4.76	12.70	17.07	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>1.750</i>	<i>0.313</i>	<i>1.813</i>	<i>0.187</i>	<i>0.500</i>	<i>0.672</i>			
# GS32-56-0476B0794-C-N	56	44.45	7.938	46.050	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>1.750</i>	<i>0.313</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-56-0476B0794-ACB-HS	56	44.45	7.938	46.050	4.76	12.70	17.07	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>1.750</i>	<i>0.313</i>	<i>1.813</i>	<i>0.187</i>	<i>0.500</i>	<i>0.672</i>			
# GS32-56-0635B0952-NS-N	56	44.45	9.520	46.050	6.35	6.35	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-56-0953B0952-HS-HS	56	44.45	9.520	46.050	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-56-0953B0952-NS-N	56	44.45	9.520	46.050	9.53	9.53	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.375</i>	<i>0.375</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-56-0635B0952-HS-HS	56	44.45	9.520	46.050	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-56-0476B0953-C-N	56	44.45	9.525	46.050	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-56-0475B0953-AC-N	56	44.45	9.525	46.050	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.750</i>	<i>0.375</i>	<i>1.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-56-0953B1270-NS-N	56	44.45	12.695	46.050	9.53	9.53	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.750</i>	<i>0.500</i>	<i>1.813</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-56-0953B1270-HS-HS	56	44.45	12.695	46.050	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.750</i>	<i>0.500</i>	<i>1.813</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-56-0635B1270-NS-N	56	44.45	12.695	46.050	6.35	6.35	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.750</i>	<i>0.500</i>	<i>1.813</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-56-0635B1270-HS-HS	56	44.45	12.695	46.050	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.750</i>	<i>0.500</i>	<i>1.813</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-60-0475B0476-ACS-HS	60	47.63	4.757	49.225	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-60-0475B0476-ACS-FL	60	47.63	4.757	49.225	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.938</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-60-0476B0476-3-HS	60	47.63	4.762	49.225	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.938</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-60-0476B0476-A2-HS	60	47.63	4.762	49.225	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.938</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-60-0475B0635-ACS-FL	60	47.63	6.345	49.225	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-60-0475B0635-ACS-HS	60	47.63	6.345	49.225	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-60-0500B0635-3-FL	60	47.63	6.345	49.225	5.00	19.00	16.99	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.197</i>	<i>0.748</i>	<i>0.669</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-60-0953B0635-HS-HS	60	47.63	6.345	49.225	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-60-0635B0635-HS-HS	60	47.63	6.345	49.225	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-60-0318B0635-A2-HS	60	47.63	6.350	49.225	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-60-0318B0635-3-HS	60	47.63	6.350	49.225	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-60-0318B0635-3-CH	60	47.63	6.350	49.225	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-60-0476B0635-A2-HS	60	47.63	6.350	49.225	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-60-0476B0635-3-HS	60	47.63	6.350	49.225	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
GS32-60-0476B0635-AC-HP	60	47.63	6.350	49.225	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
# GS32-60-0318B0635-A2-CH	60	47.63	6.350	49.225	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.938</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-60-0953B0952-HS-HS	60	47.63	9.520	49.225	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.875</i>	<i>0.375</i>	<i>1.938</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-60-0635B0952-HS-HS	60	47.63	9.520	49.225	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.875</i>	<i>0.375</i>	<i>1.938</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-60-0953B0952-NS-N	60	47.63	9.520	49.225	9.53	9.53	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.875</i>	<i>0.375</i>	<i>1.938</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-60-0635B0952-NS-N	60	47.63	9.520	49.225	6.35	6.35	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.875</i>	<i>0.375</i>	<i>1.938</i>	<i>0.250</i>	<i>0.250</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-60-0475B0953-AC-N	60	47.63	9.525	49.225	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.875</i>	<i>0.375</i>	<i>1.938</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-60-0953B1270-HS-HS	60	47.63	12.695	49.225	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.875</i>	<i>0.500</i>	<i>1.938</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-60-0635B1270-NS-N	60	47.63	12.695	49.225	6.35	6.35	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.875</i>	<i>0.500</i>	<i>1.938</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-60-0953B1270-NS-N	60	47.63	12.695	49.225	9.53	9.53	Hubless (Core Diameter = 24.99)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>1.875</i>	<i>0.500</i>	<i>1.938</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-60-0635B1270-HS-HS	60	47.63	12.695	49.225	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>1.875</i>	<i>0.500</i>	<i>1.938</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-63-0475B0476-ACS-HS	63	50.01	4.757	51.608	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.969</i>	<i>0.187</i>	<i>2.032</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-63-0475B0476-ACS-FL	63	50.01	4.757	51.608	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.969</i>	<i>0.187</i>	<i>2.032</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-63-0475B0635-ACS-HS	63	50.01	6.345	51.608	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.969</i>	<i>0.250</i>	<i>2.032</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-63-0475B0635-ACS-FL	63	50.01	6.345	51.608	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.969</i>	<i>0.250</i>	<i>2.032</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-63-0475B0953-AC-N	63	50.01	9.525	51.608	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.969</i>	<i>0.375</i>	<i>2.032</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-64-0475B0476-ACS-FL	64	50.80	4.757	52.400	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.063</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-64-0475B0476-ACS-HS	64	50.80	4.757	52.400	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-64-0476B0476-A2-HS	64	50.80	4.762	52.400	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-64-0476B0476-3-HS	64	50.80	4.762	52.400	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-64-0475B0635-ACS-FL	64	50.80	6.345	52.400	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-64-0635B0635-HS-HS	64	50.80	6.345	52.400	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-64-0953B0635-HS-HS	64	50.80	6.345	52.400	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-64-0475B0635-ACS-HS	64	50.80	6.345	52.400	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-64-0318B0635-A2-CH	64	50.80	6.350	52.400	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-64-0318B0635-A2-HS	64	50.80	6.350	52.400	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-64-0318B0635-3-HS	64	50.80	6.350	52.400	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-64-0476B0635-BAK-N	64	50.80	6.350	52.400	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-64-0318B0635-3-CH	64	50.80	6.350	52.400	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-64-0476B0635-A2-HS	64	50.80	6.350	52.400	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-64-0476B0635-3-HS	64	50.80	6.350	52.400	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-64-0476B0635-AC-HP	64	50.80	6.350	52.400	4.76	11.11	11.10	6.35 / Pin Hub - No Set Screw	20	Acetal - Black / AGMA Q9 - Moulded
		<i>2.000</i>	<i>0.250</i>	<i>2.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.437</i>			
# GS32-64-0476B0794-ACB-HS	64	50.80	7.938	52.400	4.76	12.70	17.07	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>2.000</i>	<i>0.313</i>	<i>2.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.672</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-64-0476B0794-AC-HP	64	50.80	7.938	52.400	4.76	12.70	17.07	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>2.000</i>	<i>0.313</i>	<i>2.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.672</i>			
# GS32-64-0500B0952-3-FL	64	50.80	9.517	52.400	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.375</i>	<i>2.063</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-64-0635B0952-HS-HS	64	50.80	9.520	52.400	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.000</i>	<i>0.375</i>	<i>2.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-64-0953B0952-HS-HS	64	50.80	9.520	52.400	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.000</i>	<i>0.375</i>	<i>2.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-64-0953B0952-NS-N	64	50.80	9.520	52.400	9.53	9.53	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.000</i>	<i>0.375</i>	<i>2.063</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-64-0635B0952-NS-N	64	50.80	9.520	52.400	6.35	6.35	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.000</i>	<i>0.375</i>	<i>2.063</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-64-0475B0953-AC-N	64	50.80	9.525	52.400	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.000</i>	<i>0.375</i>	<i>2.063</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-64-0476B0953-C-N	64	50.80	9.525	52.400	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>2.000</i>	<i>0.375</i>	<i>2.063</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-64-0635B1270-NS-N	64	50.80	12.695	52.400	6.35	6.35	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.000</i>	<i>0.500</i>	<i>2.063</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-64-0635B1270-HS-HS	64	50.80	12.695	52.400	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.000</i>	<i>0.500</i>	<i>2.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-64-0953B1270-NS-N	64	50.80	12.695	52.400	9.53	9.53	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.000</i>	<i>0.500</i>	<i>2.063</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-64-0953B1270-HS-HS	64	50.80	12.695	52.400	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.000</i>	<i>0.500</i>	<i>2.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-66-0475B0476-ACS-HS	66	52.39	4.757	53.988	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.063</i>	<i>0.187</i>	<i>2.126</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-66-0475B0476-ACS-FL	66	52.39	4.757	53.988	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.063</i>	<i>0.187</i>	<i>2.126</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-66-0475B0635-ACS-FL	66	52.39	6.345	53.988	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.063</i>	<i>0.250</i>	<i>2.126</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-66-0475B0635-ACS-HS	66	52.39	6.345	53.988	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.063</i>	<i>0.250</i>	<i>2.126</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-66-0475B0953-AC-N	66	52.39	9.525	53.988	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.063</i>	<i>0.375</i>	<i>2.126</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-68-0476B0476-3-HS	68	53.98	4.762	55.575	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.125</i>	<i>0.187</i>	<i>2.188</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-68-0476B0476-A2-HS	68	53.98	4.762	55.575	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.125</i>	<i>0.187</i>	<i>2.188</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-69-0475B0476-ACS-HS	69	54.77	4.757	56.370	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.156</i>	<i>0.187</i>	<i>2.219</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-69-0475B0476-ACS-FL	69	54.77	4.757	56.370	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.156</i>	<i>0.187</i>	<i>2.219</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-69-0475B0635-ACS-FL	69	54.77	6.345	56.370	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.156</i>	<i>0.250</i>	<i>2.219</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-69-0475B0635-ACS-HS	69	54.77	6.345	56.370	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.156</i>	<i>0.250</i>	<i>2.219</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-69-0475B0953-AC-N	69	54.77	9.525	56.370	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.156</i>	<i>0.375</i>	<i>2.219</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-70-0318B0635-A2-HS	70	55.56	6.350	57.162	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.187</i>	<i>0.250</i>	<i>2.250</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-70-0318B0635-3-HS	70	55.56	6.350	57.162	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.187</i>	<i>0.250</i>	<i>2.250</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-70-0318B0635-A2-CH	70	55.56	6.350	57.162	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.187</i>	<i>0.250</i>	<i>2.250</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-70-0318B0635-3-CH	70	55.56	6.350	57.162	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.187</i>	<i>0.250</i>	<i>2.250</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-70-0500B0952-3-FL	70	55.56	9.517	57.162	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>2.187</i>	<i>0.375</i>	<i>2.250</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-72-0475B0476-ACS-HS	72	57.15	4.757	58.750	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.250</i>	<i>0.187</i>	<i>2.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-72-0475B0476-ACS-FL	72	57.15	4.757	58.750	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.250</i>	<i>0.187</i>	<i>2.313</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-72-0476B0476-A2-HS	72	57.15	4.762	58.750	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.250</i>	<i>0.187</i>	<i>2.313</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-72-0476B0476-3-HS	72	57.15	4.762	58.750	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.250</i>	<i>0.187</i>	<i>2.313</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-72-0953B0635-HS-HS	72	57.15	6.345	58.750	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-72-0635B0635-HS-HS	72	57.15	6.345	58.750	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-72-0475B0635-ACS-HS	72	57.15	6.345	58.750	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-72-0475B0635-ACS-FL	72	57.15	6.345	58.750	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-72-0318B0635-3-CH	72	57.15	6.350	58.750	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-72-0476B0635-3-HS	72	57.15	6.350	58.750	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-72-0476B0635-BAK-N	72	57.15	6.350	58.750	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-72-0318B0635-A2-CH	72	57.15	6.350	58.750	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-72-0476B0635-A2-HS	72	57.15	6.350	58.750	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-72-0318B0635-3-HS	72	57.15	6.350	58.750	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-72-0318B0635-A2-HS	72	57.15	6.350	58.750	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.250</i>	<i>0.250</i>	<i>2.313</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-72-0476B0794-AC-HP	72	57.15	7.938	58.750	4.76	12.70	20.64	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>2.250</i>	<i>0.313</i>	<i>2.313</i>	<i>0.187</i>	<i>0.500</i>	<i>0.813</i>			
# GS32-72-0476B0794-ACB-HS	72	57.15	7.938	58.750	4.76	12.70	20.64	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>2.250</i>	<i>0.313</i>	<i>2.313</i>	<i>0.187</i>	<i>0.500</i>	<i>0.813</i>			
# GS32-72-0500B0952-3-FL	72	57.15	9.517	58.750	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-72-0953B0952-NS-N	72	57.15	9.520	58.750	9.53	9.53	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.375</i>	<i>0.375</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-72-0635B0952-NS-N	72	57.15	9.520	58.750	6.35	6.35	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-72-0635B0952-HS-HS	72	57.15	9.520	58.750	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-72-0953B0952-HS-HS	72	57.15	9.520	58.750	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-72-0475B0953-AC-N	72	57.15	9.525	58.750	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-72-0476B0953-C-N	72	57.15	9.525	58.750	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>2.250</i>	<i>0.375</i>	<i>2.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-72-0953B1270-HS-HS	72	57.15	12.695	58.750	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.250</i>	<i>0.500</i>	<i>2.313</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-72-0635B1270-NS-N	72	57.15	12.695	58.750	6.35	6.35	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.250</i>	<i>0.500</i>	<i>2.313</i>	<i>0.250</i>	<i>0.250</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-72-0953B1270-NS-N	72	57.15	12.695	58.750	9.53	9.53	Hubless (Core Diameter = 30.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.250</i>	<i>0.500</i>	<i>2.313</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-72-0635B1270-HS-HS	72	57.15	12.695	58.750	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.250</i>	<i>0.500</i>	<i>2.313</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-75-0475B0476-ACS-HS	75	59.53	4.757	61.133	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.344</i>	<i>0.187</i>	<i>2.407</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-75-0475B0476-ACS-FL	75	59.53	4.757	61.133	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.344</i>	<i>0.187</i>	<i>2.407</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-75-0475B0635-ACS-FL	75	59.53	6.345	61.133	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.344</i>	<i>0.250</i>	<i>2.407</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-75-0475B0635-ACS-HS	75	59.53	6.345	61.133	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.344</i>	<i>0.250</i>	<i>2.407</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-75-0318B0635-3-HS	75	59.53	6.350	61.133	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.344</i>	<i>0.250</i>	<i>2.407</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-75-0318B0635-A2-HS	75	59.53	6.350	61.133	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.344</i>	<i>0.250</i>	<i>2.407</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-75-0318B0635-A2-CH	75	59.53	6.350	61.133	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.344</i>	<i>0.250</i>	<i>2.407</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-75-0318B0635-3-CH	75	59.53	6.350	61.133	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.344</i>	<i>0.250</i>	<i>2.407</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-75-0500B0952-3-FL	75	59.53	9.517	61.133	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>2.344</i>	<i>0.375</i>	<i>2.407</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-75-0475B0953-AC-N	75	59.53	9.525	61.133	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.344</i>	<i>0.375</i>	<i>2.407</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-76-0318B0635-A2-CH	76	60.33	6.350	61.925	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.375</i>	<i>0.250</i>	<i>2.438</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-76-0318B0635-3-CH	76	60.33	6.350	61.925	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.375</i>	<i>0.250</i>	<i>2.438</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-76-0318B0635-3-HS	76	60.33	6.350	61.925	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.375</i>	<i>0.250</i>	<i>2.438</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-76-0318B0635-A2-HS	76	60.33	6.350	61.925	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.375</i>	<i>0.250</i>	<i>2.438</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-76-0476B0635-3-HS	76	60.33	6.350	61.925	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.375</i>	<i>0.250</i>	<i>2.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-76-0476B0635-A2-HS	76	60.33	6.350	61.925	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.375</i>	<i>0.250</i>	<i>2.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-80-0475B0476-ACS-FL	80	63.50	4.757	65.100	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.563</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-80-0475B0476-ACS-HS	80	63.50	4.757	65.100	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-80-0476B0476-3-HS	80	63.50	4.762	65.100	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-80-0476B0476-A2-HS	80	63.50	4.762	65.100	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-80-0953B0635-HS-HS	80	63.50	6.345	65.100	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-80-0475B0635-ACS-HS	80	63.50	6.345	65.100	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-80-0635B0635-HS-HS	80	63.50	6.345	65.100	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-80-0475B0635-ACS-FL	80	63.50	6.345	65.100	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-80-0318B0635-3-CH	80	63.50	6.350	65.100	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-80-0318B0635-A2-HS	80	63.50	6.350	65.100	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-80-0318B0635-A2-CH	80	63.50	6.350	65.100	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-80-0476B0635-BAK-N	80	63.50	6.350	65.100	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-80-0476B0635-3-HS	80	63.50	6.350	65.100	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-80-0476B0635-A2-HS	80	63.50	6.350	65.100	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-80-0318B0635-3-HS	80	63.50	6.350	65.100	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.563</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-80-0476B0794-ACB-HS	80	63.50	7.938	65.100	4.76	12.70	20.64	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>2.500</i>	<i>0.313</i>	<i>2.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.813</i>			
# GS32-80-0476B0794-AC-HP	80	63.50	7.938	65.100	4.76	12.70	20.64	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>2.500</i>	<i>0.313</i>	<i>2.563</i>	<i>0.187</i>	<i>0.500</i>	<i>0.813</i>			
# GS32-80-0500B0952-3-FL	80	63.50	9.517	65.100	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-80-0635B0952-HS-HS	80	63.50	9.520	65.100	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-80-0953B0952-NS-N	80	63.50	9.520	65.100	9.53	9.53	Hubless (Core Diameter = 35.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-80-0635B0952-NS-N	80	63.50	9.520	65.100	6.35	6.35	Hubless (Core Diameter = 35.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.250</i>	<i>0.250</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-80-0953B0952-HS-HS	80	63.50	9.520	65.100	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-80-0476B0953-C-N	80	63.50	9.525	65.100	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-80-0475B0953-AC-N	80	63.50	9.525	65.100	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.500</i>	<i>0.375</i>	<i>2.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-80-0635B1270-HS-HS	80	63.50	12.695	65.100	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.500</i>	<i>0.500</i>	<i>2.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-80-0953B1270-HS-HS	80	63.50	12.695	65.100	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>2.500</i>	<i>0.500</i>	<i>2.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-80-0635B1270-NS-N	80	63.50	12.695	65.100	6.35	6.35	Hubless (Core Diameter = 35.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.500</i>	<i>0.500</i>	<i>2.563</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-80-0953B1270-NS-N	80	63.50	12.695	65.100	9.53	9.53	Hubless (Core Diameter = 35.00)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>2.500</i>	<i>0.500</i>	<i>2.563</i>	<i>0.375</i>	<i>0.375</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-84-0475B0476-ACS-FL	84	66.68	4.757	68.275	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.625</i>	<i>0.187</i>	<i>2.688</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-84-0475B0476-ACS-HS	84	66.68	4.757	68.275	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.625</i>	<i>0.187</i>	<i>2.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-84-0476B0476-A2-HS	84	66.68	4.762	68.275	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.625</i>	<i>0.187</i>	<i>2.688</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-84-0476B0476-3-HS	84	66.68	4.762	68.275	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.625</i>	<i>0.187</i>	<i>2.688</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-84-0475B0635-ACS-HS	84	66.68	6.345	68.275	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.625</i>	<i>0.250</i>	<i>2.688</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-84-0475B0635-ACS-FL	84	66.68	6.345	68.275	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.625</i>	<i>0.250</i>	<i>2.688</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-84-0475B0953-AC-N	84	66.68	9.525	68.275	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.625</i>	<i>0.375</i>	<i>2.688</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-88-0475B0476-ACS-FL	88	69.85	4.757	71.450	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.813</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-88-0475B0476-ACS-HS	88	69.85	4.757	71.450	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-88-0476B0476-3-HS	88	69.85	4.762	71.450	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-88-0476B0476-A2-HS	88	69.85	4.762	71.450	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-88-0475B0635-ACS-FL	88	69.85	6.345	71.450	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.813</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-88-0475B0635-ACS-HS	88	69.85	6.345	71.450	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-88-0318B0635-3-HS	88	69.85	6.350	71.450	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-88-0318B0635-3-CH	88	69.85	6.350	71.450	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-88-0318B0635-A2-HS	88	69.85	6.350	71.450	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-88-0476B0635-A2-HS	88	69.85	6.350	71.450	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-88-0318B0635-A2-CH	88	69.85	6.350	71.450	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-88-0476B0953-C-N	88	69.85	9.525	71.450	4.76	4.76	Hubless	0.00 / None	20	Carbon Steel / Commercial
		<i>2.750</i>	<i>0.375</i>	<i>2.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-88-0475B0953-AC-N	88	69.85	9.525	71.450	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.750</i>	<i>0.375</i>	<i>2.813</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-90-0318B0635-3-HS	90	71.44	6.350	73.038	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.813</i>	<i>0.250</i>	<i>2.876</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

Page 83 of 103

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-90-0318B0635-A2-HS	90	71.44	6.350	73.038	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.813</i>	<i>0.250</i>	<i>2.876</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-90-0500B0952-3-FL	90	71.44	9.517	73.038	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>2.813</i>	<i>0.375</i>	<i>2.876</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-92-0475B0476-ACS-FL	92	73.03	4.757	74.625	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.875</i>	<i>0.187</i>	<i>2.938</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-92-0475B0476-ACS-HS	92	73.03	4.757	74.625	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.875</i>	<i>0.187</i>	<i>2.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-92-0476B0476-A2-HS	92	73.03	4.762	74.625	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.875</i>	<i>0.187</i>	<i>2.938</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-92-0476B0476-3-HS	92	73.03	4.762	74.625	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.875</i>	<i>0.187</i>	<i>2.938</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-92-0475B0635-ACS-FL	92	73.03	6.345	74.625	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.875</i>	<i>0.250</i>	<i>2.938</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-92-0475B0635-ACS-HS	92	73.03	6.345	74.625	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.875</i>	<i>0.250</i>	<i>2.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-92-0476B0635-A2-HS	92	73.03	6.350	74.625	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.875</i>	<i>0.250</i>	<i>2.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-92-0476B0635-3-HS	92	73.03	6.350	74.625	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.875</i>	<i>0.250</i>	<i>2.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-92-0475B0953-AC-N	92	73.03	9.525	74.625	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.875</i>	<i>0.375</i>	<i>2.938</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-96-0475B0476-ACS-FL	96	76.20	4.757	77.800	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.063</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-96-0475B0476-ACS-HS	96	76.20	4.757	77.800	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-96-0476B0476-A2-HS	96	76.20	4.762	77.800	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-96-0476B0476-3-HS	96	76.20	4.762	77.800	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-96-0475B0635-ACS-FL	96	76.20	6.345	77.800	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-96-0475B0635-ACS-HS	96	76.20	6.345	77.800	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-96-0953B0635-HS-HS	96	76.20	6.345	77.800	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-96-0635B0635-HS-HS	96	76.20	6.345	77.800	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-96-0476B0635-BAK-N	96	76.20	6.350	77.800	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-96-0318B0635-3-CH	96	76.20	6.350	77.800	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-96-0318B0635-A2-HS	96	76.20	6.350	77.800	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-96-0318B0635-A2-CH	96	76.20	6.350	77.800	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-96-0476B0635-A2-HS	96	76.20	6.350	77.800	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-96-0318B0635-3-HS	96	76.20	6.350	77.800	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-96-0476B0635-3-HS	96	76.20	6.350	77.800	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-96-0476B0794-ACB-HS	96	76.20	7.938	77.800	4.76	12.70	20.64	7.94 / Pin Hub - Set Screw	20	Acetal - Brass insert / Commercial - Moulded
		<i>3.000</i>	<i>0.313</i>	<i>3.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.813</i>			
# GS32-96-0476B0794-AC-HP	96	76.20	7.938	77.800	4.76	12.70	20.64	7.94 / Pin Hub - No Set Screw	20	Acetal / Commercial - Moulded
		<i>3.000</i>	<i>0.313</i>	<i>3.063</i>	<i>0.187</i>	<i>0.500</i>	<i>0.813</i>			
# GS32-96-0500B0952-3-FL	96	76.20	9.517	77.800	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-96-0953B0952-HS-HS	96	76.20	9.520	77.800	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-96-0953B0952-NS-N	96	76.20	9.520	77.800	9.53	9.53	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-96-0635B0952-HS-HS	96	76.20	9.520	77.800	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-96-0635B0952-NS-N	96	76.20	9.520	77.800	6.35	6.35	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.250</i>	<i>0.250</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

Page 88 of 103

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-96-0475B0953-AC-N	96	76.20	9.525	77.800	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>3.000</i>	<i>0.375</i>	<i>3.063</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-96-0953B1270-NS-N	96	76.20	12.695	77.800	9.53	9.53	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.000</i>	<i>0.500</i>	<i>3.063</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-96-0635B1270-NS-N	96	76.20	12.695	77.800	6.35	6.35	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.000</i>	<i>0.500</i>	<i>3.063</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-96-0953B1270-HS-HS	96	76.20	12.695	77.800	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.000</i>	<i>0.500</i>	<i>3.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-96-0635B1270-HS-HS	96	76.20	12.695	77.800	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.000</i>	<i>0.500</i>	<i>3.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-100-0476B0476-3-HS	100	79.38	4.762	80.975	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.125</i>	<i>0.187</i>	<i>3.188</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-100-0476B0476-A2-HS	100	79.38	4.762	80.975	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.125</i>	<i>0.187</i>	<i>3.188</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-100-0476B0635-3-HS	100	79.38	6.350	80.975	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.125</i>	<i>0.250</i>	<i>3.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-100-0476B0635-A2-HS	100	79.38	6.350	80.975	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.125</i>	<i>0.250</i>	<i>3.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-100-0318B0635-3-HS	100	79.38	6.350	80.975	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.125</i>	<i>0.250</i>	<i>3.188</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-100-0318B0635-A2-HS	100	79.38	6.350	80.975	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.125</i>	<i>0.250</i>	<i>3.188</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-100-0500B0952-3-FL	100	79.38	9.517	80.975	5.00	19.00	24.00	14.00 / Fairloc Hub	20	303 Stainless Steel / AGMA Q10
		<i>3.125</i>	<i>0.375</i>	<i>3.188</i>	<i>0.197</i>	<i>0.748</i>	<i>0.945</i>			
# GS32-104-0475B0476-ACS-FL	104	82.55	4.757	84.150	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.250</i>	<i>0.187</i>	<i>3.313</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-104-0475B0476-ACS-HS	104	82.55	4.757	84.150	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.250</i>	<i>0.187</i>	<i>3.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-104-0475B0635-ACS-FL	104	82.55	6.345	84.150	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.250</i>	<i>0.250</i>	<i>3.313</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-104-0475B0635-ACS-HS	104	82.55	6.345	84.150	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.250</i>	<i>0.250</i>	<i>3.313</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-104-0475B0953-AC-N	104	82.55	9.525	84.150	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>3.250</i>	<i>0.375</i>	<i>3.313</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-108-0475B0476-ACS-FL	108	85.73	4.757	87.325	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.375</i>	<i>0.187</i>	<i>3.438</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-108-0476B0476-3-HS	108	85.73	4.762	87.325	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.375</i>	<i>0.187</i>	<i>3.438</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-108-0476B0476-A2-HS	108	85.73	4.762	87.325	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.375</i>	<i>0.187</i>	<i>3.438</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-108-0475B0635-ACS-FL	108	85.73	6.345	87.325	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.375</i>	<i>0.250</i>	<i>3.438</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-108-0475B0635-ACS-HS	108	85.73	6.345	87.325	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.375</i>	<i>0.250</i>	<i>3.438</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-108-0475B0953-AC-N	108	85.73	9.525	87.325	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>3.375</i>	<i>0.375</i>	<i>3.438</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-110-0318B0635-A2-HS	110	87.31	6.350	88.912	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.437</i>	<i>0.250</i>	<i>3.500</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-110-0318B0635-3-HS	110	87.31	6.350	88.912	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.437</i>	<i>0.250</i>	<i>3.500</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-112-0475B0476-ACS-HS	112	88.90	4.757	90.500	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.500</i>	<i>0.187</i>	<i>3.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-112-0475B0476-ACS-FL	112	88.90	4.757	90.500	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.500</i>	<i>0.187</i>	<i>3.563</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-112-0476B0476-3-HS	112	88.90	4.762	90.500	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.500</i>	<i>0.187</i>	<i>3.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-112-0476B0476-A2-HS	112	88.90	4.762	90.500	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.500</i>	<i>0.187</i>	<i>3.563</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-112-0475B0635-ACS-FL	112	88.90	6.345	90.500	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-112-0953B0635-HS-HS	112	88.90	6.345	90.500	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-112-0635B0635-HS-HS	112	88.90	6.345	90.500	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-112-0475B0635-ACS-HS	112	88.90	6.345	90.500	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-112-0476B0635-BAK-N	112	88.90	6.350	90.500	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-112-0318B0635-A2-CH	112	88.90	6.350	90.500	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-112-0476B0635-3-HS	112	88.90	6.350	90.500	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-112-0318B0635-3-CH	112	88.90	6.350	90.500	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-112-0476B0635-A2-HS	112	88.90	6.350	90.500	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.563</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-112-0953B0952-NS-N	112	88.90	9.520	90.500	9.53	9.53	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.500</i>	<i>0.375</i>	<i>3.563</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-112-0953B0952-HS-HS	112	88.90	9.520	90.500	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.500</i>	<i>0.375</i>	<i>3.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-112-0635B0952-NS-N	112	88.90	9.520	90.500	6.35	6.35	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.500</i>	<i>0.375</i>	<i>3.563</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-112-0635B0952-HS-HS	112	88.90	9.520	90.500	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.500</i>	<i>0.375</i>	<i>3.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-112-0475B0953-AC-N	112	88.90	9.525	90.500	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>3.500</i>	<i>0.375</i>	<i>3.563</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-112-0635B1270-HS-HS	112	88.90	12.695	90.500	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.500</i>	<i>0.500</i>	<i>3.563</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-112-0953B1270-HS-HS	112	88.90	12.695	90.500	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>3.500</i>	<i>0.500</i>	<i>3.563</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-112-0953B1270-NS-N	112	88.90	12.695	90.500	9.53	9.53	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.500</i>	<i>0.500</i>	<i>3.563</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-112-0635B1270-NS-N	112	88.90	12.695	90.500	6.35	6.35	Hubless (Core Diameter = 40.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>3.500</i>	<i>0.500</i>	<i>3.563</i>	<i>0.250</i>	<i>0.250</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-116-0476B0476-3-HS	116	92.08	4.762	93.675	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.625</i>	<i>0.187</i>	<i>3.688</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-116-0476B0476-A2-HS	116	92.08	4.762	93.675	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.625</i>	<i>0.187</i>	<i>3.688</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-120-0476B0476-3-HS	120	95.25	4.762	96.850	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.750</i>	<i>0.187</i>	<i>3.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-120-0476B0476-A2-HS	120	95.25	4.762	96.850	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.750</i>	<i>0.187</i>	<i>3.813</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-120-0476B0635-3-HS	120	95.25	6.350	96.850	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.750</i>	<i>0.250</i>	<i>3.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-120-0318B0635-3-CH	120	95.25	6.350	96.850	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>3.750</i>	<i>0.250</i>	<i>3.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-120-0318B0635-3-HS	120	95.25	6.350	96.850	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.750</i>	<i>0.250</i>	<i>3.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-120-0318B0635-A2-CH	120	95.25	6.350	96.850	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.750</i>	<i>0.250</i>	<i>3.813</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-120-0476B0635-A2-HS	120	95.25	6.350	96.850	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.750</i>	<i>0.250</i>	<i>3.813</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-120-0318B0635-A2-HS	120	95.25	6.350	96.850	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.750</i>	<i>0.250</i>	<i>3.813</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-124-0475B0476-ACS-FL	124	98.43	4.757	100.025	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.875</i>	<i>0.187</i>	<i>3.938</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS32-124-0475B0476-ACS-HS	124	98.43	4.757	100.025	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.875</i>	<i>0.187</i>	<i>3.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-124-0475B0635-ACS-FL	124	98.43	6.345	100.025	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>3.875</i>	<i>0.250</i>	<i>3.938</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS32-124-0475B0635-ACS-HS	124	98.43	6.345	100.025	4.75	11.10	12.70	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>3.875</i>	<i>0.250</i>	<i>3.938</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-124-0318B0635-3-HS	124	98.43	6.350	100.025	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.875</i>	<i>0.250</i>	<i>3.938</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-124-0318B0635-A2-HS	124	98.43	6.350	100.025	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.875</i>	<i>0.250</i>	<i>3.938</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-124-0475B0953-AC-N	124	98.43	9.525	100.025	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>3.875</i>	<i>0.375</i>	<i>3.938</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-127-0318B0635-3-CH	127	100.81	6.350	102.408	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>3.969</i>	<i>0.250</i>	<i>4.032</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-127-0318B0635-A2-CH	127	100.81	6.350	102.408	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.969</i>	<i>0.250</i>	<i>4.032</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-128-0476B0476-3-HS	128	101.60	4.762	103.200	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>4.000</i>	<i>0.187</i>	<i>4.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-128-0476B0476-A2-HS	128	101.60	4.762	103.200	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.000</i>	<i>0.187</i>	<i>4.063</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-128-0953B0635-HS-HS	128	101.60	6.345	103.200	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>4.000</i>	<i>0.250</i>	<i>4.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-128-0635B0635-HS-HS	128	101.60	6.345	103.200	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>4.000</i>	<i>0.250</i>	<i>4.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-128-0476B0635-BAK-N	128	101.60	6.350	103.200	4.76	4.76	Hubless	0.00 / None	20	Bakelite / Commercial
		<i>4.000</i>	<i>0.250</i>	<i>4.063</i>	<i>0.187</i>	<i>0.187</i>				
# GS32-128-0476B0635-A2-HS	128	101.60	6.350	103.200	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.000</i>	<i>0.250</i>	<i>4.063</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-128-0318B0635-A2-CH	128	101.60	6.350	103.200	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.000</i>	<i>0.250</i>	<i>4.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-128-0318B0635-3-CH	128	101.60	6.350	103.200	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>4.000</i>	<i>0.250</i>	<i>4.063</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-128-0635B0952-NS-N	128	101.60	9.520	103.200	6.35	6.35	Hubless (Core Diameter = 50.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>4.000</i>	<i>0.375</i>	<i>4.063</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-128-0953B0952-NS-N	128	101.60	9.520	103.200	9.53	9.53	Hubless (Core Diameter = 50.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>4.000</i>	<i>0.375</i>	<i>4.063</i>	<i>0.375</i>	<i>0.375</i>				
# GS32-128-0953B0952-HS-HS	128	101.60	9.520	103.200	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>4.000</i>	<i>0.375</i>	<i>4.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-128-0635B0952-HS-HS	128	101.60	9.520	103.200	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>4.000</i>	<i>0.375</i>	<i>4.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-128-0953B1270-NS-N	128	101.60	12.695	103.200	9.53	9.53	Hubless (Core Diameter = 50.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>4.000</i>	<i>0.500</i>	<i>4.063</i>	<i>0.375</i>	<i>0.375</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-128-0635B1270-NS-N	128	101.60	12.695	103.200	6.35	6.35	Hubless (Core Diameter = 50.01)	0.00 / None	20	Cast Nylon 12 / 303 Stainless Core / AGMA 9
		<i>4.000</i>	<i>0.500</i>	<i>4.063</i>	<i>0.250</i>	<i>0.250</i>				
# GS32-128-0953B1270-HS-HS	128	101.60	12.695	103.200	9.53	15.88	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>4.000</i>	<i>0.500</i>	<i>4.063</i>	<i>0.375</i>	<i>0.625</i>	<i>0.750</i>			
# GS32-128-0635B1270-HS-HS	128	101.60	12.695	103.200	6.35	12.70	19.05	6.35 / Set Screw	20	Hardened Alloy Steel / AGMA Q10
		<i>4.000</i>	<i>0.500</i>	<i>4.063</i>	<i>0.250</i>	<i>0.500</i>	<i>0.750</i>			
# GS32-130-0476B0476-A2-HS	130	103.19	4.762	104.788	4.76	10.31	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.063</i>	<i>0.187</i>	<i>4.126</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-130-0476B0476-3-HS	130	103.19	4.762	104.788	4.76	10.31	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>4.063</i>	<i>0.187</i>	<i>4.126</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS32-130-0476B0635-A2-HS	130	103.19	6.350	104.788	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.063</i>	<i>0.250</i>	<i>4.126</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-130-0318B0635-A2-HS	130	103.19	6.350	104.788	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.063</i>	<i>0.250</i>	<i>4.126</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-130-0318B0635-3-HS	130	103.19	6.350	104.788	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>4.063</i>	<i>0.250</i>	<i>4.126</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS32-130-0476B0635-3-HS	130	103.19	6.350	104.788	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>4.063</i>	<i>0.250</i>	<i>4.126</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-132-0476B0635-A2-HS	132	104.78	6.350	106.375	4.76	11.11	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.125</i>	<i>0.250</i>	<i>4.188</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS32-132-0318B0635-3-CH	132	104.78	6.350	106.375	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>4.125</i>	<i>0.250</i>	<i>4.188</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS32-132-0318B0635-A2-CH	132	104.78	6.350	106.375	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.125</i>	<i>0.250</i>	<i>4.188</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 32 Pitch - 20 Degree

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS32-132-0476B0635-3-HS	132	104.78	6.350	106.375	4.76	11.11	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		4.125	0.250	4.188	0.187	0.437	0.500			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
