




MBA

Gears - Spur - 64 Pitch - Differential End



To suit the precision diffs listed on this site. 2024 aluminium and 303 stainless steel.

Metallic.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-040-0318B0953-3-C	40	15.88	9.525	16.67	3.18	10.31	12.70	Clamp Type	20	303 Stainless Steel
		<i>0.625</i>	<i>0.375</i>	<i>0.656</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-040-0318B0953-A2-C	40	15.88	9.525	16.67	3.18	10.31	12.70	Clamp Type	20	2024 Aluminium Anodized Before Hobbing
		<i>0.625</i>	<i>0.375</i>	<i>0.656</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-048-0318B0953-3-C	48	19.05	9.525	19.84	3.18	10.31	12.70	Clamp Type	20	303 Stainless Steel
		<i>0.750</i>	<i>0.375</i>	<i>0.781</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-048-0318B0953-A2-C	48	19.05	9.525	19.84	3.18	10.31	12.70	Clamp Type	20	2024 Aluminium Anodized Before Hobbing
		<i>0.750</i>	<i>0.375</i>	<i>0.781</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-060-0318B0953-A2-C	60	23.81	9.525	24.60	3.18	10.31	12.70	Clamp Type	20	2024 Aluminium Anodized Before Hobbing
		<i>0.937</i>	<i>0.375</i>	<i>0.969</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-060-0318B0953-3-C	60	23.81	9.525	24.60	3.18	10.31	12.70	Clamp Type	20	303 Stainless Steel
		<i>0.937</i>	<i>0.375</i>	<i>0.969</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-064-0318B0953-3-C	64	25.40	9.525	26.19	3.18	10.31	12.70	Clamp Type	20	303 Stainless Steel
		<i>1.000</i>	<i>0.375</i>	<i>1.031</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-064-0318B0953-A2-C	64	25.40	9.525	26.19	3.18	10.31	12.70	Clamp Type	20	2024 Aluminium Anodized Before Hobbing
		<i>1.000</i>	<i>0.375</i>	<i>1.031</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-72-0239B1657-A2-N	72	28.58	16.571	29.367	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.125</i>	<i>0.652</i>	<i>1.156</i>	<i>0.094</i>	<i>0.094</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-72-0239B1657-3-N	72	28.58	16.571	29.367	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.125</i>	<i>0.652</i>	<i>1.156</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-080-0318B0953-3-C	80	31.75	9.525	32.54	3.18	10.31	12.70	Clamp Type	20	303 Stainless Steel
		<i>1.250</i>	<i>0.375</i>	<i>1.281</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-080-0318B0953-A2-C	80	31.75	9.525	32.54	3.18	10.31	12.70	Clamp Type	20	2024 Aluminium Anodized Before Hobbing
		<i>1.250</i>	<i>0.375</i>	<i>1.281</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-80-0239B1657-A2-N	80	31.75	16.571	32.542	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.250</i>	<i>0.652</i>	<i>1.281</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-80-0239B1657-3-N	80	31.75	16.571	32.542	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.250</i>	<i>0.652</i>	<i>1.281</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-80-0318B2302-A2-N	80	31.75	23.015	32.542	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.250</i>	<i>0.906</i>	<i>1.281</i>	<i>0.125</i>	<i>0.125</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-80-0318B2302-3-N	80	31.75	23.015	32.542	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.250</i>	<i>0.906</i>	<i>1.281</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-82-0239B1657-A2-N	82	32.55	16.571	33.337	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.281</i>	<i>0.652</i>	<i>1.312</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-82-0239B1657-3-N	82	32.55	16.571	33.337	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.281</i>	<i>0.652</i>	<i>1.312</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-82-0318B2302-3-N	82	32.55	23.015	33.337	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.281</i>	<i>0.906</i>	<i>1.312</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-82-0318B2302-A2-N	82	32.55	23.015	33.337	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.281</i>	<i>0.906</i>	<i>1.312</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-090-0318B0953-3-C	90	35.72	9.525	36.51	3.18	10.31	12.70	Clamp Type	20	303 Stainless Steel
		<i>1.406</i>	<i>0.375</i>	<i>1.437</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-090-0318B0953-A2-C	90	35.72	9.525	36.51	3.18	10.31	12.70	Clamp Type	20	2024 Aluminium Anodized Before Hobbing
		<i>1.406</i>	<i>0.375</i>	<i>1.437</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-90-0239B1657-A2-N	90	35.72	16.571	36.512	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.406</i>	<i>0.652</i>	<i>1.437</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-90-0239B1657-3-N	90	35.72	16.571	36.512	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.406</i>	<i>0.652</i>	<i>1.437</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-90-0318B2302-A2-N	90	35.72	23.015	36.512	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.406</i>	<i>0.906</i>	<i>1.437</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-90-0318B2302-3-N	90	35.72	23.015	36.512	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.406</i>	<i>0.906</i>	<i>1.437</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-096-0318B0953-3-C	96	38.10	9.525	38.89	3.18	10.31	12.70	Clamp Type	20	303 Stainless Steel
		<i>1.500</i>	<i>0.375</i>	<i>1.531</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-096-0318B0953-A2-C	96	38.10	9.525	38.89	3.18	10.31	12.70	Clamp Type	20	2024 Aluminium Anodized Before Hobbing
		<i>1.500</i>	<i>0.375</i>	<i>1.531</i>	<i>0.125</i>	<i>0.406</i>	<i>0.500</i>			
# GS64-96-0239B1657-3-N	96	38.10	16.571	38.892	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.500</i>	<i>0.652</i>	<i>1.531</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-96-0239B1657-A2-N	96	38.10	16.571	38.892	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.500</i>	<i>0.652</i>	<i>1.531</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-96-0318B2302-A2-N	96	38.10	23.015	38.892	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.500</i>	<i>0.906</i>	<i>1.531</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-96-0318B2302-3-N	96	38.10	23.015	38.892	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.500</i>	<i>0.906</i>	<i>1.531</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-100-0239B1657-A2-N	100	39.69	16.571	40.480	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.563</i>	<i>0.652</i>	<i>1.594</i>	<i>0.094</i>	<i>0.094</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-100-0239B1657-3-N	100	39.69	16.571	40.480	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.563</i>	<i>0.652</i>	<i>1.594</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-100-0318B2302-A2-N	100	39.69	23.015	40.480	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.563</i>	<i>0.906</i>	<i>1.594</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-100-0318B2302-3-N	100	39.69	23.015	40.480	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.563</i>	<i>0.906</i>	<i>1.594</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-110-0239B1657-3-N	110	43.66	16.571	44.450	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.719</i>	<i>0.652</i>	<i>1.750</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-110-0239B1657-A2-N	110	43.66	16.571	44.450	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.719</i>	<i>0.652</i>	<i>1.750</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-110-0318B2302-3-N	110	43.66	23.015	44.450	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.719</i>	<i>0.906</i>	<i>1.750</i>	<i>0.125</i>	<i>0.125</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-110-0318B2302-A2-N	110	43.66	23.015	44.450	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.719</i>	<i>0.906</i>	<i>1.750</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-120-0239B1657-A2-N	120	47.63	16.571	48.417	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.875</i>	<i>0.652</i>	<i>1.906</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-120-0239B1657-3-N	120	47.63	16.571	48.417	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.875</i>	<i>0.652</i>	<i>1.906</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-120-0318B2302-A2-N	120	47.63	23.015	48.417	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>1.875</i>	<i>0.906</i>	<i>1.906</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-120-0318B2302-3-N	120	47.63	23.015	48.417	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>1.875</i>	<i>0.906</i>	<i>1.906</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-130-0239B1657-3-N	130	51.60	16.571	52.387	2.39	2.39	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>2.031</i>	<i>0.652</i>	<i>2.062</i>	<i>0.094</i>	<i>0.094</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 64 Pitch - Differential End

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS64-130-0239B1657-A2-N	130	51.60	16.571	52.387	2.39	2.39	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>2.031</i>	<i>0.652</i>	<i>2.062</i>	<i>0.094</i>	<i>0.094</i>				
# GS64-130-0318B2302-3-N	130	51.60	23.015	52.387	3.18	3.18	Hubless	0.00 / None	20	303 Stainless Steel / AGMA Q12
		<i>2.031</i>	<i>0.906</i>	<i>2.062</i>	<i>0.125</i>	<i>0.125</i>				
# GS64-130-0318B2302-A2-N	130	51.60	23.015	52.387	3.18	3.18	Hubless	0.00 / None	20	2024 Anodised Aluminum Alloy / AGMA Q12
		<i>2.031</i>	<i>0.906</i>	<i>2.062</i>	<i>0.125</i>	<i>0.125</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

