




MBA

Gears - Spur - 72 Pitch

Examples shown for basic dimensions. Individual gears may vary in characteristics.



PCD = No. of Teeth x 0.353mm (1/72 in.). 20 Degree Pressure Angle. 2024 aluminium, stainless steel and acetal.
Plastic and metallic.

Fairloc Hub Type require controlled shaft tolerances between 0.0025 and 0.0203 mm Clearance.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-20-0318B0318-3-HS	20	7.06	3.175	7.757	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.278</i>	<i>0.125</i>	<i>0.305</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-20-0318B0318-A2-CH	20	7.06	3.175	7.757	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.278</i>	<i>0.125</i>	<i>0.305</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time
E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-20-0318B0318-3-CH	20	7.06	3.175	7.757	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.278</i>	<i>0.125</i>	<i>0.305</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-20-0318B0318-A2-HS	20	7.06	3.175	7.757	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.278</i>	<i>0.125</i>	<i>0.305</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-22-0318B0318-A2-CH	22	7.76	3.175	8.463	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.306</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-22-0318B0318-A2-HS	22	7.76	3.175	8.463	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.306</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-22-0318B0318-3-CH	22	7.76	3.175	8.463	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.306</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-22-0318B0318-3-HS	22	7.76	3.175	8.463	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.306</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-24-0318B0318-A2-CH	24	8.47	3.175	9.167	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-24-0318B0318-A2-HS	24	8.47	3.175	9.167	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.361</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-24-0318B0318-3-HS	24	8.47	3.175	9.167	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.361</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-24-0318B0318-3-CH	24	8.47	3.175	9.167	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-24-0475B0476-3-HS	24	8.47	4.762	9.167	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.187</i>	<i>0.361</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-24-0318B0476-A2-CH	24	8.47	4.762	9.167	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.187</i>	<i>0.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-24-0318B0476-3-CH	24	8.47	4.762	9.167	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.187</i>	<i>0.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-24-0475B0476-A2-HS	24	8.47	4.762	9.167	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.187</i>	<i>0.361</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-26-0318B0318-3-HS	26	9.17	3.175	9.873	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.361</i>	<i>0.125</i>	<i>0.389</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-26-0318B0318-A2-CH	26	9.17	3.175	9.873	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.361</i>	<i>0.125</i>	<i>0.389</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-26-0318B0318-3-CH	26	9.17	3.175	9.873	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.361</i>	<i>0.125</i>	<i>0.389</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-26-0318B0318-A2-HS	26	9.17	3.175	9.873	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.361</i>	<i>0.125</i>	<i>0.389</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-27-0318B0476-A2-CH	27	9.53	4.762	10.226	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.375</i>	<i>0.187</i>	<i>0.403</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-27-0318B0476-3-CH	27	9.53	4.762	10.226	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.375</i>	<i>0.187</i>	<i>0.403</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-27-0318B0635-3-CH	27	9.53	6.350	10.226	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.375</i>	<i>0.250</i>	<i>0.403</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-27-0318B0635-A2-CH	27	9.53	6.350	10.226	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.375</i>	<i>0.250</i>	<i>0.403</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-28-0318B0318-A2-CH	28	9.88	3.175	10.579	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-28-0318B0318-A2-HS	28	9.88	3.175	10.579	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-28-0318B0318-3-CH	28	9.88	3.175	10.579	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-28-0318B0318-3-HS	28	9.88	3.175	10.579	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-28-0318B0476-A2-HS	28	9.88	4.757	10.579	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.187</i>	<i>0.416</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-28-0318B0476-3-HS	28	9.88	4.757	10.579	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.187</i>	<i>0.416</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-28-0475B0476-A2-HS	28	9.88	4.762	10.579	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.187</i>	<i>0.416</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-28-0318B0476-3-CH	28	9.88	4.762	10.579	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.187</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-28-0475B0476-3-HS	28	9.88	4.762	10.579	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.187</i>	<i>0.416</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-28-0318B0476-A2-CH	28	9.88	4.762	10.579	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.187</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-28-0318B0635-A2-CH	28	9.88	6.350	10.579	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.250</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-28-0318B0635-3-HS	28	9.88	6.350	10.579	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.250</i>	<i>0.416</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-28-0318B0635-A2-HS	28	9.88	6.350	10.579	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.250</i>	<i>0.416</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-28-0475B0635-3-HS	28	9.88	6.350	10.579	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.250</i>	<i>0.416</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-28-0318B0635-3-CH	28	9.88	6.350	10.579	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.389</i>	<i>0.250</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-28-0475B0635-A2-HS	28	9.88	6.350	10.579	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.389</i>	<i>0.250</i>	<i>0.416</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-30-0318B0318-A2-CH	30	10.58	3.175	11.285	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.444</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-30-0318B0318-3-HS	30	10.58	3.175	11.285	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.444</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-30-0318B0318-3-CH	30	10.58	3.175	11.285	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.444</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-30-0318B0318-A2-HS	30	10.58	3.175	11.285	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.444</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-30-0318B0476-3-HS	30	10.58	4.757	11.285	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.444</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-30-0318B0476-A2-HS	30	10.58	4.757	11.285	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.444</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
GS72-30-0475B0476-A2-HS	30	10.58	4.762	11.285	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.444</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-30-0475B0476-3-HS	30	10.58	4.762	11.285	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.444</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-30-0318B0476-A2-CH	30	10.58	4.762	11.285	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.444</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-30-0318B0476-3-CH	30	10.58	4.762	11.285	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.444</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-30-0318B0635-3-HS	30	10.58	6.350	11.285	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.250</i>	<i>0.444</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-30-0318B0635-A2-CH	30	10.58	6.350	11.285	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.250</i>	<i>0.444</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-30-0475B0635-3-HS	30	10.58	6.350	11.285	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.250</i>	<i>0.444</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-30-0318B0635-3-CH	30	10.58	6.350	11.285	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.250</i>	<i>0.444</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-30-0318B0635-A2-HS	30	10.58	6.350	11.285	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.250</i>	<i>0.444</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-30-0475B0635-A2-HS	30	10.58	6.350	11.285	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.250</i>	<i>0.444</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-32-0318B0318-A2-CH	32	11.29	3.175	11.989	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.444</i>	<i>0.125</i>	<i>0.472</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-32-0318B0318-3-HS	32	11.29	3.175	11.989	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.444</i>	<i>0.125</i>	<i>0.472</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-32-0318B0318-A2-HS	32	11.29	3.175	11.989	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.444</i>	<i>0.125</i>	<i>0.472</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-32-0318B0318-3-CH	32	11.29	3.175	11.989	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.444</i>	<i>0.125</i>	<i>0.472</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-32-0318B0476-A2-HS	32	11.29	4.757	11.989	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.444</i>	<i>0.187</i>	<i>0.472</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-32-0318B0476-3-HS	32	11.29	4.757	11.989	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.444</i>	<i>0.187</i>	<i>0.472</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-32-0475B0476-A2-HS	32	11.29	4.762	11.989	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.444</i>	<i>0.187</i>	<i>0.472</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-32-0475B0476-3-HS	32	11.29	4.762	11.989	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.444</i>	<i>0.187</i>	<i>0.472</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-32-0318B0476-3-CH	32	11.29	4.762	11.989	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.444</i>	<i>0.187</i>	<i>0.472</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-32-0318B0476-A2-CH	32	11.29	4.762	11.989	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.444</i>	<i>0.187</i>	<i>0.472</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-32-0318B0635-A2-CH	32	11.29	6.350	11.989	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.444</i>	<i>0.250</i>	<i>0.472</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-32-0318B0635-3-CH	32	11.29	6.350	11.989	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.444</i>	<i>0.250</i>	<i>0.472</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-34-0318B0318-3-HS	34	11.99	3.175	12.695	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.472</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-34-0318B0318-A2-CH	34	11.99	3.175	12.695	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.472</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-34-0318B0318-A2-HS	34	11.99	3.175	12.695	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.472</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-34-0318B0318-3-CH	34	11.99	3.175	12.695	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.472</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-34-0475B0476-A2-HS	34	11.99	4.762	12.695	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.472</i>	<i>0.187</i>	<i>0.500</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-34-0475B0476-3-HS	34	11.99	4.762	12.695	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.472</i>	<i>0.187</i>	<i>0.500</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-36-0318B0318-3-CH	36	12.70	3.175	13.401	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-36-0318B0318-3-HS	36	12.70	3.175	13.401	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.528</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-36-0318B0318-A2-CH	36	12.70	3.175	13.401	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-36-0318B0318-A2-HS	36	12.70	3.175	13.401	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.528</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-36-0318B0476-A2-HS	36	12.70	4.757	13.401	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.528</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-36-0318B0476-3-HS	36	12.70	4.757	13.401	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.528</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-36-0318B0476-3-CH	36	12.70	4.762	13.401	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-36-0318B0476-A2-CH	36	12.70	4.762	13.401	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-36-0318B0635-3-CH	36	12.70	6.350	13.401	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.250</i>	<i>0.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-36-0318B0635-A2-CH	36	12.70	6.350	13.401	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.250</i>	<i>0.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-38-0318B0318-A2-CH	38	13.41	3.175	14.107	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.528</i>	<i>0.125</i>	<i>0.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-38-0318B0318-A2-HS	38	13.41	3.175	14.107	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.528</i>	<i>0.125</i>	<i>0.555</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-38-0318B0318-3-HS	38	13.41	3.175	14.107	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.528</i>	<i>0.125</i>	<i>0.555</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-38-0318B0318-3-CH	38	13.41	3.175	14.107	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.528</i>	<i>0.125</i>	<i>0.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-38-0475B0476-A2-HS	38	13.41	4.762	14.107	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.528</i>	<i>0.187</i>	<i>0.555</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-38-0318B0476-A2-CH	38	13.41	4.762	14.107	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.528</i>	<i>0.187</i>	<i>0.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-38-0475B0476-3-HS	38	13.41	4.762	14.107	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.528</i>	<i>0.187</i>	<i>0.555</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-38-0318B0476-3-CH	38	13.41	4.762	14.107	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.528</i>	<i>0.187</i>	<i>0.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-38-0318B0635-A2-CH	38	13.41	6.350	14.107	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.528</i>	<i>0.250</i>	<i>0.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-38-0318B0635-A2-HS	38	13.41	6.350	14.107	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.528</i>	<i>0.250</i>	<i>0.555</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-38-0475B0635-A2-HS	38	13.41	6.350	14.107	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.528</i>	<i>0.250</i>	<i>0.555</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-38-0475B0635-3-HS	38	13.41	6.350	14.107	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.528</i>	<i>0.250</i>	<i>0.555</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-38-0318B0635-3-CH	38	13.41	6.350	14.107	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.528</i>	<i>0.250</i>	<i>0.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-40-0475B0476-ACS-FL	40	14.11	4.757	14.811	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-40-0475B0476-ACS-HS	40	14.11	4.757	14.811	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-40-0475B0635-ACS-HS	40	14.11	6.345	14.811	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-40-0475B0635-ACS-FL	40	14.11	6.345	14.811	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-40-0475B0953-AC-N	40	14.11	9.525	14.811	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.556</i>	<i>0.375</i>	<i>0.583</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-40-0318B0318-3-HS	40	14.11	3.175	14.813	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-40-0318B0318-3-CH	40	14.11	3.175	14.813	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-40-0318B0318-A2-CH	40	14.11	3.175	14.813	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-40-0318B0318-A2-HS	40	14.11	3.175	14.813	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-40-0318B0476-A2-HS	40	14.11	4.757	14.813	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-40-0318B0476-3-HS	40	14.11	4.757	14.813	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-40-0475B0476-3-HS	40	14.11	4.762	14.813	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-40-0318B0476-3-CH	40	14.11	4.762	14.813	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-40-0318B0476-A2-CH	40	14.11	4.762	14.813	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-40-0475B0476-A2-HS	40	14.11	4.762	14.813	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.187</i>	<i>0.583</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-40-0318B0635-A2-CH	40	14.11	6.350	14.813	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-40-0318B0635-A2-HS	40	14.11	6.350	14.813	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-40-0318B0635-3-CH	40	14.11	6.350	14.813	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-40-0475B0635-3-HS	40	14.11	6.350	14.813	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-40-0318B0635-3-HS	40	14.11	6.350	14.813	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-40-0475B0635-A2-HS	40	14.11	6.350	14.813	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.556</i>	<i>0.250</i>	<i>0.583</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-41-0475B0476-ACS-FL	41	14.46	4.757	15.164	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.569</i>	<i>0.187</i>	<i>0.597</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-41-0475B0476-ACS-HS	41	14.46	4.757	15.164	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.569</i>	<i>0.187</i>	<i>0.597</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-41-0475B0635-ACS-FL	41	14.46	6.345	15.164	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.569</i>	<i>0.250</i>	<i>0.597</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-41-0475B0635-ACS-HS	41	14.46	6.345	15.164	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.569</i>	<i>0.250</i>	<i>0.597</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-41-0475B0953-AC-N	41	14.46	9.525	15.164	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.569</i>	<i>0.375</i>	<i>0.597</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-42-0475B0476-ACS-HS	42	14.82	4.757	15.517	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.583</i>	<i>0.187</i>	<i>0.611</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-42-0475B0476-ACS-FL	42	14.82	4.757	15.517	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.583</i>	<i>0.187</i>	<i>0.611</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-42-0318B0476-A2-CH	42	14.82	4.762	15.517	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.187</i>	<i>0.611</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-42-0318B0476-3-CH	42	14.82	4.762	15.517	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.187</i>	<i>0.611</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-42-0475B0635-ACS-FL	42	14.82	6.345	15.517	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-42-0475B0635-ACS-HS	42	14.82	6.345	15.517	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-42-0318B0635-3-HS	42	14.82	6.350	15.517	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-42-0475B0635-3-HS	42	14.82	6.350	15.517	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-42-0318B0635-A2-HS	42	14.82	6.350	15.517	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-42-0318B0635-3-CH	42	14.82	6.350	15.517	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-42-0318B0635-A2-CH	42	14.82	6.350	15.517	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-42-0475B0635-A2-HS	42	14.82	6.350	15.517	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.611</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-42-0475B0953-AC-N	42	14.82	9.525	15.517	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.583</i>	<i>0.375</i>	<i>0.611</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-43-0475B0476-ACS-HS	43	15.17	4.757	15.870	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.597</i>	<i>0.187</i>	<i>0.625</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-43-0475B0476-ACS-FL	43	15.17	4.757	15.870	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.597</i>	<i>0.187</i>	<i>0.625</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-43-0475B0635-ACS-FL	43	15.17	6.345	15.870	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.597</i>	<i>0.250</i>	<i>0.625</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-43-0475B0635-ACS-HS	43	15.17	6.345	15.870	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.597</i>	<i>0.250</i>	<i>0.625</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-43-0475B0953-AC-N	43	15.17	9.525	15.870	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.597</i>	<i>0.375</i>	<i>0.625</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-44-0318B0318-A2-HS	44	15.52	3.175	16.223	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.125</i>	<i>0.639</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-44-0318B0318-3-CH	44	15.52	3.175	16.223	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.125</i>	<i>0.639</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-44-0318B0318-3-HS	44	15.52	3.175	16.223	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.125</i>	<i>0.639</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-44-0318B0318-A2-CH	44	15.52	3.175	16.223	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.125</i>	<i>0.639</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-44-0318B0476-3-HS	44	15.52	4.757	16.223	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-44-0475B0476-ACS-FL	44	15.52	4.757	16.223	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-44-0475B0476-ACS-HS	44	15.52	4.757	16.223	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-44-0318B0476-A2-HS	44	15.52	4.757	16.223	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-44-0475B0476-A2-HS	44	15.52	4.762	16.223	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-44-0318B0476-A2-CH	44	15.52	4.762	16.223	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-44-0475B0476-3-HS	44	15.52	4.762	16.223	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-44-0318B0476-3-CH	44	15.52	4.762	16.223	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.187</i>	<i>0.639</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-44-0475B0635-ACS-FL	44	15.52	6.345	16.223	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-44-0475B0635-ACS-HS	44	15.52	6.345	16.223	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-44-0318B0635-A2-CH	44	15.52	6.350	16.223	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-44-0475B0635-3-HS	44	15.52	6.350	16.223	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-44-0318B0635-3-CH	44	15.52	6.350	16.223	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-44-0318B0635-3-HS	44	15.52	6.350	16.223	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-44-0318B0635-A2-HS	44	15.52	6.350	16.223	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-44-0475B0635-A2-HS	44	15.52	6.350	16.223	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.611</i>	<i>0.250</i>	<i>0.639</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-44-0475B0953-AC-N	44	15.52	9.525	16.223	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.611</i>	<i>0.375</i>	<i>0.639</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-45-0318B0318-3-HS	45	15.88	3.175	16.576	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.653</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-45-0318B0318-A2-CH	45	15.88	3.175	16.576	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.653</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-45-0318B0318-A2-HS	45	15.88	3.175	16.576	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.653</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-45-0318B0318-3-CH	45	15.88	3.175	16.576	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.653</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-45-0318B0476-A2-HS	45	15.88	4.757	16.576	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.653</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-45-0475B0476-ACS-FL	45	15.88	4.757	16.576	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.653</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-45-0475B0476-ACS-HS	45	15.88	4.757	16.576	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.653</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-45-0318B0476-3-HS	45	15.88	4.757	16.576	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.653</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-45-0318B0476-A2-CH	45	15.88	4.762	16.576	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.653</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-45-0318B0476-3-CH	45	15.88	4.762	16.576	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.653</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-45-0475B0635-ACS-FL	45	15.88	6.345	16.576	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.653</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-45-0475B0635-ACS-HS	45	15.88	6.345	16.576	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.653</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-45-0318B0635-3-CH	45	15.88	6.350	16.576	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.653</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-45-0318B0635-A2-CH	45	15.88	6.350	16.576	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.653</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-45-0475B0953-AC-N	45	15.88	9.525	16.576	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.625</i>	<i>0.375</i>	<i>0.653</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-46-0475B0476-ACS-HS	46	16.23	4.757	16.927	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.639</i>	<i>0.187</i>	<i>0.666</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-46-0475B0476-ACS-FL	46	16.23	4.757	16.927	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.639</i>	<i>0.187</i>	<i>0.666</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-46-0475B0635-ACS-FL	46	16.23	6.345	16.927	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-46-0475B0635-ACS-HS	46	16.23	6.345	16.927	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-46-0475B0953-AC-N	46	16.23	9.525	16.927	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.639</i>	<i>0.375</i>	<i>0.666</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-46-0318B0318-A2-CH	46	16.23	3.175	16.929	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.639</i>	<i>0.125</i>	<i>0.666</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-46-0318B0318-3-HS	46	16.23	3.175	16.929	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.639</i>	<i>0.125</i>	<i>0.666</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-46-0318B0318-3-CH	46	16.23	3.175	16.929	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.639</i>	<i>0.125</i>	<i>0.666</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-46-0318B0318-A2-HS	46	16.23	3.175	16.929	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.639</i>	<i>0.125</i>	<i>0.666</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-46-0318B0476-A2-HS	46	16.23	4.757	16.929	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.639</i>	<i>0.187</i>	<i>0.666</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-46-0318B0476-3-HS	46	16.23	4.757	16.929	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.639</i>	<i>0.187</i>	<i>0.666</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-46-0318B0476-A2-CH	46	16.23	4.762	16.929	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.639</i>	<i>0.187</i>	<i>0.666</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-46-0318B0476-3-CH	46	16.23	4.762	16.929	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.639</i>	<i>0.187</i>	<i>0.666</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-46-0318B0635-3-CH	46	16.23	6.350	16.929	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-46-0318B0635-A2-HS	46	16.23	6.350	16.929	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-46-0475B0635-A2-HS	46	16.23	6.350	16.929	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-46-0318B0635-3-HS	46	16.23	6.350	16.929	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-46-0318B0635-A2-CH	46	16.23	6.350	16.929	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-46-0475B0635-3-HS	46	16.23	6.350	16.929	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.639</i>	<i>0.250</i>	<i>0.666</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-48-0475B0476-ACS-FL	48	16.93	4.757	17.633	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.694</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-48-0475B0476-ACS-HS	48	16.93	4.757	17.633	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-48-0475B0635-ACS-HS	48	16.93	6.345	17.633	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-48-0475B0635-ACS-FL	48	16.93	6.345	17.633	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-48-0475B0953-AC-N	48	16.93	9.525	17.633	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.667</i>	<i>0.375</i>	<i>0.694</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-48-0318B0318-A2-HS	48	16.93	3.175	17.635	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.694</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-48-0318B0318-A2-CH	48	16.93	3.175	17.635	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-48-0318B0318-3-CH	48	16.93	3.175	17.635	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-48-0318B0318-3-HS	48	16.93	3.175	17.635	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.694</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-48-0318B0476-3-HS	48	16.93	4.757	17.635	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.694</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-48-0318B0476-A2-HS	48	16.93	4.757	17.635	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.694</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-48-0318B0476-A2-CH	48	16.93	4.762	17.635	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-48-0318B0476-3-CH	48	16.93	4.762	17.635	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-48-0318B0635-A2-HS	48	16.93	6.350	17.635	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-48-0318B0635-A2-CH	48	16.93	6.350	17.635	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-48-0475B0635-3-HS	48	16.93	6.350	17.635	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-48-0318B0635-3-HS	48	16.93	6.350	17.635	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-48-0318B0635-3-CH	48	16.93	6.350	17.635	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-48-0475B0635-A2-HS	48	16.93	6.350	17.635	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.250</i>	<i>0.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-50-0318B0318-3-CH	50	17.64	3.175	18.339	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.125</i>	<i>0.722</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-50-0318B0318-A2-CH	50	17.64	3.175	18.339	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.125</i>	<i>0.722</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-50-0318B0318-3-HS	50	17.64	3.175	18.339	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.125</i>	<i>0.722</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-50-0318B0318-A2-HS	50	17.64	3.175	18.339	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.125</i>	<i>0.722</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-50-0475B0476-ACS-HS	50	17.64	4.757	18.339	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-50-0475B0476-ACS-FL	50	17.64	4.757	18.339	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-50-0318B0476-3-HS	50	17.64	4.757	18.339	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
GS72-50-0318B0476-A2-HS	50	17.64	4.757	18.339	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-50-0475B0476-3-HS	50	17.64	4.762	18.339	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-50-0318B0476-3-CH	50	17.64	4.762	18.339	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
GS72-50-0475B0476-A2-HS	50	17.64	4.762	18.339	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-50-0318B0476-A2-CH	50	17.64	4.762	18.339	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.187</i>	<i>0.722</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-50-0475B0635-ACS-HS	50	17.64	6.345	18.339	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-50-0475B0635-ACS-FL	50	17.64	6.345	18.339	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-50-0318B0635-A2-CH	50	17.64	6.350	18.339	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-50-0318B0635-A2-HS	50	17.64	6.350	18.339	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-50-0318B0635-3-HS	50	17.64	6.350	18.339	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-50-0475B0635-A2-HS	50	17.64	6.350	18.339	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-50-0318B0635-3-CH	50	17.64	6.350	18.339	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-50-0475B0635-3-HS	50	17.64	6.350	18.339	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.694</i>	<i>0.250</i>	<i>0.722</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-50-0475B0953-AC-N	50	17.64	9.525	18.339	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.694</i>	<i>0.375</i>	<i>0.722</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-54-0318B0476-A2-HS	54	19.05	4.757	19.751	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-54-0318B0476-3-HS	54	19.05	4.757	19.751	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-54-0475B0476-ACS-HS	54	19.05	4.757	19.751	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-54-0475B0476-ACS-FL	54	19.05	4.757	19.751	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-54-0475B0476-A2-HS	54	19.05	4.762	19.751	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-54-0475B0476-3-HS	54	19.05	4.762	19.751	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-54-0318B0476-A2-CH	54	19.05	4.762	19.751	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-54-0318B0476-3-CH	54	19.05	4.762	19.751	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-54-0475B0635-ACS-HS	54	19.05	6.345	19.751	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-54-0475B0635-ACS-FL	54	19.05	6.345	19.751	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.778</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-54-0475B0635-3-HS	54	19.05	6.350	19.751	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-54-0318B0635-3-HS	54	19.05	6.350	19.751	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.778</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-54-0318B0635-A2-HS	54	19.05	6.350	19.751	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.778</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-54-0475B0635-A2-HS	54	19.05	6.350	19.751	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-54-0475B0953-AC-N	54	19.05	9.525	19.751	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.750</i>	<i>0.375</i>	<i>0.778</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-56-0318B0318-A2-HS	56	19.76	3.175	20.457	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.778</i>	<i>0.125</i>	<i>0.805</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-56-0318B0318-3-HS	56	19.76	3.175	20.457	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.778</i>	<i>0.125</i>	<i>0.805</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-56-0318B0318-3-CH	56	19.76	3.175	20.457	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.778</i>	<i>0.125</i>	<i>0.805</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-56-0318B0318-A2-CH	56	19.76	3.175	20.457	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.778</i>	<i>0.125</i>	<i>0.805</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-56-0475B0476-3-HS	56	19.76	4.762	20.457	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.778</i>	<i>0.187</i>	<i>0.805</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-56-0475B0476-A2-HS	56	19.76	4.762	20.457	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.778</i>	<i>0.187</i>	<i>0.805</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-56-0318B0635-A2-CH	56	19.76	6.350	20.457	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.778</i>	<i>0.250</i>	<i>0.805</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-56-0318B0635-3-HS	56	19.76	6.350	20.457	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.778</i>	<i>0.250</i>	<i>0.805</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-56-0318B0635-A2-HS	56	19.76	6.350	20.457	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.778</i>	<i>0.250</i>	<i>0.805</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-56-0318B0635-3-CH	56	19.76	6.350	20.457	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.778</i>	<i>0.250</i>	<i>0.805</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-60-0318B0318-3-CH	60	21.17	3.175	21.867	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.861</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-60-0318B0318-3-HS	60	21.17	3.175	21.867	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.861</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-60-0318B0318-A2-HS	60	21.17	3.175	21.867	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.861</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-60-0318B0318-A2-CH	60	21.17	3.175	21.867	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.861</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-60-0475B0476-ACS-HS	60	21.17	4.757	21.867	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-60-0475B0476-ACS-FL	60	21.17	4.757	21.867	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-60-0318B0476-A2-HS	60	21.17	4.757	21.867	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-60-0318B0476-3-HS	60	21.17	4.757	21.867	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-60-0475B0476-A2-HS	60	21.17	4.762	21.867	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-60-0318B0476-3-CH	60	21.17	4.762	21.867	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-60-0318B0476-A2-CH	60	21.17	4.762	21.867	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-60-0475B0476-3-HS	60	21.17	4.762	21.867	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.861</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-60-0475B0635-ACS-HS	60	21.17	6.345	21.867	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-60-0475B0635-ACS-FL	60	21.17	6.345	21.867	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-60-0318B0635-A2-HS	60	21.17	6.350	21.867	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-60-0475B0635-3-HS	60	21.17	6.350	21.867	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-60-0475B0635-A2-HS	60	21.17	6.350	21.867	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-60-0318B0635-3-HS	60	21.17	6.350	21.867	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-60-0318B0635-3-CH	60	21.17	6.350	21.867	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-60-0318B0635-A2-CH	60	21.17	6.350	21.867	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.861</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-60-0475B0953-AC-N	60	21.17	9.525	21.867	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.833</i>	<i>0.375</i>	<i>0.861</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-63-0318B0635-A2-CH	63	22.23	6.350	22.926	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.903</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-63-0475B0635-3-HS	63	22.23	6.350	22.926	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.903</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-63-0318B0635-3-CH	63	22.23	6.350	22.926	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.903</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-63-0475B0635-A2-HS	63	22.23	6.350	22.926	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.903</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-64-0318B0318-A2-HS	64	22.58	3.175	23.279	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.889</i>	<i>0.125</i>	<i>0.916</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-64-0318B0318-3-CH	64	22.58	3.175	23.279	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.889</i>	<i>0.125</i>	<i>0.916</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-64-0318B0318-A2-CH	64	22.58	3.175	23.279	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.889</i>	<i>0.125</i>	<i>0.916</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-64-0318B0318-3-HS	64	22.58	3.175	23.279	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.889</i>	<i>0.125</i>	<i>0.916</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-64-0318B0476-3-CH	64	22.58	4.762	23.279	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.889</i>	<i>0.187</i>	<i>0.916</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-64-0318B0476-A2-CH	64	22.58	4.762	23.279	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.889</i>	<i>0.187</i>	<i>0.916</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-64-0475B0476-3-HS	64	22.58	4.762	23.279	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.889</i>	<i>0.187</i>	<i>0.916</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-64-0475B0476-A2-HS	64	22.58	4.762	23.279	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.889</i>	<i>0.187</i>	<i>0.916</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-64-0318B0635-A2-HS	64	22.58	6.350	23.279	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.889</i>	<i>0.250</i>	<i>0.916</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-64-0475B0635-A2-HS	64	22.58	6.350	23.279	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.889</i>	<i>0.250</i>	<i>0.916</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-64-0318B0635-3-CH	64	22.58	6.350	23.279	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.889</i>	<i>0.250</i>	<i>0.916</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-64-0318B0635-3-HS	64	22.58	6.350	23.279	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.889</i>	<i>0.250</i>	<i>0.916</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-64-0318B0635-A2-CH	64	22.58	6.350	23.279	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.889</i>	<i>0.250</i>	<i>0.916</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-64-0475B0635-3-HS	64	22.58	6.350	23.279	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.889</i>	<i>0.250</i>	<i>0.916</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-65-0318B0635-3-HS	65	22.93	6.350	23.632	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.903</i>	<i>0.250</i>	<i>0.930</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-65-0318B0635-A2-HS	65	22.93	6.350	23.632	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.903</i>	<i>0.250</i>	<i>0.930</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-66-0475B0476-ACS-HS	66	23.28	4.757	23.983	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.917</i>	<i>0.187</i>	<i>0.944</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-66-0475B0476-ACS-FL	66	23.28	4.757	23.983	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.917</i>	<i>0.187</i>	<i>0.944</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-66-0475B0635-ACS-FL	66	23.28	6.345	23.983	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>0.917</i>	<i>0.250</i>	<i>0.944</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-66-0475B0635-ACS-HS	66	23.28	6.345	23.983	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>0.917</i>	<i>0.250</i>	<i>0.944</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-66-0475B0953-AC-N	66	23.28	9.525	23.983	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>0.917</i>	<i>0.375</i>	<i>0.944</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-70-0318B0318-3-CH	70	24.69	3.175	25.395	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.972</i>	<i>0.125</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-70-0318B0318-3-HS	70	24.69	3.175	25.395	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.972</i>	<i>0.125</i>	<i>1.000</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-70-0318B0318-A2-HS	70	24.69	3.175	25.395	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.972</i>	<i>0.125</i>	<i>1.000</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-70-0318B0318-A2-CH	70	24.69	3.175	25.395	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.972</i>	<i>0.125</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-70-0318B0476-3-HS	70	24.69	4.757	25.395	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.972</i>	<i>0.187</i>	<i>1.000</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-70-0318B0476-A2-HS	70	24.69	4.757	25.395	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.972</i>	<i>0.187</i>	<i>1.000</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-70-0318B0476-3-CH	70	24.69	4.762	25.395	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.972</i>	<i>0.187</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-70-0318B0476-A2-CH	70	24.69	4.762	25.395	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.972</i>	<i>0.187</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-70-0318B0635-3-CH	70	24.69	6.350	25.395	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.972</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-70-0318B0635-3-HS	70	24.69	6.350	25.395	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.972</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-70-0318B0635-A2-CH	70	24.69	6.350	25.395	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.972</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-70-0475B0635-A2-HS	70	24.69	6.350	25.395	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.972</i>	<i>0.250</i>	<i>1.000</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-70-0475B0635-3-HS	70	24.69	6.350	25.395	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.972</i>	<i>0.250</i>	<i>1.000</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-70-0318B0635-A2-HS	70	24.69	6.350	25.395	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.972</i>	<i>0.250</i>	<i>1.000</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-72-0318B0318-A2-CH	72	25.40	3.175	26.101	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-72-0318B0318-3-CH	72	25.40	3.175	26.101	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-72-0318B0318-3-HS	72	25.40	3.175	26.101	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.028</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-72-0318B0318-A2-HS	72	25.40	3.175	26.101	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.028</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-72-0475B0476-ACS-FL	72	25.40	4.757	26.101	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-72-0318B0476-A2-HS	72	25.40	4.757	26.101	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-72-0475B0476-ACS-HS	72	25.40	4.757	26.101	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-72-0318B0476-3-HS	72	25.40	4.757	26.101	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-72-0318B0476-A2-CH	72	25.40	4.762	26.101	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-72-0475B0476-3-HS	72	25.40	4.762	26.101	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-72-0318B0476-3-CH	72	25.40	4.762	26.101	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-72-0475B0476-A2-HS	72	25.40	4.762	26.101	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.028</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-72-0475B0635-ACS-FL	72	25.40	6.345	26.101	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-72-0475B0635-ACS-HS	72	25.40	6.345	26.101	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-72-0475B0635-A2-HS	72	25.40	6.350	26.101	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-72-0318B0635-A2-HS	72	25.40	6.350	26.101	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-72-0318B0635-3-HS	72	25.40	6.350	26.101	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-72-0318B0635-A2-CH	72	25.40	6.350	26.101	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-72-0475B0635-3-HS	72	25.40	6.350	26.101	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-72-0318B0635-3-CH	72	25.40	6.350	26.101	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-72-0475B0953-AC-N	72	25.40	9.525	26.101	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.000</i>	<i>0.375</i>	<i>1.028</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-75-0475B0476-ACS-FL	75	26.46	4.757	27.158	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.042</i>	<i>0.187</i>	<i>1.069</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-75-0475B0476-ACS-HS	75	26.46	4.757	27.158	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.042</i>	<i>0.187</i>	<i>1.069</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-75-0475B0635-ACS-FL	75	26.46	6.345	27.158	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.042</i>	<i>0.250</i>	<i>1.069</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-75-0475B0635-ACS-HS	75	26.46	6.345	27.158	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.042</i>	<i>0.250</i>	<i>1.069</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-75-0475B0953-AC-N	75	26.46	9.525	27.158	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.042</i>	<i>0.375</i>	<i>1.069</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-75-0318B0318-A2-HS	75	26.46	3.175	27.160	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.069</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-75-0318B0318-3-HS	75	26.46	3.175	27.160	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.069</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-75-0318B0318-A2-CH	75	26.46	3.175	27.160	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.069</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-75-0318B0318-3-CH	75	26.46	3.175	27.160	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.069</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-75-0318B0476-3-HS	75	26.46	4.757	27.160	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.187</i>	<i>1.069</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-75-0318B0476-A2-HS	75	26.46	4.757	27.160	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.187</i>	<i>1.069</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-75-0318B0635-3-CH	75	26.46	6.350	27.160	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.250</i>	<i>1.069</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-75-0318B0635-A2-CH	75	26.46	6.350	27.160	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.250</i>	<i>1.069</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-80-0318B0318-3-HS	80	28.22	3.175	28.923	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.125</i>	<i>1.139</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-80-0318B0318-3-CH	80	28.22	3.175	28.923	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.125</i>	<i>1.139</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-80-0318B0318-A2-CH	80	28.22	3.175	28.923	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.125</i>	<i>1.139</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-80-0318B0318-A2-HS	80	28.22	3.175	28.923	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.125</i>	<i>1.139</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-80-0475B0476-ACS-HS	80	28.22	4.757	28.923	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-80-0318B0476-3-HS	80	28.22	4.757	28.923	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-80-0318B0476-A2-HS	80	28.22	4.757	28.923	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-80-0475B0476-ACS-FL	80	28.22	4.757	28.923	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-80-0475B0476-A2-HS	80	28.22	4.762	28.923	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-80-0318B0476-3-CH	80	28.22	4.762	28.923	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-80-0318B0476-A2-CH	80	28.22	4.762	28.923	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-80-0475B0476-3-HS	80	28.22	4.762	28.923	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.187</i>	<i>1.139</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-80-0475B0635-ACS-FL	80	28.22	6.345	28.923	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-80-0475B0635-ACS-HS	80	28.22	6.345	28.923	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-80-0475B0635-3-HS	80	28.22	6.350	28.923	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-80-0318B0635-A2-HS	80	28.22	6.350	28.923	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-80-0318B0635-A2-CH	80	28.22	6.350	28.923	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-80-0318B0635-3-HS	80	28.22	6.350	28.923	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-80-0475B0635-A2-HS	80	28.22	6.350	28.923	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-80-0318B0635-3-CH	80	28.22	6.350	28.923	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.111</i>	<i>0.250</i>	<i>1.139</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-80-0475B0953-AC-N	80	28.22	9.525	28.923	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.111</i>	<i>0.375</i>	<i>1.139</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-84-0475B0476-ACS-HS	84	29.63	4.757	30.333	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.167</i>	<i>0.187</i>	<i>1.194</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-84-0475B0476-ACS-FL	84	29.63	4.757	30.333	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.167</i>	<i>0.187</i>	<i>1.194</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-84-0475B0635-ACS-HS	84	29.63	6.345	30.333	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.167</i>	<i>0.250</i>	<i>1.194</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-84-0475B0635-ACS-FL	84	29.63	6.345	30.333	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.167</i>	<i>0.250</i>	<i>1.194</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-84-0475B0953-AC-N	84	29.63	9.525	30.333	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.167</i>	<i>0.375</i>	<i>1.194</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-84-0318B0476-3-CH	84	29.63	4.762	30.335	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.167</i>	<i>0.187</i>	<i>1.194</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-84-0318B0476-A2-CH	84	29.63	4.762	30.335	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.167</i>	<i>0.187</i>	<i>1.194</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-85-0318B0476-A2-HS	85	29.99	4.757	30.688	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.181</i>	<i>0.187</i>	<i>1.208</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-85-0318B0476-3-HS	85	29.99	4.757	30.688	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.181</i>	<i>0.187</i>	<i>1.208</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-90-0318B0318-A2-CH	90	31.75	3.175	32.451	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.278</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-90-0318B0318-3-CH	90	31.75	3.175	32.451	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.278</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-90-0318B0318-3-HS	90	31.75	3.175	32.451	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.278</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-90-0318B0318-A2-HS	90	31.75	3.175	32.451	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.278</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-90-0318B0476-A2-HS	90	31.75	4.757	32.451	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.278</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-90-0318B0476-3-HS	90	31.75	4.757	32.451	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.278</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-90-0475B0476-3-HS	90	31.75	4.762	32.451	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.278</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-90-0318B0476-3-CH	90	31.75	4.762	32.451	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.278</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-90-0475B0476-A2-HS	90	31.75	4.762	32.451	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.278</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-90-0318B0476-A2-CH	90	31.75	4.762	32.451	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.278</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-90-0318B0635-A2-HS	90	31.75	6.350	32.451	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.278</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-90-0318B0635-A2-CH	90	31.75	6.350	32.451	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.278</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-90-0475B0635-3-HS	90	31.75	6.350	32.451	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.278</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-90-0318B0635-3-CH	90	31.75	6.350	32.451	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.278</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-90-0475B0635-A2-HS	90	31.75	6.350	32.451	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.278</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-90-0318B0635-3-HS	90	31.75	6.350	32.451	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.278</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-96-0318B0318-3-HS	96	33.87	3.175	34.567	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.333</i>	<i>0.125</i>	<i>1.361</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-96-0318B0318-3-CH	96	33.87	3.175	34.567	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.333</i>	<i>0.125</i>	<i>1.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-96-0318B0318-A2-CH	96	33.87	3.175	34.567	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.333</i>	<i>0.125</i>	<i>1.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-96-0318B0318-A2-HS	96	33.87	3.175	34.567	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.333</i>	<i>0.125</i>	<i>1.361</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-96-0475B0476-ACS-FL	96	33.87	4.757	34.567	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-96-0318B0476-A2-HS	96	33.87	4.757	34.567	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-96-0318B0476-3-HS	96	33.87	4.757	34.567	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-96-0475B0476-ACS-HS	96	33.87	4.757	34.567	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-96-0475B0476-A2-HS	96	33.87	4.762	34.567	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-96-0318B0476-A2-CH	96	33.87	4.762	34.567	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-96-0318B0476-3-CH	96	33.87	4.762	34.567	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-96-0475B0476-3-HS	96	33.87	4.762	34.567	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.333</i>	<i>0.187</i>	<i>1.361</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-96-0475B0635-ACS-FL	96	33.87	6.345	34.567	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.333</i>	<i>0.250</i>	<i>1.361</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-96-0475B0635-ACS-HS	96	33.87	6.345	34.567	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.333</i>	<i>0.250</i>	<i>1.361</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-96-0318B0635-A2-HS	96	33.87	6.350	34.567	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.333</i>	<i>0.250</i>	<i>1.361</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-96-0475B0635-3-HS	96	33.87	6.350	34.567	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.333</i>	<i>0.250</i>	<i>1.361</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-96-0475B0635-A2-HS	96	33.87	6.350	34.567	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.333</i>	<i>0.250</i>	<i>1.361</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-96-0318B0635-3-HS	96	33.87	6.350	34.567	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.333</i>	<i>0.250</i>	<i>1.361</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-96-0475B0953-AC-N	96	33.87	9.525	34.567	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.333</i>	<i>0.375</i>	<i>1.361</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-99-0475B0476-ACS-HS	99	34.93	4.757	35.626	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.187</i>	<i>1.403</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-99-0475B0476-ACS-FL	99	34.93	4.757	35.626	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.187</i>	<i>1.403</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-99-0475B0635-ACS-FL	99	34.93	6.345	35.626	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.403</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-99-0475B0635-ACS-HS	99	34.93	6.345	35.626	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.403</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-99-0318B0635-A2-CH	99	34.93	6.350	35.626	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.403</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-99-0318B0635-3-CH	99	34.93	6.350	35.626	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.403</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-99-0475B0953-AC-N	99	34.93	9.525	35.626	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.375</i>	<i>0.375</i>	<i>1.403</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-100-0475B0476-ACS-FL	100	35.28	4.757	35.977	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-100-0475B0476-ACS-HS	100	35.28	4.757	35.977	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-100-0475B0635-ACS-HS	100	35.28	6.345	35.977	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.389</i>	<i>0.250</i>	<i>1.416</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-100-0475B0635-ACS-FL	100	35.28	6.345	35.977	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.389</i>	<i>0.250</i>	<i>1.416</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-100-0475B0953-AC-N	100	35.28	9.525	35.977	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.389</i>	<i>0.375</i>	<i>1.416</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-100-0318B0318-3-HS	100	35.28	3.175	35.979	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.389</i>	<i>0.125</i>	<i>1.416</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-100-0318B0318-A2-CH	100	35.28	3.175	35.979	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.389</i>	<i>0.125</i>	<i>1.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-100-0318B0318-A2-HS	100	35.28	3.175	35.979	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.389</i>	<i>0.125</i>	<i>1.416</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-100-0318B0476-A2-HS	100	35.28	4.757	35.979	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-100-0318B0476-3-HS	100	35.28	4.757	35.979	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
GS72-100-0475B0476-A2-HS	100	35.28	4.762	35.979	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-100-0318B0476-3-CH	100	35.28	4.762	35.979	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-100-0475B0476-3-HS	100	35.28	4.762	35.979	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-100-0318B0476-A2-CH	100	35.28	4.762	35.979	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.389</i>	<i>0.187</i>	<i>1.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-100-0475B0635-A2-HS	100	35.28	6.350	35.979	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.389</i>	<i>0.250</i>	<i>1.416</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-100-0318B0635-3-HS	100	35.28	6.350	35.979	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.389</i>	<i>0.250</i>	<i>1.416</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
GS72-100-0475B0635-3-HS	100	35.28	6.350	35.979	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.389</i>	<i>0.250</i>	<i>1.416</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-100-0318B0635-A2-HS	100	35.28	6.350	35.979	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.389</i>	<i>0.250</i>	<i>1.416</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-105-0475B0476-3-HS	105	37.04	4.762	37.742	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.458</i>	<i>0.187</i>	<i>1.486</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-105-0475B0476-A2-HS	105	37.04	4.762	37.742	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.458</i>	<i>0.187</i>	<i>1.486</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-108-0475B0476-ACS-HS	108	38.10	4.757	38.801	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-108-0475B0476-ACS-FL	108	38.10	4.757	38.801	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.528</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-108-0475B0476-3-HS	108	38.10	4.762	38.801	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.528</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-108-0318B0476-A2-CH	108	38.10	4.762	38.801	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-108-0475B0476-A2-HS	108	38.10	4.762	38.801	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.528</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-108-0318B0476-3-CH	108	38.10	4.762	38.801	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.187</i>	<i>1.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-108-0475B0635-ACS-HS	108	38.10	6.345	38.801	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-108-0475B0635-ACS-FL	108	38.10	6.345	38.801	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.528</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-108-0318B0635-A2-CH	108	38.10	6.350	38.801	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-108-0318B0635-3-CH	108	38.10	6.350	38.801	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.250</i>	<i>1.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-108-0475B0953-AC-N	108	38.10	9.525	38.801	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.500</i>	<i>0.375</i>	<i>1.528</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-108-0476B0635-3-HS	108		6.350		4.76	11.11	12.70	6-32/Set Screw	20	303 Stainless Steel
			<i>0.250</i>		<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-108-0476B0635-A2-HS	108		6.350		4.76	11.11	12.70	6-32/Set Screw	20	2024 Aluminium Anodized
			<i>0.250</i>		<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-110-0318B0318-A2-HS	110	38.81	3.175	39.507	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.528</i>	<i>0.125</i>	<i>1.555</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-110-0318B0318-3-CH	110	38.81	3.175	39.507	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.528</i>	<i>0.125</i>	<i>1.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-110-0318B0318-A2-CH	110	38.81	3.175	39.507	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.528</i>	<i>0.125</i>	<i>1.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-110-0318B0318-3-HS	110	38.81	3.175	39.507	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.528</i>	<i>0.125</i>	<i>1.555</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-110-0318B0476-3-HS	110	38.81	4.757	39.507	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.528</i>	<i>0.187</i>	<i>1.555</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-110-0318B0476-A2-HS	110	38.81	4.757	39.507	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.528</i>	<i>0.187</i>	<i>1.555</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-110-0475B0476-A2-HS	110	38.81	4.762	39.507	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.528</i>	<i>0.187</i>	<i>1.555</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-110-0475B0476-3-HS	110	38.81	4.762	39.507	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.528</i>	<i>0.187</i>	<i>1.555</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-110-0318B0476-A2-CH	110	38.81	4.762	39.507	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.528</i>	<i>0.187</i>	<i>1.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-110-0318B0476-3-CH	110	38.81	4.762	39.507	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.528</i>	<i>0.187</i>	<i>1.555</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-110-0318B0635-A2-HS	110	38.81	6.350	39.507	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.528</i>	<i>0.250</i>	<i>1.555</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-110-0475B0635-3-HS	110	38.81	6.350	39.507	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.528</i>	<i>0.250</i>	<i>1.555</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-110-0475B0635-A2-HS	110	38.81	6.350	39.507	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.528</i>	<i>0.250</i>	<i>1.555</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-120-0475B0476-ACS-HS	120	42.33	4.757	43.033	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-120-0475B0476-ACS-FL	120	42.33	4.757	43.033	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-120-0475B0635-ACS-HS	120	42.33	6.345	43.033	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.667</i>	<i>0.250</i>	<i>1.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-120-0475B0635-ACS-FL	120	42.33	6.345	43.033	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.667</i>	<i>0.250</i>	<i>1.694</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-120-0475B0953-AC-N	120	42.33	9.525	43.033	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.667</i>	<i>0.375</i>	<i>1.694</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-120-0318B0318-A2-CH	120	42.33	3.175	43.035	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.125</i>	<i>1.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-120-0318B0318-3-HS	120	42.33	3.175	43.035	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.125</i>	<i>1.694</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-120-0318B0318-A2-HS	120	42.33	3.175	43.035	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.125</i>	<i>1.694</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-120-0318B0318-3-CH	120	42.33	3.175	43.035	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.125</i>	<i>1.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-120-0318B0476-A2-HS	120	42.33	4.757	43.035	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-120-0318B0476-3-HS	120	42.33	4.757	43.035	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
GS72-120-0475B0476-A2-HS	120	42.33	4.762	43.035	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-120-0318B0476-A2-CH	120	42.33	4.762	43.035	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-120-0475B0476-3-HS	120	42.33	4.762	43.035	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-120-0318B0476-3-CH	120	42.33	4.762	43.035	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.694</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-120-0318B0635-3-HS	120	42.33	6.350	43.035	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.250</i>	<i>1.694</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-120-0475B0635-A2-HS	120	42.33	6.350	43.035	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.250</i>	<i>1.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-120-0475B0635-3-HS	120	42.33	6.350	43.035	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.250</i>	<i>1.694</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-120-0318B0635-A2-HS	120	42.33	6.350	43.035	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.250</i>	<i>1.694</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-126-0475B0476-ACS-FL	126	44.45	4.757	45.151	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.778</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-126-0318B0476-3-HS	126	44.45	4.757	45.151	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.778</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-126-0318B0476-A2-HS	126	44.45	4.757	45.151	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.778</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-126-0475B0476-ACS-HS	126	44.45	4.757	45.151	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-126-0318B0476-A2-CH	126	44.45	4.762	45.151	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-126-0318B0476-3-CH	126	44.45	4.762	45.151	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.187</i>	<i>1.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-126-0475B0635-ACS-HS	126	44.45	6.345	45.151	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-126-0475B0635-ACS-FL	126	44.45	6.345	45.151	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.778</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
GS72-126-0475B0635-3-HS	126	44.45	6.350	45.151	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-126-0318B0635-3-CH	126	44.45	6.350	45.151	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-126-0318B0635-A2-CH	126	44.45	6.350	45.151	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-126-0475B0635-A2-HS	126	44.45	6.350	45.151	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.250</i>	<i>1.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-126-0475B0953-AC-N	126	44.45	9.525	45.151	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.750</i>	<i>0.375</i>	<i>1.778</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-127-0475B0476-ACS-FL	127	44.80	4.757	45.502	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.764</i>	<i>0.187</i>	<i>1.791</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-127-0475B0635-ACS-FL	127	44.80	6.345	45.502	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.764</i>	<i>0.250</i>	<i>1.791</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-127-0475B0635-ACS-HS	127	44.80	6.345	45.502	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.764</i>	<i>0.250</i>	<i>1.791</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-127-0475B0953-AC-N	127	44.80	9.525	45.502	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.764</i>	<i>0.375</i>	<i>1.791</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-130-0318B0318-3-CH	130	45.86	3.175	46.563	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.806</i>	<i>0.125</i>	<i>1.833</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-130-0318B0318-A2-HS	130	45.86	3.175	46.563	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.806</i>	<i>0.125</i>	<i>1.833</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-130-0318B0318-A2-CH	130	45.86	3.175	46.563	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.806</i>	<i>0.125</i>	<i>1.833</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-130-0318B0318-3-HS	130	45.86	3.175	46.563	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.806</i>	<i>0.125</i>	<i>1.833</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-130-0318B0476-A2-CH	130	45.86	4.762	46.563	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.806</i>	<i>0.187</i>	<i>1.833</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-130-0318B0476-3-CH	130	45.86	4.762	46.563	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.806</i>	<i>0.187</i>	<i>1.833</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-130-0318B0635-3-HS	130	45.86	6.350	46.563	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.806</i>	<i>0.250</i>	<i>1.833</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-130-0318B0635-A2-HS	130	45.86	6.350	46.563	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.806</i>	<i>0.250</i>	<i>1.833</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-130-0475B0635-A2-HS	130	45.86	6.350	46.563	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.806</i>	<i>0.250</i>	<i>1.833</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-130-0475B0635-3-HS	130	45.86	6.350	46.563	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.806</i>	<i>0.250</i>	<i>1.833</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-132-0475B0476-ACS-FL	132	46.57	4.757	47.267	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.833</i>	<i>0.187</i>	<i>1.861</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-132-0475B0476-ACS-HS	132	46.57	4.757	47.267	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.833</i>	<i>0.187</i>	<i>1.861</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-132-0475B0635-ACS-FL	132	46.57	6.345	47.267	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.833</i>	<i>0.250</i>	<i>1.861</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-132-0475B0635-ACS-HS	132	46.57	6.345	47.267	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.833</i>	<i>0.250</i>	<i>1.861</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-132-0475B0953-AC-N	132	46.57	9.525	47.267	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.833</i>	<i>0.375</i>	<i>1.861</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-135-0475B0476-ACS-HS	135	47.63	4.757	48.326	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.903</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-135-0475B0476-ACS-FL	135	47.63	4.757	48.326	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.903</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-135-0475B0635-ACS-FL	135	47.63	6.345	48.326	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.903</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-135-0475B0635-ACS-HS	135	47.63	6.345	48.326	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.903</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-135-0475B0953-AC-N	135	47.63	9.525	48.326	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.875</i>	<i>0.375</i>	<i>1.903</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-136-0475B0635-3-HS	136	47.98	6.350	48.679	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.889</i>	<i>0.250</i>	<i>1.916</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-136-0475B0635-A2-HS	136	47.98	6.350	48.679	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.889</i>	<i>0.250</i>	<i>1.916</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-140-0318B0318-3-CH	140	49.39	3.175	50.089	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.944</i>	<i>0.125</i>	<i>1.972</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS72-140-0318B0318-A2-CH	140	49.39	3.175	50.089	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.944</i>	<i>0.125</i>	<i>1.972</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-140-0318B0476-A2-HS	140	49.39	4.757	50.089	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-140-0475B0476-ACS-HS	140	49.39	4.757	50.089	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-140-0475B0476-ACS-FL	140	49.39	4.757	50.089	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-140-0318B0476-3-HS	140	49.39	4.757	50.089	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-140-0475B0476-A2-HS	140	49.39	4.762	50.089	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-140-0475B0476-3-HS	140	49.39	4.762	50.089	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-140-0318B0476-3-CH	140	49.39	4.762	50.089	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-140-0318B0476-A2-CH	140	49.39	4.762	50.089	3.18	10.32	6.35	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.944</i>	<i>0.187</i>	<i>1.972</i>	<i>0.125</i>	<i>0.406</i>	<i>0.250</i>			
# GS72-140-0475B0635-ACS-FL	140	49.39	6.345	50.089	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>1.944</i>	<i>0.250</i>	<i>1.972</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-140-0475B0635-ACS-HS	140	49.39	6.345	50.089	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>1.944</i>	<i>0.250</i>	<i>1.972</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-140-0318B0635-A2-HS	140	49.39	6.350	50.089	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.944</i>	<i>0.250</i>	<i>1.972</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-140-0318B0635-3-HS	140	49.39	6.350	50.089	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.944</i>	<i>0.250</i>	<i>1.972</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-140-0475B0635-A2-HS	140	49.39	6.350	50.089	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.944</i>	<i>0.250</i>	<i>1.972</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-140-0475B0635-3-HS	140	49.39	6.350	50.089	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.944</i>	<i>0.250</i>	<i>1.972</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-140-0475B0953-AC-N	140	49.39	9.525	50.089	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>1.944</i>	<i>0.375</i>	<i>1.972</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-144-0475B0476-ACS-HS	144	50.80	4.757	51.501	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.028</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-144-0475B0476-ACS-FL	144	50.80	4.757	51.501	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.028</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-144-0318B0476-A2-HS	144	50.80	4.757	51.501	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.028</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-144-0318B0476-3-HS	144	50.80	4.757	51.501	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.028</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-144-0475B0476-3-HS	144	50.80	4.762	51.501	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.028</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-144-0475B0476-A2-HS	144	50.80	4.762	51.501	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.000</i>	<i>0.187</i>	<i>2.028</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-144-0475B0635-ACS-FL	144	50.80	6.345	51.501	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.028</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-144-0475B0635-ACS-HS	144	50.80	6.345	51.501	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.028</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-144-0318B0635-3-CH	144	50.80	6.350	51.501	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-144-0318B0635-A2-CH	144	50.80	6.350	51.501	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.000</i>	<i>0.250</i>	<i>2.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-144-0475B0953-AC-N	144	50.80	9.525	51.501	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.000</i>	<i>0.375</i>	<i>2.028</i>	<i>0.187</i>	<i>0.187</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-144-0476B0635-A2-HS	144		6.350		4.76	11.11	12.70	6-32/Set Screw	20	2024 Aluminium Anodized
			<i>0.250</i>		<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-144-0476B0635-3-HS	144		6.350		4.76	11.11	12.70	6-32/Set Screw	20	303 Stainless Steel
			<i>0.250</i>		<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-150-0318B0318-3-HS	150	52.92	3.175	53.617	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.083</i>	<i>0.125</i>	<i>2.111</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-150-0318B0318-A2-HS	150	52.92	3.175	53.617	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.083</i>	<i>0.125</i>	<i>2.111</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS72-150-0318B0476-3-HS	150	52.92	4.757	53.617	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.083</i>	<i>0.187</i>	<i>2.111</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-150-0475B0476-ACS-FL	150	52.92	4.757	53.617	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.083</i>	<i>0.187</i>	<i>2.111</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-150-0475B0476-ACS-HS	150	52.92	4.757	53.617	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.083</i>	<i>0.187</i>	<i>2.111</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-150-0318B0476-A2-HS	150	52.92	4.757	53.617	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.083</i>	<i>0.187</i>	<i>2.111</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-150-0475B0635-ACS-FL	150	52.92	6.345	53.617	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.083</i>	<i>0.250</i>	<i>2.111</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-150-0475B0635-ACS-HS	150	52.92	6.345	53.617	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.083</i>	<i>0.250</i>	<i>2.111</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-150-0318B0635-A2-HS	150	52.92	6.350	53.617	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.083</i>	<i>0.250</i>	<i>2.111</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-150-0475B0635-3-HS	150	52.92	6.350	53.617	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.083</i>	<i>0.250</i>	<i>2.111</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-150-0475B0635-A2-HS	150	52.92	6.350	53.617	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.083</i>	<i>0.250</i>	<i>2.111</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-150-0318B0635-3-HS	150	52.92	6.350	53.617	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.083</i>	<i>0.250</i>	<i>2.111</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-150-0475B0953-AC-N	150	52.92	9.525	53.617	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.083</i>	<i>0.375</i>	<i>2.111</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-160-0475B0476-ACS-HS	160	56.44	4.757	57.145	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.222</i>	<i>0.187</i>	<i>2.250</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-160-0475B0476-ACS-FL	160	56.44	4.757	57.145	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.222</i>	<i>0.187</i>	<i>2.250</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-160-0475B0476-3-HS	160	56.44	4.762	57.145	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.222</i>	<i>0.187</i>	<i>2.250</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-160-0475B0476-A2-HS	160	56.44	4.762	57.145	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.222</i>	<i>0.187</i>	<i>2.250</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-160-0475B0635-ACS-HS	160	56.44	6.345	57.145	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.222</i>	<i>0.250</i>	<i>2.250</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-160-0475B0635-ACS-FL	160	56.44	6.345	57.145	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.222</i>	<i>0.250</i>	<i>2.250</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-160-0318B0635-3-HS	160	56.44	6.350	57.145	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.222</i>	<i>0.250</i>	<i>2.250</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-160-0475B0635-3-HS	160	56.44	6.350	57.145	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.222</i>	<i>0.250</i>	<i>2.250</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-160-0318B0635-A2-HS	160	56.44	6.350	57.145	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.222</i>	<i>0.250</i>	<i>2.250</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-160-0475B0635-A2-HS	160	56.44	6.350	57.145	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.222</i>	<i>0.250</i>	<i>2.250</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-160-0475B0953-AC-N	160	56.44	9.525	57.145	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.222</i>	<i>0.375</i>	<i>2.250</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-162-0318B0476-3-HS	162	57.15	4.757	57.851	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.250</i>	<i>0.187</i>	<i>2.278</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-162-0318B0476-A2-HS	162	57.15	4.757	57.851	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.250</i>	<i>0.187</i>	<i>2.278</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-170-0318B0635-A2-HS	170	59.97	6.350	60.673	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.361</i>	<i>0.250</i>	<i>2.389</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-170-0318B0635-3-HS	170	59.97	6.350	60.673	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.361</i>	<i>0.250</i>	<i>2.389</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-180-0318B0476-3-HS	180	63.50	4.757	64.201	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.528</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-180-0475B0476-ACS-HS	180	63.50	4.757	64.201	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			
# GS72-180-0318B0476-A2-HS	180	63.50	4.757	64.201	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.528</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-180-0475B0476-ACS-FL	180	63.50	4.757	64.201	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.528</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-180-0475B0476-A2-HS	180	63.50	4.762	64.201	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.528</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-180-0475B0476-3-HS	180	63.50	4.762	64.201	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.187</i>	<i>2.528</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-180-0475B0635-ACS-HS	180	63.50	6.345	64.201	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-180-0475B0635-ACS-FL	180	63.50	6.345	64.201	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-180-0318B0635-A2-HS	180	63.50	6.350	64.201	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-180-0475B0635-3-HS	180	63.50	6.350	64.201	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-180-0318B0635-A2-CH	180	63.50	6.350	64.201	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-180-0318B0635-3-HS	180	63.50	6.350	64.201	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-180-0318B0635-3-CH	180	63.50	6.350	64.201	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-180-0475B0635-A2-HS	180	63.50	6.350	64.201	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.500</i>	<i>0.250</i>	<i>2.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-180-0475B0953-AC-N	180	63.50	9.525	64.201	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.500</i>	<i>0.375</i>	<i>2.528</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-198-0475B0476-ACS-HS	198	69.85	4.757	70.551	4.75	11.10	11.13	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.438</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-198-0475B0476-ACS-FL	198	69.85	4.757	70.551	4.75	11.50	11.13	6.75 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.778</i>	<i>0.187</i>	<i>0.453</i>	<i>0.438</i>			
# GS72-198-0318B0476-3-HS	198	69.85	4.757	70.551	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.778</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-198-0318B0476-A2-HS	198	69.85	4.757	70.551	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.750</i>	<i>0.187</i>	<i>2.778</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-198-0475B0635-ACS-HS	198	69.85	6.345	70.551	4.75	11.10	13.46	6.35 / Pin Hub - Set Screw	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.778</i>	<i>0.187</i>	<i>0.437</i>	<i>0.530</i>			
# GS72-198-0475B0635-ACS-FL	198	69.85	6.345	70.551	4.75	12.27	13.46	7.52 / Fairloc Hub	20	Acetal - Stainless hub / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.778</i>	<i>0.187</i>	<i>0.483</i>	<i>0.530</i>			
# GS72-198-0318B0635-3-CH	198	69.85	6.350	70.551	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-198-0318B0635-3-HS	198	69.85	6.350	70.551	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.778</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-198-0318B0635-A2-CH	198	69.85	6.350	70.551	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.778</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-198-0318B0635-A2-HS	198	69.85	6.350	70.551	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.750</i>	<i>0.250</i>	<i>2.778</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-198-0475B0953-AC-N	198	69.85	9.525	70.551	4.75	4.75	Hubless	0.00 / None	20	Acetal / AGMA Q10
		<i>2.750</i>	<i>0.375</i>	<i>2.778</i>	<i>0.187</i>	<i>0.187</i>				
# GS72-216-0318B0476-3-HS	216	76.20	4.757	76.901	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.028</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-216-0318B0476-A2-HS	216	76.20	4.757	76.901	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.028</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS72-216-0475B0476-A2-HS	216	76.20	4.762	76.901	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.028</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-216-0475B0476-3-HS	216	76.20	4.762	76.901	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.187</i>	<i>3.028</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-216-0318B0635-3-CH	216	76.20	6.350	76.901	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-216-0318B0635-A2-CH	216	76.20	6.350	76.901	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.028</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-216-0318B0635-A2-HS	216	76.20	6.350	76.901	3.18	9.53	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.028</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-216-0318B0635-3-HS	216	76.20	6.350	76.901	3.18	9.53	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.000</i>	<i>0.250</i>	<i>3.028</i>	<i>0.125</i>	<i>0.375</i>	<i>0.500</i>			
# GS72-234-0475B0476-A2-HS	234	82.55	4.762	83.251	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.250</i>	<i>0.187</i>	<i>3.278</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-234-0475B0476-3-HS	234	82.55	4.762	83.251	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.250</i>	<i>0.187</i>	<i>3.278</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-252-0475B0635-3-HS	252	88.90	6.350	89.601	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-252-0475B0635-A2-HS	252	88.90	6.350	89.601	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.500</i>	<i>0.250</i>	<i>3.528</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-270-0475B0476-3-HS	270	95.25	4.762	95.951	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>3.750</i>	<i>0.187</i>	<i>3.778</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-270-0475B0476-A2-HS	270	95.25	4.762	95.951	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>3.750</i>	<i>0.187</i>	<i>3.778</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-297-0318B0635-A2-CH	297	104.78	6.350	105.476	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.125</i>	<i>0.250</i>	<i>4.153</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 72 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS72-297-0318B0635-3-CH	297	104.78	6.350	105.476	3.18	10.32	7.93	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>4.125</i>	<i>0.250</i>	<i>4.153</i>	<i>0.125</i>	<i>0.406</i>	<i>0.312</i>			
# GS72-300-0475B0476-A2-HS	300	105.83	4.762	106.535	4.75	10.30	9.53	5.55 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.167</i>	<i>0.187</i>	<i>4.194</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-300-0475B0476-3-HS	300	105.83	4.762	106.535	4.75	10.30	9.53	5.55 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>4.167</i>	<i>0.187</i>	<i>4.194</i>	<i>0.187</i>	<i>0.406</i>	<i>0.375</i>			
# GS72-300-0475B0635-3-HS	300	105.83	6.350	106.535	4.75	11.10	12.70	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>4.167</i>	<i>0.250</i>	<i>4.194</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			
# GS72-300-0475B0635-A2-HS	300	105.83	6.350	106.535	4.75	11.10	12.70	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>4.167</i>	<i>0.250</i>	<i>4.194</i>	<i>0.187</i>	<i>0.437</i>	<i>0.500</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

