




MBA

Gears - Spur - 96 Pitch

Examples shown for basic dimensions. Individual gears may vary in characteristics.



PCD = No. of Teeth x 0.265mm (1/96 in.). 20 Degree Pressure Angle. 2024 aluminium and 303 stainless steel.
Metallic.

Fairloc Hub Type require controlled shaft tolerances between 0.0025 and 0.0203 mm Clearance.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-24-0238B0318-3-HS	24	6.35	3.175	6.876	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-24-0318B0318-A2-HS	24	6.35	3.175	6.876	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time
E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-24-0238B0318-A2-HS	24	6.35	3.175	6.876	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-24-0318B0318-3-HS	24	6.35	3.175	6.876	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-24-0159B0318-3-HS	24	6.35	3.175	6.876	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-24-0159B0318-A2-HS	24	6.35	3.175	6.876	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-24-0318B0318-3-CH	24	6.35	3.175	6.876	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-24-0318B0318-A2-CH	24	6.35	3.175	6.876	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.250</i>	<i>0.125</i>	<i>0.271</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-26-0238B0318-A2-HS	26	6.88	3.175	7.404	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.271</i>	<i>0.125</i>	<i>0.291</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-26-0238B0318-3-HS	26	6.88	3.175	7.404	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.271</i>	<i>0.125</i>	<i>0.291</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-28-0318B0318-3-CH	28	7.41	3.175	7.935	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.292</i>	<i>0.125</i>	<i>0.312</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-28-0318B0318-A2-HS	28	7.41	3.175	7.935	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.292</i>	<i>0.125</i>	<i>0.312</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-28-0318B0318-A2-CH	28	7.41	3.175	7.935	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.292</i>	<i>0.125</i>	<i>0.312</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-28-0238B0318-3-HS	28	7.41	3.175	7.935	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.292</i>	<i>0.125</i>	<i>0.312</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-28-0238B0318-A2-HS	28	7.41	3.175	7.935	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.292</i>	<i>0.125</i>	<i>0.312</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-28-0318B0318-3-HS	28	7.41	3.175	7.935	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.292</i>	<i>0.125</i>	<i>0.312</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-30-0318B0318-3-CH	30	7.94	3.175	8.464	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-30-0238B0318-3-HS	30	7.94	3.175	8.464	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-30-0159B0318-A2-HS	30	7.94	3.175	8.464	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-30-0318B0318-A2-HS	30	7.94	3.175	8.464	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-30-0159B0318-3-HS	30	7.94	3.175	8.464	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-30-0318B0318-A2-CH	30	7.94	3.175	8.464	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-30-0238B0318-A2-HS	30	7.94	3.175	8.464	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-30-0318B0318-3-HS	30	7.94	3.175	8.464	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.313</i>	<i>0.125</i>	<i>0.333</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-30-0318B0476-A2-HS	30	7.94	4.757	8.464	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.313</i>	<i>0.187</i>	<i>0.333</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-30-0318B0476-3-HS	30	7.94	4.757	8.464	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.313</i>	<i>0.187</i>	<i>0.333</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-32-0318B0318-3-HS	32	8.47	3.175	8.992	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.354</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-32-0318B0318-3-CH	32	8.47	3.175	8.992	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.354</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-32-0318B0318-A2-CH	32	8.47	3.175	8.992	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.354</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-32-0318B0318-A2-HS	32	8.47	3.175	8.992	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.354</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-32-0238B0318-3-HS	32	8.47	3.175	8.992	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.354</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-32-0238B0318-A2-HS	32	8.47	3.175	8.992	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.125</i>	<i>0.354</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-32-0318B0476-A2-HS	32	8.47	4.757	8.992	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.333</i>	<i>0.187</i>	<i>0.354</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-32-0318B0476-3-HS	32	8.47	4.757	8.992	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.333</i>	<i>0.187</i>	<i>0.354</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-34-0318B0318-A2-CH	34	9.00	3.175	9.523	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.354</i>	<i>0.125</i>	<i>0.375</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-34-0318B0318-3-CH	34	9.00	3.175	9.523	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.354</i>	<i>0.125</i>	<i>0.375</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-34-0318B0476-3-HS	34	9.00	4.757	9.523	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.354</i>	<i>0.187</i>	<i>0.375</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-34-0318B0476-A2-HS	34	9.00	4.757	9.523	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.354</i>	<i>0.187</i>	<i>0.375</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-35-0159B0318-3-HS	35	9.26	3.175	9.787	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.365</i>	<i>0.125</i>	<i>0.385</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-35-0159B0318-A2-HS	35	9.26	3.175	9.787	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.365</i>	<i>0.125</i>	<i>0.385</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-35-0318B0476-3-HS	35	9.26	4.757	9.787	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.365</i>	<i>0.187</i>	<i>0.385</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-35-0318B0476-A2-HS	35	9.26	4.757	9.787	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.365</i>	<i>0.187</i>	<i>0.385</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-36-0318B0318-3-CH	36	9.53	3.175	10.051	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-36-0238B0318-3-HS	36	9.53	3.175	10.051	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-36-0318B0318-3-HS	36	9.53	3.175	10.051	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-36-0318B0318-A2-CH	36	9.53	3.175	10.051	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-36-0159B0318-3-HS	36	9.53	3.175	10.051	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-36-0238B0318-A2-HS	36	9.53	3.175	10.051	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-36-0318B0318-A2-HS	36	9.53	3.175	10.051	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-36-0159B0318-A2-HS	36	9.53	3.175	10.051	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.375</i>	<i>0.125</i>	<i>0.396</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-36-0318B0476-A2-HS	36	9.53	4.757	10.051	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.375</i>	<i>0.187</i>	<i>0.396</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-36-0318B0476-3-HS	36	9.53	4.757	10.051	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.375</i>	<i>0.187</i>	<i>0.396</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-38-0159B0318-A2-HS	38	10.05	3.175	10.579	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.396</i>	<i>0.125</i>	<i>0.416</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-38-0318B0318-3-HS	38	10.05	3.175	10.579	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.396</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-38-0318B0318-A2-HS	38	10.05	3.175	10.579	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.396</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-38-0318B0318-3-CH	38	10.05	3.175	10.579	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.396</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-38-0159B0318-3-HS	38	10.05	3.175	10.579	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.396</i>	<i>0.125</i>	<i>0.416</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-38-0318B0318-A2-CH	38	10.05	3.175	10.579	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.396</i>	<i>0.125</i>	<i>0.416</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-39-0318B0318-3-HS	39	10.32	3.175	10.846	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.406</i>	<i>0.125</i>	<i>0.427</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-39-0318B0318-A2-HS	39	10.32	3.175	10.846	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.406</i>	<i>0.125</i>	<i>0.427</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-39-0318B0476-A2-HS	39	10.32	4.757	10.846	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.406</i>	<i>0.187</i>	<i>0.427</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-39-0318B0476-3-HS	39	10.32	4.757	10.846	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.406</i>	<i>0.187</i>	<i>0.427</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-40-0159B0318-A2-HS	40	10.58	3.175	11.110	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-40-0318B0318-3-CH	40	10.58	3.175	11.110	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-40-0238B0318-A2-HS	40	10.58	3.175	11.110	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-40-0318B0318-A2-CH	40	10.58	3.175	11.110	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-40-0238B0318-3-HS	40	10.58	3.175	11.110	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-40-0318B0318-A2-HS	40	10.58	3.175	11.110	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-40-0159B0318-3-HS	40	10.58	3.175	11.110	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-40-0318B0318-3-HS	40	10.58	3.175	11.110	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.125</i>	<i>0.437</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-40-0318B0476-3-HS	40	10.58	4.757	11.110	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.437</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-40-0318B0476-A2-HS	40	10.58	4.757	11.110	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.417</i>	<i>0.187</i>	<i>0.437</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-41-0318B0476-3-HS	41	10.85	4.757	11.374	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.427</i>	<i>0.187</i>	<i>0.448</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-41-0318B0476-A2-HS	41	10.85	4.757	11.374	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.427</i>	<i>0.187</i>	<i>0.448</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-42-0318B0318-3-HS	42	11.11	3.175	11.638	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.125</i>	<i>0.458</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-42-0318B0318-A2-HS	42	11.11	3.175	11.638	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.437</i>	<i>0.125</i>	<i>0.458</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-42-0238B0318-A2-HS	42	11.11	3.175	11.638	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.437</i>	<i>0.125</i>	<i>0.458</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-42-0318B0318-3-CH	42	11.11	3.175	11.638	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.125</i>	<i>0.458</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-42-0238B0318-3-HS	42	11.11	3.175	11.638	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.125</i>	<i>0.458</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-42-0318B0318-A2-CH	42	11.11	3.175	11.638	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.437</i>	<i>0.125</i>	<i>0.458</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-42-0318B0476-3-HS	42	11.11	4.757	11.638	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.437</i>	<i>0.187</i>	<i>0.458</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-42-0318B0476-A2-HS	42	11.11	4.757	11.638	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.437</i>	<i>0.187</i>	<i>0.458</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-44-0238B0318-A2-HS	44	11.64	3.175	12.167	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.458</i>	<i>0.125</i>	<i>0.479</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-44-0318B0318-A2-CH	44	11.64	3.175	12.167	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.458</i>	<i>0.125</i>	<i>0.479</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-44-0238B0318-3-HS	44	11.64	3.175	12.167	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.458</i>	<i>0.125</i>	<i>0.479</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-44-0318B0318-3-CH	44	11.64	3.175	12.167	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.458</i>	<i>0.125</i>	<i>0.479</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-44-0318B0318-A2-HS	44	11.64	3.175	12.167	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.458</i>	<i>0.125</i>	<i>0.479</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-44-0318B0318-3-HS	44	11.64	3.175	12.167	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.458</i>	<i>0.125</i>	<i>0.479</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-44-0318B0476-3-HS	44	11.64	4.757	12.167	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.458</i>	<i>0.187</i>	<i>0.479</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-44-0318B0476-A2-HS	44	11.64	4.757	12.167	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.458</i>	<i>0.187</i>	<i>0.479</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-45-0159B0318-3-HS	45	11.91	3.175	12.434	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.469</i>	<i>0.125</i>	<i>0.490</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-45-0159B0318-A2-HS	45	11.91	3.175	12.434	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.469</i>	<i>0.125</i>	<i>0.490</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-46-0238B0318-A2-HS	46	12.17	3.175	12.698	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.479</i>	<i>0.125</i>	<i>0.500</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-46-0318B0318-A2-HS	46	12.17	3.175	12.698	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.479</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-46-0238B0318-3-HS	46	12.17	3.175	12.698	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.479</i>	<i>0.125</i>	<i>0.500</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-46-0318B0318-3-CH	46	12.17	3.175	12.698	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.479</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-46-0318B0318-A2-CH	46	12.17	3.175	12.698	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.479</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-46-0318B0318-3-HS	46	12.17	3.175	12.698	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.479</i>	<i>0.125</i>	<i>0.500</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-46-0318B0476-3-HS	46	12.17	4.757	12.698	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.479</i>	<i>0.187</i>	<i>0.500</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-46-0318B0476-A2-HS	46	12.17	4.757	12.698	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.479</i>	<i>0.187</i>	<i>0.500</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-48-0318B0318-A2-HS	48	12.70	3.175	13.226	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.521</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-48-0318B0318-A2-CH	48	12.70	3.175	13.226	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.521</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-48-0238B0318-3-HS	48	12.70	3.175	13.226	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.521</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-48-0318B0318-3-CH	48	12.70	3.175	13.226	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.521</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-48-0318B0318-3-HS	48	12.70	3.175	13.226	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.521</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-48-0238B0318-A2-HS	48	12.70	3.175	13.226	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.125</i>	<i>0.521</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-48-0318B0476-3-HS	48	12.70	4.757	13.226	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.521</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-48-0318B0476-A2-HS	48	12.70	4.757	13.226	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.500</i>	<i>0.187</i>	<i>0.521</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-50-0318B0318-A2-HS	50	13.23	3.175	13.754	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-50-0318B0318-3-HS	50	13.23	3.175	13.754	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-50-0159B0318-3-HS	50	13.23	3.175	13.754	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-50-0238B0318-3-HS	50	13.23	3.175	13.754	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-50-0318B0318-A2-CH	50	13.23	3.175	13.754	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-50-0159B0318-A2-HS	50	13.23	3.175	13.754	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-50-0238B0318-A2-HS	50	13.23	3.175	13.754	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-50-0318B0318-3-CH	50	13.23	3.175	13.754	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.521</i>	<i>0.125</i>	<i>0.541</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-52-0159B0318-A2-HS	52	13.76	3.175	14.285	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.542</i>	<i>0.125</i>	<i>0.562</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-52-0159B0318-3-HS	52	13.76	3.175	14.285	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.542</i>	<i>0.125</i>	<i>0.562</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-52-0318B0635-A2-HS	52	13.76	6.345	14.285	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.542</i>	<i>0.250</i>	<i>0.562</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-52-0318B0635-3-HS	52	13.76	6.345	14.285	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.542</i>	<i>0.250</i>	<i>0.562</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-54-0159B0318-A2-HS	54	14.29	3.175	14.814	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-54-0238B0318-3-HS	54	14.29	3.175	14.814	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-54-0318B0318-A2-HS	54	14.29	3.175	14.814	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-54-0318B0318-A2-CH	54	14.29	3.175	14.814	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-54-0318B0318-3-CH	54	14.29	3.175	14.814	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-54-0159B0318-3-HS	54	14.29	3.175	14.814	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-54-0318B0318-3-HS	54	14.29	3.175	14.814	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-54-0238B0318-A2-HS	54	14.29	3.175	14.814	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.125</i>	<i>0.583</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-54-0318B0635-A2-HS	54	14.29	6.345	14.814	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.583</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-54-0318B0635-3-HS	54	14.29	6.345	14.814	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.563</i>	<i>0.250</i>	<i>0.583</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-55-0159B0318-A2-HS	55	14.55	3.175	15.078	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.573</i>	<i>0.125</i>	<i>0.594</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-55-0159B0318-3-HS	55	14.55	3.175	15.078	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.573</i>	<i>0.125</i>	<i>0.594</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-56-0159B0318-3-HS	56	14.82	3.175	15.342	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-56-0318B0318-A2-CH	56	14.82	3.175	15.342	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-56-0159B0318-A2-HS	56	14.82	3.175	15.342	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-56-0318B0318-3-HS	56	14.82	3.175	15.342	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-56-0238B0318-A2-HS	56	14.82	3.175	15.342	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-56-0318B0318-A2-HS	56	14.82	3.175	15.342	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-56-0318B0318-3-CH	56	14.82	3.175	15.342	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-56-0238B0318-3-HS	56	14.82	3.175	15.342	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.125</i>	<i>0.604</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-56-0318B0476-3-HS	56	14.82	4.757	15.342	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.187</i>	<i>0.604</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-56-0318B0476-A2-HS	56	14.82	4.757	15.342	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.187</i>	<i>0.604</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-56-0318B0635-A2-HS	56	14.82	6.345	15.342	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.604</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-56-0318B0635-3-HS	56	14.82	6.345	15.342	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.583</i>	<i>0.250</i>	<i>0.604</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-60-0318B0318-A2-CH	60	15.88	3.175	16.401	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-60-0159B0318-3-HS	60	15.88	3.175	16.401	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-60-0238B0318-3-HS	60	15.88	3.175	16.401	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-60-0318B0318-3-CH	60	15.88	3.175	16.401	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-60-0238B0318-A2-HS	60	15.88	3.175	16.401	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-60-0318B0318-A2-HS	60	15.88	3.175	16.401	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-60-0159B0318-A2-HS	60	15.88	3.175	16.401	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-60-0318B0318-3-HS	60	15.88	3.175	16.401	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.125</i>	<i>0.646</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-60-0318B0476-A2-HS	60	15.88	4.757	16.401	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.646</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-60-0318B0476-3-HS	60	15.88	4.757	16.401	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.187</i>	<i>0.646</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-60-0318B0635-3-HS	60	15.88	6.345	16.401	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.646</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-60-0318B0635-A2-HS	60	15.88	6.345	16.401	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.625</i>	<i>0.250</i>	<i>0.646</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-63-0318B0635-A2-HS	63	16.67	6.345	17.196	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.656</i>	<i>0.250</i>	<i>0.677</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-63-0318B0635-3-HS	63	16.67	6.345	17.196	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.656</i>	<i>0.250</i>	<i>0.677</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-64-0318B0318-A2-HS	64	16.93	3.175	17.460	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-64-0159B0318-3-HS	64	16.93	3.175	17.460	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-64-0318B0318-3-CH	64	16.93	3.175	17.460	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-64-0159B0318-A2-HS	64	16.93	3.175	17.460	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-64-0238B0318-A2-HS	64	16.93	3.175	17.460	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-64-0238B0318-3-HS	64	16.93	3.175	17.460	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-64-0318B0318-A2-CH	64	16.93	3.175	17.460	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-64-0318B0318-3-HS	64	16.93	3.175	17.460	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.125</i>	<i>0.687</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-64-0318B0476-A2-HS	64	16.93	4.757	17.460	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.687</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-64-0318B0476-3-HS	64	16.93	4.757	17.460	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.667</i>	<i>0.187</i>	<i>0.687</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-65-0318B0318-A2-HS	65	17.20	3.175	17.724	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.677</i>	<i>0.125</i>	<i>0.698</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-65-0238B0318-3-HS	65	17.20	3.175	17.724	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.677</i>	<i>0.125</i>	<i>0.698</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-65-0159B0318-A2-HS	65	17.20	3.175	17.724	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.677</i>	<i>0.125</i>	<i>0.698</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-65-0159B0318-3-HS	65	17.20	3.175	17.724	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.677</i>	<i>0.125</i>	<i>0.698</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-65-0238B0318-A2-HS	65	17.20	3.175	17.724	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.677</i>	<i>0.125</i>	<i>0.698</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-65-0318B0318-3-HS	65	17.20	3.175	17.724	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.677</i>	<i>0.125</i>	<i>0.698</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-70-0238B0318-3-HS	70	18.52	3.175	19.048	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-70-0318B0318-3-CH	70	18.52	3.175	19.048	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-70-0159B0318-3-HS	70	18.52	3.175	19.048	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-70-0238B0318-A2-HS	70	18.52	3.175	19.048	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-70-0318B0318-A2-CH	70	18.52	3.175	19.048	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-70-0318B0318-3-HS	70	18.52	3.175	19.048	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-70-0318B0318-A2-HS	70	18.52	3.175	19.048	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-70-0159B0318-A2-HS	70	18.52	3.175	19.048	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.729</i>	<i>0.125</i>	<i>0.750</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-72-0238B0318-A2-HS	72	19.05	3.175	19.576	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-72-0159B0318-3-HS	72	19.05	3.175	19.576	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-72-0318B0318-3-CH	72	19.05	3.175	19.576	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-72-0159B0318-A2-HS	72	19.05	3.175	19.576	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-72-0318B0318-A2-CH	72	19.05	3.175	19.576	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-72-0318B0318-A2-HS	72	19.05	3.175	19.576	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-72-0238B0318-3-HS	72	19.05	3.175	19.576	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-72-0318B0318-3-HS	72	19.05	3.175	19.576	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.125</i>	<i>0.771</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-72-0318B0476-3-HS	72	19.05	4.757	19.576	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.771</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-72-0318B0476-A2-HS	72	19.05	4.757	19.576	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.187</i>	<i>0.771</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-72-0318B0635-3-HS	72	19.05	6.345	19.576	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.771</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-72-0318B0635-A2-HS	72	19.05	6.345	19.576	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.750</i>	<i>0.250</i>	<i>0.771</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-75-0238B0318-A2-HS	75	19.85	3.175	20.371	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.781</i>	<i>0.125</i>	<i>0.802</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-75-0238B0318-3-HS	75	19.85	3.175	20.371	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.781</i>	<i>0.125</i>	<i>0.802</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-75-0318B0318-3-HS	75	19.85	3.175	20.371	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.781</i>	<i>0.125</i>	<i>0.802</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-75-0159B0318-A2-HS	75	19.85	3.175	20.371	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.781</i>	<i>0.125</i>	<i>0.802</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-75-0318B0318-A2-HS	75	19.85	3.175	20.371	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.781</i>	<i>0.125</i>	<i>0.802</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-75-0159B0318-3-HS	75	19.85	3.175	20.371	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.781</i>	<i>0.125</i>	<i>0.802</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-75-0318B0476-A2-HS	75	19.85	4.757	20.371	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.781</i>	<i>0.187</i>	<i>0.802</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-75-0318B0476-3-HS	75	19.85	4.757	20.371	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.781</i>	<i>0.187</i>	<i>0.802</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-76-0318B0318-A2-CH	76	20.11	3.175	20.635	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.792</i>	<i>0.125</i>	<i>0.812</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-76-0318B0318-3-CH	76	20.11	3.175	20.635	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.792</i>	<i>0.125</i>	<i>0.812</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-76-0318B0635-3-HS	76	20.11	6.345	20.635	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.792</i>	<i>0.250</i>	<i>0.812</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-76-0318B0635-A2-HS	76	20.11	6.345	20.635	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.792</i>	<i>0.250</i>	<i>0.812</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-78-0318B0635-3-HS	78	20.64	6.345	21.164	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.833</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-78-0318B0635-A2-HS	78	20.64	6.345	21.164	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.813</i>	<i>0.250</i>	<i>0.833</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-80-0238B0318-A2-HS	80	21.17	3.175	21.692	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-80-0159B0318-3-HS	80	21.17	3.175	21.692	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-80-0318B0318-A2-HS	80	21.17	3.175	21.692	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-80-0238B0318-3-HS	80	21.17	3.175	21.692	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-80-0159B0318-A2-HS	80	21.17	3.175	21.692	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-80-0318B0318-3-CH	80	21.17	3.175	21.692	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-80-0318B0318-3-HS	80	21.17	3.175	21.692	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-80-0318B0318-A2-CH	80	21.17	3.175	21.692	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.125</i>	<i>0.854</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-80-0318B0476-3-HS	80	21.17	4.757	21.692	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.854</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-80-0318B0476-A2-HS	80	21.17	4.757	21.692	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.187</i>	<i>0.854</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-80-0318B0635-A2-HS	80	21.17	6.345	21.692	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.854</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-80-0318B0635-3-HS	80	21.17	6.345	21.692	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.833</i>	<i>0.250</i>	<i>0.854</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-82-0159B0318-3-HS	82	21.70	3.175	22.223	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.854</i>	<i>0.125</i>	<i>0.875</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-82-0159B0318-A2-HS	82	21.70	3.175	22.223	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.854</i>	<i>0.125</i>	<i>0.875</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-84-0238B0318-A2-HS	84	22.23	3.175	22.751	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.125</i>	<i>0.896</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-84-0318B0318-A2-CH	84	22.23	3.175	22.751	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.125</i>	<i>0.896</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-84-0238B0318-3-HS	84	22.23	3.175	22.751	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.125</i>	<i>0.896</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-84-0318B0318-3-CH	84	22.23	3.175	22.751	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.125</i>	<i>0.896</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-84-0318B0635-A2-HS	84	22.23	6.345	22.751	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.896</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-84-0318B0635-3-HS	84	22.23	6.345	22.751	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.875</i>	<i>0.250</i>	<i>0.896</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-85-0159B0318-3-HS	85	22.49	3.175	23.015	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.885</i>	<i>0.125</i>	<i>0.906</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-85-0159B0318-A2-HS	85	22.49	3.175	23.015	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.885</i>	<i>0.125</i>	<i>0.906</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-85-0318B0476-3-HS	85	22.49	4.757	23.015	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.885</i>	<i>0.187</i>	<i>0.906</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-85-0318B0476-A2-HS	85	22.49	4.757	23.015	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.885</i>	<i>0.187</i>	<i>0.906</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-90-0318B0318-3-HS	90	23.81	3.175	24.338	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-90-0238B0318-A2-HS	90	23.81	3.175	24.338	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-90-0318B0318-3-CH	90	23.81	3.175	24.338	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-90-0318B0318-A2-CH	90	23.81	3.175	24.338	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-90-0318B0318-A2-HS	90	23.81	3.175	24.338	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-90-0238B0318-3-HS	90	23.81	3.175	24.338	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-90-0159B0318-3-HS	90	23.81	3.175	24.338	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-90-0159B0318-A2-HS	90	23.81	3.175	24.338	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.125</i>	<i>0.958</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-90-0318B0476-A2-HS	90	23.81	4.757	24.338	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.187</i>	<i>0.958</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-90-0318B0476-3-HS	90	23.81	4.757	24.338	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.187</i>	<i>0.958</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-90-0318B0635-A2-HS	90	23.81	6.345	24.338	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>0.958</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-90-0318B0635-3-HS	90	23.81	6.345	24.338	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.937</i>	<i>0.250</i>	<i>0.958</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-92-0318B0635-A2-HS	92	24.34	6.345	24.867	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.958</i>	<i>0.250</i>	<i>0.979</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-92-0318B0635-3-HS	92	24.34	6.345	24.867	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.958</i>	<i>0.250</i>	<i>0.979</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-95-0159B0318-A2-HS	95	25.14	3.175	25.662	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>0.990</i>	<i>0.125</i>	<i>1.010</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-95-0159B0318-3-HS	95	25.14	3.175	25.662	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>0.990</i>	<i>0.125</i>	<i>1.010</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-96-0318B0318-A2-CH	96	25.40	3.175	25.926	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-96-0318B0318-3-HS	96	25.40	3.175	25.926	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-96-0238B0318-A2-HS	96	25.40	3.175	25.926	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-96-0159B0318-3-HS	96	25.40	3.175	25.926	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-96-0238B0318-3-HS	96	25.40	3.175	25.926	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-96-0318B0318-A2-HS	96	25.40	3.175	25.926	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-96-0159B0318-A2-HS	96	25.40	3.175	25.926	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-96-0318B0318-3-CH	96	25.40	3.175	25.926	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.125</i>	<i>1.021</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-96-0318B0476-3-HS	96	25.40	4.757	25.926	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.021</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-96-0318B0476-A2-HS	96	25.40	4.757	25.926	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.187</i>	<i>1.021</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-96-0318B0635-A2-HS	96	25.40	6.345	25.926	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.021</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-96-0318B0635-3-HS	96	25.40	6.345	25.926	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.000</i>	<i>0.250</i>	<i>1.021</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-100-0159B0318-A2-HS	100	26.46	3.175	26.985	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-100-0318B0318-A2-CH	100	26.46	3.175	26.985	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-100-0318B0318-3-HS	100	26.46	3.175	26.985	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-100-0318B0318-3-CH	100	26.46	3.175	26.985	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-100-0238B0318-A2-HS	100	26.46	3.175	26.985	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-100-0159B0318-3-HS	100	26.46	3.175	26.985	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-100-0318B0318-A2-HS	100	26.46	3.175	26.985	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-100-0238B0318-3-HS	100	26.46	3.175	26.985	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.125</i>	<i>1.062</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-100-0318B0476-3-HS	100	26.46	4.757	26.985	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.187</i>	<i>1.062</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-100-0318B0476-A2-HS	100	26.46	4.757	26.985	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.187</i>	<i>1.062</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-100-0318B0635-A2-HS	100	26.46	6.345	26.985	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.042</i>	<i>0.250</i>	<i>1.062</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-100-0318B0635-3-HS	100	26.46	6.345	26.985	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.042</i>	<i>0.250</i>	<i>1.062</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-104-0318B0476-3-HS	104	27.52	4.757	28.042	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.083</i>	<i>0.187</i>	<i>1.104</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-104-0318B0476-A2-HS	104	27.52	4.757	28.042	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.083</i>	<i>0.187</i>	<i>1.104</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-105-0159B0318-3-HS	105	27.78	3.175	28.309	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.094</i>	<i>0.125</i>	<i>1.115</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-105-0159B0318-A2-HS	105	27.78	3.175	28.309	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.094</i>	<i>0.125</i>	<i>1.115</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-105-0238B0318-A2-HS	105	27.78	3.175	28.309	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.094</i>	<i>0.125</i>	<i>1.115</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-105-0238B0318-3-HS	105	27.78	3.175	28.309	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.094</i>	<i>0.125</i>	<i>1.115</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-105-0318B0318-A2-HS	105	27.78	3.175	28.309	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.094</i>	<i>0.125</i>	<i>1.115</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-105-0318B0318-3-HS	105	27.78	3.175	28.309	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.094</i>	<i>0.125</i>	<i>1.115</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-108-0159B0318-3-HS	108	28.58	3.175	29.101	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.125</i>	<i>1.146</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-108-0159B0318-A2-HS	108	28.58	3.175	29.101	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.125</i>	<i>0.125</i>	<i>1.146</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-108-0238B0318-A2-HS	108	28.58	3.175	29.101	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.125</i>	<i>0.125</i>	<i>1.146</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-108-0238B0318-3-HS	108	28.58	3.175	29.101	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.125</i>	<i>1.146</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-108-0318B0635-A2-HS	108	28.58	6.345	29.101	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.146</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-108-0318B0635-3-HS	108	28.58	6.345	29.101	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.125</i>	<i>0.250</i>	<i>1.146</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-110-0159B0318-A2-HS	110	29.10	3.175	29.629	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.146</i>	<i>0.125</i>	<i>1.166</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-110-0159B0318-3-HS	110	29.10	3.175	29.629	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.146</i>	<i>0.125</i>	<i>1.166</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-110-0318B0476-3-HS	110	29.10	4.757	29.629	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.146</i>	<i>0.187</i>	<i>1.166</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-110-0318B0476-A2-HS	110	29.10	4.757	29.629	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.146</i>	<i>0.187</i>	<i>1.166</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-110-0318B0635-3-HS	110	29.10	6.345	29.629	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.146</i>	<i>0.250</i>	<i>1.166</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-110-0318B0635-A2-HS	110	29.10	6.345	29.629	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.146</i>	<i>0.250</i>	<i>1.166</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-112-0318B0635-3-HS	112	29.63	6.345	30.160	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.167</i>	<i>0.250</i>	<i>1.187</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-112-0318B0635-A2-HS	112	29.63	6.345	30.160	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.167</i>	<i>0.250</i>	<i>1.187</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-120-0159B0318-3-HS	120	31.75	3.175	32.276	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-120-0318B0318-A2-CH	120	31.75	3.175	32.276	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-120-0238B0318-3-HS	120	31.75	3.175	32.276	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-120-0318B0318-3-HS	120	31.75	3.175	32.276	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-120-0159B0318-A2-HS	120	31.75	3.175	32.276	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-120-0318B0318-3-CH	120	31.75	3.175	32.276	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-120-0238B0318-A2-HS	120	31.75	3.175	32.276	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-120-0318B0318-A2-HS	120	31.75	3.175	32.276	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.125</i>	<i>1.271</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-120-0318B0476-A2-HS	120	31.75	4.757	32.276	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.271</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-120-0318B0476-3-HS	120	31.75	4.757	32.276	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.187</i>	<i>1.271</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-120-0318B0635-A2-HS	120	31.75	6.345	32.276	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.271</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-120-0318B0635-3-HS	120	31.75	6.345	32.276	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.250</i>	<i>0.250</i>	<i>1.271</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-125-0318B0635-3-HS	125	33.07	6.345	33.597	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.302</i>	<i>0.250</i>	<i>1.323</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-125-0318B0635-A2-HS	125	33.07	6.345	33.597	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.302</i>	<i>0.250</i>	<i>1.323</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-126-0318B0635-3-HS	126	33.34	6.345	33.864	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.333</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-126-0318B0635-A2-HS	126	33.34	6.345	33.864	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.313</i>	<i>0.250</i>	<i>1.333</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-130-0318B0476-A2-HS	130	34.40	4.757	34.923	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.354</i>	<i>0.187</i>	<i>1.375</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-130-0318B0476-3-HS	130	34.40	4.757	34.923	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.354</i>	<i>0.187</i>	<i>1.375</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-130-0318B0635-A2-HS	130	34.40	6.345	34.923	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.354</i>	<i>0.250</i>	<i>1.375</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-130-0318B0635-3-HS	130	34.40	6.345	34.923	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.354</i>	<i>0.250</i>	<i>1.375</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-132-0238B0318-3-HS	132	34.93	3.175	35.451	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.375</i>	<i>0.125</i>	<i>1.396</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-132-0318B0635-3-HS	132	34.93	6.345	35.451	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.396</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-132-0318B0635-A2-HS	132	34.93	6.345	35.451	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.375</i>	<i>0.250</i>	<i>1.396</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-140-0318B0476-A2-HS	140	37.04	4.757	37.567	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.458</i>	<i>0.187</i>	<i>1.479</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-140-0318B0476-3-HS	140	37.04	4.757	37.567	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.458</i>	<i>0.187</i>	<i>1.479</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-140-0318B0635-A2-HS	140	37.04	6.345	37.567	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.458</i>	<i>0.250</i>	<i>1.479</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-140-0318B0635-3-HS	140	37.04	6.345	37.567	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.458</i>	<i>0.250</i>	<i>1.479</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-144-0238B0318-A2-HS	144	38.10	3.175	38.626	2.38	7.14	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-144-0318B0318-A2-CH	144	38.10	3.175	38.626	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-144-0318B0318-3-CH	144	38.10	3.175	38.626	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-144-0159B0318-3-HS	144	38.10	3.175	38.626	1.59	6.35	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			
# GS96-144-0159B0318-A2-HS	144	38.10	3.175	38.626	1.59	6.35	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.063</i>	<i>0.250</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-144-0318B0318-A2-HS	144	38.10	3.175	38.626	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-144-0238B0318-3-HS	144	38.10	3.175	38.626	2.38	7.14	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.094</i>	<i>0.281</i>	<i>0.312</i>			
# GS96-144-0318B0318-3-HS	144	38.10	3.175	38.626	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.500</i>	<i>0.125</i>	<i>1.521</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-149-0318B0635-A2-HS	149	39.42	6.345	39.949	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.552</i>	<i>0.250</i>	<i>1.573</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-149-0318B0635-3-HS	149	39.42	6.345	39.949	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.552</i>	<i>0.250</i>	<i>1.573</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-150-0318B0476-A2-HS	150	39.69	4.757	40.214	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.563</i>	<i>0.187</i>	<i>1.583</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-150-0318B0476-3-HS	150	39.69	4.757	40.214	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.563</i>	<i>0.187</i>	<i>1.583</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-150-0318B0635-3-HS	150	39.69	6.345	40.214	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.583</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-150-0318B0635-A2-HS	150	39.69	6.345	40.214	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.563</i>	<i>0.250</i>	<i>1.583</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-156-0318B0318-3-HS	156	41.28	3.175	41.801	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.625</i>	<i>0.125</i>	<i>1.646</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-156-0318B0318-3-CH	156	41.28	3.175	41.801	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.625</i>	<i>0.125</i>	<i>1.646</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-156-0318B0318-A2-CH	156	41.28	3.175	41.801	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.625</i>	<i>0.125</i>	<i>1.646</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-156-0318B0318-A2-HS	156	41.28	3.175	41.801	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.625</i>	<i>0.125</i>	<i>1.646</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-160-0318B0476-3-HS	160	42.33	4.757	42.860	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.687</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-160-0318B0476-A2-HS	160	42.33	4.757	42.860	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.667</i>	<i>0.187</i>	<i>1.687</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-163-0318B0635-A2-HS	163	43.13	6.345	43.653	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.698</i>	<i>0.250</i>	<i>1.719</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-163-0318B0635-3-HS	163	43.13	6.345	43.653	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.698</i>	<i>0.250</i>	<i>1.719</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-168-0318B0318-3-HS	168	44.45	3.175	44.976	3.18	7.94	7.93	4.76 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.125</i>	<i>1.771</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-168-0318B0318-A2-HS	168	44.45	3.175	44.976	3.18	7.94	7.93	4.76 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.125</i>	<i>1.771</i>	<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-168-0318B0318-3-CH	168	44.45	3.175	44.976	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.750</i>	<i>0.125</i>	<i>1.771</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-168-0318B0318-A2-CH	168	44.45	3.175	44.976	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.750</i>	<i>0.125</i>	<i>1.771</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-170-0318B0635-A2-HS	170	44.98	6.345	45.504	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.771</i>	<i>0.250</i>	<i>1.791</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-170-0318B0635-3-HS	170	44.98	6.345	45.504	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.771</i>	<i>0.250</i>	<i>1.791</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-180-0318B0318-3-CH	180	47.63	3.175	48.151	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.125</i>	<i>1.896</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-180-0318B0318-A2-CH	180	47.63	3.175	48.151	3.18	10.32	4.78	7.14 / Clamp Type (Clamp Area 6.35mm)	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.875</i>	<i>0.125</i>	<i>1.896</i>	<i>0.125</i>	<i>0.406</i>	<i>0.188</i>			
# GS96-180-0318B0476-3-HS	180	47.63	4.757	48.151	3.18	8.72	9.53	5.54 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.896</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-180-0318B0476-A2-HS	180	47.63	4.757	48.151	3.18	8.72	9.53	5.54 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.875</i>	<i>0.187</i>	<i>1.896</i>	<i>0.125</i>	<i>0.343</i>	<i>0.375</i>			
# GS96-180-0318B0635-3-HS	180	47.63	6.345	48.151	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.896</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-180-0318B0635-A2-HS	180	47.63	6.345	48.151	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.875</i>	<i>0.250</i>	<i>1.896</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-190-0318B0635-A2-HS	190	50.27	6.345	50.798	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>1.979</i>	<i>0.250</i>	<i>2.000</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Gears - Spur - 96 Pitch

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (OD) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS96-190-0318B0635-3-HS	190	50.27	6.345	50.798	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>1.979</i>	<i>0.250</i>	<i>2.000</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-192-0318B0318-A2-HS	192	50.88	3.175		3.18	7.94	7.93	2-56/Set Screw	20	2024 Aluminium Anodized
		<i>2.003</i>	<i>0.125</i>		<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-192-0318B0318-3-HS	192	50.88	3.175		3.18	7.94	7.93	2-56/Set Screw	20	303 Stainless Steel
		<i>2.003</i>	<i>0.125</i>		<i>0.125</i>	<i>0.313</i>	<i>0.312</i>			
# GS96-220-0318B0635-3-HS	220	58.21	6.345	58.735	3.18	9.53	9.53	6.35 / Set Screw	20	303 Stainless Steel / AGMA Q10
		<i>2.292</i>	<i>0.250</i>	<i>2.312</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			
# GS96-220-0318B0635-A2-HS	220	58.21	6.345	58.735	3.18	9.53	9.53	6.35 / Set Screw	20	2024 Aluminum Alloy / AGMA Q10
		<i>2.292</i>	<i>0.250</i>	<i>2.312</i>	<i>0.125</i>	<i>0.375</i>	<i>0.375</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
