




MBA

Gears - Spur - Circular Pitch 5



PCD = No. of Teeth x 1.591mm (5.000 / Pi.). Various styles and materials.

Fairloc Hub Type require controlled shaft tolerances between 0.0025 and 0.0203 mm Clearance.

Gears - Spur - Circular Pitch 5

Part Number	Teeth (No.)	Pitch Circle Diameter (PD) mm	Bore (d) mm	Outside Diameter (D) mm	Face Width (FW) mm	Overall Width (FW+HL) mm	Hub Diameter (D1) mm	Hub Proj / Locking Method (HL) mm	Pressure Angle Deg.	Material / Quality
# GS5CP-20-1500B1000-ST	20	31.83	10.000	35.010	15.000	25.00	25.00	10.000 / No Locking Method	20	AISI 4135 Steel / ISO 5 - Ground
		<i>1.253</i>	<i>0.394</i>	<i>1.378</i>	<i>0.591</i>	<i>0.984</i>	<i>0.984</i>			
# GS5CP-25-1500B1000-ST	25	39.79	10.000	42.970	15.000	25.00	30.00	10.000 / No Locking Method	20	AISI 4135 Steel / ISO 5 - Ground
		<i>1.567</i>	<i>0.394</i>	<i>1.692</i>	<i>0.591</i>	<i>0.984</i>	<i>1.181</i>			
# GS5CP-30-1500B1000-ST	30	47.75	10.000	50.930	15.000	25.00	40.00	10.000 / No Locking Method	20	AISI 4135 Steel / ISO 5 - Ground
		<i>1.880</i>	<i>0.394</i>	<i>2.005</i>	<i>0.591</i>	<i>0.984</i>	<i>1.575</i>			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

