




MBA

Hoist Rings - Side Pull



Material: Alloy Steel. Bushing: Zinc plated silver passivate. Finish: Black Oxide.

- Performance
- Convenient part handling.
 - Rated at 5:1 strength factor.
 - Clevis, ring, bushing and cap screw are magnetic particle inspected.
 - Available with Envirotex™ Protective finish upon request.
 - Clevis is X-rayed.
 - Proof tested to 200% of rated load capacity.
 - All products CE marked.

Replacement Bolt Kits available.

Stated load capacity is based upon specific thread torques shown in chart. It is recommended that these torques be used when installing hoist rings.

- Prevents rusting
- Environmentally safe.

Alloy Steel. Bushing: Zinc plated silver passivate. Finish: Black Oxide.

Hoist Rings - Side Pull

Part Number	Thread Size	Load Capacity kg	Inside Diameter (ØB) mm	Length (C) mm	Base Width (D) mm	Base Diameter (E) mm	Thread Length (F) mm	Ring Thickness (G) mm	Finish	Thread Torque (Kg-m)
			<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		
# M8-47351	M8 x 1.25	325.00	50.80 <i>2.000</i>	61.00 <i>2.402</i>	50.80 <i>2.000</i>	38.10 <i>1.500</i>	16.00 <i>0.630</i>	9.50 <i>0.374</i>	Standard Finish	0.43
# M10-47352	M10 x 1.50	500.00	50.80 <i>2.000</i>	63.00 <i>2.480</i>	50.80 <i>2.000</i>	38.10 <i>1.500</i>	20.00 <i>0.787</i>	9.50 <i>0.374</i>	Standard Finish	0.60
# M12-47353	M12 x 1.75	725.00	76.20 <i>3.000</i>	85.00 <i>3.346</i>	81.00 <i>3.189</i>	60.30 <i>2.374</i>	24.00 <i>0.945</i>	15.90 <i>0.626</i>	Standard Finish	2.00
# M16-47354	M16 x 2.00	1400.00	76.20 <i>3.000</i>	94.00 <i>3.701</i>	81.00 <i>3.189</i>	60.30 <i>2.374</i>	31.00 <i>1.220</i>	15.90 <i>0.626</i>	Standard Finish	3.50

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Hoist Rings - Side Pull

Part Number	Thread Size	Load Capacity kg	Inside Diameter (ØB) mm	Length (C) mm	Base Width (D) mm	Base Diameter (E) mm	Thread Length (F) mm	Ring Thickness (G) mm	Finish	Thread Torque (Kg-m)
			<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		
# M20-47355	M20 x 2.50	2290.00	101.60 <i>4.000</i>	133.00 <i>5.236</i>	125.40 <i>4.937</i>	95.30 <i>3.752</i>	40.00 <i>1.575</i>	25.40 <i>1.000</i>	Standard Finish	7.00
# M24-47356	M24 x 3.00	3050.00	101.60 <i>4.000</i>	147.00 <i>5.787</i>	125.40 <i>4.937</i>	95.30 <i>3.752</i>	47.00 <i>1.850</i>	25.40 <i>1.000</i>	Standard Finish	12.50
# M30-47357	M30 x 3.50	4850.00	127.00 <i>5.000</i>	173.80 <i>6.843</i>	173.00 <i>6.811</i>	117.50 <i>4.626</i>	43.60 <i>1.717</i>	31.70 <i>1.248</i>	Standard Finish	34.60

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
