



MBA


Housings - Linear - Twin Pillow Block

Includes Bearings.

Housing: Aluminium - carbon steel and engineered polymer bearing fitted.

Super Smart Ball Bushing™ Bearing fitted.

Designed for use with Hard Linear Shafting (h6 Tolerance).



Housings - Linear - Twin Pillow Block

Part Number	Bore Diameter mm	Centre Height mm	Height mm	Width mm	Length mm	Distance Between Bolts / Width mm	Bolt Size mm	Dynamic Load	Load Limit	Type
# LSTB-8AJ	8.0 <i>0.315</i>	15.0 <i>0.591</i>	28.0 <i>1.102</i>	35.0 <i>1.378</i>	62.0 <i>2.441</i>	50 / 25	M4	500	550	Closed - Adjustable
# LSTB-8	8.0 <i>0.315</i>	15.0 <i>0.591</i>	28.0 <i>1.102</i>	35.0 <i>1.378</i>	62.0 <i>2.441</i>	50 / 25	M4	500	550	Closed - Fixed
# LSTB-12OPAJ	12.0 <i>0.472</i>	18.0 <i>0.709</i>	28.0 <i>1.102</i>	43.0 <i>1.693</i>	76.0 <i>2.992</i>	56 / 32	M5	1220	1340	Open - Adjustable

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Housings - Linear - Twin Pillow Block

Part Number	Bore Diameter mm	Centre Height mm	Height mm	Width mm	Length mm	Distance Between Bolts / Width mm	Bolt Size mm	Dynamic Load	Load Limit	Type
# LSTB-12OP	12.0 <i>0.472</i>	18.0 <i>0.709</i>	28.0 <i>1.102</i>	43.0 <i>1.693</i>	76.0 <i>2.992</i>	56 / 32	M5	1220	1340	Open - Fixed
# LSTB-12	12.0 <i>0.472</i>	18.0 <i>0.709</i>	35.0 <i>1.378</i>	43.0 <i>1.693</i>	76.0 <i>2.992</i>	56 / 32	M5	1060	1165	Closed - Fixed
# LSTB-12AJ	12.0 <i>0.472</i>	18.0 <i>0.709</i>	35.0 <i>1.378</i>	43.0 <i>1.693</i>	76.0 <i>2.992</i>	56 / 32	M5	1060	1165	Closed - Adjustable
# LSTB-16OP	16.0 <i>0.630</i>	22.0 <i>0.866</i>	35.0 <i>1.378</i>	53.0 <i>2.087</i>	84.0 <i>3.307</i>	64 / 40	M6	4400	4800	Open - Fixed
# LSTB-16OPAJ	16.0 <i>0.630</i>	22.0 <i>0.866</i>	35.0 <i>1.378</i>	53.0 <i>2.087</i>	84.0 <i>3.307</i>	64 / 40	M6	4400	4800	Open - Adjustable
# LSTB-16	16.0 <i>0.630</i>	22.0 <i>0.866</i>	42.0 <i>1.654</i>	53.0 <i>2.087</i>	84.0 <i>3.307</i>	64 / 40	M6	4400	4800	Closed - Fixed
# LSTB-16AJ	16.0 <i>0.630</i>	22.0 <i>0.866</i>	42.0 <i>1.654</i>	53.0 <i>2.087</i>	84.0 <i>3.307</i>	64 / 40	M6	4400	4800	Closed - Adjustable
# LSTB-20OPAJ	20.0 <i>0.787</i>	25.0 <i>0.984</i>	42.0 <i>1.654</i>	60.0 <i>2.362</i>	104.0 <i>4.094</i>	76 / 45	M8	8000	8800	Open - Adjustable
# LSTB-20OP	20.0 <i>0.787</i>	25.0 <i>0.984</i>	42.0 <i>1.654</i>	60.0 <i>2.362</i>	104.0 <i>4.094</i>	76 / 45	M8	8000	8800	Open - Fixed

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Housings - Linear - Twin Pillow Block

Part Number	Bore Diameter mm	Centre Height mm	Height mm	Width mm	Length mm	Distance Between Bolts / Width mm	Bolt Size mm	Dynamic Load	Load Limit	Type
# LSTB-20	20.0 <i>0.787</i>	25.0 <i>0.984</i>	50.0 <i>1.969</i>	60.0 <i>2.362</i>	104.0 <i>4.094</i>	76 / 45	M8	8000	8800	Closed - Fixed
# LSTB-20AJ	20.0 <i>0.787</i>	25.0 <i>0.984</i>	50.0 <i>1.969</i>	60.0 <i>2.362</i>	104.0 <i>4.094</i>	76 / 45	M8	8000	8800	Closed - Adjustable
# LSTB-25OPAJ	25.0 <i>0.984</i>	30.0 <i>1.181</i>	51.0 <i>2.008</i>	78.0 <i>3.071</i>	130.0 <i>5.118</i>	94 / 60	M10	13400	14600	Open - Adjustable
# LSTB-25OP	25.0 <i>0.984</i>	30.0 <i>1.181</i>	51.0 <i>2.008</i>	78.0 <i>3.071</i>	130.0 <i>5.118</i>	94 / 60	M10	13400	14600	Open - Fixed
# LSTB-25AJ	25.0 <i>0.984</i>	30.0 <i>1.181</i>	60.0 <i>2.362</i>	78.0 <i>3.071</i>	130.0 <i>5.118</i>	94 / 60	M10	13400	14600	Closed - Adjustable
# LSTB-25	25.0 <i>0.984</i>	30.0 <i>1.181</i>	60.0 <i>2.362</i>	78.0 <i>3.071</i>	130.0 <i>5.118</i>	94 / 60	M10	13400	14600	Closed - Fixed
# LSTB-30OPAJ	30.0 <i>1.181</i>	35.0 <i>1.378</i>	60.0 <i>2.362</i>	87.0 <i>3.425</i>	152.0 <i>5.984</i>	106 / 68	M10	16600	18200	Open - Adjustable
# LSTB-30OP	30.0 <i>1.181</i>	35.0 <i>1.378</i>	60.0 <i>2.362</i>	87.0 <i>3.425</i>	152.0 <i>5.984</i>	106 / 68	M10	16600	18200	Open - Fixed
# LSTB-30	30.0 <i>1.181</i>	35.0 <i>1.378</i>	71.0 <i>2.795</i>	87.0 <i>3.425</i>	152.0 <i>5.984</i>	106 / 68	M10	16600	18200	Closed - Fixed

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Housings - Linear - Twin Pillow Block

Part Number	Bore Diameter mm	Centre Height mm	Height mm	Width mm	Length mm	Distance Between Bolts / Width mm	Bolt Size mm	Dynamic Load	Load Limit	Type
# LSTB-30AJ	30.0	35.0	71.0	87.0	152.0	106 / 68	M10	16600	18200	Closed - Adjustable
	<i>1.181</i>	<i>1.378</i>	<i>2.795</i>	<i>3.425</i>	<i>5.984</i>					
# LSTB-40OPAJ	40.0	45.0	77.0	108.0	176.0	124 / 83	M12	27400	30000	Open - Adjustable
	<i>1.575</i>	<i>1.772</i>	<i>3.031</i>	<i>4.252</i>	<i>6.929</i>					
# LSTB-40OP	40.0	45.0	77.0	108.0	176.0	124 / 83	M12	27400	30000	Open - Fixed
	<i>1.575</i>	<i>1.772</i>	<i>3.031</i>	<i>4.252</i>	<i>6.929</i>					
# LSTB-40	40.0	45.0	91.0	108.0	176.0	124 / 86	M12	27400	30000	Closed - Fixed
	<i>1.575</i>	<i>1.772</i>	<i>3.583</i>	<i>4.252</i>	<i>6.929</i>					
# LSTB-40AJ	40.0	45.0	91.0	108.0	176.0	124 / 86	M12	27400	30000	Closed - Adjustable
	<i>1.575</i>	<i>1.772</i>	<i>3.583</i>	<i>4.252</i>	<i>6.929</i>					

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

