



MBA

Inserts - Thread Repair



Stainless inserts.

Replacement Individual Inserts - Require full kit to obtain correct tap.

Manufactured to BS 4377 BS 3049 parts 1 & 2.

Recoil helically-wound thread inserts are formed from 18-8 (Type 304) Stainless Steel.

The wire in most sizes has a tensile strength of greater than 200,000 P.S.I. and a finish better than 32 micro inches.

Inserts - Thread Repair

Part Number	Size	Material
# RI25023	M2.00 - 0.40	Stainless Steel
# RI25253	M2.50 - 0.45	Stainless Steel
# RI25013	M2.20 - 0.45	Stainless Steel
# RI25353	M3.50 - 0.60	Stainless Steel
# RI25033	M3.00 - 0.50	Stainless Steel

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Inserts - Thread Repair

Part Number	Size	Material
# RI25043	M4.00 - 0.70	Stainless Steel
# RI25053	M5.00 - 0.80	Stainless Steel
# RI25063	M6.00 - 1.00	Stainless Steel
# RI25073	M7.00 - 1.00	Stainless Steel
# RI25083	M8.00 - 1.25	Stainless Steel
RI25093	M9.00 - 1.25	Stainless Steel
# RI25104	M10.00 - 1.5x2D	Stainless Steel
RI25103	M10.00 - 1.50	Stainless Steel
# RI25113	M11.00 - 1.50	Stainless Steel
# RI25123	M12.00 - 1.75	Stainless Steel
# RI28123	M12.00 - 1.25	Stainless Steel
# RI28147	M14.00 - 1.25 x 7/16	Stainless Steel

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

