



# MBA

## Knobs - Oval Tapered - Press On - Phenolic

Press on knobs hold on securely without threads or set screws

Shaft diameter should be +0.000 / - 0.076 mm for best performance

Knob is held in place by a ribbed insert that squeezes onto the shaft.

Eliminates machining costs

Knobs will not come off with normal use but can be removed by knocking with a hammer on the underside.

### Knobs - Oval Tapered - Press On - Phenolic

Part Number	Diameter mm <i>inches</i>	Length mm <i>inches</i>	Shaft Diameter mm <i>inches</i>	Bore Depth mm <i>inches</i>
# POK-70RS	38.10 <i>1.500</i>	7.93 <i>0.312</i>	7.98 <i>0.314</i>	14.29 <i>0.563</i>
# POK-75RS	50.80 <i>2.000</i>	9.52 <i>0.375</i>	9.53 <i>0.375</i>	19.05 <i>0.750</i>

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

