




# MBA

## Leadscrews - Metric - Whirled Thread



Trapezoidal thread design. Use with metric leadscrew nuts listed in separate category.

Longer lengths may be available on request.

Single Start.

LRH: Steel 080 M40 (ck40) / LSRH: 303 Stainless Steel.

Whirled screw left hand and right hand cut on same single piece of material to DIN103 Grade 7e.

Use with Trapezoidal Nuts.

This catalogue to be read in conjunction with information at [http://www.minibearings.com.au/ogue/tech/leadscrew/trapezoidal\\_tech.pdf](http://www.minibearings.com.au/ogue/tech/leadscrew/trapezoidal_tech.pdf)

### Leadscrews - Metric - Whirled Thread

Part Number	Overall Diameter (D) mm <i>inches</i>	Lead (P) mm <i>inches</i>	Thread Length (b) mm <i>inches</i>	Blank Width (a) mm <i>inches</i>	Overall Length mm <i>inches</i>	Material
# LSRH164-1	16 <i>0.630</i>	4 <i>0.157</i>	496 <i>19.528</i>	8 <i>0.315</i>	1000 <i>39.370</i>	303 Stainless
# LRH164-1	16 <i>0.630</i>	4 <i>0.157</i>	496 <i>19.528</i>	8 <i>0.315</i>	1000 <i>39.370</i>	Steel 080 M40
# LRH184-1	18 <i>0.709</i>	4 <i>0.157</i>	496 <i>19.528</i>	8 <i>0.315</i>	1000 <i>39.370</i>	Steel 080 M40

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Leadscrews - Metric - Whirled Thread

Part Number	Overall Diameter (D) mm <i>inches</i>	Lead (P) mm <i>inches</i>	Thread Length (b) mm <i>inches</i>	Blank Width (a) mm <i>inches</i>	Overall Length mm <i>inches</i>	Material
# LSRH184-1	18 <i>0.709</i>	4 <i>0.157</i>	496 <i>19.528</i>	8 <i>0.315</i>	1000 <i>39.370</i>	303 Stainless
# LSRH204-1	20 <i>0.787</i>	4 <i>0.157</i>	496 <i>19.528</i>	8 <i>0.315</i>	1000 <i>39.370</i>	303 Stainless
# LRH204-1	20 <i>0.787</i>	4 <i>0.157</i>	496 <i>19.528</i>	8 <i>0.315</i>	1000 <i>39.370</i>	Steel 080 M40
# LSRH245-1	24 <i>0.945</i>	5 <i>0.197</i>	495 <i>19.488</i>	10 <i>0.394</i>	1000 <i>39.370</i>	303 Stainless
# LRH245-1	24 <i>0.945</i>	5 <i>0.197</i>	495 <i>19.488</i>	10 <i>0.394</i>	1000 <i>39.370</i>	Steel 080 M40
# LRH285-1	28 <i>1.102</i>	5 <i>0.197</i>	495 <i>19.488</i>	10 <i>0.394</i>	1000 <i>39.370</i>	Steel 080 M40
# LSRH306-1	30 <i>1.181</i>	6 <i>0.236</i>	494 <i>19.449</i>	12 <i>0.472</i>	1000 <i>39.370</i>	303 Stainless
# LRH306-1	30 <i>1.181</i>	6 <i>0.236</i>	494 <i>19.449</i>	12 <i>0.472</i>	1000 <i>39.370</i>	Steel 080 M40
# LSRH326-1	32 <i>1.260</i>	6 <i>0.236</i>	494 <i>19.449</i>	12 <i>0.472</i>	1000 <i>39.370</i>	303 Stainless
# LRH326-1	32 <i>1.260</i>	6 <i>0.236</i>	494 <i>19.449</i>	12 <i>0.472</i>	1000 <i>39.370</i>	Steel 080 M40

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Leadscrews - Metric - Whirled Thread

Part Number	Overall Diameter (D) mm	Lead (P) mm	Thread Length (b) mm	Blank Width (a) mm	Overall Length mm	Material
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	
# LRH366-1	36 <i>1.417</i>	6 <i>0.236</i>	494 <i>19.449</i>	12 <i>0.472</i>	1000 <i>39.370</i>	Steel 080 M40

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

