



## Motors - DC 30.5X24.2 mm

Part Number	Body Diameter mm	Overall Length mm	Operating Voltage V	Nominal Voltage V	Shaft Size mm	Body Type	Current (No Load/Max Effic) amps	Speed (No Load/Max Efficiency) RPM	Direction	Torque (Max Effic/Stall) g-cm
M-28C-2865-4.5V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	4.5 ~ 6.0	4.5	2 x 10.6mm	Round	0.270 / 1.365	13600 / 11350	CW	29.70 / 180.00
M-28-20120-4.5V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	3.0 ~ 6.0	4.5	2 x 10.4mm	Round	0.095 / 0.420	7500 / 6300	CW	18.10 / 113.00
M-28CS-2865-4.5V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	4.5 ~ 6.0	4.5	2 x 10.6mm	Round	0.220 / 1.223	10700 / 9070	CW	35.80 / 235.00
M-28C-2485-4.5V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	4.5 ~ 7.2	4.5	2 x 10.6mm	Round	0.150 / 0.770	10300 / 8600	CW	22.80 / 140.00
M-28S-2295-6.0V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	3.0 ~ 6.0	6.0	2 x 10.4mm	Round	0.150 / 0.771	9600 / 8170	CW	32.80 / 220.00
M-28CS-2485-6.0V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	4.5 ~ 9.0	6.0	2 x 10.6mm	Round	0.180 / 0.986	10800 / 9130	CW	37.80 / 245.00
M-28CS-20120-6.0V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	4.5 ~ 12.0	6.0	2 x 10.6mm	Round	0.115 / 0.572	7700 / 6400	CW	29.30 / 175.00
M-28C-20120-6.0V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	4.5 ~ 9.0	6.0	2 x 10.6mm	Round	0.120 / 0.582	9900 / 8200	CW	23.10 / 135.00
M-28CS-09400-24.0V	24.200 <i>0.953</i>	45.000 <i>1.772</i>	12.0 ~ 24.0	24.0	2 x 10.6mm	Round	0.035 / 0.163	9200 / 7570	CW	29.20 / 165.00

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

