




MBA

Mounts - Leveling Carry - Ball Type



Vibration Dampening with retractable ball for movement.

Carry mount is a moveable mount in which the rubber mount is incorporated with a rotating ball.

Allows movement of machines and provides vibration dampening.

Simply turn the adjusting hole with a screwdriver to lift or lower the ball.

Mounts - Leveling Carry - Ball Type

Part Number	Working Load Max kgf	Base Height (H2) mm	Bolt Thread	Usable Bolt Legth (L) mm	Overall Diameter (D1) mm	Pad Diameter (D2) mm	H1 mm	D3 mm	h1 mm	h2 mm
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# MLCBT-200	200	70.00 <i>2.756</i>	M12	67.00 <i>2.638</i>	100.00 <i>3.937</i>	80.00 <i>3.150</i>	58.00 <i>2.283</i>	44.00 <i>1.732</i>	7.50 <i>0.295</i>	12.00 <i>0.472</i>
# MLCBT-600	600	79.00 <i>3.110</i>	M16	72.00 <i>2.835</i>	140.00 <i>5.512</i>	120.00 <i>4.724</i>	65.00 <i>2.559</i>	54.00 <i>2.126</i>	7.50 <i>0.295</i>	14.00 <i>0.551</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

