




MBA

Mounts - M Style



Excellent in controlling vibrations of 600cpm or more.

Used for oscillating motion.

Mild steel painted plates.

Natural rubber isolators.

Mounts - M Style

Part Number	Standard Load (Z Direction) kgf	Length (L) mm <i>inches</i>	Bolt Hole Centres (A) mm <i>inches</i>	Allowable Load (Z / X / Y) kgf	Width (B) mm <i>inches</i>	Plate Thickness (S) mm <i>inches</i>	Mount Height (h) mm <i>inches</i>	Stud Length (h1) mm <i>inches</i>	Bolt Hole Dia. (d) mm <i>inches</i>	Centre Bolt Thread
# MSM-15.00	15 - 35	125 <i>4.921</i>	104 <i>4.094</i>	70 / 12 / 14	30.00 <i>1.181</i>	4.5 <i>0.177</i>	40.0 <i>1.575</i>	29.0 <i>1.142</i>	11.0 <i>0.433</i>	M10
# MSM-30.00	30 - 50	160 <i>6.299</i>	130 <i>5.118</i>	100 / 22 / 20	35.00 <i>1.378</i>	4.5 <i>0.177</i>	45.0 <i>1.772</i>	34.0 <i>1.339</i>	14.0 <i>0.551</i>	M12
# MSM-50.00	50 - 90	210 <i>8.268</i>	170 <i>6.693</i>	175 / 45 / 35	40.00 <i>1.575</i>	6.0 <i>0.236</i>	55.0 <i>2.165</i>	54.0 <i>2.126</i>	17.0 <i>0.669</i>	M16
# MSM-80.00	80 - 125	245 <i>9.646</i>	205 <i>8.071</i>	250 / 45 / 40	50.00 <i>1.969</i>	8.0 <i>0.315</i>	65.0 <i>2.559</i>	52.0 <i>2.047</i>	20.0 <i>0.787</i>	M16

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

