







MBA

Mounts - Square

Fastener may be steel, brass or zinc plated.

Natural rubber isolator.



Model	Maximum Load	Forcing Frequency in Cycles per Minute									
		1100	1250	1500	1750	2000	2250	2500	2750	3000	3600
SM-02.31	2.31	—	—	—	2.31	1.76	1.46	1.17	0.95	0.81	—
SM-02.90	2.90	—	—	—	2.90	2.18	1.84	1.50	1.26	1.08	0.91
SM-02.24	0.24	—	—	—	4.89	3.82	3.20	2.70	2.36	1.71	—
SM-02.24	0.24	—	—	—	—	5.54	4.64	4.00	3.47	2.66	—

Model	Maximum Load	Forcing Frequency in Cycles per Minute									
		1100	1250	1500	1750	2000	2250	2500	2750	3000	3600
SM-02.31	1.17	1.08	0.81	0.59	0.41	0.32	0.27	*	*	*	*
SM-02.90	1.62	1.63	1.26	0.89	0.63	0.46	0.36	0.32	0.27	*	*
SM-02.90	1.67	—	2.21	1.62	1.31	0.99	0.69	0.68	0.59	0.58	0.41
SM-02.24	2.15	—	3.15	2.20	1.76	1.40	1.17	0.96	0.81	0.72	0.54

*At these forcing frequencies, lesser loads will yield 81% isolation.

Model	Maximum Load	Forcing Frequency in Cycles per Minute							
		1500	1750	2000	2250	2500	2750	3000	3600
SM-02.99	2.99	—	—	—	—	2.42	2.05	1.44	—
SM-03.94	3.94	—	—	—	—	3.83	3.11	2.16	—
SM-05.43	5.43	—	—	—	—	—	5.19	3.60	—
SM-06.97	6.97	—	—	—	—	—	—	6.21	—

Model	Maximum Load	Forcing Frequency in Cycles per Minute							
		1500	1750	2000	2250	2500	2750	3000	3600
SM-02.99	1.98	1.48	1.00	0.76	0.63	0.56	—	—	—
SM-03.94	2.46	2.16	1.62	1.26	0.99	0.86	0.72	—	—
SM-05.43	3.51	2.47	2.70	2.21	1.80	1.60	1.40	—	—
SM-06.97	4.46	—	3.69	3.02	2.82	2.12	1.85	—	—

*At these forcing frequencies, lesser loads will yield 81% isolation.

Mounts - Square

Part Number	Max Compression Load kg (lbs)	Max Shear Load kg (lbs)	Body Length mm <i>inches</i>	Body Square mm <i>inches</i>	Thread Size	Thread Length mm <i>inches</i>
# SM-02.31	2.31 (5)	1.18 (3)	12.70 <i>0.500</i>	9.53 <i>0.375</i>	8-32 UNC	9.53 <i>0.375</i>
# SM-02.90	2.9 (6)	1.63 (4)	12.70 <i>0.500</i>	9.53 <i>0.375</i>	8-32 UNC	9.53 <i>0.375</i>
# SM-02.99	2.99 (7)	1.99 (4)	7.94 <i>0.313</i>	9.53 <i>0.375</i>	8-32 UNC	5.56 <i>0.219</i>
# SM-03.94	3.94 (9)	2.49 (6)	7.94 <i>0.313</i>	9.53 <i>0.375</i>	8-32 UNC	5.56 <i>0.219</i>

Indicates item not stocked at time of printing - Please enquire for lead time
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Mounts - Square

Part Number	Max Compression Load kg (lbs)	Max Shear Load kg (lbs)	Body Length mm <i>inches</i>	Body Square mm <i>inches</i>	Thread Size	Thread Length mm <i>inches</i>
# SM-05.02	5.02 (11)	2.58 (6)	12.70 <i>0.500</i>	9.53 <i>0.375</i>	8-32 UNC	9.53 <i>0.375</i>
# SM-05.43	5.43 (12)	3.53 (8)	7.94 <i>0.313</i>	9.53 <i>0.375</i>	8-32 UNC	5.56 <i>0.219</i>
# SM-06.24	6.24 (14)	3.21 (7)	12.70 <i>0.500</i>	9.53 <i>0.375</i>	8-32 UNC	9.53 <i>0.375</i>
SM-06.97	6.97 (15)	4.48 (10)	7.94 <i>0.313</i>	9.53 <i>0.375</i>	8-32 UNC	5.56 <i>0.219</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

