




# MBA

## Mounts - V Style



Higher stiffness horizontally than cylindrical rubber mounts.

Easy to install.

Base plate type (Type 2) - A rubber pad is fitted to the base plate.

Mounting Plates : Mild Steel - Painted.

Isolators : Natural Rubber.

This catalogue to be read in conjunction with information at [http://www.minibearings.com.au/ogue/tech/mounts/mvvs\\_pdf.pdf](http://www.minibearings.com.au/ogue/tech/mounts/mvvs_pdf.pdf)

### Mounts - V Style

Part Number	Figure	Standard Load Z Direction kg (lbs)	Spring Rate Z Direction kgf.cm	A mm	B mm	Style	F mm	Thread (d1)	Allowable Loads Z / X / Y kg (lbs)	G mm
# MVVS-KC035	1	4-10 (9-22)	65	60	30	Fig 1. E = 30	26	M10	20 / 13 / 5 (44 / 29 / 11)	29
				2.362	1.181		1.024			1.142
# MVVS-KC045	1	25-45 (55-99)	235	82	50	Fig 1. E = 40	40	M12	90 / 55 / 25 (199 / 122 / 55)	34
				3.228	1.969		1.575			1.339

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Mounts - V Style

Part Number	Figure	Standard Load Z Direction kg (lbs)	Spring Rate Z Direction kgf.cm	A mm	B mm	Style	F mm	Thread (d1)	Allowable Loads Z / X / Y kg (lbs)	G mm
# MVVS-KC075	1	30-90 (66-198)	190	135	70	Fig 1. E = 76	56	M12	170 / 105 / 40 (376 / 232 / 88)	44
				<i>5.315</i>	<i>2.756</i>		<i>2.205</i>			<i>1.732</i>
# MVVS-KC060	1	30-95 (66-209)	380	108	70	Fig 1. E = 45	56	M12	185 / 65 / 30 (409 / 144 / 66)	44
				<i>4.252</i>	<i>2.756</i>		<i>2.205</i>			<i>1.732</i>
# MVVS-KC080	1	35-135 (77-297)	300	148	90	Fig 1. E = 76	65	M16	260 / 155 / 60 (575 / 343 / 133)	52
				<i>5.827</i>	<i>3.543</i>		<i>2.559</i>			<i>2.047</i>
# MVVS-KC070	1	50-150 (110-330)	520	124	90	Fig 1. E = 55	65	M16	290 / 110 / 55 (641 / 243 / 122)	52
				<i>4.882</i>	<i>3.543</i>		<i>2.559</i>			<i>2.047</i>
# MVVS-KC075BP	2	30-90 (66-198)	190	135	70	Fig 2.	56	M12	170 / 105 / 40 (376 / 232 / 88)	44
				<i>5.315</i>	<i>2.756</i>		<i>2.205</i>			<i>1.732</i>
# MVVS-KC080BP	2	35-135 (77-297)	300	148	90	Fig 2.	65	M16	260 / 155 / 60 (575 / 343 / 133)	52
				<i>5.827</i>	<i>3.543</i>		<i>2.559</i>			<i>2.047</i>
# MVVS-KC100BP	2	100-300 (220-660)	600	180	110	Fig 2.	100	M20	600 / 260 / 120 (1326 / 575 / 265)	57
				<i>7.087</i>	<i>4.331</i>		<i>3.937</i>			<i>2.244</i>

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Mounts - V Style

Part Number	Figure	Standard Load Z Direction kg (lbs)	Spring Rate Z Direction kgf.cm	A mm	B mm	Style	F mm	Thread (d1)	Allowable Loads Z / X / Y kg (lbs)	G mm
# MVVS-KC140BP	3	300-650 (660-1430)	1200	250	240	Fig 3.	127	M20 (2)	1300 / 550 / 250 (2873 / 1216 / 553)	56
				9.843	9.449		5.000			2.205
# MVVS-KC170BP	3	500-900 (1100-1980)	1700	288	180	Fig 3.	184	M20 (2)	1750 / 650 / 280 (3868 / 1437 / 619)	56
				11.339	7.087		7.244			2.205

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

