



MBA

Nuts - Hexagonal - Binx



Manufactured from A2 302/304 grade stainless steel.

The standard Binx's entire locking action is contained within the nut body which is no thicker than a standard full nut.

The ingenious design incorporates two opposing cantilever type springs which lock onto the bolt with inward and downward pressure.

May be removed and placed repeatedly with minimum thread wear.

Nuts - Hexagonal - Binx

| Part Number | Thread Size | Thickness (H) mm <i>inches</i> | Width Across Flats (A) mm <i>inches</i> | Material | Type | Pitch in mm / Threads Per Inch mm / No. |
|--------------|-----------------------------|-----------------------------------|---|---------------|------|--|
| BINX-M4 | 4.0mm (M4x0.7 Standard) | 0.700mm / 36.29 TPI | | 304 Stainless | | |
| # BINX-M5 | 5.0mm (M5x0.8 Standard) | 0.800mm / 31.75 TPI | | 304 Stainless | | |
| # BINX-M6 | 6.0mm (M6x1 Standard) | 1.000 mm / 25.4 TPI | | 304 Stainless | | |
| # BINX-M6-A4 | 6.0mm (M6x1 Standard) | 1.000 mm / 25.4 TPI | | 316 Stainless | | |
| # BINX-M8 | 8.0mm (M8x1.25 Standard) | 1.250 mm / 20.32 TPI | | 304 Stainless | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Nuts - Hexagonal - Binx

| Part Number | Thread Size | Thickness (H) mm <i>inches</i> | Width Across Flats (A) mm <i>inches</i> | Material | Type | Pitch in mm / Threads Per Inch mm / No. |
|-------------|-------------------------------|-----------------------------------|---|----------|------|--|
| # BINX-M10 | 10.0mm (M10x1.5) | 1.500 mm / 16.93 TPI | 304 Stainless | | | |
| # BINX-M12 | 12.0mm (M12x1.75 Standard) | 1.750 mm / 14.51 TPI | 304 Stainless | | | |
| # BINX-M16 | 16.0mm (M16x2 Standard) | 2.000 mm / 12.7 TPI | 304 Stainless | | | |
| # BINX-M20 | 20mm (M20x2.5 Standard) | 2.500 mm / 10.16 TPI | 304 Stainless | | | |
| # BINX-M24 | 24.0mm (M24x3 Standard) | 3.000 mm / 8.46 TPI | 304 Stainless | | | |
| # BINX-M30 | 30.0mm (M30x3.5 Standard) | 3.500 mm / 72.6 TPI | 304 Stainless | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

| | | | | | |
|--|--|--|--|--|--|
| | | | | | |
| | | | | | |
| | | | | | |