




MBA

R-Clips - Single Coil



Also known as internal hitch pins or humpback pins

R-Clips - Single Coil

Part Number	Wire Thickness (d) mm	Length (L) mm	Material mm	Drill Hole Size mm	Inside Eye Diameter (D) mm	Shaft Size Range mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
RCL-011-025-Z	1.1 <i>0.043</i>	25 <i>0.984</i>	Zinc Plated	1.19 <i>0.047</i>	6.35 <i>0.250</i>	4.76 to 6.35
RCL-012-015-Z	1.2 <i>0.047</i>	15 <i>0.591</i>	Zinc Plated	1.59 <i>0.063</i>	3.18 <i>0.125</i>	3.18 to 4.76
RCL-012-025-Z	1.2 <i>0.047</i>	25 <i>0.984</i>	Zinc Plated	1.50 <i>0.059</i>	3.50 <i>0.138</i>	5.00 to 8.00
RCL-016-026-Z	1.6 <i>0.063</i>	26 <i>1.024</i>	Zinc Plated	2.00 <i>0.079</i>	5.00 <i>0.197</i>	7.00 to 12.00

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

R-Clips - Single Coil

Part Number	Wire Thickness (d) mm	Length (L) mm	Material mm	Drill Hole Size mm	Inside Eye Diameter (D) mm	Shaft Size Range mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
RCL-016-033-Z	1.6 <i>0.063</i>	33 <i>1.299</i>	Spring Wire, Oil-Tempered	1.98 <i>0.078</i>	7.94 <i>0.313</i>	6.35 to 12.70
RCL-016-040-Z	1.6 <i>0.063</i>	40 <i>1.575</i>	Spring Wire, Oil-Tempered	1.98 <i>0.078</i>	7.94 <i>0.313</i>	9.53 to 12.70
RCL-018-038-Z	1.8 <i>0.071</i>	38 <i>1.496</i>	Zinc Plated	2.20 <i>0.087</i>	7.50 <i>0.295</i>	8.00 to 13.00
RCL-020-030-Z	2 <i>0.079</i>	30 <i>1.181</i>	Spring Wire, Oil-Tempered	2.38 <i>0.094</i>	6.35 <i>0.250</i>	6.35 to 9.53
RCL-020-040-Z	2 <i>0.079</i>	40 <i>1.575</i>	Spring Wire, Oil-Tempered	2.38 <i>0.094</i>	7.94 <i>0.313</i>	9.53 to 12.70
# RCL-020-047-4	2 <i>0.079</i>	40 <i>1.575</i>	304 Stainless Steel			
RCL-020-057-Z	2 <i>0.079</i>	57 <i>2.244</i>	Zinc Plated	2.50 <i>0.098</i>	10.00 <i>0.394</i>	9.00 to 14.00
RCL-024-041-Z	2.4 <i>0.094</i>	41 <i>1.614</i>	Zinc Plated	2.78 <i>0.109</i>	9.53 <i>0.375</i>	6.35 to 12.70
RCL-024-059-Z	2.4 <i>0.094</i>	59 <i>2.323</i>	Spring Wire, Oil-Tempered	2.78 <i>0.109</i>	15.88 <i>0.625</i>	6.35 to 15.88

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

R-Clips - Single Coil

Part Number	Wire Thickness (d) mm	Length (L) mm	Material mm	Drill Hole Size mm	Inside Eye Diameter (D) mm	Shaft Size Range mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
RCL-024-064-Z	2.4 <i>0.094</i>	64 <i>2.520</i>	Spring Wire, Oil-Tempered	2.78 <i>0.109</i>	11.11 <i>0.437</i>	9.53 to 19.05
# RCL-025-065-4	2.5 <i>0.098</i>	65 <i>2.559</i>	304 Stainless Steel			
# RCL-030-072-4	3 <i>0.118</i>	71.6 <i>2.819</i>	304 Stainless Steel			
RCL-030-072-Z	3 <i>0.118</i>	72 <i>2.835</i>	Zinc Plated	3.50 <i>0.138</i>	18.00 <i>0.709</i>	10.00 to 16.00
RCL-032-065-Z	3.2 <i>0.126</i>	65 <i>2.559</i>	Zinc Plated	3.57 <i>0.141</i>	14.29 <i>0.563</i>	11.11 to 19.05
# RCL-035-065-Z	3.5 <i>0.138</i>	65 <i>2.559</i>	Zinc Plated	3.97 <i>0.156</i>	15.88 <i>0.625</i>	12.70 to 19.05
# RCL-038-075-Z	3.8 <i>0.150</i>	75 <i>2.953</i>	Zinc Plated			
RCL-040-074-Z	4 <i>0.157</i>	74 <i>2.913</i>	Zinc Plated	4.50 <i>0.177</i>	20.00 <i>0.787</i>	16.00 to 20.00
# RCL-040-086-4	4 <i>0.157</i>	86 <i>3.386</i>	304 Stainless Steel			
# RCL-045-083-Z	4.5 <i>0.177</i>	83 <i>3.268</i>	Zinc Plated			

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

R-Clips - Single Coil

Part Number	Wire Thickness (d) mm <i>inches</i>	Length (L) mm <i>inches</i>	Material mm <i>inches</i>	Drill Hole Size mm <i>inches</i>	Inside Eye Diameter (D) mm <i>inches</i>	Shaft Size Range mm <i>inches</i>
# RCL-050-096-Z	5 <i>0.197</i>	96 <i>3.780</i>	Zinc Plated			
# RCL-050-098-4	5 <i>0.197</i>	98 <i>3.858</i>	304 Stainless Steel			
# RCL-050-102-Z	5 <i>0.197</i>	102 <i>4.016</i>	Zinc Plated	6.00 <i>0.236</i>	24.00 <i>0.945</i>	20.00 to 28.00
# RCL-060-108-4	6 <i>0.236</i>	108.3 <i>4.264</i>	304 Stainless Steel			
# RCL-060-126-Z	6 <i>0.236</i>	126 <i>4.961</i>	Zinc Plated	7.00 <i>0.276</i>	30.00 <i>1.181</i>	28.00 to 40.00
# RCL-062-102-Z	6.2 <i>0.244</i>	102 <i>4.016</i>	Zinc Plated			
# RCL-070-104-Z	7 <i>0.276</i>	104 <i>4.094</i>	Zinc Plated			
# RCL-070-127-Z	7 <i>0.276</i>	127 <i>5.000</i>	Zinc Plated	8.00 <i>0.315</i>	30.00 <i>1.181</i>	28.00 to 45.00
# RCL-079-104-Z	7.9 <i>0.311</i>	104 <i>4.094</i>	Zinc Plated			
# RCL-080-132-Z	8 <i>0.315</i>	132 <i>5.197</i>	Zinc Plated	9.00 <i>0.354</i>	28.00 <i>1.102</i>	30.00 to 45.00

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

