




MBA

Rail Supports - With Shaft



Includes shaft.

Includes shaft to h6 tolerances.

Rail Supports - With Shaft

Part Number	Shaft Size (d) mm	Height to Shaft Centre (H) mm	Length (+0/- 1.59mm) mm	Foot Height (V) mm	Base Width (A) mm	Support Angle (a) Deg	Hole Spacing (T) mm	Base Mtg. Hole (U) mm	Shaft Mtg. Hole (O) mm	Bolt Hole Centres (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# WU50-012T2ZA	12.0 <i>0.472</i>	22.0 <i>0.866</i>	600.0 <i>23.622</i>	5.0 <i>0.197</i>	40.0 <i>1.575</i>	50.0	120.0 <i>4.724</i>	4.5 <i>0.177</i>	4.5 <i>0.177</i>	29.0 <i>1.142</i>
# WU50-012T1ZA	12.0 <i>0.472</i>	22.0 <i>0.866</i>	600.0 <i>23.622</i>	5.0 <i>0.197</i>	40.0 <i>1.575</i>	50.0	75.0 <i>2.953</i>	4.5 <i>0.177</i>	4.5 <i>0.177</i>	29.0 <i>1.142</i>
# WU50-016T1ZA	16.0 <i>0.630</i>	26.0 <i>1.024</i>	600.0 <i>23.622</i>	5.0 <i>0.197</i>	45.0 <i>1.772</i>	50.0	100.0 <i>3.937</i>	5.5 <i>0.217</i>	5.5 <i>0.217</i>	33.0 <i>1.299</i>
# WU50-016T2ZA	16.0 <i>0.630</i>	26.0 <i>1.024</i>	600.0 <i>23.622</i>	5.0 <i>0.197</i>	45.0 <i>1.772</i>	50.0	150.0 <i>5.906</i>	5.5 <i>0.217</i>	5.5 <i>0.217</i>	33.0 <i>1.299</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rail Supports - With Shaft

Part Number	Shaft Size (d) mm	Height to Shaft Centre (H) mm	Length (+0/- 1.59mm) mm	Foot Height (V) mm	Base Width (A) mm	Support Angle (a) Deg	Hole Spacing (T) mm	Base Mtg. Hole (U) mm	Shaft Mtg. Hole (O) mm	Bolt Hole Centres (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# WU50-020T1ZA	20.0 <i>0.787</i>	32.0 <i>1.260</i>	600.0 <i>23.622</i>	6.0 <i>0.236</i>	52.0 <i>2.047</i>	50.0	100.0 <i>3.937</i>	6.6 <i>0.260</i>	6.6 <i>0.260</i>	37.0 <i>1.457</i>
# WU50-020T2ZA	20.0 <i>0.787</i>	32.0 <i>1.260</i>	600.0 <i>23.622</i>	6.0 <i>0.236</i>	52.0 <i>2.047</i>	50.0	150.0 <i>5.906</i>	6.6 <i>0.260</i>	6.6 <i>0.260</i>	37.0 <i>1.457</i>
# WU50-025T2ZA	25.0 <i>0.984</i>	36.0 <i>1.417</i>	600.0 <i>23.622</i>	6.0 <i>0.236</i>	57.0 <i>2.244</i>	50.0	200.0 <i>7.874</i>	6.6 <i>0.260</i>	9.0 <i>0.354</i>	42.0 <i>1.654</i>
# WU50-025T1ZA	25.0 <i>0.984</i>	36.0 <i>1.417</i>	600.0 <i>23.622</i>	6.0 <i>0.236</i>	57.0 <i>2.244</i>	50.0	120.0 <i>4.724</i>	6.6 <i>0.260</i>	9.0 <i>0.354</i>	42.0 <i>1.654</i>
# WU50-030T2ZA	30.0 <i>1.181</i>	42.0 <i>1.654</i>	600.0 <i>23.622</i>	7.0 <i>0.276</i>	69.0 <i>2.717</i>	50.0	200.0 <i>7.874</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	51.0 <i>2.008</i>
# WU50-030T1ZA	30.0 <i>1.181</i>	42.0 <i>1.654</i>	600.0 <i>23.622</i>	7.0 <i>0.276</i>	69.0 <i>2.717</i>	50.0	150.0 <i>5.906</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	51.0 <i>2.008</i>
# WU50-040T1ZA	40.0 <i>1.575</i>	50.0 <i>1.969</i>	600.0 <i>23.622</i>	8.0 <i>0.315</i>	73.0 <i>2.874</i>	50.0	200.0 <i>7.874</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	55.0 <i>2.165</i>
# WU50-040T2ZA	40.0 <i>1.575</i>	50.0 <i>1.969</i>	600.0 <i>23.622</i>	8.0 <i>0.315</i>	73.0 <i>2.874</i>	50.0	300.0 <i>11.811</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	55.0 <i>2.165</i>
# WU50-050T1ZA	50.0 <i>1.969</i>	60.0 <i>2.362</i>	600.0 <i>23.622</i>	9.0 <i>0.354</i>	84.0 <i>3.307</i>	46.0	200.0 <i>7.874</i>	11.0 <i>0.433</i>	13.0 <i>0.512</i>	62.0 <i>2.441</i>
# WU50-050T2ZA	50.0 <i>1.969</i>	60.0 <i>2.362</i>	600.0 <i>23.622</i>	9.0 <i>0.354</i>	84.0 <i>3.307</i>	46.0	300.0 <i>11.811</i>	11.0 <i>0.433</i>	13.0 <i>0.512</i>	62.0 <i>2.441</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rail Supports - With Shaft

Part Number	Shaft Size (d) mm	Height to Shaft Centre (H) mm	Length (+0/- 1.59mm) mm	Foot Height (V) mm	Base Width (A) mm	Support Angle (a) Deg	Hole Spacing (T) mm	Base Mtg. Hole (U) mm	Shaft Mtg. Hole (O) mm	Bolt Hole Centres (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# WU50-060T1ZA	60.0 <i>2.362</i>	68.0 <i>2.677</i>	600.0 <i>23.622</i>	10.0 <i>0.394</i>	94.0 <i>3.701</i>	46.0	300.0 <i>11.811</i>	11.0 <i>0.433</i>	15.0 <i>0.591</i>	72.0 <i>2.835</i>
# WU50-080T1ZA	80.0 <i>3.150</i>	86.0 <i>3.386</i>	600.0 <i>23.622</i>	12.0 <i>0.472</i>	116.0 <i>4.567</i>	46.0	300.0 <i>11.811</i>	13.0 <i>0.512</i>	17.0 <i>0.669</i>	92.0 <i>3.622</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

