




MBA

Rail Supports - Without Shaft



For mounting of shafting.

Shafting sold separately.

Rail Supports - Without Shaft

Part Number	Suits Nom. Shaft Size (d) mm	Height to Shaft Centre (H) mm	Length (+0/-1.59mm) mm	Foot Height (V) mm	Base Width (A) mm	Support Angle (a) Deg	Hole Spacing (T) mm	Base Mtg. Hole (U) mm	Shaft Mtg. Hole (O) mm	Bolt Hole Centres (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# WU50-012	12.00 <i>0.472</i>	22 <i>0.866</i>	600.0 <i>23.622</i>	5.00 <i>0.197</i>	40.0 <i>1.575</i>	50	Undrilled	Undrilled	Undrilled	Undrilled
# WU50-012T1	12.0 <i>0.472</i>	22.0 <i>0.866</i>	600.0 <i>23.622</i>	5.0 <i>0.197</i>	40.0 <i>1.575</i>	50.0	75.0 <i>2.953</i>	4.5 <i>0.177</i>	4.5 <i>0.177</i>	29.0 <i>1.142</i>
# WU50-012T2	12.0 <i>0.472</i>	22.0 <i>0.866</i>	600.0 <i>23.622</i>	5.0 <i>0.197</i>	40.0 <i>1.575</i>	50.0	120.0 <i>4.724</i>	4.5 <i>0.177</i>	4.5 <i>0.177</i>	29.0 <i>1.142</i>
# SH-SUP-12.700x610	12.700 <i>0.500</i>	28.575 <i>1.125</i>	609.600 <i>24.000</i>	4.8 <i>0.189</i>	38.1 <i>1.500</i>	Straight 6.4mm Wide	101.6 <i>4.000</i>	Extruded Aluminium	6UNC x 22.225	25.40 <i>1.000</i>

Indicates item not stocked at time of printing - Please enquire for lead time
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rail Supports - Without Shaft

Part Number	Suits Nom. Shaft Size (d) mm	Height to Shaft Centre (H) mm	Length (+0/-1.59mm) mm	Foot Height (V) mm	Base Width (A) mm	Support Angle (a) Deg	Hole Spacing (T) mm	Base Mtg. Hole (U) mm	Shaft Mtg. Hole (O) mm	Bolt Hole Centres (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# SH-SUP-15.875x610	15.875	28.575	609.600	6.4	41.3	Straight 7.9mm Wide	101.6	Extruded Aluminium	8 UNC x 22.225	28.58
	<i>0.625</i>	<i>1.125</i>	<i>24.000</i>	<i>0.252</i>	<i>1.626</i>		<i>4.000</i>			<i>1.125</i>
# WU50-016	16.00	26	600.0	5.00	45.0	50	Undrilled	Undrilled	Undrilled	Undrilled
	<i>0.630</i>	<i>1.024</i>	<i>23.622</i>	<i>0.197</i>	<i>1.772</i>					
# WU50-016T1	16.0	26.0	600.0	5.0	45.0	50.0	100.0	5.5	5.5	33.0
	<i>0.630</i>	<i>1.024</i>	<i>23.622</i>	<i>0.197</i>	<i>1.772</i>		<i>3.937</i>	<i>0.217</i>	<i>0.217</i>	<i>1.299</i>
# WU50-016T2	16.0	26.0	600.0	5.0	45.0	50.0	150.0	5.5	5.5	33.0
	<i>0.630</i>	<i>1.024</i>	<i>23.622</i>	<i>0.197</i>	<i>1.772</i>		<i>5.906</i>	<i>0.217</i>	<i>0.217</i>	<i>1.299</i>
# SH-SUP-19.050x610	19.050	38.1	609.600	6.4	44.5	Straight 9.5mm Wide	152.4	Extruded Aluminium	10 UNF x 31.750	31.75
	<i>0.750</i>	<i>1.500</i>	<i>24.000</i>	<i>0.252</i>	<i>1.752</i>		<i>6.000</i>			<i>1.250</i>
# WU50-020T2	20.0	32.0	600.0	6.0	52.0	50.0	150.0	6.6	6.6	37.0
	<i>0.787</i>	<i>1.260</i>	<i>23.622</i>	<i>0.236</i>	<i>2.047</i>		<i>5.906</i>	<i>0.260</i>	<i>0.260</i>	<i>1.457</i>
# WU50-020	20.00	32	600.0	6.00	52.0	50	Undrilled	Undrilled	Undrilled	Undrilled
	<i>0.787</i>	<i>1.260</i>	<i>23.622</i>	<i>0.236</i>	<i>2.047</i>					
# WU50-020T1	20.0	32.0	600.0	6.0	52.0	50.0	100.0	6.6	6.6	37.0
	<i>0.787</i>	<i>1.260</i>	<i>23.622</i>	<i>0.236</i>	<i>2.047</i>		<i>3.937</i>	<i>0.260</i>	<i>0.260</i>	<i>1.457</i>
# WU50-025T1	25.0	36.0	600.0	6.0	57.0	50.0	120.0	6.6	9.0	42.0
	<i>0.984</i>	<i>1.417</i>	<i>23.622</i>	<i>0.236</i>	<i>2.244</i>		<i>4.724</i>	<i>0.260</i>	<i>0.354</i>	<i>1.654</i>
# WU50-025T2	25.0	36.0	600.0	6.0	57.0	50.0	200.0	6.6	9.0	42.0
	<i>0.984</i>	<i>1.417</i>	<i>23.622</i>	<i>0.236</i>	<i>2.244</i>		<i>7.874</i>	<i>0.260</i>	<i>0.354</i>	<i>1.654</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rail Supports - Without Shaft

Part Number	Suits Nom. Shaft Size (d) mm	Height to Shaft Centre (H) mm	Length (+0/-1.59mm) mm	Foot Height (V) mm	Base Width (A) mm	Support Angle (a) Deg	Hole Spacing (T) mm	Base Mtg. Hole (U) mm	Shaft Mtg. Hole (O) mm	Bolt Hole Centres (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# WU50-025	25.00 <i>0.984</i>	36 <i>1.417</i>	600.0 <i>23.622</i>	6.00 <i>0.236</i>	57.0 <i>2.244</i>	50	Undrilled	Undrilled	Undrilled	Undrilled
# SH-SUP-25.400x610	25.400 <i>1.000</i>	44.450 <i>1.750</i>	609.600 <i>24.000</i>	6.4 <i>0.252</i>	54.0 <i>2.126</i>	Straight 12.7mm Wide	152.4 <i>6.000</i>	Extruded Aluminium	1/4 UNC x 38.100	38.10 <i>1.500</i>
# WU50-030	30.00 <i>1.181</i>	42 <i>1.654</i>	600.0 <i>23.622</i>	7.00 <i>0.276</i>	69.0 <i>2.717</i>	50	Undrilled	Undrilled	Undrilled	Undrilled
# WU50-030T1	30.0 <i>1.181</i>	42.0 <i>1.654</i>	600.0 <i>23.622</i>	7.0 <i>0.276</i>	69.0 <i>2.717</i>	50.0	150.0 <i>5.906</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	51.0 <i>2.008</i>
# WU50-030T2	30.0 <i>1.181</i>	42.0 <i>1.654</i>	600.0 <i>23.622</i>	7.0 <i>0.276</i>	69.0 <i>2.717</i>	50.0	200.0 <i>7.874</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	51.0 <i>2.008</i>
# SH-SUP-31.750x610	31.750 <i>1.250</i>	53.975 <i>2.125</i>	609.600 <i>24.000</i>	7.9 <i>0.311</i>	63.5 <i>2.500</i>	Straight 14.3mm Wide	152.4 <i>6.000</i>	Extruded Aluminium	5/16 UNC x 44.450	47.63 <i>1.875</i>
# WU50-040T2	40.0 <i>1.575</i>	50.0 <i>1.969</i>	600.0 <i>23.622</i>	8.0 <i>0.315</i>	73.0 <i>2.874</i>	50.0	300.0 <i>11.811</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	55.0 <i>2.165</i>
# WU50-040	40.00 <i>1.575</i>	50 <i>1.969</i>	600.0 <i>23.622</i>	8.00 <i>0.315</i>	73.0 <i>2.874</i>	50	Undrilled	Undrilled	Undrilled	Undrilled
# WU50-040T1	40.0 <i>1.575</i>	50.0 <i>1.969</i>	600.0 <i>23.622</i>	8.0 <i>0.315</i>	73.0 <i>2.874</i>	50.0	200.0 <i>7.874</i>	9.0 <i>0.354</i>	11.0 <i>0.433</i>	55.0 <i>2.165</i>
# WU50-050T2	50.0 <i>1.969</i>	60.0 <i>2.362</i>	600.0 <i>23.622</i>	9.0 <i>0.354</i>	84.0 <i>3.307</i>	46.0	300.0 <i>11.811</i>	11.0 <i>0.433</i>	13.0 <i>0.512</i>	62.0 <i>2.441</i>

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rail Supports - Without Shaft

Part Number	Suits Nom. Shaft Size (d) mm	Height to Shaft Centre (H) mm	Length (+0/-1.59mm) mm	Foot Height (V) mm	Base Width (A) mm	Support Angle (a) Deg	Hole Spacing (T) mm	Base Mtg. Hole (U) mm	Shaft Mtg. Hole (O) mm	Bolt Hole Centres (E) mm
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
# WU50-050	50.00 <i>1.969</i>	60 <i>2.362</i>	600.0 <i>23.622</i>	9.00 <i>0.354</i>	84.0 <i>3.307</i>	46	Undrilled	Undrilled	Undrilled	Undrilled
# WU50-050T1	50.0 <i>1.969</i>	60.0 <i>2.362</i>	600.0 <i>23.622</i>	9.0 <i>0.354</i>	84.0 <i>3.307</i>	46.0	200.0 <i>7.874</i>	11.0 <i>0.433</i>	13.0 <i>0.512</i>	62.0 <i>2.441</i>
# WU50-060	60.00 <i>2.362</i>	68 <i>2.677</i>	600.0 <i>23.622</i>	10.00 <i>0.394</i>	94.0 <i>3.701</i>	46	Undrilled	Undrilled	Undrilled	Undrilled
# WU50-060T1	60.0 <i>2.362</i>	68.0 <i>2.677</i>	600.0 <i>23.622</i>	10.0 <i>0.394</i>	94.0 <i>3.701</i>	46.0	300.0 <i>11.811</i>	11.0 <i>0.433</i>	15.0 <i>0.591</i>	72.0 <i>2.835</i>
# WU50-080T1	80.0 <i>3.150</i>	86.0 <i>3.386</i>	600.0 <i>23.622</i>	12.0 <i>0.472</i>	116.0 <i>4.567</i>	46.0	300.0 <i>11.811</i>	13.0 <i>0.512</i>	17.0 <i>0.669</i>	92.0 <i>3.622</i>
# WU50-080	80.00 <i>3.150</i>	86 <i>3.386</i>	600.0 <i>23.622</i>	12.00 <i>0.472</i>	116.0 <i>4.567</i>	46	Undrilled	Undrilled	Undrilled	Undrilled

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

