




MBA

Rod Ends - Plastic



Thermoplastic Body / L280® Polymer Ball.

Dimensions not shown are available on request.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm	Overall Length (L) mm	Head Width (D) mm	Type	Thread Size (T)	Width (W/W1) mm	l1 / l2 mm	D2 / D3 mm	Max. Angle of Pivot Deg.	Max Torque Strength n.m
	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	<i>inches</i>	<i>inches</i>		
# REF-02.00-R-P	2.00	17.00	9.00	Female / Right Hand	M2	3.00 / 4.00	12.50 / 6.00	4.00 / 4.60	30	1.0
	<i>0.079</i>	<i>0.669</i>	<i>0.354</i>							
# REF-02.00-L-P	2.00	17.00	9.00	Female / Left Hand	M2	3.00 / 4.00	12.50 / 6.00	4.00 / 4.60	30	1.0
	<i>0.079</i>	<i>0.669</i>	<i>0.354</i>							
# REF-03.00-L-P	3.00	25.00	13.00	Female / Left Hand	M3	4.50 / 6.00	18.50 / 8.00	6.50 / 8.00	30	2.0
	<i>0.118</i>	<i>0.984</i>	<i>0.512</i>							

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
REF-03.00-R-P	3.00 <i>0.118</i>	25.00 <i>0.984</i>	13.00 <i>0.512</i>	Female / Right Hand	M3	4.50 / 6.00	18.50 / 8.00	6.50 / 8.00	30	2.0
# REF-04.00-L-P-N	4.00 <i>0.157</i>	30.00 <i>1.181</i>	15.00 <i>0.591</i>	Female / Left Hand	M4	3.50 / 5.00	22.25 / 9.50	8.00 / 9.20	33	2.0
# REF-04.00-R-P-N	4.00 <i>0.157</i>	30.00 <i>1.181</i>	15.00 <i>0.591</i>	Female / Right Hand	M4	3.50 / 5.00	22.25 / 9.50	8.00 / 9.20	33	2.0
# REF-04.83-R-P	4.83 <i>0.190</i>	34.90 <i>1.374</i>	14.29 <i>0.563</i>	Female / Right Hand	10-32	5.94 / 7.92	26.97 / 12.70	10.31 / 12.70	25	2.0
# REF-04.83-L-P	4.83 <i>0.190</i>	34.90 <i>1.374</i>	14.29 <i>0.563</i>	Female / Left Hand	10-32	5.94 / 7.92	26.97 / 12.70	10.31 / 12.70	25	2.0
# REM-04.83-R-P	4.83 <i>0.190</i>	39.70 <i>1.563</i>	15.88 <i>0.625</i>	Male / Right Hand	10-32	5.94 / 7.92	31.75 / 19.05		25	3.0
# REM-04.83-L-P	4.83 <i>0.190</i>	39.70 <i>1.563</i>	15.88 <i>0.625</i>	Male / Left Hand	10-32	5.94 / 7.92	31.75 / 19.05		25	3.0
# REF-05.00-M4R-P	5.00 <i>0.197</i>	36.00 <i>1.417</i>	13.00 <i>0.512</i>	Female / Right Hand	M4	6.00 / 8.00	27.00 / 10.00	9.00 / 12.00	30	5.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-05.00-M4L-P	5.00 <i>0.197</i>	36.00 <i>1.417</i>	13.00 <i>0.512</i>	Female / Left Hand	M4	6.00 / 8.00	28.00 / 10.00	9.00 / 12.00	30	5.0
REF-05.00-R-P	5.00 <i>0.197</i>	36.00 <i>1.417</i>	18.00 <i>0.709</i>	Female / Right Hand	M5	6.00 / 8.00	27.00 / 10.00	9.00 / 12.00	30	5.0
# REF-05.00-L-P	5.00 <i>0.197</i>	36.00 <i>1.417</i>	18.00 <i>0.709</i>	Female / Left Hand	M5	6.00 / 8.00	27.00 / 10.00	9.00 / 12.00	30	5.0
# REF-05.00-L-P-N	5.00 <i>0.197</i>	39.50 <i>1.555</i>	19.00 <i>0.748</i>	Female / Left Hand	M5	4.40 / 6.00	30.00 / 12.00	9.00 / 11.00	33	2.0
# REF-05.00-R-P-N	5.00 <i>0.197</i>	39.50 <i>1.555</i>	19.00 <i>0.748</i>	Female / Right Hand	M5	4.40 / 6.00	30.00 / 12.00	9.00 / 11.00	33	2.0
REM-05.00-R-P	5.00 <i>0.197</i>	42.00 <i>1.654</i>	18.00 <i>0.709</i>	Male / Right Hand	M5	6.00 / 8.00	33.00 <i>1.299</i>	19.00 <i>0.748</i>	30	5.0
# REM-05.00-L-P	5.00 <i>0.197</i>	42.00 <i>1.654</i>	18.00 <i>0.709</i>	Male / Left Hand	M5	6.00 / 8.00	33.00 <i>1.299</i>	19.00 <i>0.748</i>	30	5.0
# REM-05.00-R-P-N	5.00 <i>0.197</i>	45.50 <i>1.791</i>	19.00 <i>0.748</i>	Male / Right Hand	M5	4.40 / 6.00	36.00 <i>1.417</i>	20.00 <i>0.787</i>	33	2.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-05.00-L-P-N	5.00 <i>0.197</i>	45.50 <i>1.791</i>	19.00 <i>0.748</i>	Male / Left Hand	M5	4.40 / 6.00	36.00 <i>1.417</i>	20.00 <i>0.787</i>	33	2.0
REF-06.00-R-P	6.00 <i>0.236</i>	40.00 <i>1.575</i>	20.00 <i>0.787</i>	Female / Right Hand	M6	7.00 / 9.00	30.00 / 12.00	10.00 / 13.00	29	10.0
# REF-06.00-L-P	6.00 <i>0.236</i>	40.00 <i>1.575</i>	20.00 <i>0.787</i>	Female / Left Hand	M6	7.00 / 9.00	30.00 / 12.00	10.00 / 13.00	29	10.0
# REF-06.00-R-P-N	6.00 <i>0.236</i>	40.50 <i>1.594</i>	21.00 <i>0.827</i>	Female / Right Hand	M6	4.40 / 6.00	30.00 / 12.00	11.00 / 13.00	27	2.5
# REF-06.00-L-P-N	6.00 <i>0.236</i>	40.50 <i>1.594</i>	21.00 <i>0.827</i>	Female / Left Hand	M6	4.40 / 6.00	30.00 / 12.00	11.00 / 13.00	27	2.5
# REM-06.00-R-P	6.00 <i>0.236</i>	46.00 <i>1.811</i>	20.00 <i>0.787</i>	Male / Right Hand	M6	7.00 / 9.00	36.00 <i>1.417</i>	21.00 <i>0.827</i>	29	10.0
# REM-06.00-L-P	6.00 <i>0.236</i>	46.00 <i>1.811</i>	20.00 <i>0.787</i>	Male / Left Hand	M6	7.00 / 9.00	36.00 <i>1.417</i>	21.00 <i>0.827</i>	29	10.0
# REM-06.00-R-P-N	6.00 <i>0.236</i>	46.50 <i>1.831</i>	21.00 <i>0.827</i>	Male / Right Hand	M6	4.40 / 6.00	36.00 <i>1.417</i>	20.00 <i>0.787</i>	27	2.5

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm	Overall Length (L) mm	Head Width (D) mm	Type	Thread Size (T)	Width (W/W1) mm	I1 / I2 mm	D2 / D3 mm	Max. Angle of Pivot Deg.	Max Torque Strength n.m
	<i>inches</i>	<i>inches</i>	<i>inches</i>			<i>inches</i>	<i>inches</i>	<i>inches</i>		
# REM-06.00-L-P-N	6.00	46.50	21.00	Male / Left Hand	M6	4.40 / 6.00	36.00	20.00	27	2.5
	<i>0.236</i>	<i>1.831</i>	<i>0.827</i>				<i>1.417</i>	<i>0.787</i>		
# REF-06.35-R-P	6.35	42.85	16.67	Female / Right Hand	1/4-28	6.35 / 9.27	33.32 / 17.45	11.91 / 17.45	25	5.0
	<i>0.250</i>	<i>1.687</i>	<i>0.656</i>							
# REF-06.35-L-P	6.35	42.85	16.67	Female / Left Hand	1/4-28	6.35 / 9.27	33.32 / 17.45	11.91 / 17.45	25	5.0
	<i>0.250</i>	<i>1.687</i>	<i>0.656</i>							
# REM-06.35-R-P	6.35	49.20	19.05	Male / Right Hand	1/4-28	6.35 / 9.27	39.67	25.40	25	4.0
	<i>0.250</i>	<i>1.937</i>	<i>0.750</i>				<i>1.562</i>	<i>1.000</i>		
# REM-06.35-L-P	6.35	49.20	19.05	Male / Left Hand	1/4-28	6.35 / 9.27	39.67	25.40	25	4.0
	<i>0.250</i>	<i>1.937</i>	<i>0.750</i>				<i>1.562</i>	<i>1.000</i>		
# REF-07.94-R-P	7.94	46.05	19.05	Female / Right Hand	5/16-24	7.92 / 11.10	34.93 / 17.45	12.70 / 17.45	25	6.0
	<i>0.313</i>	<i>1.813</i>	<i>0.750</i>							
# REF-07.94-L-P	7.94	46.05	19.05	Female / Left Hand	5/16-24	7.92 / 11.10	34.93 / 17.45	12.70 / 17.45	25	6.0
	<i>0.313</i>	<i>1.813</i>	<i>0.750</i>							
# REM-07.94-R-P	7.94	58.75	22.23	Male / Right Hand	5/16-24	7.92 / 11.10	47.63	31.75	25	10.0
	<i>0.313</i>	<i>2.313</i>	<i>0.875</i>				<i>1.875</i>	<i>1.250</i>		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-07.94-L-P	7.94 <i>0.313</i>	58.75 <i>2.313</i>	22.23 <i>0.875</i>	Male / Left Hand	5/16-24	7.92 / 11.10	47.63 <i>1.875</i>	31.75 <i>1.250</i>	25	10.0
# REF-08.00-L-P-N	8.00 <i>0.315</i>	48.00 <i>1.890</i>	24.00 <i>0.945</i>	Female / Left Hand	M8	6.00 / 8.00	36.00 / 16.00	13.00 / 16.00	24	7.0
REF-08.00-R-P	8.00 <i>0.315</i>	48.00 <i>1.890</i>	24.00 <i>0.945</i>	Female / Right Hand	M8	9.00 / 12.00	36.00 / 16.00	13.00 / 16.00	25	12.1
# REF-08.00-R-P-N	8.00 <i>0.315</i>	48.00 <i>1.890</i>	24.00 <i>0.945</i>	Female / Right Hand	M8	6.00 / 8.00	36.00 / 16.00	13.00 / 16.00	24	7.0
# REF-08.00-L-P	8.00 <i>0.315</i>	48.00 <i>1.890</i>	24.00 <i>0.945</i>	Female / Left Hand	M8	9.00 / 12.00	36.00 / 16.00	13.00 / 16.00	25	12.1
# REM-08.00-L-P-N	8.00 <i>0.315</i>	53.00 <i>2.087</i>	24.00 <i>0.945</i>	Male / Left Hand	M8	6.00 / 8.00	41.00 <i>1.614</i>	24.00 <i>0.945</i>	24	7.0
# REM-08.00-R-P-N	8.00 <i>0.315</i>	53.00 <i>2.087</i>	24.00 <i>0.945</i>	Male / Right Hand	M8	6.00 / 8.00	41.00 <i>1.614</i>	24.00 <i>0.945</i>	24	7.0
# REM-08.00-L-P	8.00 <i>0.315</i>	55.00 <i>2.165</i>	24.00 <i>0.945</i>	Male / Left Hand	M8	9.00 / 12.00	42.00 <i>1.654</i>	25.00 <i>0.984</i>	25	12.1

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
REM-08.00-R-P	8.00 <i>0.315</i>	55.00 <i>2.165</i>	24.00 <i>0.945</i>	Male / Right Hand	M8	9.00 / 12.00 <i>1.654</i>	42.00 <i>0.984</i>	25.00	25	12.1
# REF-09.53-R-P	9.53 <i>0.375</i>	53.98 <i>2.125</i>	20.64 <i>0.813</i>	Female / Right Hand	3/8-24	9.12 / 12.70	41.28 / 20.62	17.45 / 20.62	22	7.0
# REF-09.53-L-P	9.53 <i>0.375</i>	53.98 <i>2.125</i>	20.64 <i>0.813</i>	Female / Left Hand	3/8-24	9.12 / 12.70	41.28 / 20.62	17.45 / 20.62	22	7.0
# REM-09.53-L-P	9.53 <i>0.375</i>	61.93 <i>2.438</i>	25.40 <i>1.000</i>	Male / Left Hand	3/8-24	9.19 / 12.70 <i>1.938</i>	49.23 <i>1.250</i>	31.75	22	15.0
# REM-09.53-R-P	9.53 <i>0.375</i>	61.93 <i>2.438</i>	25.40 <i>1.000</i>	Male / Right Hand	3/8-24	9.19 / 12.70 <i>1.938</i>	49.23 <i>1.250</i>	31.75	22	15.0
# REF-10.00-L-P-N	10.00 <i>0.394</i>	57.50 <i>2.264</i>	29.00 <i>1.142</i>	Female / Left Hand	M10	7.00 / 9.00	43.00 / 18.00	15.00 / 19.00	24	14.0
# REF-10.00-R-P-N	10.00 <i>0.394</i>	57.50 <i>2.264</i>	29.00 <i>1.142</i>	Female / Right Hand	M10	7.00 / 9.00	43.00 / 18.00	15.00 / 19.00	24	14.0
# REF-10.00-FL-P-N	10.00 <i>0.394</i>	57.57 <i>2.267</i>	29.00 <i>1.142</i>	Female / Left Hand	M10 x 1.25	7.00 / 9.00	43.00 / 18.00	15.00 / 19.00	24	14.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-10.00-FR-P-N	10.00 <i>0.394</i>	57.57 <i>2.267</i>	29.00 <i>1.142</i>	Female / Right Hand	M10 x 1.25	7.00 / 9.00	43.00 / 18.00	15.00 / 19.00	24	14.0
# REF-10.00-L-P	10.00 <i>0.394</i>	58.00 <i>2.283</i>	30.00 <i>1.181</i>	Female / Left Hand	M10	10.50 / 14.00	43.00 / 20.00	15.00 / 19.00	25	20.1
# REF-10.00-FR-P	10.00 <i>0.394</i>	58.00 <i>2.283</i>	30.00 <i>1.181</i>	Female / Right Hand	M10 x 1.25	10.50 / 14.00	43.00 / 20.00	15.00 / 19.00	25	20.0
# REF-10.00-R-P	10.00 <i>0.394</i>	58.00 <i>2.283</i>	30.00 <i>1.181</i>	Female / Right Hand	M10	10.50 / 14.00	43.00 / 20.00	15.00 / 19.00	25	20.1
# REF-10.00-FL-P	10.00 <i>0.394</i>	58.00 <i>2.283</i>	30.00 <i>1.181</i>	Female / Left Hand	M10x1.25	10.50 / 14.00	43.00 / 20.00	15.00 / 19.00	25	20.0
# REM-10.00-R-P-N	10.00 <i>0.394</i>	62.00 <i>2.441</i>	29.00 <i>1.142</i>	Male / Right Hand	M10 x 1.5	7.00 / 9.00	47.00 <i>1.850</i>	27.00 <i>1.063</i>	24	14.0
# REM-10.00-FR-P-N	10.00 <i>0.394</i>	62.00 <i>2.441</i>	29.00 <i>1.142</i>	Male / Right Hand	M10 x 1.25	7.00 / 9.00	47.50 <i>1.870</i>	27.00 <i>1.063</i>	24	14.0
# REM-10.00-FL-P-N	10.00 <i>0.394</i>	62.00 <i>2.441</i>	29.00 <i>1.142</i>	Male / Left Hand	M10 x 1.25	7.00 / 9.00	47.50 <i>1.870</i>	27.00 <i>1.063</i>	24	14.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-10.00-L-P-N	10.00 <i>0.394</i>	62.00 <i>2.441</i>	29.00 <i>1.142</i>	Male / Left Hand	M10 x 1.5	7.00 / 9.00 <i>0.276 / 0.354</i>	47.00 <i>1.850</i>	27.00 <i>1.063</i>	24	14.0
# REM-10.00-L-P	10.00 <i>0.394</i>	63.00 <i>2.480</i>	30.00 <i>1.181</i>	Male / Left Hand	M10 x 1.5	10.50 / 14.00 <i>0.413 / 0.551</i>	48.00 <i>1.890</i>	28.00 <i>1.102</i>	25	20.1
# REM-10.00-FR-P	10.00 <i>0.394</i>	63.00 <i>2.480</i>	30.00 <i>1.181</i>	Male / Right Hand	M10 x 1.25	10.50 / 14.00 <i>0.413 / 0.551</i>	48.00 <i>1.890</i>	28.00 <i>1.102</i>	25	20.0
# REM-10.00-FL-P	10.00 <i>0.394</i>	63.00 <i>2.480</i>	30.00 <i>1.181</i>	Male / Left Hand	M10 x 1.25	10.50 / 14.00 <i>0.413 / 0.551</i>	48.00 <i>1.890</i>	28.00 <i>1.102</i>	25	20.0
REM-10.00-R-P	10.00 <i>0.394</i>	63.00 <i>2.480</i>	30.00 <i>1.181</i>	Male / Right Hand	M10 x 1.5	10.50 / 14.00 <i>0.413 / 0.551</i>	48.00 <i>1.890</i>	28.00 <i>1.102</i>	25	20.1
# REF-11.11-L-P	11.11 <i>0.437</i>	60.30 <i>2.374</i>	23.02 <i>0.906</i>	Female / Left Hand	7/16-20	10.31 / 14.27 <i>0.406 / 0.562</i>	46.02 / 23.80 <i>1.812 / 0.937</i>	19.05 / 23.80 <i>0.750 / 0.937</i>	22	18.0
# REF-11.11-R-P	11.11 <i>0.437</i>	60.30 <i>2.374</i>	23.02 <i>0.906</i>	Female / Right Hand	7/16-20	10.31 / 14.27 <i>0.406 / 0.562</i>	46.02 / 23.80 <i>1.812 / 0.937</i>	19.05 / 23.80 <i>0.750 / 0.937</i>	22	18.0
# REM-11.11-L-P	11.11 <i>0.437</i>	68.28 <i>2.688</i>	28.58 <i>1.125</i>	Male / Left Hand	7/16-20	10.31 / 14.27 <i>0.406 / 0.562</i>	53.98 <i>2.125</i>	34.93 <i>1.375</i>	22	25.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-11.11-R-P	11.11 <i>0.437</i>	68.28 <i>2.688</i>	28.58 <i>1.125</i>	Male / Right Hand	7/16-20	10.31 / 14.27 <i>2.125</i>	53.98 <i>2.125</i>	34.93 <i>1.375</i>	22	25.0
# REF-12.00-R-P-N	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Right Hand	M12	8.00 / 10.00	50.00 / 20.00	18.00 / 22.00	21	25.0
# REF-12.00-R-P	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Right Hand	M12	12.00 / 16.00	50.00 / 22.00	18.00 / 22.00	25	30.0
# REF-12.00-L-P-N	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Left Hand	M12	8.00 / 10.00	50.00 / 20.00	18.00 / 22.00	21	25.0
# REF-12.00-L-P	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Left Hand	M12	12.00 / 16.00	50.00 / 22.00	18.00 / 22.00	25	30.0
# REF-12.00-FL-P	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Left Hand	M12 x 1.25	12.00 / 16.00	50.00 / 22.00	18.00 / 22.00	25	35.0
# REF-12.00-FL-P-N	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Left Hand	M12 x 1.25	8.00 / 10.00	50.00 / 20.00	18.00 / 22.00	21	25.0
# REF-12.00-FR-P	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Right Hand	M12 x 1.25	12.00 / 16.00	50.00 / 22.00	18.00 / 22.00	25	35.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-12.00-FR-P-N	12.00 <i>0.472</i>	67.00 <i>2.638</i>	34.00 <i>1.339</i>	Female / Right Hand	M12 x 1.25	8.00 / 10.00	50.00 / 20.00	18.00 / 22.00	21	25.0
# REM-12.00-FR-P-N	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Right Hand	M12 x 1.25	8.00 / 10.00	54.00 <i>2.126</i>	29.00 <i>1.142</i>	21	25.0
# REM-12.00-R-P	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Right Hand	M12 x 1.75	12.00 / 16.00	54.00 <i>2.126</i>	32.00 <i>1.260</i>	25	30.0
# REM-12.00-FL-P	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Left Hand	M12 x 1.25	12.00 / 16.00	54.00 <i>2.126</i>	32.00 <i>1.260</i>	25	30.0
# REM-12.00-L-P-N	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Left Hand	M12 x 1.75	8.00 / 10.00	54.00 <i>2.126</i>	29.00 <i>1.142</i>	21	25.0
# REM-12.00-L-P	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Left Hand	M12 x 1.75	12.00 / 16.00	54.00 <i>2.126</i>	32.00 <i>1.260</i>	25	30.0
# REM-12.00-FL-P-N	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Left Hand	M12 x 1.25	8.00 / 10.00	54.00 <i>2.126</i>	29.00 <i>1.142</i>	21	25.0
# REM-12.00-FR-P	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Right Hand	M12 x 1.25	12.00 / 16.00	54.00 <i>2.126</i>	32.00 <i>1.260</i>	25	30.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-12.00-R-P-N	12.00 <i>0.472</i>	71.00 <i>2.795</i>	34.00 <i>1.339</i>	Male / Right Hand	M12 x 1.75	8.00 / 10.00	54.00 <i>2.126</i>	29.00 <i>1.142</i>	21	25.0
# REF-12.70-R-P	12.70 <i>0.500</i>	70.64 <i>2.781</i>	25.40 <i>1.000</i>	Female / Right Hand	1/2-20	11.51 / 15.88	53.98 / 26.97	22.23 / 26.97	22	23.0
# REF-12.70-L-P	12.70 <i>0.500</i>	70.64 <i>2.781</i>	25.40 <i>1.000</i>	Female / Left Hand	1/2-20	11.51 / 15.88	53.98 / 26.97	22.23 / 26.97	22	23.0
# REM-12.70-L-P	12.70 <i>0.500</i>	78.59 <i>3.094</i>	33.32 <i>1.312</i>	Male / Left Hand	1/2-20	11.51 / 15.88	61.67 <i>2.428</i>	38.10 <i>1.500</i>	22	35.0
# REM-12.70-R-P	12.70 <i>0.500</i>	78.59 <i>3.094</i>	33.32 <i>1.312</i>	Male / Right Hand	1/2-20	11.51 / 15.88	61.67 <i>2.428</i>	38.10 <i>1.500</i>	22	35.0
# REF-14.00-R-P	14.00 <i>0.551</i>	76.00 <i>2.992</i>	38.00 <i>1.496</i>	Female / Right Hand	M14	13.50 / 19.00	57.00 / 25.00	20.00 / 25.00	23	35.0
# REF-14.00-L-P	14.00 <i>0.551</i>	76.00 <i>2.992</i>	38.00 <i>1.496</i>	Female / Left Hand	M14	13.50 / 19.00	57.00 / 25.00	20.00 / 25.00	23	35.0
# REM-14.00-L-P	14.00 <i>0.551</i>	79.00 <i>3.110</i>	38.00 <i>1.496</i>	Male / Left Hand	M14	13.50 / 19.00	61.00 <i>2.402</i>	36.00 <i>1.417</i>	25	35.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-14.00-R-P	14.00 <i>0.551</i>	79.00 <i>3.110</i>	38.00 <i>1.496</i>	Male / Right Hand	M14	13.50 / 19.00 <i>0.531 / 0.748</i>	61.00 <i>2.402</i>	36.00 <i>1.417</i>	25	35.0
# REF-15.00-R-P-N	15.00 <i>0.591</i>	81.00 <i>3.189</i>	40.00 <i>1.575</i>	Female / Right Hand	M14	10.00 / 12.00	61.00 / 26.00	21.00 / 26.00	21	30.0
# REF-15.00-L-P-N	15.00 <i>0.591</i>	81.00 <i>3.189</i>	40.00 <i>1.575</i>	Female / Left Hand	M14	10.00 / 12.00	61.00 / 26.00	21.00 / 26.00	21	30.0
# REM-15.00-L-P-N	15.00 <i>0.591</i>	83.00 <i>3.268</i>	40.00 <i>1.575</i>	Male / Left Hand	M14	10.00 / 12.00	63.00 <i>2.480</i>	34.00 <i>1.339</i>	21	30.0
# REM-15.00-R-P-N	15.00 <i>0.591</i>	83.00 <i>3.268</i>	40.00 <i>1.575</i>	Male / Right Hand	M14	10.00 / 12.00	63.00 <i>2.480</i>	34.00 <i>1.339</i>	21	30.0
# REF-15.88-L-P	15.88 <i>0.625</i>	82.55 <i>3.250</i>	28.58 <i>1.125</i>	Female / Left Hand	5/8-18	11.79 / 19.05	63.50 / 34.93	25.40 / 34.93	22	30.0
# REF-15.88-R-P	15.88 <i>0.625</i>	82.55 <i>3.250</i>	28.58 <i>1.125</i>	Female / Right Hand	5/8-18	11.79 / 19.05	63.50 / 34.93	25.40 / 34.93	22	30.0
# REM-15.88-L-P	15.88 <i>0.625</i>	85.73 <i>3.375</i>	38.10 <i>1.500</i>	Male / Left Hand	5/8-18	12.29 / 19.05	66.68 <i>2.625</i>	41.28 <i>1.625</i>	22	50.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-15.88-R-P	15.88 <i>0.625</i>	85.73 <i>3.375</i>	38.10 <i>1.500</i>	Male / Right Hand	5/8-18	12.29 / 19.05	66.68 <i>2.625</i>	41.28 <i>1.625</i>	22	50.0
# REF-16.00-R-P	16.00 <i>0.630</i>	85.00 <i>3.346</i>	42.00 <i>1.654</i>	Female / Right Hand	M16	15.00 / 21.00	64.00 / 28.00	22.00 / 27.00	23	40.0
# REF-16.00-L-P	16.00 <i>0.630</i>	85.00 <i>3.346</i>	42.00 <i>1.654</i>	Female / Left Hand	M16	15.00 / 21.00	64.00 / 28.00	22.00 / 27.00	23	40.0
# REM-16.00-L-P	16.00 <i>0.630</i>	88.00 <i>3.465</i>	42.00 <i>1.654</i>	Male / Left Hand	M16	15.00 / 21.00	66.00 <i>2.598</i>	37.00 <i>1.457</i>	23	40.0
REM-16.00-FR-P	16.00 <i>0.630</i>	88.00 <i>3.465</i>	42.00 <i>1.654</i>	Male / Right Hand	M16 x 1.50	15.00 / 21.00	66.00 <i>2.598</i>	37.00 <i>1.457</i>	23	40.0
# REM-16.00-FL-P	16.00 <i>0.630</i>	88.00 <i>3.465</i>	42.00 <i>1.654</i>	Male / Left Hand	M16 x 1.50	15.00 / 21.00	66.00 <i>2.598</i>	37.00 <i>1.457</i>	23	40.0
# REM-16.00-R-P	16.00 <i>0.630</i>	88.00 <i>3.465</i>	42.00 <i>1.654</i>	Male / Right Hand	M16	15.00 / 21.00	66.00 <i>2.598</i>	37.00 <i>1.457</i>	23	40.0
# REF-17.00-R-P-N	17.00 <i>0.669</i>	90.00 <i>3.543</i>	46.00 <i>1.811</i>	Female / Right Hand	M16	11.00 / 14.00	67.00 / 27.00	24.00 / 30.00	21	35.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-17.00-L-P-N	17.00 <i>0.669</i>	90.00 <i>3.543</i>	46.00 <i>1.811</i>	Female / Left Hand	M16	11.00 / 14.00	67.00 / 27.00	24.00 / 30.00	21	35.0
# REF-17.00-FR-P-N	17.00 <i>0.669</i>	90.00 <i>3.543</i>	46.00 <i>1.811</i>	Female / Right Hand	M16 x 1.50	11.00 / 14.00	67.00 / 27.00	24.00 / 30.00	18	35.0
# REF-17.00-FL-P-N	17.00 <i>0.669</i>	90.00 <i>3.543</i>	46.00 <i>1.811</i>	Female / Left Hand	M16 x 1.50	11.00 / 14.00	67.00 / 27.00	24.00 / 30.00	18	35.0
# REM-17.00-FR-P-N	17.00 <i>0.669</i>	92.00 <i>3.622</i>	46.00 <i>1.811</i>	Male / Right Hand	M16 x 1.50	11.00 / 14.00	69.00 <i>2.717</i>	37.00 <i>1.457</i>	18	35.0
# REM-17.00-R-P-N	17.00 <i>0.669</i>	92.00 <i>3.622</i>	46.00 <i>1.811</i>	Male / Right Hand	M16	11.00 / 14.00	69.00 <i>2.717</i>	37.00 <i>1.457</i>	21	35.0
# REM-17.00-FL-P-N	17.00 <i>0.669</i>	92.00 <i>3.622</i>	46.00 <i>1.811</i>	Male / Left Hand	M16 x 1.50	11.00 / 14.00	69.00 <i>2.717</i>	37.00 <i>1.457</i>	18	35.0
# REM-17.00-L-P-N	17.00 <i>0.669</i>	92.00 <i>3.622</i>	46.00 <i>1.811</i>	Male / Left Hand	M16	11.00 / 14.00	69.00 <i>2.717</i>	37.00 <i>1.457</i>	21	35.0
# REF-18.00-L-P	18.00 <i>0.709</i>	94.00 <i>3.701</i>	46.00 <i>1.811</i>	Female / Left Hand	M18 x 1.50	16.50 / 23.00	71.00 / 32.00	25.00 / 31.00	23	45.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-18.00-R-P	18.00 <i>0.709</i>	94.00 <i>3.701</i>	46.00 <i>1.811</i>	Female / Right Hand	M18 x 1.50	16.50 / 23.00	71.00 / 32.00	25.00 / 31.00	23	45.0
# REM-18.00-L-P	18.00 <i>0.709</i>	96.00 <i>3.780</i>	46.00 <i>1.811</i>	Male / Left Hand	M18 x 1.50	16.50 / 23.00	72.00 <i>2.835</i>	41.00 <i>1.614</i>	23	45.0
# REM-18.00-R-P	18.00 <i>0.709</i>	96.00 <i>3.780</i>	46.00 <i>1.811</i>	Male / Right Hand	M18 x 1.50	16.50 / 23.00	72.00 <i>2.835</i>	41.00 <i>1.614</i>	23	45.0
# REF-19.05-L-P	19.05 <i>0.750</i>	95.25 <i>3.750</i>	36.51 <i>1.437</i>	Female / Left Hand	3/4-16	15.06 / 22.23	73.03 / 39.67	28.58 / 39.67	22	40.0
# REF-19.05-R-P	19.05 <i>0.750</i>	95.25 <i>3.750</i>	36.51 <i>1.437</i>	Female / Right Hand	3/4-16	15.06 / 22.23	73.03 / 39.67	28.58 / 39.67	22	40.0
# REM-19.05-L-P	19.05 <i>0.750</i>	95.25 <i>3.750</i>	44.45 <i>1.750</i>	Male / Left Hand	3/4-16	15.06 / 22.23	73.03 <i>2.875</i>	44.45 <i>1.750</i>	22	70.0
# REM-19.05-R-P	19.05 <i>0.750</i>	95.25 <i>3.750</i>	44.45 <i>1.750</i>	Male / Right Hand	3/4-16	15.06 / 22.23	73.03 <i>2.875</i>	44.45 <i>1.750</i>	22	70.0
# REF-20.00-FL-P	20.00 <i>0.787</i>	102.00 <i>4.016</i>	50.00 <i>1.969</i>	Female / Left Hand	M20 x 1.50	18.00 / 25.00	77.00 / 33.00	28.00 / 34.00	23	55.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-20.00-FR-P	20.00 <i>0.787</i>	102.00 <i>4.016</i>	50.00 <i>1.969</i>	Female / Right Hand	M20 x 1.50	18.00 / 25.00	77.00 / 33.00	28.00 / 34.00	23	55.0
# REF-20.00-L-P	20.00 <i>0.787</i>	102.00 <i>4.016</i>	50.00 <i>1.969</i>	Female / Left Hand	M20 x 1.50	18.00 / 25.00	77.00 / 33.00	28.00 / 34.00	23	55.0
# REF-20.00-R-P	20.00 <i>0.787</i>	102.00 <i>4.016</i>	50.00 <i>1.969</i>	Female / Right Hand	M20 x 1.50	18.00 / 25.00	77.00 / 33.00	28.00 / 34.00	23	55.0
# REF-20.00-FL-P-N	20.00 <i>0.787</i>	103.50 <i>4.075</i>	53.00 <i>2.087</i>	Female / Left Hand	M20 x 1.50	13.00 / 16.00	77.00 / 31.00	27.00 / 34.00	18	40.0
# REF-20.00-FR-P-N	20.00 <i>0.787</i>	103.50 <i>4.075</i>	53.00 <i>2.087</i>	Female / Right Hand	M20 x 1.50	13.00 / 16.00	77.00 / 31.00	27.00 / 34.00	18	40.0
# REF-20.00-L-P-N	20.00 <i>0.787</i>	103.50 <i>4.075</i>	53.00 <i>2.087</i>	Female / Left Hand	M20	13.00 / 16.00	77.00 / 31.00	27.00 / 34.00	16	40.0
# REF-20.00-R-P-N	20.00 <i>0.787</i>	103.50 <i>4.075</i>	53.00 <i>2.087</i>	Female / Right Hand	M20	13.00 / 16.00	77.00 / 31.00	27.00 / 34.00	16	40.0
REM-20.00-R-P	20.00 <i>0.787</i>	104.00 <i>4.094</i>	50.00 <i>1.969</i>	Male / Right Hand	M20 x 1.50	18.00 / 25.00	78.00 <i>3.071</i>	45.00 <i>1.772</i>	23	55.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REM-20.00-L-P	20.00 <i>0.787</i>	104.00 <i>4.094</i>	50.00 <i>1.969</i>	Male / Left Hand	M20 x 1.50	18.00 / 25.00 <i>0.709 / 0.984</i>	78.00 <i>3.071</i>	45.00 <i>1.772</i>	23	55.0
# REM-20.00-FL-P	20.00 <i>0.787</i>	104.00 <i>4.094</i>	50.00 <i>1.969</i>	Male / Left Hand	M20 x 1.50	18.00 / 25.00 <i>0.709 / 0.984</i>	78.00 <i>3.071</i>	45.00 <i>1.772</i>	23	55.0
# REM-20.00-FR-P	20.00 <i>0.787</i>	104.00 <i>4.094</i>	50.00 <i>1.969</i>	Male / Right Hand	M20 x 1.50	18.00 / 25.00 <i>0.709 / 0.984</i>	78.00 <i>3.071</i>	45.00 <i>1.772</i>	23	55.0
# REM-20.00-FR-P-N	20.00 <i>0.787</i>	106.50 <i>4.193</i>	53.00 <i>2.087</i>	Male / Right Hand	M20 x 1.50	13.00 / 16.00 <i>0.512 / 0.630</i>	78.00 <i>3.071</i>	43.00 <i>1.693</i>	18	40.0
# REM-20.00-L-P-N	20.00 <i>0.787</i>	106.50 <i>4.193</i>	53.00 <i>2.087</i>	Male / Left Hand	M20	13.00 / 16.00 <i>0.512 / 0.630</i>	80.00 <i>3.150</i>	43.00 <i>1.693</i>	16	40.0
# REM-20.00-FL-P-N	20.00 <i>0.787</i>	106.50 <i>4.193</i>	53.00 <i>2.087</i>	Male / Left Hand	M20 x 1.50	13.00 / 16.00 <i>0.512 / 0.630</i>	78.00 <i>3.071</i>	43.00 <i>1.693</i>	18	40.0
# REM-20.00-R-P-N	20.00 <i>0.787</i>	106.50 <i>4.193</i>	53.00 <i>2.087</i>	Male / Right Hand	M20	13.00 / 16.00 <i>0.512 / 0.630</i>	80.00 <i>3.150</i>	43.00 <i>1.693</i>	16	40.0
# REF-22.00-L-P	22.00 <i>0.866</i>	112.00 <i>4.409</i>	56.00 <i>2.205</i>	Female / Left Hand	M22 x 1.50	20.00 / 28.00 <i>0.787 / 1.102</i>	84.00 / 37.00 <i>3.307 / 1.457</i>	30.00 / 37.00 <i>1.181 / 1.457</i>	22	60.1

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-22.00-R-P	22.00 <i>0.866</i>	112.00 <i>4.409</i>	56.00 <i>2.205</i>	Female / Right Hand	M22 x 1.50	20.00 / 28.00	84.00 / 37.00	30.00 / 37.00	22	60.1
# REM-22.00-R-P	22.00 <i>0.866</i>	112.00 <i>4.409</i>	56.00 <i>2.205</i>	Male / Right Hand	M22 x 1.50	20.00 / 28.00	84.00 <i>3.307</i>	48.00 <i>1.890</i>	22	60.1
# REM-22.00-L-P	22.00 <i>0.866</i>	112.00 <i>4.409</i>	56.00 <i>2.205</i>	Male / Left Hand	M22 x 1.50	20.00 / 28.00	84.00 <i>3.307</i>	48.00 <i>1.890</i>	22	60.1
# REF-25.00-L-P	25.00 <i>0.984</i>	124.00 <i>4.882</i>	60.00 <i>2.362</i>	Female / Left Hand	M24 x 2.00	22.00 / 31.00	94.00 / 42.00	32.00 / 41.00	22	60.1
# REF-25.00-R-P	25.00 <i>0.984</i>	124.00 <i>4.882</i>	60.00 <i>2.362</i>	Female / Right Hand	M24 x 2.00	22.00 / 31.00	94.00 / 42.00	32.00 / 41.00	22	60.1
# REM-25.00-R-P	25.00 <i>0.984</i>	125.00 <i>4.921</i>	60.00 <i>2.362</i>	Male / Right Hand	M24 x 2.00	22.00 / 31.00	94.00 <i>3.701</i>	55.00 <i>2.165</i>	22	64.9
# REM-25.00-L-P	25.00 <i>0.984</i>	125.00 <i>4.921</i>	60.00 <i>2.362</i>	Male / Left Hand	M24 x 2.00	22.00 / 31.00	94.00 <i>3.701</i>	55.00 <i>2.165</i>	22	64.9
# REF-25.00-L-P-N	25.00 <i>0.984</i>	126.50 <i>4.980</i>	64.00 <i>2.520</i>	Female / Left Hand	M25	17.00 / 20.00	94.00 / 38.00	34.00 / 41.00	16	55.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-25.00-R-P-N	25.00 <i>0.984</i>	126.50 <i>4.980</i>	64.00 <i>2.520</i>	Female / Right Hand	M25	17.00 / 20.00	94.00 / 38.00	34.00 / 41.00	16	55.0
# REM-25.00-R-P-N	25.00 <i>0.984</i>	129.00 <i>5.079</i>	64.00 <i>2.520</i>	Male / Right Hand	M25	17.00 / 20.00	94.00 <i>3.701</i>	53.00 <i>2.087</i>	16	55.0
# REM-25.00-L-P-N	25.00 <i>0.984</i>	129.00 <i>5.079</i>	64.00 <i>2.520</i>	Male / Left Hand	M25	17.00 / 20.00	94.00 <i>3.701</i>	53.00 <i>2.087</i>	16	55.0
# REF-25.40-L-P	25.40 <i>1.000</i>	139.70 <i>5.500</i>	69.85 <i>2.750</i>	Female / Left Hand	1-12	25.53 / 34.93	104.78 / 53.98	41.28 / 53.98	20	46.0
# REM-25.40-L-P	25.40 <i>1.000</i>	139.70 <i>5.500</i>	69.85 <i>2.750</i>	Male / Left Hand	1-12	25.40 / 34.93	104.78 <i>4.125</i>	59.69 <i>2.350</i>	20	85.0
# REF-25.40-R-P	25.40 <i>1.000</i>	139.70 <i>5.500</i>	69.85 <i>2.750</i>	Female / Right Hand	1-12	25.53 / 34.93	104.78 / 53.98	41.28 / 53.98	20	46.0
# REM-25.40-R-P	25.40 <i>1.000</i>	139.70 <i>5.500</i>	69.85 <i>2.750</i>	Male / Right Hand	1-12	25.40 / 34.93	104.78 <i>4.125</i>	59.69 <i>2.350</i>	20	85.0
# REF-30.00-L-P	30.00 <i>1.181</i>	145.00 <i>5.709</i>	70.00 <i>2.756</i>	Female / Left Hand	M30	25.00 / 37.00	110.00 / 51.00	37.00 / 50.00	22	60.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Rod Ends - Plastic

Part Number	Inside Diameter (d1) mm <i>inches</i>	Overall Length (L) mm <i>inches</i>	Head Width (D) mm <i>inches</i>	Type	Thread Size (T)	Width (W/W1) mm <i>inches</i>	I1 / I2 mm <i>inches</i>	D2 / D3 mm <i>inches</i>	Max. Angle of Pivot Deg.	Max Torque Strength n.m
# REF-30.00-R-P	30.00 <i>1.181</i>	145.00 <i>5.709</i>	70.00 <i>2.756</i>	Female / Right Hand	M30	25.00 / 37.00	110.00 / 51.00	37.00 / 50.00	22	60.0
# REF-30.00-R-P-N	30.00 <i>1.181</i>	146.50 <i>5.768</i>	73.00 <i>2.874</i>	Female / Right Hand	M30	19.00 / 22.00	110.00 / 47.00	41.00 / 48.00	13	70.0
# REF-30.00-L-P-N	30.00 <i>1.181</i>	146.50 <i>5.768</i>	73.00 <i>2.874</i>	Female / Left Hand	M30	19.00 / 22.00	110.00 / 47.00	41.00 / 48.00	13	70.0
# REM-30.00-L-P	30.00 <i>1.181</i>	147.00 <i>5.787</i>	70.00 <i>2.756</i>	Male / Left Hand	M30	25.00 / 37.00	110.00 <i>4.331</i>	66.00 <i>2.598</i>	22	70.0
# REM-30.00-R-P	30.00 <i>1.181</i>	147.00 <i>5.787</i>	70.00 <i>2.756</i>	Male / Right Hand	M30	25.00 / 37.00	110.00 <i>4.331</i>	66.00 <i>2.598</i>	22	70.0
# REM-30.00-R-P-N	30.00 <i>1.181</i>	149.50 <i>5.886</i>	73.00 <i>2.874</i>	Male / Right Hand	M30	19.00 / 22.00	110.00 <i>4.331</i>	65.00 <i>2.559</i>	13	70.0
# REM-30.00-L-P-N	30.00 <i>1.181</i>	149.50 <i>5.886</i>	73.00 <i>2.874</i>	Male / Left Hand	M30	19.00 / 22.00	110.00 <i>4.331</i>	65.00 <i>2.559</i>	13	70.0

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

