




MBA

Screws - Machine - Brass - Countersunk Head



Flat Head Countersunk UNC - UNF - BA - METRIC - Various Head Types.

Nuts sold seperately - See Nuts.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
SKM010x003.0-SL-B	1mm (M1x0.25)	3 <i>0.118</i>	Brass	Countersunk / Slotted	0.250 mm / 101.6 TPI
SKM010x006.0-SL-B	1mm (M1x0.25)	6 <i>0.236</i>	Brass	Countersunk / Slotted	0.250 mm / 101.6 TPI
SKM010x010.0-SL-B	1mm (M1x0.25)	10 <i>0.394</i>	Brass	Countersunk / Slotted	0.250 mm / 101.6 TPI
SKM014x003.0-SL-B	1.4mm (M1.4x0.30)	3 <i>0.118</i>	Brass	Countersunk / Slotted	0.300 mm / 84.67 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
SKM014x006.0-SL-B	1.4mm (M1.4x0.30)	6 <i>0.236</i>	Brass	Countersunk / Slotted	0.300 mm / 84.67 TPI
SKM014x010.0-SL-B	1.4mm (M1.4x0.30)	10 <i>0.394</i>	Brass	Countersunk / Slotted	0.300 mm / 84.67 TPI
SKM016x006.0-SL-B	1.6mm (M1.6x0.35)	6 <i>0.236</i>	Brass	Countersunk / Slotted	0.350 mm / 72.57 TPI
SKM016x010.0-SL-B	1.6mm (M1.6x0.35)	10 <i>0.394</i>	Brass	Countersunk / Slotted	0.350 mm / 72.57 TPI
# BRCSP256	2.5mm (M2.5x0.45)	6 <i>0.236</i>	Brass	Flat Countersunk / Slotted	0.450 mm / 56.44 TPI
# BRCSP258	2.5mm (M2.5x0.45)	8 <i>0.315</i>	Brass	Flat Countersunk / Slotted	0.450 mm / 56.44 TPI
# BRCSP2510	2.5mm (M2.5x0.45)	10 <i>0.394</i>	Brass	Flat Countersunk / Slotted	0.450 mm / 56.44 TPI
# BRCSP2512	2.5mm (M2.5x0.45)	12 <i>0.472</i>	Brass	Flat Countersunk / Slotted	0.450 mm / 56.44 TPI
# BRCSP2516	2.5mm (M2.5x0.45)	16 <i>0.630</i>	Brass	Flat Countersunk / Slotted	0.450 mm / 56.44 TPI
# BRCSP2520	2.5mm (M2.5x0.45)	20 <i>0.787</i>	Brass	Flat Countersunk / Slotted	0.450 mm / 56.44 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# BRCSP2525	2.5mm (M2.5x0.45)	25 <i>0.984</i>	Brass	Flat Countersunk / Slotted	0.450 mm / 56.44 TPI
# BRCSP36	3.0mm (M3x0.5 Standard)	6 <i>0.236</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP38	3.0mm (M3x0.5 Standard)	8 <i>0.315</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP310	3.0mm (M3x0.5 Standard)	10 <i>0.394</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP312	3.0mm (M3x0.5 Standard)	12 <i>0.472</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP316	3.0mm (M3x0.5 Standard)	16 <i>0.630</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP320	3.0mm (M3x0.5 Standard)	20 <i>0.787</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP325	3.0mm (M3x0.5 Standard)	25 <i>0.984</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP330	3.0mm (M3x0.5 Standard)	30 <i>1.181</i>	Brass	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# BRCSP1814	3.175mm (1/8-40 BSW)	6.35 <i>0.250</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# BRCSP1838	3.175mm (1/8-40 BSW)	9.525 <i>0.375</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI
# BRCSP1812	3.175mm (1/8-40 BSW)	12.7 <i>0.500</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI
# BRCSP1834	3.175mm (1/8-40 BSW)	19.05 <i>0.750</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI
# BRCSP181	3.175mm (1/8-40 BSW)	25.4 <i>1.000</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI
# BRCSP18114	3.175mm (1/8-40 BSW)	31.8 <i>1.252</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI
# BRCSP18112	3.175mm (1/8-40 BSW)	38.1 <i>1.500</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI
# BRCSP182	3.175mm (1/8-40 BSW)	50.8 <i>2.000</i>	Brass	Flat Countersunk / Slotted	0.635 mm / 40 TPI
# BRCSP53238	3.969mm (5/32-32 BSW)	9.525 <i>0.375</i>	Brass	Flat Countersunk / Slotted	0.794 mm / 32 TPI
# BRCSP53212	3.969mm (5/32-32 BSW)	12.7 <i>0.500</i>	Brass	Flat Countersunk / Slotted	0.794 mm / 32 TPI
# BRCSP53234	3.969mm (5/32-32 BSW)	19.05 <i>0.750</i>	Brass	Flat Countersunk / Slotted	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# BRCSP5321	3.969mm (5/32-32 BSW)	25.4 <i>1.000</i>	Brass	Flat Countersunk / Slotted	0.794 mm / 32 TPI
# BRCSP532114	3.969mm (5/32-32 BSW)	31.8 <i>1.252</i>	Brass	Flat Countersunk / Slotted	0.794 mm / 32 TPI
# BRCSP532112	3.969mm (5/32-32 BSW)	38.1 <i>1.500</i>	Brass	Flat Countersunk / Slotted	0.794 mm / 32 TPI
# BRCSP5322	3.969mm (5/32-32 BSW)	50.8 <i>2.000</i>	Brass	Flat Countersunk / Slotted	0.794 mm / 32 TPI
# BRCSP46	4.0mm (M4x0.7 Standard)	6 <i>0.236</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP48	4.0mm (M4x0.7 Standard)	8 <i>0.315</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP410	4.0mm (M4x0.7 Standard)	10 <i>0.394</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP412	4.0mm (M4x0.7 Standard)	12 <i>0.472</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP416	4.0mm (M4x0.7 Standard)	16 <i>0.630</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP420	4.0mm (M4x0.7 Standard)	20 <i>0.787</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# BRCSP425	4.0mm (M4x0.7 Standard)	25 <i>0.984</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP430	4.0mm (M4x0.7 Standard)	30 <i>1.181</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP440	4.0mm (M4x0.7 Standard)	40 <i>1.575</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# BRCSP450	4.0mm (M4x0.7 Standard)	50 <i>1.969</i>	Brass	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# SK316Wx006.4-SL-BR	4.762mm (3/16-24 BSW)	6.4 <i>0.252</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx009.5-SL-BR	4.762mm (3/16-24 BSW)	9.5 <i>0.374</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx012.7-SL-BR	4.762mm (3/16-24 BSW)	12.7 <i>0.500</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx015.9-SL-BR	4.762mm (3/16-24 BSW)	15.9 <i>0.626</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx019.1-SL-BR	4.762mm (3/16-24 BSW)	19.1 <i>0.752</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx025.4-SL-BR	4.762mm (3/16-24 BSW)	25.4 <i>1.000</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK316Wx031.8-SL-BR	4.762mm (3/16-24 BSW)	31.8 <i>1.252</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx038.1-SL-BR	4.762mm (3/16-24 BSW)	38.1 <i>1.500</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx050.8-SL-BR	4.762mm (3/16-24 BSW)	50.8 <i>2.000</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx063.5-SL-BR	4.762mm (3/16-24 BSW)	63.5 <i>2.500</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SK316Wx076.2-SL-BR	4.762mm (3/16-24 BSW)	76.2 <i>3.000</i>	Brass	Countersunk / Slotted	1.058 mm / 24 TPI
# SKM050x010.0-SL-BR	5.0mm (M5x0.8 Standard)	10 <i>0.394</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM050x012.0-SL-BR	5.0mm (M5x0.8 Standard)	12 <i>0.472</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM050x016.0-SL-BR	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM050x020.0-SL-BR	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM050x025.0-SL-BR	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SKM050x030.0-SL-BR	5.0mm (M5x0.8 Standard)	30 <i>1.181</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM050x040.0-SL-BR	5.0mm (M5x0.8 Standard)	40 <i>1.575</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM050x050.0-SL-BR	5.0mm (M5x0.8 Standard)	50 <i>1.969</i>	Brass	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM060x010.0-SL-BR	6.0mm (M6x1 Standard)	10 <i>0.394</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x012.0-SL-BR	6.0mm (M6x1 Standard)	12 <i>0.472</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x016.0-SL-BR	6.0mm (M6x1 Standard)	16 <i>0.630</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x020.0-SL-BR	6.0mm (M6x1 Standard)	20 <i>0.787</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x025.0-SL-BR	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x030.0-SL-BR	6.0mm (M6x1 Standard)	30 <i>1.181</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x040.0-SL-BR	6.0mm (M6x1 Standard)	40 <i>1.575</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SKM060x050.0-SL-BR	6.0mm (M6x1 Standard)	50 <i>1.969</i>	Brass	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SK14Wx012.7-SL-BR	6.35mm (1/4-20 BSW)	12.7 <i>0.500</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx015.9-SL-BR	6.35mm (1/4-20 BSW)	15.9 <i>0.626</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx019.1-SL-BR	6.35mm (1/4-20 BSW)	19.1 <i>0.752</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx025.4-SL-BR	6.35mm (1/4-20 BSW)	25.4 <i>1.000</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx031.8-SL-BR	6.35mm (1/4-20 BSW)	31.8 <i>1.252</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx038.1-SL-BR	6.35mm (1/4-20 BSW)	38.1 <i>1.500</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx050.8-SL-BR	6.35mm (1/4-20 BSW)	50.8 <i>2.000</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx063.5-SL-BR	6.35mm (1/4-20 BSW)	63.5 <i>2.500</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Wx076.2-SL-BR	6.35mm (1/4-20 BSW)	76.2 <i>3.000</i>	Brass	Countersunk / Slotted	1.270 mm / 20 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# BRCSP51634	7.938mm (5/16-18 BSW)	19.05 <i>0.750</i>	Brass	Flat Countersunk / Slotted	1.411 mm / 18 TPI
# BRCSP5161	7.938mm (5/16-18 BSW)	25.4 <i>1.000</i>	Brass	Flat Countersunk / Slotted	1.411 mm / 18 TPI
# BRCSP516114	7.938mm (5/16-18 BSW)	31.8 <i>1.252</i>	Brass	Flat Countersunk / Slotted	1.411 mm / 18 TPI
# BRCSP516112	7.938mm (5/16-18 BSW)	38.1 <i>1.500</i>	Brass	Flat Countersunk / Slotted	1.411 mm / 18 TPI
# BRCSP5162	7.938mm (5/16-18 BSW)	50.8 <i>2.000</i>	Brass	Flat Countersunk / Slotted	1.411 mm / 18 TPI
# BRCSP820	6.0mm (M6x1 Standard)	20 <i>0.787</i>	Brass	Flat Countersunk / Slotted	1.250 mm / 20.32 TPI
# BRCSP825	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Brass	Flat Countersunk / Slotted	1.250 mm / 20.32 TPI
# BRCSP830	6.0mm (M6x1 Standard)	30 <i>1.181</i>	Brass	Flat Countersunk / Slotted	1.250 mm / 20.32 TPI
# BRCSP840	6.0mm (M6x1 Standard)	40 <i>1.575</i>	Brass	Flat Countersunk / Slotted	1.250 mm / 20.32 TPI
# BRCSP850	6.0mm (M6x1 Standard)	50 <i>1.969</i>	Brass	Flat Countersunk / Slotted	1.250 mm / 20.32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Brass - Countersunk Head

Part Number	Thread Size (C)	Length to top edge (L) mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# BRCSP3834	9.525mm (3/8-16 BSW)	19.05 <i>0.750</i>	Brass	Flat Countersunk / Slotted	1.588 mm / 16 TPI
# BRCSP381	9.525mm (3/8-16 BSW)	25.4 <i>1.000</i>	Brass	Flat Countersunk / Slotted	1.588 mm / 16 TPI
# BRCSP38112	9.525mm (3/8-16 BSW)	38.1 <i>1.500</i>	Brass	Flat Countersunk / Slotted	1.588 mm / 16 TPI
# BRCSP382	9.525mm (3/8-16 BSW)	50.8 <i>2.000</i>	Brass	Flat Countersunk / Slotted	1.588 mm / 16 TPI
# BRCSP1020	10.0mm (M10x1.5 Standard)	20 <i>0.787</i>	Brass	Flat Countersunk / Slotted	1.500 mm / 16.93 TPI
# BRCSP1025	10.0mm (M10x1.5 Standard)	25 <i>0.984</i>	Brass	Flat Countersunk / Slotted	1.500 mm / 16.93 TPI
# BRCSP1030	10.0mm (M10x1.5 Standard)	30 <i>1.181</i>	Brass	Flat Countersunk / Slotted	1.500 mm / 16.93 TPI
# BRCSP1040	10.0mm (M10x1.5 Standard)	40 <i>1.575</i>	Brass	Flat Countersunk / Slotted	1.500 mm / 16.93 TPI
# BRCSP1050	10.0mm (M10x1.5 Standard)	50 <i>1.969</i>	Brass	Flat Countersunk / Slotted	1.500 mm / 16.93 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
