




MBA

Screws - Machine - Nylon - Countersunk Head



Flat Head Countersunk UNC and UNF.

- Non Conductive.
- Non Corrosive.
- Non Magnetic.
- Lightweight.
- Vibration Resistant.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>			
# SK256Cx003.2-SL-NY	2.184mm (2-56 UNC)	3.2 <i>0.126</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
SK256Cx004.8-SL-NY	2.184mm (2-56 UNC)	4.8 <i>0.189</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
SK256Cx006.4-SL-NY	2.184mm (2-56 UNC)	6.4 <i>0.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK256Cx007.9-SL-NY	2.184mm (2-56 UNC)	7.9 <i>0.311</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
# SK256Cx009.5-SL-NY	2.184mm (2-56 UNC)	9.5 <i>0.374</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
# SK256Cx012.7-SL-NY	2.184mm (2-56 UNC)	12.7 <i>0.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
# SK256Cx015.9-SL-NY	2.184mm (2-56 UNC)	15.9 <i>0.626</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
# SK256Cx019.1-SL-NY	2.184mm (2-56 UNC)	19.1 <i>0.752</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
# SK256Cx025.4-SL-NY	2.184mm (2-56 UNC)	25.4 <i>1.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.454 mm / 56 TPI
# SK440Cx003.2-SL-NY	2.845mm (4-40 UNC)	3.2 <i>0.126</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
SK440Cx004.8-SL-NY	2.845mm (4-40 UNC)	4.8 <i>0.189</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
# SK440Cx006.4-SL-NY	2.845mm (4-40 UNC)	6.4 <i>0.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
# SK440Cx007.9-SL-NY	2.845mm (4-40 UNC)	7.9 <i>0.311</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK440Cx009.5-SL-NY	2.845mm (4-40 UNC)	9.5 <i>0.374</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
# SK440Cx012.7-SL-NY	2.845mm (4-40 UNC)	12.7 <i>0.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
# SK440Cx015.9-SL-NY	2.845mm (4-40 UNC)	15.9 <i>0.626</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
# SK440Cx019.1-SL-NY	2.845mm (4-40 UNC)	19.1 <i>0.752</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
# SK440Cx022.2-SL-NY	2.845mm (4-40 UNC)	22.2 <i>0.874</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
# SK440Cx025.4-SL-NY	2.845mm (4-40 UNC)	25.4 <i>1.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.635 mm / 40 TPI
SKM030x016.0-SL-NY	3.0mm (M3x0.5 Standard)	16 <i>0.630</i>	Nylon	Flat Countersunk / Slotted	0.500 mm / 50.8 TPI
# SK632Cx004.8-SL-NY	3.5mm (6-32 UNC)	4.8 <i>0.189</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx006.4-SL-NM	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx006.4-SL-NY	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK632Cx007.9-SL-NY	3.5mm (6-32 UNC)	7.9 <i>0.311</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx009.5-SL-NM	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx009.5-SL-NY	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx011.1-SL-NY	3.5mm (6-32 UNC)	11.1 <i>0.437</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
SK632Cx012.7-SL-NY	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx012.7-SL-NM	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx015.9-SL-NY	3.5mm (6-32 UNC)	15.9 <i>0.626</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx015.9-SL-NM	3.5mm (6-32 UNC)	15.9 <i>0.626</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx019.1-SL-NY	3.5mm (6-32 UNC)	19.1 <i>0.752</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx019.1-SL-NM	3.5mm (6-32 UNC)	19.1 <i>0.752</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK632Cx022.2-SL-NY	3.5mm (6-32 UNC)	22.2 <i>0.874</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx025.4-SL-NY	3.5mm (6-32 UNC)	25.4 <i>1.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK632Cx031.8-SL-NY	3.5mm (6-32 UNC)	31.8 <i>1.252</i>	Nylon	Countersunk / Slotted	0.794 mm / 32 TPI
# SKM040x012.0-SL-NY	4.0mm (M4x0.7 Standard)	12 <i>0.472</i>	Nylon	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
# SKM040x016.0-SL-NY	4.0mm (M4x0.7 Standard)	16 <i>0.630</i>	Nylon	Flat Countersunk / Slotted	0.700 mm / 36.29 TPI
SKM040x030.0-SL-NY	4.0mm (M4x0.7 Standard)	30 <i>1.181</i>	Nylon	Countersunk / Slotted	0.700 mm / 36.29 TPI
# SK832Cx003.2-SL-NY	4.166mm (8-32 UNC)	3.2 <i>0.126</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
SK832Cx006.4-SL-NY	4.166mm (8-32 UNC)	6.4 <i>0.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx007.9-SL-NY	4.166mm (8-32 UNC)	7.9 <i>0.311</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx009.5-SL-NM	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
SK832Cx009.5-SL-NY	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx012.7-SL-NY	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx012.7-SL-NM	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx015.9-SL-NY	4.166mm (8-32 UNC)	15.9 <i>0.626</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx019.1-SL-NM	4.166mm (8-32 UNC)	19.1 <i>0.752</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx019.1-SL-NY	4.166mm (8-32 UNC)	19.1 <i>0.752</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx022.2-SL-NY	4.166mm (8-32 UNC)	22.2 <i>0.874</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx025.4-SL-NM	4.166mm (8-32 UNC)	25.4 <i>1.000</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK832Cx025.4-SL-NY	4.166mm (8-32 UNC)	25.4 <i>1.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1024Cx006.4-SL-NY	4.762mm (10-24 UNC)	6.4 <i>0.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK1024Cx007.9-SL-NY	4.762mm (10-24 UNC)	7.9 <i>0.311</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI
# SK1024Cx009.5-SL-NY	4.762mm (10-24 UNC)	9.5 <i>0.374</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI
# SK1024Cx012.7-SL-NY	4.762mm (10-24 UNC)	12.7 <i>0.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI
# SK1024Cx015.9-SL-NY	4.762mm (10-24 UNC)	15.9 <i>0.626</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI
# SK1024Cx019.1-SL-NY	4.762mm (10-24 UNC)	19.1 <i>0.752</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI
SK1024Cx025.4-SL-NY	4.762mm (10-24 UNC)	25.4 <i>1.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI
# SK1024Cx038.1-SL-NY	4.762mm (10-24 UNC)	38.1 <i>1.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.058 mm / 24 TPI
# SK1032Fx006.4-SL-NY	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx007.9-SL-NY	4.762mm (10-32 UNF)	7.9 <i>0.311</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx009.5-SL-NM	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK1032Fx009.5-SL-NY	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx012.7-SL-NM	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx012.7-SL-NY	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx015.9-SL-NY	4.762mm (10-32 UNF)	15.9 <i>0.626</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx019.1-SL-NM	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx019.1-SL-NY	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx025.4-SL-NY	4.762mm (10-32 UNF)	25.4 <i>1.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	0.794 mm / 32 TPI
# SK1032Fx025.4-SL-NM	4.762mm (10-32 UNF)	25.4 <i>1.000</i>	Nylon with Metal Core	Countersunk / Slotted	0.794 mm / 32 TPI
# SKM050x012.0-SL-NY	5.0mm (M5x0.8 Standard)	12 <i>0.472</i>	Nylon	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM050x016.0-SL-NY	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	Nylon	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SKM050x040.0-SL-NY	5.0mm (M5x0.8 Standard)	40 <i>1.575</i>	Nylon	Flat Countersunk / Slotted	0.800 mm / 31.75 TPI
# SKM060x020.0-SL-NY	6.0mm (M6x1 Standard)	20 <i>0.787</i>	Nylon	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x025.0-SL-NY	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Nylon	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SKM060x045.0-SL-NY	6.0mm (M6x1 Standard)	45 <i>1.772</i>	Nylon	Flat Countersunk / Slotted	1.000 mm / 25.4 TPI
# SK14Cx006.4-SL-NY	6.35mm (1/4-20 UNC)	6.4 <i>0.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx009.5-SL-NY	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx009.5-SL-NM	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	Nylon with Metal Core	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx012.7-SL-NM	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	Nylon with Metal Core	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx015.9-SL-NM	6.35mm (1/4-20 UNC)	15.9 <i>0.626</i>	Nylon with Metal Core	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx015.9-SL-NY	6.35mm (1/4-20 UNC)	15.9 <i>0.626</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm <i>inches</i>	Material	Type	Pitch in mm / Threads Per Inch mm / No.
# SK14Cx019.1-SL-NY	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx019.1-SL-NM	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	Nylon with Metal Core	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx025.4-SL-NM	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	Nylon with Metal Core	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx025.4-SL-NY	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx031.8-SL-NM	6.35mm (1/4-20 UNC)	31.8 <i>1.252</i>	Nylon with Metal Core	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx031.8-SL-NY	6.35mm (1/4-20 UNC)	31.8 <i>1.252</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx038.1-SL-NY	6.35mm (1/4-20 UNC)	38.1 <i>1.500</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx038.1-SL-NM	6.35mm (1/4-20 UNC)	38.1 <i>1.500</i>	Nylon with Metal Core	Countersunk / Slotted	1.270 mm / 20 TPI
# SK14Cx050.8-SL-NY	6.35mm (1/4-20 UNC)	50.8 <i>2.000</i>	Nylon (Zytel 101)	Countersunk / Slotted	1.270 mm / 20 TPI
SK14Cx063.5-SL-NY	6.35mm (1/4-20 UNC)	63.5 <i>2.500</i>	Nylon	Countersunk / Slotted	1.270 mm / 20 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Machine - Nylon - Countersunk Head

Part Number	Thread Size (C)	Overall Length mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>			
# SKM080x030.0-SL-NY	8.0mm (M8x1.25 Standard)	30 <i>1.181</i>	Nylon	Flat Countersunk / Slotted	1.250 mm / 20.32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
