



# MBA

## Screws - Socket - Button - Aluminium



Variety of colours available.

Other colours available on request. Minimum quantities will apply.

Metric Sizes to DIN7380.

This catalogue to be read in conjunction with information at [http://www.minibearings.com.au/ogue/tech/fasteners/aluminium\\_tech.pdf](http://www.minibearings.com.au/ogue/tech/fasteners/aluminium_tech.pdf)

### Screws - Socket - Button - Aluminium

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Colour	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SCM050x016.0-BT-SKT-ALBK	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	Aluminium	Black	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x016.0-BT-SKT-ALBL	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	Aluminium	Blue	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x016.0-BT-SKT-ALRD	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	Aluminium	Red	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x016.0-BT-SKT-AL	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	Aluminium	Clear Anodised	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Screws - Socket - Button - Aluminium

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Colour	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM050x020.0-BT-SKT-AL	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	Aluminium	Clear Anodised	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x020.0-BT-SKT-ALBK	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	Aluminium	Black	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x020.0-BT-SKT-ALBL	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	Aluminium	Blue	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x020.0-BT-SKT-ALRD	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	Aluminium	Red	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x025.0-BT-SKT-AL	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	Aluminium	Clear Anodised	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x025.0-BT-SKT-ALBK	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	Aluminium	Black	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x025.0-BT-SKT-ALBL	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	Aluminium	Blue	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x025.0-BT-SKT-ALRD	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	Aluminium	Red	3.0 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM060x016.0-BT-SKT-ALRD	6.0mm (M6x1 Standard)	16 <i>0.630</i>	Aluminium	Red	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x016.0-BT-SKT-AL	6.0mm (M6x1 Standard)	16 <i>0.630</i>	Aluminium	Clear Anodised	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Screws - Socket - Button - Aluminium

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Colour	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM060x016.0-BT-SKT-ALBL	6.0mm (M6x1 Standard)	16 <i>0.630</i>	Aluminium	Blue	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x016.0-BT-SKT-ALBK	6.0mm (M6x1 Standard)	16 <i>0.630</i>	Aluminium	Black	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x020.0-BT-SKT-AL	6.0mm (M6x1 Standard)	20 <i>0.787</i>	Aluminium	Clear Anodised	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x020.0-BT-SKT-ALBK	6.0mm (M6x1 Standard)	20 <i>0.787</i>	Aluminium	Black	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x020.0-BT-SKT-ALBL	6.0mm (M6x1 Standard)	20 <i>0.787</i>	Aluminium	Blue	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x020.0-BT-SKT-ALRD	6.0mm (M6x1 Standard)	20 <i>0.787</i>	Aluminium	Red	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x025.0-BT-SKT-AL	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Aluminium	Clear Anodised	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x025.0-BT-SKT-ALBK	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Aluminium	Black	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x025.0-BT-SKT-ALBL	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Aluminium	Blue	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x025.0-BT-SKT-ALRD	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Aluminium	Red	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Screws - Socket - Button - Aluminium

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Colour	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM060x025.0-BT-SKT-ALSI	6.0mm (M6x1 Standard)	25 <i>0.984</i>	Aluminium	Silver	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x030.0-BT-SKT-ALRD	6.0mm (M6x1 Standard)	30 <i>1.181</i>	Aluminium	Red	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x030.0-BT-SKT-AL	6.0mm (M6x1 Standard)	30 <i>1.181</i>	Aluminium	Clear Anodised	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x030.0-BT-SKT-ALBK	6.0mm (M6x1 Standard)	30 <i>1.181</i>	Aluminium	Black	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x030.0-BT-SKT-ALBL	6.0mm (M6x1 Standard)	30 <i>1.181</i>	Aluminium	Blue	4.0 <i>0.157</i>	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

