



MBA

Screws - Socket - Button - Stainless Steel



UNC - UNF - METRIC.

Imperial Sizes to ANSI B18.3.

Metric Sizes to DIN7380.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SC080Fx003.2-BT-SKT-4	1.524mm (0-80 UNF)	3.2 <i>0.126</i>	304 Stainless	0.89 (0.035in.)	0.318 mm / 80 TPI
SC080Fx004.8-BT-SKT-4	1.524mm (0-80 UNF)	4.8 <i>0.189</i>	304 Stainless	0.89 (0.035in.)	0.318 mm / 80 TPI
SC080Fx006.4-BT-SKT-4	1.524mm (0-80 UNF)	6.4 <i>0.252</i>	304 Stainless	0.89 (0.035in.)	0.318 mm / 80 TPI
# SC080Fx008.0-BTSKT4	1.524mm (0-80 UNF)	7.98 <i>0.314</i>	304 Stainless	0.89 (0.035in.)	0.318 mm / 80 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SC080Fx009.5-BT-SKT-4	1.524mm (0-80 UNF)	9.5 <i>0.374</i>	304 Stainless	0.89 (0.035in.)	0.318 mm / 80 TPI
SC172Fx004.8-BT-SKT-4	1.854mm (1-72 UNF)	4.8 <i>0.189</i>	304 Stainless	1.27 (0.050in.)	0.353 mm / 72 TPI
SC172Fx009.5-BT-SKT-4	1.854mm (1-72 UNF)	9.5 <i>0.374</i>	304 Stainless	1.27 (0.050in.)	0.353 mm / 72 TPI
SCM020x003.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	3 <i>0.118</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x003.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	3 <i>0.118</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
SCM020x004.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	4 <i>0.157</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x004.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	4 <i>0.157</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x005.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	5 <i>0.197</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
SCM020x005.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	5 <i>0.197</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x006.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	6 <i>0.236</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SCM020x006.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	6 <i>0.236</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
SCM020x008.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	8 <i>0.315</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x008.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	8 <i>0.315</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
SCM020x010.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	10 <i>0.394</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x010.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	10 <i>0.394</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
SCM020x012.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	12 <i>0.472</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x012.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	12 <i>0.472</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x016.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	16 <i>0.630</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
SCM020x016.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	16 <i>0.630</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
# SCM020x020.0-BT-SKT-6	2.0mm (M2x0.4 Standard)	20 <i>0.787</i>	316 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM020x020.0-BT-SKT-4	2.0mm (M2x0.4 Standard)	20 <i>0.787</i>	304 Stainless	1.27 (0.050in.)	0.400 mm / 63.5 TPI
SC256Cx006.4-BT-SKT-4	2.184mm (2-56 UNC)	6.4 <i>0.252</i>	304 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx006.4-BT-SKT-6	2.184mm (2-56 UNC)	6.4 <i>0.252</i>	316 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx009.5-BT-SKT-6	2.184mm (2-56 UNC)	9.5 <i>0.374</i>	316 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx009.5-BT-SKT-4	2.184mm (2-56 UNC)	9.5 <i>0.374</i>	304 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
SC256Cx012.7-BT-SKT-4	2.184mm (2-56 UNC)	12.7 <i>0.500</i>	304 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx012.7-BT-SKT-6	2.184mm (2-56 UNC)	12.7 <i>0.500</i>	316 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx015.9-BT-SKT-6	2.184mm (2-56 UNC)	15.9 <i>0.626</i>	316 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx015.9-BT-SKT-4	2.184mm (2-56 UNC)	15.9 <i>0.626</i>	304 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx019.1-BT-SKT-4	2.184mm (2-56 UNC)	19.1 <i>0.752</i>	304 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC256Cx019.1-BT-SKT-6	2.184mm (2-56 UNC)	19.1 <i>0.752</i>	316 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx025.4-BT-SKT-4	2.184mm (2-56 UNC)	25.4 <i>1.000</i>	304 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SC256Cx025.4-BT-SKT-6	2.184mm (2-56 UNC)	25.4 <i>1.000</i>	316 Stainless	1.27 (0.050in.)	0.454 mm / 56 TPI
# SCM025x004.0-BT-SKT-4	2.5mm (M2.5x0.45)	4 <i>0.157</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
# SCM025x005.0-BT-SKT-4	2.5mm (M2.5x0.45)	5 <i>0.197</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
SCM025x006.0-BT-SKT-4	2.5mm (M2.5x0.45)	6 <i>0.236</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
# SCM025x008.0-BT-SKT-4	2.5mm (M2.5x0.45)	8 <i>0.315</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
# SCM025x010.0-BT-SKT-4	2.5mm (M2.5x0.45)	10 <i>0.394</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
SCM025x012.0-BT-SKT-4	2.5mm (M2.5x0.45)	12 <i>0.472</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
# SCM025x016.0-BT-SKT-4	2.5mm (M2.5x0.45)	16 <i>0.630</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM025x020.0-BT-SKT-4	2.5mm (M2.5x0.45)	20 <i>0.787</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
# SCM025x025.0-BT-SKT-4	2.5mm (M2.5x0.45)	25 <i>0.984</i>	304 Stainless	1.50 <i>0.059</i>	0.450 mm / 56.44 TPI
SC348Cx006.4-BT-SKT-4	2.515mm (3-48 UNC)	6.4 <i>0.252</i>	304 Stainless	1.59 (1/16)	0.529 mm / 48 TPI
SC348Cx012.7-BT-SKT-4	2.515mm (3-48 UNC)	12.7 <i>0.500</i>	304 Stainless	1.59 (1/16)	0.529 mm / 48 TPI
# SC440Cx004.8-BT-SKT-6	2.845mm (4-40 UNC)	4.8 <i>0.189</i>	316 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
SC440Cx004.8-BT-SKT-4	2.845mm (4-40 UNC)	4.8 <i>0.189</i>	304 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
# SC440Cx006.4-BT-SKT-4	2.845mm (4-40 UNC)	6.4 <i>0.252</i>	304 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
# SC440Cx009.5-BT-SKT-4	2.845mm (4-40 UNC)	9.5 <i>0.374</i>	304 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
SC440Cx012.7-BT-SKT-4	2.845mm (4-40 UNC)	12.7 <i>0.500</i>	304 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
# SC440Cx015.9-BT-SKT-6	2.845mm (4-40 UNC)	15.9 <i>0.626</i>	316 Stainless	1.59 (1/16)	0.635 mm / 40 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC440Cx015.9-BT-SKT-4	2.845mm (4-40 UNC)	15.9 <i>0.626</i>	304 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
# SC440Cx019.1-BT-SKT-4	2.845mm (4-40 UNC)	19.1 <i>0.752</i>	304 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
# SC440Cx019.1-BT-SKT-6	2.845mm (4-40 UNC)	19.1 <i>0.752</i>	316 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
SC440Cx025.4-BT-SKT-4	2.845mm (4-40 UNC)	25.4 <i>1.000</i>	304 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
# SC440Cx025.4-BT-SKT-6	2.845mm (4-40 UNC)	25.4 <i>1.000</i>	316 Stainless	1.59 (1/16)	0.635 mm / 40 TPI
SCM030x005.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	5 <i>0.197</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
# SCM030x005.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	5 <i>0.197</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x006.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	6 <i>0.236</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x006.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	6 <i>0.236</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x008.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	8 <i>0.315</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SCM030x008.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	8 <i>0.315</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
# SCM030x010.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	10 <i>0.394</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x010.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	10 <i>0.394</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x012.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	12 <i>0.472</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x012.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	12 <i>0.472</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x016.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	16 <i>0.630</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x016.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	16 <i>0.630</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
# SCM030x020.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	20 <i>0.787</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x020.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	20 <i>0.787</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
# SCM030x025.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	25 <i>0.984</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SCM030x025.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	25 <i>0.984</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
# SCM030x030.0-BT-SKT-6	3.0mm (M3x0.5 Standard)	30 <i>1.181</i>	316 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x030.0-BT-SKT-4	3.0mm (M3x0.5 Standard)	30 <i>1.181</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
SCM030x040.0-BTSKT4	3.0mm (M3x0.5 Standard)	40 <i>1.575</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
# SCM030x050.0-BTSKT4	3.0mm (M3x0.5 Standard)	50 <i>1.969</i>	304 Stainless	2.00 <i>0.079</i>	0.500 mm / 50.8 TPI
# SC540Cx006.4-BT-SKT-6	3.175mm (5-40 UNC)	6.4 <i>0.252</i>	316 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx006.4-BT-SKT-4	3.175mm (5-40 UNC)	6.4 <i>0.252</i>	304 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx009.5-BT-SKT-6	3.175mm (5-40 UNC)	9.5 <i>0.374</i>	316 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx009.5-BT-SKT-4	3.175mm (5-40 UNC)	9.5 <i>0.374</i>	304 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx012.7-BT-SKT-6	3.175mm (5-40 UNC)	12.7 <i>0.500</i>	316 Stainless	1.98 (5/64)	0.635 mm / 40 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC540Cx012.7-BT-SKT-4	3.175mm (5-40 UNC)	12.7 <i>0.500</i>	304 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx019.1-BT-SKT-4	3.175mm (5-40 UNC)	19.1 <i>0.752</i>	304 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx019.1-BT-SKT-6	3.175mm (5-40 UNC)	19.1 <i>0.752</i>	316 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx025.4-BT-SKT-6	3.175mm (5-40 UNC)	25.4 <i>1.000</i>	316 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC540Cx025.4-BT-SKT-4	3.175mm (5-40 UNC)	25.4 <i>1.000</i>	304 Stainless	1.98 (5/64)	0.635 mm / 40 TPI
# SC632Cx006.4-BT-SKT-6	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	316 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
SC632Cx006.4-BT-SKT-4	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	304 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx009.5-BT-SKT-4	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	304 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx009.5-BT-SKT-6	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	316 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
SC632Cx012.7-BT-SKT-4	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	304 Stainless	1.98 (5/64)	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC632Cx012.7-BT-SKT-6	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	316 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx015.9-BT-SKT-4	3.5mm (6-32 UNC)	15.9 <i>0.626</i>	304 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx015.9-BT-SKT-6	3.5mm (6-32 UNC)	15.9 <i>0.626</i>	316 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx019.1-BT-SKT-6	3.5mm (6-32 UNC)	19.1 <i>0.752</i>	316 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx019.1-BT-SKT-4	3.5mm (6-32 UNC)	19.1 <i>0.752</i>	304 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx025.4-BT-SKT-4	3.5mm (6-32 UNC)	25.4 <i>1.000</i>	304 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SC632Cx025.4-BT-SKT-6	3.5mm (6-32 UNC)	25.4 <i>1.000</i>	316 Stainless	1.98 (5/64)	0.794 mm / 32 TPI
# SCM040x004.0-BTSKT4	4.0mm (M4x0.7 Standard)	4 <i>0.157</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x005.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	5 <i>0.197</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x005.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	5 <i>0.197</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM040x006.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	6 <i>0.236</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x006.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	6 <i>0.236</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x008.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	8 <i>0.315</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x008.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	8 <i>0.315</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x010.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	10 <i>0.394</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x010.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	10 <i>0.394</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x012.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	12 <i>0.472</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x012.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	12 <i>0.472</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x016.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	16 <i>0.630</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x016.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	16 <i>0.630</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM040x020.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	20 <i>0.787</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x020.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	20 <i>0.787</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x025.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	25 <i>0.984</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x025.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	25 <i>0.984</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x030.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	30 <i>1.181</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x030.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	30 <i>1.181</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x035.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	35 <i>1.378</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x035.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	35 <i>1.378</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x040.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	40 <i>1.575</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x040.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	40 <i>1.575</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM040x045.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	45 <i>1.772</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x045.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	45 <i>1.772</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x050.0-BT-SKT-4	4.0mm (M4x0.7 Standard)	50 <i>1.969</i>	304 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x050.0-BT-SKT-6	4.0mm (M4x0.7 Standard)	50 <i>1.969</i>	316 Stainless	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SC832Cx006.4-BT-SKT-6	4.166mm (8-32 UNC)	6.4 <i>0.252</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx006.4-BT-SKT-4	4.166mm (8-32 UNC)	6.4 <i>0.252</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx009.5-BT-SKT-6	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx009.5-BT-SKT-4	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx012.7-BT-SKT-6	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx012.7-BT-SKT-4	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC832Cx015.9-BT-SKT-6	4.166mm (8-32 UNC)	15.9 <i>0.626</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx015.9-BT-SKT-4	4.166mm (8-32 UNC)	15.9 <i>0.626</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx019.1-BT-SKT-4	4.166mm (8-32 UNC)	19.1 <i>0.752</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx019.1-BT-SKT-6	4.166mm (8-32 UNC)	19.1 <i>0.752</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx025.4-BT-SKT-6	4.166mm (8-32 UNC)	25.4 <i>1.000</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx025.4-BT-SKT-4	4.166mm (8-32 UNC)	25.4 <i>1.000</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx031.8-BT-SKT-6	4.166mm (8-32 UNC)	31.8 <i>1.252</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx031.8-BT-SKT-4	4.166mm (8-32 UNC)	31.8 <i>1.252</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx038.1-BT-SKT-6	4.166mm (8-32 UNC)	38.1 <i>1.500</i>	316 Stainless	2.38 (3/32)	0.794 mm / 32 TPI
# SC832Cx038.1-BT-SKT-4	4.166mm (8-32 UNC)	38.1 <i>1.500</i>	304 Stainless	2.38 (3/32)	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC1024Cx006.4-BT-SKT-6	4.762mm (10-24 UNC)	6.4 <i>0.252</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx006.4-BT-SKT-4	4.762mm (10-24 UNC)	6.4 <i>0.252</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx009.5-BT-SKT-4	4.762mm (10-24 UNC)	9.5 <i>0.374</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx009.5-BT-SKT-6	4.762mm (10-24 UNC)	9.5 <i>0.374</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
SC1024Cx012.7-BT-SKT-4	4.762mm (10-24 UNC)	12.7 <i>0.500</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx012.7-BT-SKT-6	4.762mm (10-24 UNC)	12.7 <i>0.500</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx015.9-BT-SKT-6	4.762mm (10-24 UNC)	15.9 <i>0.626</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx015.9-BT-SKT-4	4.762mm (10-24 UNC)	15.9 <i>0.626</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
SC1024Cx019.1-BT-SKT-4	4.762mm (10-24 UNC)	19.1 <i>0.752</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx019.1-BT-SKT-6	4.762mm (10-24 UNC)	19.1 <i>0.752</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SC1024Cx025.4-BT-SKT-4	4.762mm (10-24 UNC)	25.4 <i>1.000</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx025.4-BT-SKT-6	4.762mm (10-24 UNC)	25.4 <i>1.000</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx031.8-BT-SKT-4	4.762mm (10-24 UNC)	31.8 <i>1.252</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx031.8-BT-SKT-6	4.762mm (10-24 UNC)	31.8 <i>1.252</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx038.1-BT-SKT-4	4.762mm (10-24 UNC)	38.1 <i>1.500</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx038.1-BT-SKT-6	4.762mm (10-24 UNC)	38.1 <i>1.500</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx050.8-BT-SKT-6	4.762mm (10-24 UNC)	50.8 <i>2.000</i>	316 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1024Cx050.8-BT-SKT-4	4.762mm (10-24 UNC)	50.8 <i>2.000</i>	304 Stainless	3.18 (1/8)	1.058 mm / 24 TPI
# SC1032Fx006.4-BT-SKT-4	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx006.4-BT-SKT-6	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC1032Fx007.9-BT-SKT-4	4.762mm (10-32 UNF)	7.9 <i>0.311</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx007.9-BT-SKT-6	4.762mm (10-32 UNF)	7.9 <i>0.311</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
SC1032Fx009.5-BT-SKT-4	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx009.5-BT-SKT-6	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx012.7-BT-SKT-6	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx012.7-BT-SKT-4	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx015.9-BT-SKT-4	4.762mm (10-32 UNF)	15.9 <i>0.626</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx015.9-BT-SKT-6	4.762mm (10-32 UNF)	15.9 <i>0.626</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx019.1-BT-SKT-4	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx019.1-BT-SKT-6	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC1032Fx022.2-BT-SKT-4	4.762mm (10-32 UNF)	22.2 <i>0.874</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx022.2-BT-SKT-6	4.762mm (10-32 UNF)	22.2 <i>0.874</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx025.4-BT-SKT-6	4.762mm (10-32 UNF)	25.4 <i>1.000</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx025.4-BT-SKT-4	4.762mm (10-32 UNF)	25.4 <i>1.000</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx031.8-BT-SKT-6	4.762mm (10-32 UNF)	31.8 <i>1.252</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx031.8-BT-SKT-4	4.762mm (10-32 UNF)	31.8 <i>1.252</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx038.1-BT-SKT-6	4.762mm (10-32 UNF)	38.1 <i>1.500</i>	316 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
# SC1032Fx038.1-BT-SKT-4	4.762mm (10-32 UNF)	38.1 <i>1.500</i>	304 Stainless	3.18 (1/8)	0.794 mm / 32 TPI
SCM050x006.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	6 <i>0.236</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x006.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	6 <i>0.236</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
SCM050x008.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	8 <i>0.315</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x008.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	8 <i>0.315</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x010.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	10 <i>0.394</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM050x010.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	10 <i>0.394</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x012.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	12 <i>0.472</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM050x012.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	12 <i>0.472</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM050x016.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x016.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM050x020.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x020.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM050x025.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM050x025.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x030.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	30 <i>1.181</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x030.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	30 <i>1.181</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x035.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	35 <i>1.378</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x035.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	35 <i>1.378</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x040.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	40 <i>1.575</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x040.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	40 <i>1.575</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x045.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	45 <i>1.772</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x045.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	45 <i>1.772</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM050x050.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	50 <i>1.969</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x050.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	50 <i>1.969</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x055.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	55 <i>2.165</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x055.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	55 <i>2.165</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x060.0-BT-SKT-6	5.0mm (M5x0.8 Standard)	60 <i>2.362</i>	316 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x060.0-BT-SKT-4	5.0mm (M5x0.8 Standard)	60 <i>2.362</i>	304 Stainless	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM060x008.0-BT-SKT-4	6.0mm (M6x1 Standard)	8 <i>0.315</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
SCM060x008.0-BT-SKT-6	6.0mm (M6x1 Standard)	8 <i>0.315</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x010.0-BT-SKT-6	6.0mm (M6x1 Standard)	10 <i>0.394</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
SCM060x010.0-BT-SKT-4	6.0mm (M6x1 Standard)	10 <i>0.394</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
SCM060x012.0-BT-SKT-4	6.0mm (M6x1 Standard)	12 <i>0.472</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x012.0-BT-SKT-6	6.0mm (M6x1 Standard)	12 <i>0.472</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
SCM060x016.0-BT-SKT-4	6.0mm (M6x1 Standard)	16 <i>0.630</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x016.0-BT-SKT-6	6.0mm (M6x1 Standard)	16 <i>0.630</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
SCM060x020.0-BT-SKT-4	6.0mm (M6x1 Standard)	20 <i>0.787</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x020.0-BT-SKT-6	6.0mm (M6x1 Standard)	20 <i>0.787</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x025.0-BT-SKT-6	6.0mm (M6x1 Standard)	25 <i>0.984</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x025.0-BT-SKT-4	6.0mm (M6x1 Standard)	25 <i>0.984</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x030.0-BT-SKT-6	6.0mm (M6x1 Standard)	30 <i>1.181</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x030.0-BT-SKT-4	6.0mm (M6x1 Standard)	30 <i>1.181</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM060x035.0-BT-SKT-4	6.0mm (M6x1 Standard)	35 <i>1.378</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x035.0-BT-SKT-6	6.0mm (M6x1 Standard)	35 <i>1.378</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x040.0-BT-SKT-6	6.0mm (M6x1 Standard)	40 <i>1.575</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
SCM060x040.0-BT-SKT-4	6.0mm (M6x1 Standard)	40 <i>1.575</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x045.0-BT-SKT-6	6.0mm (M6x1 Standard)	45 <i>1.772</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x045.0-BT-SKT-4	6.0mm (M6x1 Standard)	45 <i>1.772</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x050.0-BT-SKT-6	6.0mm (M6x1 Standard)	50 <i>1.969</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x050.0-BT-SKT-4	6.0mm (M6x1 Standard)	50 <i>1.969</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x055.0-BT-SKT-4	6.0mm (M6x1 Standard)	55 <i>2.165</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x055.0-BT-SKT-6	6.0mm (M6x1 Standard)	55 <i>2.165</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM060x060.0-BT-SKT-6	6.0mm (M6x1 Standard)	60 <i>2.362</i>	316 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x060.0-BT-SKT-4	6.0mm (M6x1 Standard)	60 <i>2.362</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x080.0-BTSKT4	6.0mm (M6x1 Standard)	80 <i>3.150</i>	304 Stainless	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SC14Cx009.5-BT-SKT-4	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx009.5-BT-SKT-6	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
SC14Cx012.7-BT-SKT-4	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx012.7-BT-SKT-6	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx015.9-BT-SKT-6	6.35mm (1/4-20 UNC)	15.9 <i>0.626</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx015.9-BT-SKT-4	6.35mm (1/4-20 UNC)	15.9 <i>0.626</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx019.1-BT-SKT-6	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC14Cx019.1-BT-SKT-4	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx025.4-BT-SKT-6	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx025.4-BT-SKT-4	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx031.8-BT-SKT-6	6.35mm (1/4-20 UNC)	31.8 <i>1.252</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx031.8-BT-SKT-4	6.35mm (1/4-20 UNC)	31.8 <i>1.252</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx038.1-BT-SKT-4	6.35mm (1/4-20 UNC)	38.1 <i>1.500</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx038.1-BT-SKT-6	6.35mm (1/4-20 UNC)	38.1 <i>1.500</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx050.8-BT-SKT-4	6.35mm (1/4-20 UNC)	50.8 <i>2.000</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx050.8-BT-SKT-6	6.35mm (1/4-20 UNC)	50.8 <i>2.000</i>	316 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Cx063.8-BTSKT4	6.35mm (1/4-20 UNC)	63.8 <i>2.512</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC14Cx076.2-BTSKT4	6.35mm (1/4-20 UNC)	76.2 <i>3.000</i>	304 Stainless	3.97 (5/32)	1.270 mm / 20 TPI
# SC14Fx009.5-BTSKT4	6.35mm (1/4-28 UNF)	9.5 <i>0.374</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx012.7-BT-SKT-6	6.35mm (1/4-28 UNF)	12.7 <i>0.500</i>	316 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
SC14Fx012.7-BT-SKT-4	6.35mm (1/4-28 UNF)	12.7 <i>0.500</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx015.9-BT-SKT-6	6.35mm (1/4-28 UNF)	15.9 <i>0.626</i>	316 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx015.9-BT-SKT-4	6.35mm (1/4-28 UNF)	15.9 <i>0.626</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx019.1-BT-SKT-4	6.35mm (1/4-28 UNF)	19.1 <i>0.752</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx019.1-BT-SKT-6	6.35mm (1/4-28 UNF)	19.1 <i>0.752</i>	316 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx025.4-BT-SKT-6	6.35mm (1/4-28 UNF)	25.4 <i>1.000</i>	316 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx025.4-BT-SKT-4	6.35mm (1/4-28 UNF)	25.4 <i>1.000</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC14Fx031.8-BTSKT4	6.35mm (1/4-28 UNF)	31.8 <i>1.252</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx038.1-BTSKT4	6.35mm (1/4-28 UNF)	38.1 <i>1.500</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC14Fx050.8-BTSKT4	6.35mm (1/4-28 UNF)	50.8 <i>2.000</i>	304 Stainless	3.97 (5/32)	0.907 mm / 28 TPI
# SC516Cx012.7-BT-SKT-6	7.938mm (5/16-18 UNC)	12.7 <i>0.500</i>	316 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx012.7-BT-SKT-4	7.938mm (5/16-18 UNC)	12.7 <i>0.500</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx015.9-BT-SKT-6	7.938mm (5/16-18 UNC)	15.9 <i>0.626</i>	316 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx015.9-BT-SKT-4	7.938mm (5/16-18 UNC)	15.9 <i>0.626</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx019.1-BT-SKT-4	7.938mm (5/16-18 UNC)	19.1 <i>0.752</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx019.1-BT-SKT-6	7.938mm (5/16-18 UNC)	19.1 <i>0.752</i>	316 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx025.4-BT-SKT-4	7.938mm (5/16-18 UNC)	25.4 <i>1.000</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC516Cx025.4-BT-SKT-6	7.938mm (5/16-18 UNC)	25.4 <i>1.000</i>	316 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx031.8-BT-SKT-4	7.938mm (5/16-18 UNC)	31.8 <i>1.252</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx031.8-BT-SKT-6	7.938mm (5/16-18 UNC)	31.8 <i>1.252</i>	316 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx038.1-BT-SKT-4	7.938mm (5/16-18 UNC)	38.1 <i>1.500</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx038.1-BT-SKT-6	7.938mm (5/16-18 UNC)	38.1 <i>1.500</i>	316 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx050.8-BT-SKT-6	7.938mm (5/16-18 UNC)	50.8 <i>2.000</i>	316 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx050.8-BT-SKT-4	7.938mm (5/16-18 UNC)	50.8 <i>2.000</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx063.5-BTSKT4	7.938mm (5/16-18 UNC)	63.5 <i>2.500</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Cx076.2-BTSKT4	7.938mm (5/16-18 UNC)	76.2 <i>3.000</i>	304 Stainless	4.76 (3/16)	1.411 mm / 18 TPI
# SC516Fx019.1-BTSKT4	7.938mm (5/16-24 UNF)	19.1 <i>0.752</i>	304 Stainless	4.76 (3/16)	1.058 mm / 24 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC516Fx025.4-BT-SKT-6	7.938mm (5/16-24 UNF)	25.4 <i>1.000</i>	316 Stainless	4.76 (3/16)	1.058 mm / 24 TPI
# SC516Fx025.4-BT-SKT-4	7.938mm (5/16-24 UNF)	25.4 <i>1.000</i>	304 Stainless	4.76 (3/16)	1.058 mm / 24 TPI
# SC516Fx031.8-BTSKT4	7.938mm (5/16-24 UNF)	31.8 <i>1.252</i>	304 Stainless	4.76 (3/16)	1.058 mm / 24 TPI
# SC516Fx038.1-BT-SKT-6	7.938mm (5/16-24 UNF)	38.1 <i>1.500</i>	316 Stainless	4.76 (3/16)	1.058 mm / 24 TPI
# SC516Fx038.1-BT-SKT-4	7.938mm (5/16-24 UNF)	38.1 <i>1.500</i>	304 Stainless	4.76 (3/16)	1.058 mm / 24 TPI
# SC516Fx050.8-BTSKT4	7.938mm (5/16-24 UNF)	50.8 <i>2.000</i>	304 Stainless	4.76 (3/16)	1.058 mm / 24 TPI
# SCM080x010.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	10 <i>0.394</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x010.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	10 <i>0.394</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x012.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	12 <i>0.472</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x012.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	12 <i>0.472</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM080x016.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	16 <i>0.630</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x016.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	16 <i>0.630</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x020.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	20 <i>0.787</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x020.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	20 <i>0.787</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x025.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	25 <i>0.984</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x025.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	25 <i>0.984</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x030.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	30 <i>1.181</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x030.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	30 <i>1.181</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x035.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	35 <i>1.378</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x035.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	35 <i>1.378</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM080x040.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	40 <i>1.575</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x040.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	40 <i>1.575</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x045.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	45 <i>1.772</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x045.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	45 <i>1.772</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x050.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	50 <i>1.969</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x050.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	50 <i>1.969</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x055.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	55 <i>2.165</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x055.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	55 <i>2.165</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
SCM080x060.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	60 <i>2.362</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x060.0-BT-SKT-6	8.0mm (M8x1.25 Standard)	60 <i>2.362</i>	316 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM080x070.0-BT-SKT-4	8.0mm (M8x1.25 Standard)	70 <i>2.756</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x080.0-BTSKT4	8.0mm (M8x1.25 Standard)	80 <i>3.150</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x100.0-BTSKT4	8.0mm (M8x1.25 Standard)	100 <i>3.937</i>	304 Stainless	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SC38Cx019.1-BT-SKT-6	9.525mm (3/8-16 UNC)	19.1 <i>0.752</i>	316 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx019.1-BT-SKT-4	9.525mm (3/8-16 UNC)	19.1 <i>0.752</i>	304 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx025.4-BT-SKT-6	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	316 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx025.4-BT-SKT-4	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	304 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx031.8-BT-SKT-6	9.525mm (3/8-16 UNC)	31.8 <i>1.252</i>	316 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx031.8-BT-SKT-4	9.525mm (3/8-16 UNC)	31.8 <i>1.252</i>	304 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx038.1-BT-SKT-6	9.525mm (3/8-16 UNC)	38.1 <i>1.500</i>	316 Stainless	5.56 (7/32)	1.588 mm / 16 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC38Cx038.1-BT-SKT-4	9.525mm (3/8-16 UNC)	38.1 <i>1.500</i>	304 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx050.8-BT-SKT-4	9.525mm (3/8-16 UNC)	50.8 <i>2.000</i>	304 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx050.8-BT-SKT-6	9.525mm (3/8-16 UNC)	50.8 <i>2.000</i>	316 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx063.5-BT-SKT-4	9.525mm (3/8-16 UNC)	63.5 <i>2.500</i>	304 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx063.5-BT-SKT-6	9.525mm (3/8-16 UNC)	63.5 <i>2.500</i>	316 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx076.2-BT-SKT-6	9.525mm (3/8-16 UNC)	76.2 <i>3.000</i>	316 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Cx076.2-BT-SKT-4	9.525mm (3/8-16 UNC)	76.2 <i>3.000</i>	304 Stainless	5.56 (7/32)	1.588 mm / 16 TPI
# SC38Fx019.1-BTSKT4	9.525mm (3/8-24 UNF)	19.1 <i>0.752</i>	304 Stainless	5.56 (7/32)	1.058 mm / 24 TPI
# SC38Fx025.4-BT-SKT-4	9.525mm (3/8-24 UNF)	25.4 <i>1.000</i>	304 Stainless	5.56 (7/32)	1.058 mm / 24 TPI
# SC38Fx025.4-BT-SKT-6	9.525mm (3/8-24 UNF)	25.4 <i>1.000</i>	316 Stainless	5.56 (7/32)	1.058 mm / 24 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC38Fx031.8-BTSKT4	9.525mm (3/8-24 UNF)	31.8 <i>1.252</i>	304 Stainless	5.56 (7/32)	1.058 mm / 24 TPI
# SC38Fx038.1-BTSKT4	9.525mm (3/8-24 UNF)	38.1 <i>1.500</i>	304 Stainless	5.56 (7/32)	1.058 mm / 24 TPI
# SCM100x012.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	12 <i>0.472</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x012.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	12 <i>0.472</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x016.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	16 <i>0.630</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x016.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	16 <i>0.630</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x020.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	20 <i>0.787</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x020.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	20 <i>0.787</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x025.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	25 <i>0.984</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x025.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	25 <i>0.984</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM100x030.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	30 <i>1.181</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x030.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	30 <i>1.181</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x035.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	35 <i>1.378</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x035.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	35 <i>1.378</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x040.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	40 <i>1.575</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x040.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	40 <i>1.575</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x045.0-BTSKT4	10.0mm (M10x1.5 Standard)	45 <i>1.772</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x050.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	50 <i>1.969</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x050.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	50 <i>1.969</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x055.0-BTSKT4	10.0mm (M10x1.5 Standard)	55 <i>2.165</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM100x060.0-BT-SKT-4	10.0mm (M10x1.5 Standard)	60 <i>2.362</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x060.0-BT-SKT-6	10.0mm (M10x1.5 Standard)	60 <i>2.362</i>	316 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x070.0-BTSKT4	10.0mm (M10x1.5 Standard)	70 <i>2.756</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x080.0-BTSKT4	10.0mm (M10x1.5 Standard)	80 <i>3.150</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x090.0-BTSKT4	10.0mm (M10x1.5 Standard)	90 <i>3.543</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM100x100.0-BTSKT4	10.0mm (M10x1.5 Standard)	100 <i>3.937</i>	304 Stainless	6.00 <i>0.236</i>	1.500 mm / 16.93 TPI
# SCM120x010.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	10 <i>0.394</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x016.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	16 <i>0.630</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x016.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	16 <i>0.630</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x020.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	20 <i>0.787</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm	Material	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	
# SCM120x020.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	20 <i>0.787</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x025.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	25 <i>0.984</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x025.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	25 <i>0.984</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x030.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	30 <i>1.181</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x030.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	30 <i>1.181</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x035.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	35 <i>1.378</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x035.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	35 <i>1.378</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x040.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	40 <i>1.575</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x040.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	40 <i>1.575</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x050.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	50 <i>1.969</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SCM120x050.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	50 <i>1.969</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x060.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	60 <i>2.362</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x060.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	60 <i>2.362</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x070.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	70 <i>2.756</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x070.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	70 <i>2.756</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x080.0-BT-SKT-4	12.0mm (M12x1.75 Standard)	80 <i>3.150</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x080.0-BT-SKT-6	12.0mm (M12x1.75 Standard)	80 <i>3.150</i>	316 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x090.0-BTSKT4	12.0mm (M12x1.75 Standard)	90 <i>3.543</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x100.0-BTSKT4	12.0mm (M12x1.75 Standard)	100 <i>3.937</i>	304 Stainless	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SC12Cx019.1-BTSKT4	12.7mm (1/2-13 UNC)	19.1 <i>0.752</i>	304 Stainless	7.94 (5/16)	1.954 mm / 13 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC12Cx025.4-BT-SKT-4	12.7mm (1/2-13 UNC)	25.4 <i>1.000</i>	304 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx025.4-BT-SKT-6	12.7mm (1/2-13 UNC)	25.4 <i>1.000</i>	316 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx031.8-BT-SKT-4	12.7mm (1/2-13 UNC)	31.8 <i>1.252</i>	304 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx031.8-BT-SKT-6	12.7mm (1/2-13 UNC)	31.8 <i>1.252</i>	316 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx038.1-BT-SKT-6	12.7mm (1/2-13 UNC)	38.1 <i>1.500</i>	316 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx038.1-BT-SKT-4	12.7mm (1/2-13 UNC)	38.1 <i>1.500</i>	304 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx050.8-BT-SKT-6	12.7mm (1/2-13 UNC)	50.8 <i>2.000</i>	316 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx050.8-BT-SKT-4	12.7mm (1/2-13 UNC)	50.8 <i>2.000</i>	304 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx063.5-BTSKT4	12.7mm (1/2-13 UNC)	63.5 <i>2.500</i>	304 Stainless	7.94 (5/16)	1.954 mm / 13 TPI
# SC12Cx076.2-BTSKT4	12.7mm (1/2-13 UNC)	76.2 <i>3.000</i>	304 Stainless	7.94 (5/16)	1.954 mm / 13 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Button - Stainless Steel

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC58Cx050.8-BTSKT4	15.875mm (5/8-11 UNC)	50.8 <i>2.000</i>	304 Stainless	9.53 (3/8)	2.309 mm / 11 TPI
# SC58Cx063.5-BTSKT4	15.875mm (5/8-11 UNC)	63.5 <i>2.500</i>	304 Stainless	9.53 (3/8)	2.309 mm / 11 TPI
# SC58Cx076.2-BTSKT4	15.875mm (5/8-11 UNC)	76.2 <i>3.000</i>	304 Stainless	9.53 (3/8)	2.309 mm / 11 TPI
# SCM160x050.0-BTSKT4	16.0mm (M16x2 Standard)	50 <i>1.969</i>	304 Stainless	10.00 <i>0.394</i>	2.000 mm / 12.7 TPI
# SCM160x060.0-BTSKT4	16.0mm (M16x2 Standard)	60 <i>2.362</i>	304 Stainless	10.00 <i>0.394</i>	2.000 mm / 12.7 TPI
# SCM160x080.0-BTSKT4	16.0mm (M16x2 Standard)	80 <i>3.150</i>	304 Stainless	10.00 <i>0.394</i>	2.000 mm / 12.7 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
