




MBA

Screws - Socket - Cap - Aluminium



Variety of colours available.

Other colours available on request. Minimum quantities will apply.

Metric Sizes to DIN912.

This catalogue to be read in conjunction with information at http://www.minibearings.com.au/ogue/tech/fasteners/aluminium_tech.pdf

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|--------------------------|--------------------|---------------|-----------|-------------------------|---------------------------|--------|----------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| SC440Cx006.4-CP-SKT-AL | 2.845mm (4-40 UNC) | 6.4 | Aluminium | 2.9 | 4.7 | | 2.38 (3/32) | 0.635 mm / 40 TPI |
| | | <i>0.252</i> | | <i>0.114</i> | <i>0.185</i> | | | |
| SC440Cx012.7-CP-SKT-AL | 2.845mm (4-40 UNC) | 12.7 | Aluminium | 2.9 | 4.7 | | 2.38 (3/32) | 0.635 mm / 40 TPI |
| | | <i>0.500</i> | | <i>0.114</i> | <i>0.185</i> | | | |
| # SC440Cx025.4-CP-SKT-AL | 2.845mm (4-40 UNC) | 25.4 | Aluminium | 2.9 | 4.7 | | 2.38 (3/32) | 0.635 mm / 40 TPI |
| | | <i>1.000</i> | | <i>0.114</i> | <i>0.185</i> | | | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-------------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM050x010.0-CP-SKT-AL | 5.0mm (M5x0.8 Standard) | 10 <i>0.394</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Clear Anodised | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x010.0-CP-SKT-ALBK | 5.0mm (M5x0.8 Standard) | 10 <i>0.394</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Black | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x010.0-CP-SKT-ALBL | 5.0mm (M5x0.8 Standard) | 10 <i>0.394</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Blue | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x010.0-CP-SKT-ALRD | 5.0mm (M5x0.8 Standard) | 10 <i>0.394</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Red | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x012.0-CP-SKT-AL | 5.0mm (M5x0.8 Standard) | 12 <i>0.472</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Clear Anodised | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| SCM050x012.0-CP-SKT-ALBK | 5.0mm (M5x0.8 Standard) | 12 <i>0.472</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Black | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x012.0-CP-SKT-ALBL | 5.0mm (M5x0.8 Standard) | 12 <i>0.472</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Blue | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x012.0-CP-SKT-ALRD | 5.0mm (M5x0.8 Standard) | 12 <i>0.472</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Red | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-------------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM050x016.0-CP-SKT-ALBK | 5.0mm (M5x0.8 Standard) | 16 <i>0.630</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Black | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x016.0-CP-SKT-ALBL | 5.0mm (M5x0.8 Standard) | 16 <i>0.630</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Blue | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| SCM050x016.0-CP-SKT-AL | 5.0mm (M5x0.8 Standard) | 16 <i>0.630</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Clear Anodised | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x016.0-CP-SKT-ALRD | 5.0mm (M5x0.8 Standard) | 16 <i>0.630</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Red | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x020.0-CP-SKT-AL | 5.0mm (M5x0.8 Standard) | 20 <i>0.787</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Clear Anodised | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x020.0-CP-SKT-ALBK | 5.0mm (M5x0.8 Standard) | 20 <i>0.787</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Black | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x020.0-CP-SKT-ALBL | 5.0mm (M5x0.8 Standard) | 20 <i>0.787</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Blue | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x020.0-CP-SKT-ALRD | 5.0mm (M5x0.8 Standard) | 20 <i>0.787</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Red | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-------------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| SCM050x025.0-CP-SKT-AL | 5.0mm (M5x0.8 Standard) | 25 <i>0.984</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Clear Anodised | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x025.0-CP-SKT-ALRD | 5.0mm (M5x0.8 Standard) | 25 <i>0.984</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Red | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x025.0-CP-SKT-ALBK | 5.0mm (M5x0.8 Standard) | 25 <i>0.984</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Black | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x025.0-CP-SKT-ALBL | 5.0mm (M5x0.8 Standard) | 25 <i>0.984</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Blue | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x030.0-CP-SKT-AL | 5.0mm (M5x0.8 Standard) | 30 <i>1.181</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Clear Anodised | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x030.0-CP-SKT-ALBK | 5.0mm (M5x0.8 Standard) | 30 <i>1.181</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Black | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x030.0-CP-SKT-ALBL | 5.0mm (M5x0.8 Standard) | 30 <i>1.181</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Blue | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x030.0-CP-SKT-ALRD | 5.0mm (M5x0.8 Standard) | 30 <i>1.181</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Red | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-------------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM050x040.0-CP-SKT-ALBL | 5.0mm (M5x0.8 Standard) | 40 <i>1.575</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Blue | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x040.0-CP-SKT-ALRD | 5.0mm (M5x0.8 Standard) | 40 <i>1.575</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Red | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x040.0-CP-SKT-ALBK | 5.0mm (M5x0.8 Standard) | 40 <i>1.575</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Black | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM050x040.0-CP-SKT-AL | 5.0mm (M5x0.8 Standard) | 40 <i>1.575</i> | Aluminium | 5.0 <i>0.197</i> | 8.5 <i>0.335</i> | Clear Anodised | 4.00 <i>0.157</i> | 0.800 mm / 31.75 TPI |
| # SCM060x010.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 10 <i>0.394</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x010.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 10 <i>0.394</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x010.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 10 <i>0.394</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| SCM060x010.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 10 <i>0.394</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-----------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x012.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 12 <i>0.472</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x012.0-CP-SKT-ALSI | 6.0mm (M6x1 Standard) | 12 <i>0.472</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Silver | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x012.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 12 <i>0.472</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x012.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 12 <i>0.472</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x012.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 12 <i>0.472</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x016.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 16 <i>0.630</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x016.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 16 <i>0.630</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x016.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 16 <i>0.630</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-----------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x016.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 16 <i>0.630</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x020.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 20 <i>0.787</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x020.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 20 <i>0.787</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x020.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 20 <i>0.787</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| SCM060x020.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 20 <i>0.787</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x025.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 25 <i>0.984</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x025.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 25 <i>0.984</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x025.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 25 <i>0.984</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-----------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x025.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 25 <i>0.984</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| SCM060x030.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 30 <i>1.181</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x030.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 30 <i>1.181</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x030.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 30 <i>1.181</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x030.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 30 <i>1.181</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x035.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 35 <i>1.378</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x035.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 35 <i>1.378</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x035.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 35 <i>1.378</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-----------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x035.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 35 <i>1.378</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x040.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 40 <i>1.575</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x040.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 40 <i>1.575</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x040.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 40 <i>1.575</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x040.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 40 <i>1.575</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x045.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 45 <i>1.772</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x045.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 45 <i>1.772</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x045.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 45 <i>1.772</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-----------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x045.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 45 <i>1.772</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| SCM060x050.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 50 <i>1.969</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x050.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 50 <i>1.969</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x050.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 50 <i>1.969</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x050.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 50 <i>1.969</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x055.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 55 <i>2.165</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x055.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 55 <i>2.165</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x055.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 55 <i>2.165</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-----------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x055.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 55 <i>2.165</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x060.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 60 <i>2.362</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x060.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 60 <i>2.362</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x060.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 60 <i>2.362</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x060.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 60 <i>2.362</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x070.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 70 <i>2.756</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x070.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 70 <i>2.756</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x070.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 70 <i>2.756</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|-----------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x070.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 70 <i>2.756</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x080.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 80 <i>3.150</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x080.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 80 <i>3.150</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x080.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 80 <i>3.150</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x080.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 80 <i>3.150</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x090.0-CP-SKT-AL | 6.0mm (M6x1 Standard) | 90 <i>3.543</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Clear Anodised | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x090.0-CP-SKT-ALBK | 6.0mm (M6x1 Standard) | 90 <i>3.543</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Black | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SCM060x090.0-CP-SKT-ALBL | 6.0mm (M6x1 Standard) | 90 <i>3.543</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Blue | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|--------------------------|----------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM060x090.0-CP-SKT-ALRD | 6.0mm (M6x1 Standard) | 90 <i>3.543</i> | Aluminium | 6.0 <i>0.236</i> | 10.0 <i>0.394</i> | Red | 5.00 <i>0.197</i> | 1.000 mm / 25.4 TPI |
| # SC14Cx038.1-CP-SKT-AL | 6.35mm (1/4-20 UNC) | 38.1 <i>1.500</i> | Aluminium | 6.4 <i>0.252</i> | 9.5 <i>0.374</i> | | 4.76 (3/16) | 1.270 mm / 20 TPI |
| # SCM080x020.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 20 <i>0.787</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Clear Anodised | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x020.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 20 <i>0.787</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x020.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 20 <i>0.787</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Black | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x020.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 20 <i>0.787</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Blue | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x025.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 25 <i>0.984</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Clear Anodised | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x025.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 25 <i>0.984</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Black | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|--------------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM080x025.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 25 <i>0.984</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Blue | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x025.0-CP-SKT-ALGD | 8.0mm (M8x1.25 Standard) | 25 <i>0.984</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Gold | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x025.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 25 <i>0.984</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| SCM080x030.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 30 <i>1.181</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Clear Anodised | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x030.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 30 <i>1.181</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x030.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 30 <i>1.181</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Black | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x030.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 30 <i>1.181</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Blue | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x035.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 35 <i>1.378</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|--------------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM080x035.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 35 <i>1.378</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Clear Anodised | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x035.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 35 <i>1.378</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Black | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x035.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 35 <i>1.378</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Blue | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x040.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 40 <i>1.575</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x040.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 40 <i>1.575</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Blue | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x040.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 40 <i>1.575</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Clear Anodised | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x040.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 40 <i>1.575</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Black | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x050.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 50 <i>1.969</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Clear Anodised | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|--------------------------|--------------------|-----------|-------------------------|---------------------------|----------------|----------------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| # SCM080x050.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 50 <i>1.969</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Black | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x050.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 50 <i>1.969</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Blue | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x050.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 50 <i>1.969</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x060.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 60 <i>2.362</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Clear Anodised | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x060.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 60 <i>2.362</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Black | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x060.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 60 <i>2.362</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Blue | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x060.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 60 <i>2.362</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |
| # SCM080x070.0-CP-SKT-ALRD | 8.0mm (M8x1.25 Standard) | 70 <i>2.756</i> | Aluminium | 8.0 <i>0.315</i> | 13.0 <i>0.512</i> | Red | 6.00 <i>0.236</i> | 1.250 mm / 20.32 TPI |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Aluminium

| Part Number | Thread Size (C) | Length (L) mm | Material | Head Length (B Max.) mm | Head Diameter (A Max.) mm | Colour | Hex Key (D) mm | Pitch in mm / Threads Per Inch mm / No. |
|----------------------------|--------------------------|---------------|-----------|-------------------------|---------------------------|----------------|----------------|---|
| | | <i>inches</i> | | <i>inches</i> | <i>inches</i> | | <i>inches</i> | |
| SCM080x070.0-CP-SKT-AL | 8.0mm (M8x1.25 Standard) | 70 | Aluminium | 8.0 | 13.0 | Clear Anodised | 6.00 | 1.250 mm / 20.32 TPI |
| | | <i>2.756</i> | | <i>0.315</i> | <i>0.512</i> | | <i>0.236</i> | |
| # SCM080x070.0-CP-SKT-ALBK | 8.0mm (M8x1.25 Standard) | 70 | Aluminium | 8.0 | 13.0 | Black | 6.00 | 1.250 mm / 20.32 TPI |
| | | <i>2.756</i> | | <i>0.315</i> | <i>0.512</i> | | <i>0.236</i> | |
| # SCM080x070.0-CP-SKT-ALBL | 8.0mm (M8x1.25 Standard) | 70 | Aluminium | 8.0 | 13.0 | Blue | 6.00 | 1.250 mm / 20.32 TPI |
| | | <i>2.756</i> | | <i>0.315</i> | <i>0.512</i> | | <i>0.236</i> | |

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

