



MBA

Screws - Socket - Cap - Molybdenum Disulphide Coated

UNC - UNF - METRIC.

Imperial Sizes to ANSI B18.3.

Metric Sizes to DIN912.

Screws - Socket - Cap - Molybdenum Disulphide Coated

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length (B Max.) mm	Head Diameter (A Max.) mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SC256Cx006.4-CP-SKT-HM	2.184mm (2-56 UNC)	6.4	High Tensile Steel Black Ox/Moly Coated	2.2	3.6	1.98 (5/64)	0.454 mm / 56 TPI
		<i>0.252</i>		<i>0.087</i>	<i>0.142</i>		
# SC256Cx009.5-CP-SKT-HM	2.184mm (2-56 UNC)	9.5	High Tensile Steel Black Ox/Moly Coated	2.2	3.6	1.98 (5/64)	0.454 mm / 56 TPI
		<i>0.374</i>		<i>0.087</i>	<i>0.142</i>		
SCM025x006.0-CP-SKT-HM	2.5mm (M2.5x0.45)	6	High Tensile Steel Black Ox/Moly Coated	2.5	4.5	2.00	0.450 mm / 56.44 TPI
		<i>0.236</i>		<i>0.098</i>	<i>0.177</i>	<i>0.079</i>	

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Molybdenum Disulphide Coated

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length (B Max.) mm	Head Diameter (A Max.) mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
SCM025x008.0-CP-SKT-HM	2.5mm (M2.5x0.45)	8	High Tensile Steel Black Ox/Moly Coated	2.5	4.5	2.00	0.450 mm / 56.44 TPI
		<i>0.315</i>		<i>0.098</i>	<i>0.177</i>	<i>0.079</i>	
# SCM025x010.0-CP-SKT-HM	2.5mm (M2.5x0.45)	10	High Tensile Steel Black Ox/Moly Coated	2.5	4.5	2.00	0.450 mm / 56.44 TPI
		<i>0.394</i>		<i>0.098</i>	<i>0.177</i>	<i>0.079</i>	
# SCM025x012.0-CP-SKT-HM	2.5mm (M2.5x0.45)	12	High Tensile Steel Black Ox/Moly Coated	2.5	4.5	2.00	0.450 mm / 56.44 TPI
		<i>0.472</i>		<i>0.098</i>	<i>0.177</i>	<i>0.079</i>	
# SC348Cx009.5-CP-SKT-HM	2.515mm (3-48 UNC)	9.5	High Tensile Steel Black Ox/Moly Coated	2.5	4.1	1.98 (5/64)	0.529 mm / 48 TPI
		<i>0.374</i>		<i>0.098</i>	<i>0.161</i>		
# SC348Cx012.7-CP-SKT-HM	2.515mm (3-48 UNC)	12.7	High Tensile Steel Black Ox/Moly Coated	2.5	4.1	1.98 (5/64)	0.529 mm / 48 TPI
		<i>0.500</i>		<i>0.098</i>	<i>0.161</i>		
# SC440Cx006.4-CP-SKT-HM	2.845mm (4-40 UNC)	6.4	High Tensile Steel Black Ox/Moly Coated	2.9	4.7	2.38 (3/32)	0.635 mm / 40 TPI
		<i>0.252</i>		<i>0.114</i>	<i>0.185</i>		
# SC440Cx009.5-CP-SKT-HM	2.845mm (4-40 UNC)	9.5	High Tensile Steel Black Ox/Moly Coated	2.9	4.7	2.38 (3/32)	0.635 mm / 40 TPI
		<i>0.374</i>		<i>0.114</i>	<i>0.185</i>		
# SC440Cx012.7-CP-SKT-HM	2.845mm (4-40 UNC)	12.7	High Tensile Steel Black Ox/Moly Coated	2.9	4.7	2.38 (3/32)	0.635 mm / 40 TPI
		<i>0.500</i>		<i>0.114</i>	<i>0.185</i>		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Molybdenum Disulphide Coated

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Head Length (B Max.) mm <i>inches</i>	Head Diameter (A Max.) mm <i>inches</i>	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC440Cx019.1-CP-SKT-HM	2.845mm (4-40 UNC)	19.1 <i>0.752</i>	High Tensile Steel Black Ox/Moly Coated	2.9 <i>0.114</i>	4.7 <i>0.185</i>	2.38 (3/32)	0.635 mm / 40 TPI
SCM030x006.0-CP-SKT-HM	3.0mm (M3x0.5 Standard)	6 <i>0.236</i>	High Tensile Steel Black Ox/Moly Coated	3.0 <i>0.118</i>	5.5 <i>0.217</i>	2.50 <i>0.098</i>	0.500 mm / 50.8 TPI
SCM030x008.0-CP-SKT-HM	3.0mm (M3x0.5 Standard)	8 <i>0.315</i>	High Tensile Steel Black Ox/Moly Coated	3.0 <i>0.118</i>	5.5 <i>0.217</i>	2.50 <i>0.098</i>	0.500 mm / 50.8 TPI
# SCM030x010.0-CP-SKT-HM	3.0mm (M3x0.5 Standard)	10 <i>0.394</i>	High Tensile Steel Black Ox/Moly Coated	3.0 <i>0.118</i>	5.5 <i>0.217</i>	2.50 <i>0.098</i>	0.500 mm / 50.8 TPI
# SCM030x012.0-CP-SKT-HM	3.0mm (M3x0.5 Standard)	12 <i>0.472</i>	High Tensile Steel Black Ox/Moly Coated	3.0 <i>0.118</i>	5.5 <i>0.217</i>	2.50 <i>0.098</i>	0.500 mm / 50.8 TPI
SCM030x016.0-CP-SKT-HM	3.0mm (M3x0.5 Standard)	16 <i>0.630</i>	High Tensile Steel Black Ox/Moly Coated	3.0 <i>0.118</i>	5.5 <i>0.217</i>	2.50 <i>0.098</i>	0.500 mm / 50.8 TPI
# SC632Cx006.4-CP-SKT-HM	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.794 mm / 32 TPI
# SC632Cx012.7-CP-SKT-HM	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Molybdenum Disulphide Coated

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Head Length (B Max.) mm <i>inches</i>	Head Diameter (A Max.) mm <i>inches</i>	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC632Cx015.9-CP-SKT-HM	3.5mm (6-32 UNC)	15.9 <i>0.626</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.794 mm / 32 TPI
# SC632Cx019.1-CP-SKT-HM	3.5mm (6-32 UNC)	19.1 <i>0.752</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.794 mm / 32 TPI
# SC640Fx006.4-CP-SKT-HM	3.5mm (6-40 UNF)	6.4 <i>0.252</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.635 mm / 40 TPI
# SC640Fx012.7-CP-SKT-HM	3.5mm (6-40 UNF)	12.7 <i>0.500</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.635 mm / 40 TPI
SC640Fx015.9-CP-SKT-HM	3.5mm (6-40 UNF)	15.9 <i>0.626</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.635 mm / 40 TPI
# SC640Fx019.1-CP-SKT-HM	3.5mm (6-40 UNF)	19.1 <i>0.752</i>	High Tensile Steel Black Ox/Moly Coated	3.5 <i>0.138</i>	5.8 <i>0.228</i>	2.78 (7/64)	0.635 mm / 40 TPI
# SCM040x008.0-CP-SKT-HM	4.0mm (M4x0.7 Standard)	8 <i>0.315</i>	High Tensile Steel Black Ox/Moly Coated	4.0 <i>0.157</i>	7.0 <i>0.276</i>	3.00 <i>0.118</i>	0.700 mm / 36.29 TPI
SCM040x010.0-CP-SKT-HM	4.0mm (M4x0.7 Standard)	10 <i>0.394</i>	High Tensile Steel Black Ox/Moly Coated	4.0 <i>0.157</i>	7.0 <i>0.276</i>	3.00 <i>0.118</i>	0.700 mm / 36.29 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Molybdenum Disulphide Coated

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length (B Max.) mm	Head Diameter (A Max.) mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
SCM040x012.0-CP-SKT-HM	4.0mm (M4x0.7 Standard)	12	High Tensile Steel Black Ox/Moly Coated	4.0	7.0	3.00	0.700 mm / 36.29 TPI
		<i>0.472</i>		<i>0.157</i>	<i>0.276</i>	<i>0.118</i>	
SCM040x016.0-CP-SKT-HM	4.0mm (M4x0.7 Standard)	16	High Tensile Steel Black Ox/Moly Coated	4.0	7.0	3.00	0.700 mm / 36.29 TPI
		<i>0.630</i>		<i>0.157</i>	<i>0.276</i>	<i>0.118</i>	
# SCM040x020.0-CP-SKT-HM	4.0mm (M4x0.7 Standard)	20	High Tensile Steel Black Ox/Moly Coated	4.0	7.0	3.00	0.700 mm / 36.29 TPI
		<i>0.787</i>		<i>0.157</i>	<i>0.276</i>	<i>0.118</i>	
# SC832Cx012.7-CP-SKT-HM	4.166mm (8-32 UNC)	12.7	High Tensile Steel Black Ox/Moly Coated	4.2	6.9	3.57 (9/64)	0.794 mm / 32 TPI
		<i>0.500</i>		<i>0.165</i>	<i>0.272</i>		
# SC832Cx019.1-CP-SKT-HM	4.166mm (8-32 UNC)	19.1	High Tensile Steel Black Ox/Moly Coated	4.2	6.9	3.57 (9/64)	0.794 mm / 32 TPI
		<i>0.752</i>		<i>0.165</i>	<i>0.272</i>		
# SC832Cx025.4-CP-SKT-HM	4.166mm (8-32 UNC)	25.4	High Tensile Steel Black Ox/Moly Coated	4.2	6.9	3.57 (9/64)	0.794 mm / 32 TPI
		<i>1.000</i>		<i>0.165</i>	<i>0.272</i>		
# SC1032Fx012.7-CP-SKT-HM	4.762mm (10-32 UNF)	12.7	High Tensile Steel Black Ox/Moly Coated	4.8	7.9	3.97 (5/32)	0.794 mm / 32 TPI
		<i>0.500</i>		<i>0.189</i>	<i>0.311</i>		
# SC1032Fx019.1-CP-SKT-HM	4.762mm (10-32 UNF)	19.1	High Tensile Steel Black Ox/Moly Coated	4.8	7.9	3.97 (5/32)	0.794 mm / 32 TPI
		<i>0.752</i>		<i>0.189</i>	<i>0.311</i>		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Cap - Molybdenum Disulphide Coated

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length (B Max.) mm	Head Diameter (A Max.) mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SC1032Fx025.4-CP-SKT-HM	4.762mm (10-32 UNF)	25.4	High Tensile Steel Black Ox/Moly Coated	4.8	7.9	3.97 (5/32)	0.794 mm / 32 TPI
		<i>1.000</i>		<i>0.189</i>	<i>0.311</i>		
SC14Cx012.7-CP-SKT-HM	6.35mm (1/4-20 UNC)	12.7	High Tensile Steel Black Ox/Moly Coated	6.4	9.5	4.76 (3/16)	1.270 mm / 20 TPI
		<i>0.500</i>		<i>0.252</i>	<i>0.374</i>		
# SC14Cx019.1-CP-SKT-HM	6.35mm (1/4-20 UNC)	19.1	High Tensile Steel Black Ox/Moly Coated	6.4	9.5	4.76 (3/16)	1.270 mm / 20 TPI
		<i>0.752</i>		<i>0.252</i>	<i>0.374</i>		
# SC14Cx025.4-CP-SKT-HM	6.35mm (1/4-20 UNC)	25.4	High Tensile Steel Black Ox/Moly Coated	6.4	9.5	4.76 (3/16)	1.270 mm / 20 TPI
		<i>1.000</i>		<i>0.252</i>	<i>0.374</i>		
# SC14Cx038.1-CP-SKT-HM	6.35mm (1/4-20 UNC)	38.1	High Tensile Steel Black Ox/Moly Coated	6.4	9.5	4.76 (3/16)	1.270 mm / 20 TPI
		<i>1.500</i>		<i>0.252</i>	<i>0.374</i>		

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
