




MBA

Screws - Socket - Low Head



UNC - UNF - METRIC - Alloy Steel.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM040x006.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	6 <i>0.236</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x008.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	8 <i>0.315</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x010.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	10 <i>0.394</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x012.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	12 <i>0.472</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM040x016.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	16 <i>0.630</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
SCM040x020.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	20 <i>0.787</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x025.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	25 <i>0.984</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SCM040x030.0-LH-SKT-H	4.0mm (M4x0.7 Standard)	30 <i>1.181</i>	High Tensile Steel / Black Oxide	3.82 - 4.00	6.78 - 7.22	2.50 <i>0.098</i>	0.700 mm / 36.29 TPI
# SC832Cx009.5-LH-SKT-H	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	High Tensile Steel / Black Oxide			1.98 (5/64)	
# SC832Cx012.7-LH-SKT-H	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	High Tensile Steel / Black Oxide			1.98 (5/64)	
# SC832Cx015.9-LH-SKT-H	4.166mm (8-32 UNC)	15.9 <i>0.626</i>	High Tensile Steel / Black Oxide			1.98 (5/64)	
# SC832Cx019.1-LH-SKT-H	4.166mm (8-32 UNC)	19.1 <i>0.752</i>	High Tensile Steel / Black Oxide			1.98 (5/64)	

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SC832Cx025.4-LH-SKT-H	4.166mm (8-32 UNC)	25.4 <i>1.000</i>	High Tensile Steel / Black Oxide			1.98 (5/64)	
# SC1024Cx009.5-LH-SKT-H	4.762mm (10-24 UNC)	9.5 <i>0.374</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	1.058 mm / 24 TPI
# SC1024Cx012.7-LH-SKT-H	4.762mm (10-24 UNC)	12.7 <i>0.500</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	1.058 mm / 24 TPI
# SC1024Cx015.9-LH-SKT-H	4.762mm (10-24 UNC)	15.9 <i>0.626</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	1.058 mm / 24 TPI
# SC1024Cx019.1-LH-SKT-H	4.762mm (10-24 UNC)	19.1 <i>0.752</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	1.058 mm / 24 TPI
# SC1024Cx025.4-LH-SKT-H	4.762mm (10-24 UNC)	25.4 <i>1.000</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	1.058 mm / 24 TPI
# SC1032Fx006.4-LH-SKT-H	4.762mm (10-32 UNF)	6.4 <i>0.252</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	0.794 mm / 32 TPI
# SC1032Fx009.5-LH-SKT-H	4.762mm (10-32 UNF)	9.5 <i>0.374</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SC1032Fx012.7-LH-SKT-H	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	0.794 mm / 32 TPI
# SC1032Fx015.9-LH-SKT-H	4.762mm (10-32 UNF)	15.9 <i>0.626</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	0.794 mm / 32 TPI
# SC1032Fx019.1-LH-SKT-H	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	0.794 mm / 32 TPI
# SC1032Fx025.4-LH-SKT-H	4.762mm (10-32 UNF)	25.4 <i>1.000</i>	High Tensile Steel / Black Oxide			2.38 (3/32)	0.794 mm / 32 TPI
# SCM050x008.0-LH-SKT-H	5.0mm (M5x0.8 Standard)	8 <i>0.315</i>	High Tensile Steel / Black Oxide	4.82 - 5.00	8.28 - 8.72	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM050x010.0-LH-SKT-H	5.0mm (M5x0.8 Standard)	10 <i>0.394</i>	High Tensile Steel / Black Oxide	4.82 - 5.00	8.28 - 8.72	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x012.0-LH-SKT-H	5.0mm (M5x0.8 Standard)	12 <i>0.472</i>	High Tensile Steel / Black Oxide	4.82 - 5.00	8.28 - 8.72	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
SCM050x016.0-LH-SKT-H	5.0mm (M5x0.8 Standard)	16 <i>0.630</i>	High Tensile Steel / Black Oxide	4.82 - 5.00	8.28 - 8.72	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
SCM050x020.0-LH-SKT-H	5.0mm (M5x0.8 Standard)	20 <i>0.787</i>	High Tensile Steel / Black Oxide	4.82 - 5.00	8.28 - 8.72	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x025.0-LH-SKT-H	5.0mm (M5x0.8 Standard)	25 <i>0.984</i>	High Tensile Steel / Black Oxide	4.82 - 5.00	8.28 - 8.72	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM050x030.0-LH-SKT-H	5.0mm (M5x0.8 Standard)	30 <i>1.181</i>	High Tensile Steel / Black Oxide	4.82 - 5.00	8.28 - 8.72	3.00 <i>0.118</i>	0.800 mm / 31.75 TPI
# SCM060x008.0-LH-SKT-H	6.0mm (M6x1 Standard)	8 <i>0.315</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x010.0-LH-SKT-H	6.0mm (M6x1 Standard)	10 <i>0.394</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x012.0-LH-SKT-H	6.0mm (M6x1 Standard)	12 <i>0.472</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x016.0-LH-SKT-H	6.0mm (M6x1 Standard)	16 <i>0.630</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x020.0-LH-SKT-H	6.0mm (M6x1 Standard)	20 <i>0.787</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM060x025.0-LH-SKT-H	6.0mm (M6x1 Standard)	25 <i>0.984</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x030.0-LH-SKT-H	6.0mm (M6x1 Standard)	30 <i>1.181</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x035.0-LH-SKT-H	6.0mm (M6x1 Standard)	35 <i>1.378</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x040.0-LH-SKT-H	6.0mm (M6x1 Standard)	40 <i>1.575</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SCM060x050.0-LH-SKT-H	6.0mm (M6x1 Standard)	50 <i>1.969</i>	High Tensile Steel / Black Oxide	5.70 - 6.00	9.78 - 10.22	4.00 <i>0.157</i>	1.000 mm / 25.4 TPI
# SC14Cx009.5-LH-SKT-H	6.35mm (1/4-20 UNC)	9.5 <i>0.374</i>	High Tensile Steel / Black Oxide			3.18 (1/8)	1.270 mm / 20 TPI
# SC14Cx012.7-LH-SKT-H	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	High Tensile Steel / Black Oxide			3.18 (1/8)	1.270 mm / 20 TPI
# SC14Cx015.9-LH-SKT-H	6.35mm (1/4-20 UNC)	15.9 <i>0.626</i>	High Tensile Steel / Black Oxide			3.18 (1/8)	1.270 mm / 20 TPI

Indicates item not stocked at time of printing - Please enquire for lead time
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm <i>inches</i>	Material	Head Length mm <i>inches</i>	Head Diameter mm <i>inches</i>	Hex Key (D) mm <i>inches</i>	Pitch in mm / Threads Per Inch mm / No.
# SC14Cx019.1-LH-SKT-H	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	High Tensile Steel / Black Oxide			3.18 (1/8)	1.270 mm / 20 TPI
# SC14Cx025.4-LH-SKT-H	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	High Tensile Steel / Black Oxide			3.18 (1/8)	1.270 mm / 20 TPI
# SC14Cx031.8-LH-SKT-H	6.35mm (1/4-20 UNC)	31.8 <i>1.252</i>	High Tensile Steel / Black Oxide			3.18 (1/8)	1.270 mm / 20 TPI
# SC14Cx038.1-LH-SKT-H	6.35mm (1/4-20 UNC)	38.1 <i>1.500</i>	High Tensile Steel / Black Oxide			3.18 (1/8)	1.270 mm / 20 TPI
# SC516Cx012.7-LH-SKT-H	7.938mm (5/16-18 UNC)	12.7 <i>0.500</i>	High Tensile Steel / Black Oxide			3.97 (5/32)	1.411 mm / 18 TPI
# SC516Cx015.9-LH-SKT-H	7.938mm (5/16-18 UNC)	15.9 <i>0.626</i>	High Tensile Steel / Black Oxide			3.97 (5/32)	1.411 mm / 18 TPI
# SC516Cx019.1-LH-SKT-H	7.938mm (5/16-18 UNC)	19.1 <i>0.752</i>	High Tensile Steel / Black Oxide			3.97 (5/32)	1.411 mm / 18 TPI
# SC516Cx025.4-LH-SKT-H	7.938mm (5/16-18 UNC)	25.4 <i>1.000</i>	High Tensile Steel / Black Oxide			3.97 (5/32)	1.411 mm / 18 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SC516Cx031.8-LH-SKT-H	7.938mm (5/16-18 UNC)	31.8 <i>1.252</i>	High Tensile Steel / Black Oxide			3.97 (5/32)	1.411 mm / 18 TPI
# SC516Cx038.1-LH-SKT-H	7.938mm (5/16-18 UNC)	38.1 <i>1.500</i>	High Tensile Steel / Black Oxide			3.97 (5/32)	1.411 mm / 18 TPI
# SC516Cx044.5-LH-SKT-H	7.938mm (5/16-18 UNC)	44.5 <i>1.752</i>	High Tensile Steel / Black Oxide			3.97 (5/32)	1.411 mm / 18 TPI
SCM080x010.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	10 <i>0.394</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x012.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	12 <i>0.472</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x016.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	16 <i>0.630</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x020.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	20 <i>0.787</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x025.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	25 <i>0.984</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM080x030.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	30 <i>1.181</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x035.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	35 <i>1.378</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x040.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	40 <i>1.575</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x045.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	45 <i>1.772</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x050.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	50 <i>1.969</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x055.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	55 <i>2.165</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SCM080x060.0-LH-SKT-H	8.0mm (M8x1.25 Standard)	60 <i>2.362</i>	High Tensile Steel / Black Oxide	7.64 - 8.00	12.73 - 13.27	5.00 <i>0.197</i>	1.250 mm / 20.32 TPI
# SC38Cx012.7-LH-SKT-H	9.525mm (3/8-16 UNC)	12.7 <i>0.500</i>	High Tensile Steel / Black Oxide			4.76 (3/16)	1.588 mm / 16 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SC38Cx015.9-LH-SKT-H	9.525mm (3/8-16 UNC)	15.9 <i>0.626</i>	High Tensile Steel / Black Oxide			4.76 (3/16)	1.588 mm / 16 TPI
# SC38Cx019.1-LH-SKT-H	9.525mm (3/8-16 UNC)	19.1 <i>0.752</i>	High Tensile Steel / Black Oxide			4.76 (3/16)	1.588 mm / 16 TPI
# SC38Cx025.4-LH-SKT-H	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	High Tensile Steel / Black Oxide			4.76 (3/16)	1.588 mm / 16 TPI
# SC38Cx031.8-LH-SKT-H	9.525mm (3/8-16 UNC)	31.8 <i>1.252</i>	High Tensile Steel / Black Oxide			4.76 (3/16)	1.588 mm / 16 TPI
# SC38Cx038.1-LH-SKT-H	9.525mm (3/8-16 UNC)	38.1 <i>1.500</i>	High Tensile Steel / Black Oxide			4.76 (3/16)	1.588 mm / 16 TPI
# SCM100x012.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	12 <i>0.472</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x016.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	16 <i>0.630</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x020.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	20 <i>0.787</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM100x025.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	25 <i>0.984</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x030.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	30 <i>1.181</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x035.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	35 <i>1.378</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x040.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	40 <i>1.575</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x045.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	45 <i>1.772</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x050.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	50 <i>1.969</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x060.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	60 <i>2.362</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x065.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	65 <i>2.559</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM100x070.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	70 <i>2.756</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM100x080.0-LH-SKT-H	10.0mm (M10x1.5 Standard)	80 <i>3.150</i>	High Tensile Steel / Black Oxide	9.64 - 10.00	15.73 - 16.27	7.00 <i>0.276</i>	1.500 mm / 16.93 TPI
# SCM120x016.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	16 <i>0.630</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x020.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	20 <i>0.787</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x025.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	25 <i>0.984</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x030.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	30 <i>1.181</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x035.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	35 <i>1.378</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x040.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	40 <i>1.575</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM120x045.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	45 <i>1.772</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x050.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	50 <i>1.969</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x055.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	55 <i>2.165</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x060.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	60 <i>2.362</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x070.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	70 <i>2.756</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SCM120x080.0-LH-SKT-H	12.0mm (M12x1.75 Standard)	80 <i>3.150</i>	High Tensile Steel / Black Oxide	11.57 - 12.00	17.73 - 18.27	8.00 <i>0.315</i>	1.750 mm / 14.51 TPI
# SC12Cx019.1-LH-SKT-H	12.7mm (1/2-13 UNC)	19.1 <i>0.752</i>	High Tensile Steel / Black Oxide			6.35 (1/4)	1.954 mm / 13 TPI
# SC12Cx025.4-LH-SKT-H	12.7mm (1/2-13 UNC)	25.4 <i>1.000</i>	High Tensile Steel / Black Oxide			6.35 (1/4)	1.954 mm / 13 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SC12Cx031.8-LH-SKT-H	12.7mm (1/2-13 UNC)	31.8 <i>1.252</i>	High Tensile Steel / Black Oxide			6.35 (1/4)	1.954 mm / 13 TPI
# SC12Cx038.1-LH-SKT-H	12.7mm (1/2-13 UNC)	38.1 <i>1.500</i>	High Tensile Steel / Black Oxide			6.35 (1/4)	1.954 mm / 13 TPI
# SCM160x030.0-LH-SKT-H	16.0mm (M16x2 Standard)	30 <i>1.181</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI
# SCM160x035.0-LH-SKT-H	16.0mm (M16x2 Standard)	35 <i>1.378</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI
# SCM160x040.0-LH-SKT-H	16.0mm (M16x2 Standard)	40 <i>1.575</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI
# SCM160x050.0-LH-SKT-H	16.0mm (M16x2 Standard)	50 <i>1.969</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI
# SCM160x055.0-LH-SKT-H	16.0mm (M16x2 Standard)	55 <i>2.165</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI
# SCM160x060.0-LH-SKT-H	16.0mm (M16x2 Standard)	60 <i>2.362</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Socket - Low Head

Part Number	Thread Size (C)	Length (L) mm	Material	Head Length mm	Head Diameter mm	Hex Key (D) mm	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>	<i>inches</i>	<i>inches</i>	
# SCM160x070.0-LH-SKT-H	16.0mm (M16x2 Standard)	70 <i>2.756</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI
# SCM160x080.0-LH-SKT-H	16.0mm (M16x2 Standard)	80 <i>3.150</i>	High Tensile Steel / Black Oxide	15.57 - 16.00	23.67 - 24.33	12.00 <i>0.472</i>	2.000 mm / 12.7 TPI
# SCM200x040.0-LH-SKT-H	20mm (M20x2.5 Standard)	40 <i>1.575</i>	High Tensile Steel / Black Oxide			14.00 <i>0.551</i>	2.500 mm / 10.16 TPI
# SCM200x045.0-LH-SKT-H	20mm (M20x2.5 Standard)	45 <i>1.772</i>	High Tensile Steel / Black Oxide			14.00 <i>0.551</i>	2.500 mm / 10.16 TPI
# SCM200x050.0-LH-SKT-H	20mm (M20x2.5 Standard)	50 <i>1.969</i>	High Tensile Steel / Black Oxide			14.00 <i>0.551</i>	2.500 mm / 10.16 TPI
# SCM200x060.0-LH-SKT-H	20mm (M20x2.5 Standard)	60 <i>2.362</i>	High Tensile Steel / Black Oxide			14.00 <i>0.551</i>	2.500 mm / 10.16 TPI
# SCM200x070.0-LH-SKT-H	20mm (M20x2.5 Standard)	70 <i>2.756</i>	High Tensile Steel / Black Oxide			14.00 <i>0.551</i>	2.500 mm / 10.16 TPI
# SCM200x080.0-LH-SKT-H	20mm (M20x2.5 Standard)	80 <i>3.150</i>	High Tensile Steel / Black Oxide			14.00 <i>0.551</i>	2.500 mm / 10.16 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au
