




MBA

Screws - Thumb



Steel, stainless and nylon.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STK440Cx00064-NY	2.845mm (4-40 UNC)	6.4 <i>0.252</i>	Nylon	13.487 <i>0.531</i>	Nylon Knurl	7.94 <i>0.313</i>		0.635 mm / 40 TPI
STK440Cx00095-BRN	2.845mm (4-40 UNC)	9.5 <i>0.374</i>	Brass	17.069 <i>0.672</i>	Knurled	7.94 <i>0.313</i>	Nickel Plated	0.635 mm / 40 TPI
# STK440Cx00095-NY	2.845mm (4-40 UNC)	9.5 <i>0.374</i>	Nylon	16.662 <i>0.656</i>	Nylon Knurl	7.94 <i>0.313</i>		0.635 mm / 40 TPI
STK440Cx00127-BRN	2.845mm (4-40 UNC)	12.7 <i>0.500</i>	Brass	20.00 <i>0.787</i>	Knurled	7.94 <i>0.313</i>	Nickel Plated	0.635 mm / 40 TPI

Indicates item not stocked at time of printing - Please enquire for lead time
 E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd
 MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
STK440Cx00127-NY	2.845mm (4-40 UNC)	12.7 <i>0.500</i>	Nylon	19.837 <i>0.781</i>	Nylon Knurl	7.94 <i>0.313</i>		0.635 mm / 40 TPI
STK440Cx00191-BRN	2.845mm (4-40 UNC)	19.1 <i>0.752</i>	Brass	26.187 <i>1.031</i>	Knurled	7.94 <i>0.313</i>	Nickel Plated	0.635 mm / 40 TPI
# STK440Cx00191-NY	2.845mm (4-40 UNC)	19.1 <i>0.752</i>	Nylon	26.187 <i>1.031</i>	Nylon Knurl	7.94 <i>0.313</i>		0.635 mm / 40 TPI
# STKM030x00060-3	3.0mm (M3x0.5 Standard)	6.0 <i>0.236</i>	303 Stainless Steel	10.50 <i>0.413</i>	Knurled	12.00 <i>0.472</i>	-	0.500 mm / 50.8 TPI
# STKM030x00080-3	3.0mm (M3x0.5 Standard)	8.0 <i>0.315</i>	303 Stainless Steel	12.50 <i>0.492</i>	Knurled	12.00 <i>0.472</i>	-	0.500 mm / 50.8 TPI
STKM030x00100-3	3.0mm (M3x0.5 Standard)	10.0 <i>0.394</i>	303 Stainless Steel	14.50 <i>0.571</i>	Knurled	12.00 <i>0.472</i>	-	0.500 mm / 50.8 TPI
# STKM030x00140-3	3.0mm (M3x0.5 Standard)	14.0 <i>0.551</i>	303 Stainless Steel	18.50 <i>0.728</i>	Knurled	12.00 <i>0.472</i>	-	0.500 mm / 50.8 TPI
# STK632Cx00064-NY	3.5mm (6-32 UNC)	6.4 <i>0.252</i>	Nylon	13.487 <i>0.531</i>	Nylon Knurl			0.794 mm / 32 TPI
# STK632Cx00095-NY	3.5mm (6-32 UNC)	9.5 <i>0.374</i>	Nylon	16.662 <i>0.656</i>	Nylon Knurl			0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STK632Cx00103-BR	3.5mm (6-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	9.525 <i>0.375</i>	Nickel Plated	0.794 mm / 32 TPI
# STK632Cx00103-BRN-B	3.5mm (6-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	11.112 <i>0.437</i>	Nickel Plated	0.794 mm / 32 TPI
# STK632Cx00103-BRN-C	3.5mm (6-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	12.700 <i>0.500</i>	Nickel Plated	0.794 mm / 32 TPI
# STK632Cx00103-BRO-A	3.5mm (6-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	9.525 <i>0.375</i>	Black Oxide	0.794 mm / 32 TPI
# STK632Cx00103-BRO-B	3.5mm (6-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	12.700 <i>0.500</i>	Black Oxide	0.794 mm / 32 TPI
# STK632Cx00127-BRO-A	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl	9.525 <i>0.375</i>	Black Oxide	0.794 mm / 32 TPI
# STK632Cx00127-BR	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl	12.700 <i>0.500</i>	Nickel Plated	0.794 mm / 32 TPI
STK632Cx00127-BRN-C	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl	11.112 <i>0.437</i>	Nickel Plated	0.794 mm / 32 TPI
# STK632Cx00127-BRO-B	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl	12.700 <i>0.500</i>	Black Oxide	0.794 mm / 32 TPI
# STK632Cx00127-BRN-B	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl	9.525 <i>0.375</i>	Nickel Plated	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STK632Cx00127-NY	3.5mm (6-32 UNC)	12.7 <i>0.500</i>	Nylon	19.837 <i>0.781</i>	Nylon Knurl			0.794 mm / 32 TPI
STK632Cx00191-NY	3.5mm (6-32 UNC)	19.1 <i>0.752</i>	Nylon	26.187 <i>1.031</i>	Nylon Knurl			0.794 mm / 32 TPI
STK632Cx00254-NY	3.5mm (6-32 UNC)	25.4 <i>1.000</i>	Nylon	32.537 <i>1.281</i>	Nylon Knurl			0.794 mm / 32 TPI
STKM040x00080-3	4.0mm (M4x0.7 Standard)	8.0 <i>0.315</i>	303 Stainless Steel	13.50 <i>0.531</i>	Knurled	16.00 <i>0.630</i>	-	0.700 mm / 36.29 TPI
# STKM040x00100-3	4.0mm (M4x0.7 Standard)	10.0 <i>0.394</i>	303 Stainless Steel	15.50 <i>0.610</i>	Knurled	16.00 <i>0.630</i>	-	0.700 mm / 36.29 TPI
# STKM040x00140-3	4.0mm (M4x0.7 Standard)	14.0 <i>0.551</i>	303 Stainless Steel	19.50 <i>0.768</i>	Knurled	16.00 <i>0.630</i>	-	0.700 mm / 36.29 TPI
# STKM040x00170-3	4.0mm (M4x0.7 Standard)	17.0 <i>0.669</i>	303 Stainless Steel	23.50 <i>0.925</i>	Knurled	16.00 <i>0.630</i>	-	0.700 mm / 36.29 TPI
STK832Cx00095-NY	4.166mm (8-32 UNC)	9.5 <i>0.374</i>	Nylon	13.106 <i>0.516</i>	Nylon Knurl			0.794 mm / 32 TPI
STK832Cx00103-BRO-C	4.166mm (8-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	11.112 <i>0.437</i>	Black Oxide	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STK832Cx00103-BRO-A	4.166mm (8-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	12.700 <i>0.500</i>	Black Oxide	0.794 mm / 32 TPI
# STK832Cx00103-BRO-B	4.166mm (8-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	9.525 <i>0.375</i>	Black Oxide	0.794 mm / 32 TPI
# STK832Cx00103-BR	4.166mm (8-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	9.525 <i>0.375</i>	Nickel Plated	0.794 mm / 32 TPI
# STK832Cx00103-BRN-B	4.166mm (8-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	11.112 <i>0.437</i>	Nickel Plated	0.794 mm / 32 TPI
# STK832Cx00103-BRN-C	4.166mm (8-32 UNC)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	12.700 <i>0.500</i>	Nickel Plated	0.794 mm / 32 TPI
# STK832Cx00127-BRO	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl		Black Oxide	0.794 mm / 32 TPI
STK832Cx00127-BR	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl	11.112 <i>0.437</i>	Nickel Plated	0.794 mm / 32 TPI
# STK832Cx00127-BRN-B	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	Brass	20.638 <i>0.813</i>	Diamond Knurl	9.525 <i>0.375</i>	Nickel Plated	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STK832Cx00127-NY	4.166mm (8-32 UNC)	12.7 <i>0.500</i>	Nylon	16.281 <i>0.641</i>	Nylon Knurl			0.794 mm / 32 TPI
# STK832Cx00191-NY	4.166mm (8-32 UNC)	19.1 <i>0.752</i>	Nylon	22.631 <i>0.891</i>	Nylon Knurl			0.794 mm / 32 TPI
# STK832Cx00254-NY	4.166mm (8-32 UNC)	25.4 <i>1.000</i>	Nylon	28.981 <i>1.141</i>	Nylon Knurl			0.794 mm / 32 TPI
# STK1024Cx00127-NY	4.762mm (10-24 UNC)	12.7 <i>0.500</i>	Nylon	16.281 <i>0.641</i>	Nylon Knurl			1.058 mm / 24 TPI
# STK1024Cx00191-NY	4.762mm (10-24 UNC)	19.1 <i>0.752</i>	Nylon	22.631 <i>0.891</i>	Nylon Knurl			1.058 mm / 24 TPI
# STK1024Cx00254-NY	4.762mm (10-24 UNC)	25.4 <i>1.000</i>	Nylon	28.981 <i>1.141</i>	Nylon Knurl			1.058 mm / 24 TPI
# STK1032Fx00103-BRN-C	4.762mm (10-32 UNF)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	12.700 <i>0.500</i>	Nickel Plated	0.794 mm / 32 TPI
# STK1032Fx00103-BR	4.762mm (10-32 UNF)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	9.525 <i>0.375</i>	Nickel Plated	0.794 mm / 32 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
STK1032Fx00103-BRN-B	4.762mm (10-32 UNF)	10.3 <i>0.406</i>	Brass	18.256 <i>0.719</i>	Diamond Knurl	11.112 <i>0.437</i>	Nickel Plated	0.794 mm / 32 TPI
# STK1032Fx00127-NY	4.762mm (10-32 UNF)	12.7 <i>0.500</i>	Nylon	16.281 <i>0.641</i>	Nylon Knurl			0.794 mm / 32 TPI
# STK1032Fx00191-NY	4.762mm (10-32 UNF)	19.1 <i>0.752</i>	Nylon	22.631 <i>0.891</i>	Nylon Knurl			0.794 mm / 32 TPI
# STK1032Fx00254-NY	4.762mm (10-32 UNF)	25.4 <i>1.000</i>	Nylon	28.981 <i>1.141</i>	Nylon Knurl			0.794 mm / 32 TPI
# STF316Wx00127-ST	4.762mm (3/16-24 BSW)	12.7 <i>0.500</i>	Steel	31.8 <i>1.252</i>	Flat Key Head	13.7 <i>0.539</i>	Zinc Plated	1.058 mm / 24 TPI
STF316Wx00191-ST	4.762mm (3/16-24 BSW)	19.1 <i>0.752</i>	Steel	30.4 <i>1.197</i>	Flat Key Head	13.7 <i>0.539</i>	Zinc Plated	1.058 mm / 24 TPI
# STF316Wx00254-ST	4.762mm (3/16-24 BSW)	25.4 <i>1.000</i>	Steel	44.5 <i>1.752</i>	Flat Key Head	13.7 <i>0.539</i>	Zinc Plated	1.058 mm / 24 TPI
STKM050x00100-3	5.0mm (M5x0.8 Standard)	10.0 <i>0.394</i>	303 Stainless Steel	16.00 <i>0.630</i>	Knurled	20.00 <i>0.787</i>	-	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
STFM050x00120-ST	5.0mm (M5x0.8 Standard)	12.0 <i>0.472</i>	Steel	23.7 <i>0.933</i>	Flat Key Head	13.7 <i>0.539</i>	Zinc Plated	0.800 mm / 31.75 TPI
STKM050x00140-3	5.0mm (M5x0.8 Standard)	14.0 <i>0.551</i>	303 Stainless Steel	20.00 <i>0.787</i>	Knurled	20.00 <i>0.787</i>	-	0.800 mm / 31.75 TPI
# STFM050x00160-ST	5.0mm (M5x0.8 Standard)	16.0 <i>0.630</i>	Steel	27.7 <i>1.091</i>	Flat Key Head	13.7 <i>0.539</i>	Zinc Plated	0.800 mm / 31.75 TPI
# STKM050x00170-3	5.0mm (M5x0.8 Standard)	17.0 <i>0.669</i>	303 Stainless Steel	24.00 <i>0.945</i>	Knurled	20.00 <i>0.787</i>	-	0.800 mm / 31.75 TPI
# STFM050x00200-ST	5.0mm (M5x0.8 Standard)	20.0 <i>0.787</i>	Steel	31.7 <i>1.248</i>	Flat Key Head	13.7 <i>0.539</i>	Zinc Plated	0.800 mm / 31.75 TPI
STKM050x00220-3	5.0mm (M5x0.8 Standard)	22.0 <i>0.866</i>	303 Stainless Steel	29.00 <i>1.142</i>	Knurled	20.00 <i>0.787</i>	-	0.800 mm / 31.75 TPI
STFM050x00250-ST	5.0mm (M5x0.8 Standard)	25.0 <i>0.984</i>	Steel	36.7 <i>1.445</i>	Flat Key Head	13.7 <i>0.539</i>	Zinc Plated	0.800 mm / 31.75 TPI
# STKM050x00270-3	5.0mm (M5x0.8 Standard)	27.0 <i>1.063</i>	303 Stainless Steel	34.00 <i>1.339</i>	Knurled	20.00 <i>0.787</i>	-	0.800 mm / 31.75 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STFM060x00120-ST	6.0mm (M6x1 Standard)	12.0 <i>0.472</i>	Steel		Flat Key Head		Zinc Plated	1.000 mm / 25.4 TPI
STKM060x00140-3	6.0mm (M6x1 Standard)	14.0 <i>0.551</i>	303 Stainless Steel	21.00 <i>0.827</i>	Knurled	24.00 <i>0.945</i>	-	1.000 mm / 25.4 TPI
# STFM060x00160-ST	6.0mm (M6x1 Standard)	16.0 <i>0.630</i>	Steel		Flat Key Head		Zinc Plated	1.000 mm / 25.4 TPI
# STKM060x00160-3	6.0mm (M6x1 Standard)	16.0 <i>0.630</i>	303 Stainless Steel	25.00 <i>0.984</i>	Knurled	24.00 <i>0.945</i>	-	1.000 mm / 25.4 TPI
# STFM060x00200-ST	6.0mm (M6x1 Standard)	20.0 <i>0.787</i>	Steel		Flat Key Head		Zinc Plated	1.000 mm / 25.4 TPI
# STKM060x00210-3	6.0mm (M6x1 Standard)	21.0 <i>0.827</i>	303 Stainless Steel	30.00 <i>1.181</i>	Knurled	24.00 <i>0.945</i>	-	1.000 mm / 25.4 TPI
# STFM060x00250-ST	6.0mm (M6x1 Standard)	25.0 <i>0.984</i>	Steel		Flat Key Head		Zinc Plated	1.000 mm / 25.4 TPI
STKM060x00260-3	6.0mm (M6x1 Standard)	26.0 <i>1.024</i>	303 Stainless Steel	35.00 <i>1.378</i>	Knurled	24.00 <i>0.945</i>	-	1.000 mm / 25.4 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STFM060x00400-ST	6.0mm (M6x1 Standard)	40.0 <i>1.575</i>	Steel		Flat Key Head		Zinc Plated	1.000 mm / 25.4 TPI
# STF14Wx00127-ST	6.35mm (1/4-20 BSW)	12.7 <i>0.500</i>	Steel		Flat Key Head		Zinc Plated	1.270 mm / 20 TPI
# STF14Wx00191-ST	6.35mm (1/4-20 BSW)	19.1 <i>0.752</i>	Steel		Flat Key Head		Zinc Plated	1.270 mm / 20 TPI
# STF14Wx00254-ST	6.35mm (1/4-20 BSW)	25.4 <i>1.000</i>	Steel		Flat Key Head		Zinc Plated	1.270 mm / 20 TPI
# STF14Wx00318-ST	6.35mm (1/4-20 BSW)	31.8 <i>1.252</i>	Steel		Flat Key Head		Zinc Plated	1.270 mm / 20 TPI
# STF14Wx00381-ST	6.35mm (1/4-20 BSW)	38.1 <i>1.500</i>	Steel		Flat Key Head		Zinc Plated	1.270 mm / 20 TPI
STK14Cx00127-NY	6.35mm (1/4-20 UNC)	12.7 <i>0.500</i>	Nylon	16.662 <i>0.656</i>	Nylon Knurl			1.270 mm / 20 TPI
# STK14Cx00191-NY	6.35mm (1/4-20 UNC)	19.1 <i>0.752</i>	Nylon	23.012 <i>0.906</i>	Nylon Knurl			1.270 mm / 20 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
STK14Cx00254-NY	6.35mm (1/4-20 UNC)	25.4 <i>1.000</i>	Nylon	29.362 <i>1.156</i>	Nylon Knurl			1.270 mm / 20 TPI
STF14Cx00508-NY	6.35mm (1/4-20 UNC)	50.8 <i>2.000</i>	Nylon		Flat Key Head			1.270 mm / 20 TPI
# STF516Wx00191-ST	7.938mm (5/16-18 BSW)	19.1 <i>0.752</i>	Steel		Flat Key Head		Zinc Plated	1.411 mm / 18 TPI
# STF516Wx00254-ST	7.938mm (5/16-18 BSW)	25.4 <i>1.000</i>	Steel		Flat Key Head		Zinc Plated	1.411 mm / 18 TPI
# STF516Wx00318-ST	7.938mm (5/16-18 BSW)	31.8 <i>1.252</i>	Steel		Flat Key Head		Zinc Plated	1.411 mm / 18 TPI
# STF516Wx00381-ST	7.938mm (5/16-18 BSW)	38.1 <i>1.500</i>	Steel		Flat Key Head		Zinc Plated	1.411 mm / 18 TPI
# STK516Cx00127-NY	7.938mm (5/16-18 UNC)	12.7 <i>0.500</i>	Nylon	17.069 <i>0.672</i>	Nylon Knurl			1.411 mm / 18 TPI
# STK516Cx00254-NY	7.938mm (5/16-18 UNC)	25.4 <i>1.000</i>	Nylon	29.769 <i>1.172</i>	Nylon Knurl			1.411 mm / 18 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STK516Cx00381-NY	7.938mm (5/16-18 UNC)	38.1 <i>1.500</i>	Nylon	42.469 <i>1.672</i>	Nylon Knurl			1.411 mm / 18 TPI
# STK516Cx00508-NY	7.938mm (5/16-18 UNC)	50.8 <i>2.000</i>	Nylon	55.169 <i>2.172</i>	Nylon Knurl			1.411 mm / 18 TPI
# STK38Cx00127-NY	9.525mm (3/8-16 UNC)	12.7 <i>0.500</i>	Nylon	17.462 <i>0.687</i>	Nylon Knurl			1.588 mm / 16 TPI
STK38Cx00254-NY	9.525mm (3/8-16 UNC)	25.4 <i>1.000</i>	Nylon	30.162 <i>1.187</i>	Nylon Knurl			1.588 mm / 16 TPI
# STK38Cx00381-NY	9.525mm (3/8-16 UNC)	38.1 <i>1.500</i>	Nylon	42.862 <i>1.687</i>	Nylon Knurl			1.588 mm / 16 TPI
# STK38Cx00508-NY	9.525mm (3/8-16 UNC)	50.8 <i>2.000</i>	Nylon	55.562 <i>2.187</i>	Nylon Knurl			1.588 mm / 16 TPI
# STK12Cx00254-NY	12.7mm (1/2-13 UNC)	25.4 <i>1.000</i>	Nylon	30.556 <i>1.203</i>	Nylon Knurl			1.954 mm / 13 TPI
# STK12Cx00381-NY	12.7mm (1/2-13 UNC)	38.1 <i>1.500</i>	Nylon	43.332 <i>1.706</i>	Nylon Knurl			1.954 mm / 13 TPI

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

Screws - Thumb

Part Number	Thread Size (C)	Thread Length (TI) mm	Material	Overall Length (L) mm	Head Type	Head Diameter (D) mm	Finish	Pitch in mm / Threads Per Inch mm / No.
		<i>inches</i>		<i>inches</i>		<i>inches</i>		
# STK12Cx00508-NY	12.7mm (1/2-13 UNC)	50.8	Nylon	55.956	Nylon Knurl			1.954 mm / 13 TPI
		<i>2.000</i>		<i>2.203</i>				

Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to catalogues@minibearings.com.au

