




# MBA

## Shock Absorbers



Body: Steel with black oxide finish, Stainless Steel or Chrome plated piston rod.

Operating Temperature Range: -10 °C to +70 °C.

Important: Provide mechanical stop 0.5mm before end of stroke.

### Shock Absorbers

Part Number	Stroke	Thread (A)	Length (B/C/D) mm <i>inches</i>	Shaft Diameter (d1) mm <i>inches</i>	Nut Thickness (l1) mm <i>inches</i>	Max. Energy Capacity Nm Per Cy	Effective Weight me KG	Return Spring Force N	Rod Reset Time (s)	More Information
# RMSA-85	5.00	M8x0.75	37 / 10 / 22	2.00 <i>0.079</i>	2.00 <i>0.079</i>	0.70	0.6 - 5	38474.00	0.30	For More Information Please Contact Us
# RMSA-80	5.00	M8x0.75	37 / 10 / 22	2.00 <i>0.079</i>	2.00 <i>0.079</i>	0.40	0.3 - 3	38474.00	0.30	For More Information Please Contact Us

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Shock Absorbers

Part Number	Stroke	Thread (A)	Length (B/C/D) mm  <i>inches</i>	Shaft Diameter (d1) mm  <i>inches</i>	Nut Thickness (I1) mm  <i>inches</i>	Max. Energy Capacity Nm Per Cy	Effective Weight me KG	Return Spring Force N	Rod Reset Time (s)	More Information
# RMSA-150	5.00	M10x1.00	39 / 12 / 22	3.00	3.00	1.00	38565.00	38506.00	0.40	For More Information Please Contact Us
				<i>0.118</i>	<i>0.118</i>					
# RMSA-100	5.00	M10x1.00	39 / 12 / 22	3.00	3.00	0.70	0.6 - 5	38506.00	0.40	For More Information Please Contact Us
				<i>0.118</i>	<i>0.118</i>					
# RMSA-250	8.00	M10x1.00	53 / 15 / 33	3.00	3.00	1.50	1.4 - 10	38506.00	0.40	For More Information Please Contact Us
				<i>0.118</i>	<i>0.118</i>					
# RMSA-200	8.00	M10x1.00	53 / 15 / 33	3.00	3.00	1.00	0.8 - 7	38506.00	0.40	For More Information Please Contact Us
				<i>0.118</i>	<i>0.118</i>					
# RMSA-350	10.00	M12x1.00	68 / 18 / 45	3.50	4.00	2.50	10990.00	38630.00	0.50	For More Information Please Contact Us
				<i>0.138</i>	<i>0.157</i>					
# RMSA-300	10.00	M12x1.00	68 / 18 / 45	3.50	4.00	2.00	1.6 - 15	38630.00	0.50	For More Information Please Contact Us
				<i>0.138</i>	<i>0.157</i>					

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Shock Absorbers

Part Number	Stroke	Thread (A)	Length (B/C/D) mm  <i>inches</i>	Shaft Diameter (d1) mm  <i>inches</i>	Nut Thickness (I1) mm  <i>inches</i>	Max. Energy Capacity Nm Per Cy	Effective Weight me KG	Return Spring Force N	Rod Reset Time (s)	More Information
# RMSA-500	19.00	M20 x 1.5	118 / 13.2 / 12	4.80	6.00	25.00	2.3 - 226	38630.00	0.10	For More Information Please Contact Us
				<i>0.189</i>	<i>0.236</i>					
# RMSA-600	25.40	M25 x 1.5	143 / 16.5 / 12	6.30	8.00	68.00	5 - 1360	11232.00	0.20	For More Information Please Contact Us
				<i>0.248</i>	<i>0.315</i>					
# RMSA-900	40.00	M25 x 1.5	189 / 06.5 / 12	6.30	8.00	100.00	14 - 2040	13058.00	0.40	For More Information Please Contact Us
				<i>0.248</i>	<i>0.315</i>					

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)
