




# MBA

## Socket Set Screws - Acetal Tipped



Acetal tipped grub screws. Soft tip compresses into threads to become self locking. Helps to prevent shaft damage.

### Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM040x0060SKT-B	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	7.0 <i>0.276</i>	2.0 <i>0.079</i>		Black Oxide Steel	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM040x0060SKT-3	4.0mm (M4x0.7 Standard)	6.0 <i>0.236</i>	7.0 <i>0.276</i>	2.0 <i>0.079</i>		303 Stainless	Acetal Tipped	0.700 mm / 36.29 TPI
SSATM040x0080SKT-3	4.0mm (M4x0.7 Standard)	8.0 <i>0.315</i>	9.0 <i>0.354</i>	2.0 <i>0.079</i>		303 Stainless	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM040x0080SKT-B	4.0mm (M4x0.7 Standard)	8.0 <i>0.315</i>	9.0 <i>0.354</i>	2.0 <i>0.079</i>		Black Oxide Steel	Acetal Tipped	0.700 mm / 36.29 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM040x0100SKT-3	4.0mm (M4x0.7 Standard)	10.0 <i>0.394</i>	11.0 <i>0.433</i>	2.0 <i>0.079</i>		303 Stainless	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM040x0100SKT-B	4.0mm (M4x0.7 Standard)	10.0 <i>0.394</i>	11.0 <i>0.433</i>	2.0 <i>0.079</i>		Black Oxide Steel	Acetal Tipped	0.700 mm / 36.29 TPI
SSATM040x0120SKT-3	4.0mm (M4x0.7 Standard)	12.0 <i>0.472</i>	13.0 <i>0.512</i>	2.0 <i>0.079</i>		303 Stainless	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM040x0120SKT-B	4.0mm (M4x0.7 Standard)	12.0 <i>0.472</i>	13.0 <i>0.512</i>	2.0 <i>0.079</i>		Black Oxide Steel	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM040x0160SKT-3	4.0mm (M4x0.7 Standard)	16.0 <i>0.630</i>	17.0 <i>0.669</i>	2.0 <i>0.079</i>		303 Stainless	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM040x0160SKT-B	4.0mm (M4x0.7 Standard)	16.0 <i>0.630</i>	17.0 <i>0.669</i>	2.0 <i>0.079</i>		Black Oxide Steel	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM040x0200SKT-B	4.0mm (M4x0.7 Standard)	20.0 <i>0.787</i>	21.0 <i>0.827</i>	3.0 <i>0.118</i>		Black Oxide Steel	Acetal Tipped	0.700 mm / 36.29 TPI
# SSATM050x0080SKT-3	5.0mm (M5x0.8)	8.0 <i>0.315</i>	9.0 <i>0.354</i>	3.0 <i>0.118</i>		303 Stainless	Acetal Tipped	0.800 mm / 31.75 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM050x0080SKT-B	5.0mm (M5x0.8)	8.0 <i>0.315</i>	9.0 <i>0.354</i>	3.0 <i>0.118</i>		Black Oxide Steel	Acetal Tipped	0.800 mm / 31.75 TPI
# SSATM050x0100SKT-3	5.0mm (M5x0.8)	10.0 <i>0.394</i>	11.0 <i>0.433</i>	3.0 <i>0.118</i>		303 Stainless	Acetal Tipped	0.800 mm / 31.75 TPI
# SSATM050x0100SKT-B	5.0mm (M5x0.8)	10.0 <i>0.394</i>	11.0 <i>0.433</i>	3.0 <i>0.118</i>		Black Oxide Steel	Acetal Tipped	0.800 mm / 31.75 TPI
# SSATM050x0120SKT-3	5.0mm (M5x0.8)	12.0 <i>0.472</i>	13.0 <i>0.512</i>	3.0 <i>0.118</i>		303 Stainless	Acetal Tipped	0.800 mm / 31.75 TPI
# SSATM050x0120SKT-B	5.0mm (M5x0.8)	12.0 <i>0.472</i>	13.0 <i>0.512</i>	3.0 <i>0.118</i>		Black Oxide Steel	Acetal Tipped	0.800 mm / 31.75 TPI
# SSATM050x0160SKT-B	5.0mm (M5x0.8)	16.0 <i>0.630</i>	17.0 <i>0.669</i>	3.0 <i>0.118</i>		Black Oxide Steel	Acetal Tipped	0.800 mm / 31.75 TPI
# SSATM050x0160SKT-3	5.0mm (M5x0.8)	16.0 <i>0.630</i>	17.0 <i>0.669</i>	3.0 <i>0.118</i>		303 Stainless	Acetal Tipped	0.800 mm / 31.75 TPI
# SSATM050x0200SKT-B	5.0mm (M5x0.8)	20.0 <i>0.787</i>	21.0 <i>0.827</i>	3.0 <i>0.118</i>		Black Oxide Steel	Acetal Tipped	0.800 mm / 31.75 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM050x0200SKT-3	5.0mm (M5x0.8)	20.0	21.0	3.0		303 Stainless	Acetal Tipped	0.800 mm / 31.75 TPI
		<i>0.787</i>	<i>0.827</i>	<i>0.118</i>				
# SSATM050x0250SKT-B	5.0mm (M5x0.8)	25.0	26.0	3.0		Black Oxide Steel	Acetal Tipped	0.800 mm / 31.75 TPI
		<i>0.984</i>	<i>1.024</i>	<i>0.118</i>				
# SSATM060x0100SKT-3	6.0mm (M6x1 Standard)	10.0	11.3	4.0		303 Stainless	Acetal Tipped	1.000 mm / 25.4 TPI
		<i>0.394</i>	<i>0.445</i>	<i>0.157</i>				
# SSATM060x0100SKT-B	6.0mm (M6x1 Standard)	10.0	11.3	3.5		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI
		<i>0.394</i>	<i>0.445</i>	<i>0.138</i>				
# SSATM060x0120SKT-3	6.0mm (M6x1 Standard)	12.0	13.3	4.0		303 Stainless	Acetal Tipped	1.000 mm / 25.4 TPI
		<i>0.472</i>	<i>0.524</i>	<i>0.157</i>				
# SSATM060x0120SKT-B	6.0mm (M6x1 Standard)	12.0	13.3	3.5		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI
		<i>0.472</i>	<i>0.524</i>	<i>0.138</i>				
# SSATM060x0160SKT-3	6.0mm (M6x1 Standard)	16.0	17.3	4.0		303 Stainless	Acetal Tipped	1.000 mm / 25.4 TPI
		<i>0.630</i>	<i>0.681</i>	<i>0.157</i>				
# SSATM060x0160SKT-B	6.0mm (M6x1 Standard)	16.0	17.3	3.5		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI
		<i>0.630</i>	<i>0.681</i>	<i>0.138</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM060x0200SKT-3	6.0mm (M6x1 Standard)	20.0 <i>0.787</i>	21.3 <i>0.839</i>	4.0 <i>0.157</i>		303 Stainless	Acetal Tipped	1.000 mm / 25.4 TPI
# SSATM060x0200SKT-B	6.0mm (M6x1 Standard)	20.0 <i>0.787</i>	21.3 <i>0.839</i>	3.5 <i>0.138</i>		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI
# SSATM060x0250SKT-B	6.0mm (M6x1 Standard)	25.0 <i>0.984</i>	26.3 <i>1.035</i>	3.5 <i>0.138</i>		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI
# SSATM060x0250SKT-3	6.0mm (M6x1 Standard)	25.0 <i>0.984</i>	26.3 <i>1.035</i>	4.0 <i>0.157</i>		303 Stainless	Acetal Tipped	1.000 mm / 25.4 TPI
# SSATM060x0320SKT-3	6.0mm (M6x1 Standard)	32.0 <i>1.260</i>	33.3 <i>1.311</i>	4.0 <i>0.157</i>		303 Stainless	Acetal Tipped	1.000 mm / 25.4 TPI
# SSATM060x0320SKT-B	6.0mm (M6x1 Standard)	32.0 <i>1.260</i>	33.3 <i>1.311</i>	3.5 <i>0.138</i>		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI
# SSATM060x0400SKT-B	6.0mm (M6x1 Standard)	40.0 <i>1.575</i>	41.3 <i>1.626</i>	3.5 <i>0.138</i>		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI
# SSATM060x0500SKT-B	6.0mm (M6x1 Standard)	50.0 <i>1.969</i>	51.3 <i>2.020</i>	3.5 <i>0.138</i>		Black Oxide Steel	Acetal Tipped	1.000 mm / 25.4 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM080x0120SKT-3	8.0mm (M8x1.25 Standard)	12.0 <i>0.472</i>	13.60 <i>0.535</i>	6.0 <i>0.236</i>		303 Stainless	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0120SKT-B	8.0mm (M8x1.25 Standard)	12.0 <i>0.472</i>	13.6 <i>0.535</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0160SKT-B	8.0mm (M8x1.25 Standard)	16.0 <i>0.630</i>	17.6 <i>0.693</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0160SKT-3	8.0mm (M8x1.25 Standard)	16.0 <i>0.630</i>	17.60 <i>0.693</i>	6.0 <i>0.236</i>		303 Stainless	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0200SKT-3	8.0mm (M8x1.25 Standard)	20.0 <i>0.787</i>	21.60 <i>0.850</i>	6.0 <i>0.236</i>		303 Stainless	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0200SKT-B	8.0mm (M8x1.25 Standard)	20.0 <i>0.787</i>	21.6 <i>0.850</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0250SKT-3	8.0mm (M8x1.25 Standard)	25.0 <i>0.984</i>	26.60 <i>1.047</i>	6.0 <i>0.236</i>		303 Stainless	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0250SKT-B	8.0mm (M8x1.25 Standard)	25.0 <i>0.984</i>	26.6 <i>1.047</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM080x0320SKT-3	8.0mm (M8x1.25 Standard)	32.0 <i>1.260</i>	33.60 <i>1.323</i>	6.0 <i>0.236</i>		303 Stainless	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0320SKT-B	8.0mm (M8x1.25 Standard)	32.0 <i>1.260</i>	33.6 <i>1.323</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0400SKT-B	8.0mm (M8x1.25 Standard)	40.0 <i>1.575</i>	41.6 <i>1.638</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0400SKT-3	8.0mm (M8x1.25 Standard)	40.0 <i>1.575</i>	41.60 <i>1.638</i>	6.0 <i>0.236</i>		303 Stainless	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0500SKT-B	8.0mm (M8x1.25 Standard)	50.0 <i>1.969</i>	51.6 <i>2.031</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM080x0630SKT-B	8.0mm (M8x1.25 Standard)	63.0 <i>2.480</i>	64.6 <i>2.543</i>	5.0 <i>0.197</i>		Black Oxide Steel	Acetal Tipped	1.250 mm / 20.32 TPI
# SSATM100x0160SKT-3	10.0mm (M10x1.5)	16.0 <i>0.630</i>	17.90 <i>0.705</i>	8.0 <i>0.315</i>		303 Stainless	Acetal Tipped	1.500 mm / 16.93 TPI
# SSATM100x0160SKT-B	10.0mm (M10x1.5)	16.0 <i>0.630</i>	17.9 <i>0.705</i>	6.5 <i>0.256</i>		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM100x0200SKT-3	10.0mm (M10x1.5)	20.0	21.90	8.0		303 Stainless	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>0.787</i>	<i>0.862</i>	<i>0.315</i>				
# SSATM100x0200SKT-B	10.0mm (M10x1.5)	20.0	21.9	6.5		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>0.787</i>	<i>0.862</i>	<i>0.256</i>				
# SSATM100x0250SKT-3	10.0mm (M10x1.5)	25.0	26.90	8.0		303 Stainless	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>0.984</i>	<i>1.059</i>	<i>0.315</i>				
# SSATM100x0250SKT-B	10.0mm (M10x1.5)	25.0	26.9	6.5		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>0.984</i>	<i>1.059</i>	<i>0.256</i>				
# SSATM100x0320SKT-B	10.0mm (M10x1.5)	32.0	33.9	6.5		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>1.260</i>	<i>1.335</i>	<i>0.256</i>				
# SSATM100x0320SKT-3	10.0mm (M10x1.5)	32.0	33.90	8.0		303 Stainless	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>1.260</i>	<i>1.335</i>	<i>0.315</i>				
# SSATM100x0400SKT-B	10.0mm (M10x1.5)	40.0	41.9	6.5		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>1.575</i>	<i>1.650</i>	<i>0.256</i>				
# SSATM100x0400SKT-3	10.0mm (M10x1.5)	40.0	41.90	8.0		303 Stainless	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>1.575</i>	<i>1.650</i>	<i>0.315</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM100x0500SKT-3	10.0mm (M10x1.5)	50.0	51.90	8.0		303 Stainless	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>1.969</i>	<i>2.043</i>	<i>0.315</i>				
# SSATM100x0500SKT-B	10.0mm (M10x1.5)	50.0	51.9	6.5		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>1.969</i>	<i>2.043</i>	<i>0.256</i>				
# SSATM100x0630SKT-B	10.0mm (M10x1.5)	63.0	64.9	6.5		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>2.480</i>	<i>2.555</i>	<i>0.256</i>				
# SSATM100x0800SKT-B	10.0mm (M10x1.5)	80.0	81.9	6.5		Black Oxide Steel	Acetal Tipped	1.500 mm / 16.93 TPI
		<i>3.150</i>	<i>3.224</i>	<i>0.256</i>				
# SSATM120x0200SKT-3	12.0mm (M12x1.75 Standard)	20.0	22.10	10.0		303 Stainless	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>0.787</i>	<i>0.870</i>	<i>0.394</i>				
# SSATM120x0200SKT-B	12.0mm (M12x1.75 Standard)	20.0	22.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>0.787</i>	<i>0.870</i>	<i>0.315</i>				
# SSATM120x0250SKT-B	12.0mm (M12x1.75 Standard)	25.0	27.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>0.984</i>	<i>1.067</i>	<i>0.315</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM120x0250SKT-3	12.0mm (M12x1.75 Standard)	25.0	27.10	10.0		303 Stainless	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>0.984</i>	<i>1.067</i>	<i>0.394</i>				
# SSATM120x0320SKT-3	12.0mm (M12x1.75 Standard)	32.0	34.10	10.0		303 Stainless	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>1.260</i>	<i>1.343</i>	<i>0.394</i>				
# SSATM120x0320SKT-B	12.0mm (M12x1.75 Standard)	32.0	34.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>1.260</i>	<i>1.343</i>	<i>0.315</i>				
# SSATM120x0400SKT-3	12.0mm (M12x1.75 Standard)	40.0	42.10	10.0		303 Stainless	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>1.575</i>	<i>1.657</i>	<i>0.394</i>				
# SSATM120x0400SKT-B	12.0mm (M12x1.75 Standard)	40.0	42.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>1.575</i>	<i>1.657</i>	<i>0.315</i>				
# SSATM120x0500SKT-3	12.0mm (M12x1.75 Standard)	50.0	52.10	10.0		303 Stainless	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>1.969</i>	<i>2.051</i>	<i>0.394</i>				
# SSATM120x0500SKT-B	12.0mm (M12x1.75 Standard)	50.0	52.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>1.969</i>	<i>2.051</i>	<i>0.315</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.

## Socket Set Screws - Acetal Tipped

Part Number	Major Thread Diameter (d) mm	Thread Length (l) mm	Overall Length (l + l1) mm	Tip Diameter (D) mm	Hex Key Size mm	Material	Type	Pitch in mm / Threads Per Inch mm / No.
	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>			
# SSATM120x0630SKT-3	12.0mm (M12x1.75 Standard)	63.0	65.10	10.0		303 Stainless	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>2.480</i>	<i>2.563</i>	<i>0.394</i>				
# SSATM120x0630SKT-B	12.0mm (M12x1.75 Standard)	63.0	65.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>2.480</i>	<i>2.563</i>	<i>0.315</i>				
# SSATM120x0800SKT-B	12.0mm (M12x1.75 Standard)	80.0	82.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>3.150</i>	<i>3.232</i>	<i>0.315</i>				
# SSATM120x1000SKT-B	12.0mm (M12x1.75 Standard)	100.0	102.1	8.0		Black Oxide Steel	Acetal Tipped	1.750 mm / 14.51 TPI
		<i>3.937</i>	<i>4.020</i>	<i>0.315</i>				

# Indicates item not stocked at time of printing - Please enquire for lead time

E&OE Pricing and all details subject to change without notice - Copyright Miniature Bearings Australia Pty Ltd

MBA Size Listings are a guide to sizes only and must not be solely relied on for critical design information.



DISTRIBUTED BY

Ask us to put your name and address here

<http://www.minibearings.com.au/product>

Ph +61 7 3245 7977

Fax +61 7 3245 1017

Catalogue requests to [catalogues@minibearings.com.au](mailto:catalogues@minibearings.com.au)

